

ETSI TS 125 106 V5.3.0 (2002-12)

Technical Specification

**Universal Mobile Telecommunications System (UMTS);
UTRA Repeater;
Radio transmission and reception
(3GPP TS 25.106 version 5.3.0 Release 5)**



Reference

RTS/TSGR-0425106v530

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

All published ETSI deliverables shall include information which directs the reader to the above source of information.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp> .

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Foreword..... | 5 |
| 1 Scope | 6 |
| 2 References | 6 |
| 3 Definitions, symbols and abbreviations | 6 |
| 3.1 Definitions | 6 |
| 3.2 Symbols..... | 6 |
| 3.3 Abbreviations | 7 |
| 4 General | 7 |
| 4.1 Relationship between Minimum Requirements and Test Requirements | 7 |
| 4.2 Regional requirements..... | 7 |
| 5 Frequency bands and channel arrangement..... | 8 |
| 5.1 Frequency bands..... | 8 |
| 5.2 Up-link to down-link frequency separation..... | 9 |
| 5.3 Channel arrangement..... | 9 |
| 5.3.1 Channel spacing..... | 9 |
| 5.3.2 Channel raster | 9 |
| 5.3.3 Channel number | 9 |
| 6 Output power..... | 9 |
| 6.1 Maximum output power | 9 |
| 6.1.1 Minimum Requirements | 9 |
| 7 Frequency stability | 10 |
| 7.1 Minimum requirement..... | 10 |
| 8 Out of band gain | 10 |
| 8.1 Minimum requirement..... | 10 |
| 9 Unwanted emission | 11 |
| 9.1 Out of band emission..... | 11 |
| 9.1.1 Spectrum emission mask | 11 |
| 9.2 Spurious emissions | 13 |
| 9.2.1 General Requirements..... | 13 |
| 9.2.1.1 Minimum Requirement (Category A) | 13 |
| 9.2.1.2 Minimum Requirement (Category B) | 14 |
| 9.2.2 Co-location with UTRA-FDD BS | 15 |
| 9.2.2.1 Minimum Requirement | 15 |
| 9.2.3 Co-existence with GSM 900..... | 16 |
| 9.2.3.1 Operation in the same geographic area | 16 |
| 9.2.3.1.1 Minimum Requirement | 16 |
| 9.2.3.2 Co-located Repeaters and GSM 900 base stations | 16 |
| 9.2.3.2.1 Minimum Requirement | 16 |
| 9.2.4 Co-existence with DCS 1800..... | 16 |
| 9.2.4.1 Operation in the same geographic area | 16 |
| 9.2.4.1.1 Minimum Requirement | 16 |
| 9.2.4.2 Co-located Repeaters and DCS 1800 base stations | 16 |
| 9.2.4.2.1 Minimum Requirement | 17 |
| 9.2.5 Co-existence with PHS | 17 |
| 9.2.5.1 Minimum Requirement | 17 |
| 9.2.6 Co-existence with UTRA-TDD | 17 |
| 9.2.6.1 Operation in the same geographic area | 17 |
| 9.2.6.1.1 Minimum Requirement | 17 |

| | | |
|-------------------------------|---|-----------|
| 9.2.6.2 | Co-located Repeaters and UTRA-TDD base stations | 17 |
| 9.2.6.2.1 | Minimum Requirement | 17 |
| 10 | Modulation accuracy | 18 |
| 10.1 | Error Vector Magnitude | 18 |
| 10.1.1 | Minimum requirement | 18 |
| 10.2 | Peak code domain error | 18 |
| 10.2.1 | Minimum requirement | 18 |
| 11 | Input Intermodulation..... | 18 |
| 11.1 | General Requirement..... | 18 |
| 11.1.1 | Minimum requirement | 19 |
| 11.2 | Co-location with GSM 900 and/or DCS 1800..... | 19 |
| 11.2.1 | Minimum requirements..... | 19 |
| 11.3 | Co-existence with GSM 900 and/or DCS 1800..... | 19 |
| 11.3.1 | Minimum requirements..... | 19 |
| 12 | Output intermodulation | 20 |
| 12.1 | Minimum requirement | 20 |
| Annex A (informative): | Change History | 21 |
| History | | 22 |

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document..

1 Scope

The present document establishes the minimum radio frequency performance of UTRA repeaters.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] ITU-R Recommendation SM.329-9: "Spurious emissions".
 - [2] 3GPP TS 25.143: "UTRA Repeater Conformance Testing".
 - [3] 3GPP TS 25.113: "Base Station and Repeater Electromagnetic Compatibility".
 - [4] ETSI ETR 273-1-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement of radiated methods of measurement (using test sites) and evaluation of the corresponding measurement uncertainties; Part 1: Uncertainties in the measurement of mobile radio equipment characteristics; Sub-part 2: Examples and annexes".
-

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Donor coupling loss: is the coupling loss between the repeater and the donor base station.

Down-link: Signal path where base station transmits and mobile receives.

Operating band: The repeater can have one or several operating bands. The operating band is the frequency range that the repeater operates in with operational configuration. This frequency range can correspond to one or several consecutive nominal 5 MHz channels. If they are not consecutive each subset of channels shall be considered as an individual operating band.

Repeater: A device that receives, amplifies and transmits the radiated or conducted RF carrier both in the down-link direction (from the base station to the mobile area) and in the up-link direction (from the mobile to the base station)

Up-link: Signal path where mobile transmits and base station receives.

3.2 Symbols

(void)

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|---------|--|
| EVM | Error Vector Magnitude |
| FDD | Frequency Division Duplex |
| FFS | For Further Study |
| IMT2000 | International Mobile Telecommunication-2000 |
| ITU | International Telecommunication Union |
| RF | Radio Frequency |
| UARFCN | UTRA Absolute Radio Frequency Channel Number |
| UMTS | Universal Mobile Telecommunication System |
| UTRA | Universal Terrestrial Radio Access |
| WCDMA | Wide band Code Division Multiple Access |

4 General

This specification applies only to UTRA-FDD repeaters.

Unless otherwise stated, all requirements in this specification apply to both the up-link and down-link directions.

4.1 Relationship between Minimum Requirements and Test Requirements

The Minimum Requirements given in this specification make no allowance for measurement uncertainty. The repeater test specification 25.143 section 5 [2] defines Test Tolerances. These Test Tolerances are individually calculated for each test. The Test Tolerances are used to relax the Minimum Requirements in this specification to create Test Requirements.

The measurement results returned by the Test System are compared - without any modification - against the Test Requirements as defined by the shared risk principle.

The Shared Risk principle is defined in ETR 273 Part 1 sub-part 2 section 6.5.[4]

4.2 Regional requirements

Some requirements in TS 25.106 may only apply in certain regions. Table 4.1 lists all requirements that may be applied differently in different regions.

Table 4.1: List of regional requirements.

| Clause number | Requirement | Comments |
|---------------|--|--|
| 5.1 | Frequency bands | Some bands may be applied regionally. |
| 5.2 | Up-link to down-link frequency Separation | The requirement is applied according to which frequency bands in Clause 5.2 that are supported by the Repeater. |
| 6.1 | Maximum output power | In certain regions, the minimum requirement for normal conditions may apply also for some conditions outside the ranges of conditions defined as normal. |
| 9.1.1 | Spectrum emission mask | The mask specified may be mandatory in certain regions. In other regions this mask may not be applied. |
| 9.2.1.1 | Spurious emissions (Category A) | These requirements shall be met in cases where Category A limits for spurious emissions, as defined in ITU-R Recommendation SM.329 [1], are applied. |
| 9.2.1.2 | Spurious emissions (Category B) | These requirements shall be met in cases where Category B limits for spurious emissions, as defined in ITU-R Recommendation SM.329 [1], are applied. |
| 9.2.3.1 | Spurious emissions: Co-existence with GSM900 -Operation in the same geographic area | This requirement may be applied for the protection of GSM900 MS in geographic areas in which both GSM900 and UTRA FDD Repeaters are deployed. |
| 9.2.3.2 | Spurious emissions: Co-existence with GSM900 - Co-location | This requirement may be applied for the protection of GSM900 BTS receivers when GSM900 BTS and UTRA FDD Repeaters are co-located. |
| 9.2.4.1 | Spurious emissions: Co-existence with DCS1800 -Operation in the same geographic area | This requirement may be applied for the protection of DCS1800 MS in geographic areas in which both DCS1800 and UTRA FDD Repeaters are deployed. |
| 9.2.4.2 | Spurious emissions: Co-existence with DCS1800 - Co-location | This requirement may be applied for the protection of DCS1800 BTS receivers when DCS1800 BTS and UTRA FDD Repeaters are co-located. |
| 9.2.5 | Spurious emissions: Co-existence with PHS | This requirement may be applied for the protection of PHS in geographic areas in which both PHS and UTRA FDD Repeaters are deployed. |
| 11.2 | Input Intermodulation: Co-location with GSM900 and/or DCS1800 | The requirement may be applied when GSM900 BTS and/or DCS1800 BTS and UTRA-FDD Repeaters are co-located. |

5 Frequency bands and channel arrangement

5.1 Frequency bands

A UTRA/FDD Repeater is designed to operate in one or several operating bands within either of the following paired frequency bands;

- a) 1920 – 1980 MHz: Up-link (Mobile transmit, base receive)
2110 – 2170 MHz: Down-link (Base transmit, mobile receive)
- b) 1850 – 1910 MHz: Up-link (Mobile transmit, base receive)
1930 – 1990 MHz: Down-link (Base transmit, mobile receive)
(Note 1)

NOTE 1: Used in Region 2. Additional allocations in ITU region 2 are FFS.

NOTE 2: Deployment in other frequency bands is not precluded.

5.2 Up-link to down-link frequency separation

- a) The minimum up-link to down-link frequency separation is 134.8 MHz and the maximum value is 245.2 MHz and all UTRA/FDD repeaters shall support an up-link to down-link frequency separation of 190 MHz when operating in the paired frequency band defined in sub-clause 5.1(a).
- b) A UTRA/FDD repeater can support both fixed and variable up-link to down-link frequency separation.
- c) When operating in the paired frequency band defined in sub-clause 5.1(b), all UTRA/FDD repeaters shall support an up-link to down-link frequency separation of 80 MHz.
- d) The use of other up-link to down-link frequency separations in existing or other frequency bands shall not be precluded.

5.3 Channel arrangement

5.3.1 Channel spacing

The nominal channel spacing is 5 MHz, but this can be adjusted to optimise performance in a particular deployment scenario.

5.3.2 Channel raster

The channel raster is 200 kHz, which means that the centre frequency must be an integer multiple of 200 kHz.

5.3.3 Channel number

The carrier frequency is designated by the UTRA Absolute Radio Frequency Channel Number (UARFCN). The value of the UARFCN in the IMT2000 band is defined as follows:

Table 5.1: UTRA Absolute Radio Frequency Channel Number

| | | |
|-----------|---------------------------------|---|
| Up-link | $N_u = 5 * F_{\text{uplink}}$ | $0.0 \text{ MHz} \leq F_{\text{uplink}} \leq 3276.6 \text{ MHz}$ where F_{uplink} is the up-link frequency in MHz |
| Down-link | $N_d = 5 * F_{\text{downlink}}$ | $0.0 \text{ MHz} \leq F_{\text{downlink}} \leq 3276.6 \text{ MHz}$ where F_{downlink} is the down-link frequency in MHz |

6 Output power

Output power, P_{out} , of the repeater is the mean power of one carrier at maximum repeater gain delivered to a load with resistance equal to the nominal load impedance of the transmitter.

Rated output power, PRAT, of the repeater is the mean power level per carrier at maximum repeater gain that the manufacturer has declared to be available at the antenna connector.

6.1 Maximum output power

Maximum output power, P_{max} , of the repeater is the mean power level per carrier measured at the antenna connector in specified reference condition.

6.1.1 Minimum Requirements

The requirements shall apply at maximum gain, with WCDMA signals in the operating band of the repeater, at levels that produce the maximum rated output power per channel.

When the power of all signals is increased by 10 dB, compared to the power level that produce the maximum rated output power, the requirements shall still be met.

In normal conditions, the Repeater maximum output power shall remain within limits specified in Table 6.1 relative to the manufacturer's rated output power.

Table 6.1: Repeater output power; normal conditions

| Rated output power | Limit |
|----------------------|-----------------|
| $P \geq 43$ dBm | +2 dB and -2 dB |
| $39 \leq P < 43$ dBm | +2 dB and -2 dB |
| $31 \leq P < 39$ dBm | +2 dB and -2 dB |
| $P < 31$ dBm | +3 dB and -3 dB |

In extreme conditions, the Repeater maximum output power shall remain within the limits specified in Table 6.2 relative to the manufacturer's rated output power.

Table 6.2: Repeater output power; extreme conditions

| Rated output power | Limit |
|----------------------|---------------------|
| $P \geq 43$ dBm | +2.5 dB and -2.5 dB |
| $39 \leq P < 43$ dBm | +2.5 dB and -2.5 dB |
| $31 \leq P < 39$ dBm | +2.5 dB and -2.5 dB |
| $P < 31$ dBm | +4 dB and -4 dB |

In certain regions, the minimum requirement for normal conditions may apply also for some conditions outside the ranges of conditions defined as normal.

7 Frequency stability

Frequency stability is the ability to maintain the same frequency on the output signal with respect to the input signal.

7.1 Minimum requirement

The frequency deviation of the output signal with respect to the input signal shall be no more than $\pm 0,01$ ppm.

8 Out of band gain

Out of band gain refers to the gain of the repeater outside the operating band.

8.1 Minimum requirement

The intended use of a repeater in a system is to amplify the in band signals and not to amplify the out of band emission of the donor base station.

In the intended application of the repeater, the out of band gain is less than the donor coupling loss.

The repeater minimum donor coupling loss shall be declared by the manufacturer. This is this the minimum required attenuation between the donor BS and the repeater for proper repeater operation.

The gain outside the operating band shall not exceed the maximum level specified in table 8.1, where:

- f_{offset} is the distance from the centre frequency of the first or last 5 MHz channel within the operating band.

Table 8.1: Out of band gain limits 1

| Frequency offset from the carrier frequency, f_{offset} | Maximum gain |
|--|--------------|
| $2,7 \leq f_{\text{offset}} < 3,5$ MHz | 60 dB |
| $3,5 \leq f_{\text{offset}} < 7,5$ MHz | 45 dB |
| $7,5 \leq f_{\text{offset}} < 12,5$ MHz | 45 dB |
| $12,5 \text{ MHz} \leq f_{\text{offset}}$ | 35 dB |

For $12,5 \text{ MHz} \leq f_{\text{offset}}$ the out of band gain shall not exceed the maximum gain of table 8.2 or the maximum gain stated in table 8.1 whichever is lower.

Table 8.2: Out of band gain limits 2

| Repeater maximum output power as in 9.1.1.1 | Maximum gain |
|---|---|
| $P < 31$ dBm | Out of band gain \leq minimum donor coupling loss |
| $31 \text{ dBm} \leq P < 43$ dBm | Out of band gain \leq minimum donor coupling loss |
| $P \geq 43$ dBm | Out of band gain \leq minimum donor coupling loss – (P-43dBm) |
| Note 1: The out of band gain is considered with $12,5 \text{ MHz} \leq f_{\text{offset}}$ | |

9 Unwanted emission

9.1 Out of band emission

Out of band emissions are unwanted emissions immediately outside the operating band resulting from the modulation process and non-linearity in the transmitter but excluding spurious emissions. This out of band emission requirement is specified in terms of a spectrum emission mask.

9.1.1 Spectrum emission mask

The mask defined in tables 9.1 to 9.4 below may be mandatory in certain regions. In other regions this mask may not be applied.

For regions where this clause applies, the requirement shall be met by a repeater's RF-signal output at maximum gain with WCDMA signals in the operating band of the repeater, at levels that produce the maximum rated output power per channel. The requirements shall also apply at maximum gain without WCDMA signals in the operating band.

Emissions shall not exceed the maximum level specified in tables 9.1 to 9.4 for the appropriate repeater maximum output power, in the frequency range from $\Delta f = 2,5$ MHz to Δf_{max} from the 5 MHz channel, where:

- Δf is the separation between the centre frequency of first or last 5 MHz channel used in the operating band and the nominal -3 dB point of the measuring filter closest to the carrier frequency.
- f_{offset} is the separation between the centre frequency of first or last 5 MHz channel in the operating band and the centre of the measuring filter.
- $f_{\text{offset}_{\text{max}}}$ is either 12,5 MHz or the offset to the UTRA band edge at both up- and down-link as defined in section 5.1, whichever is the greater.
- Δf_{max} is equal to $f_{\text{offset}_{\text{max}}}$ minus half of the bandwidth of the measurement filter.




Figure 9.1: Illustrative diagram of spectrum emission mask

Table 9.1: Spectrum emission mask values, maximum output power $P \geq 43$ dBm

| Frequency offset of measurement filter – 3dB point, Δf | Frequency offset of measurement filter centre frequency, f_{offset} | Maximum level | Measurement bandwidth |
|--|---|---|-----------------------|
| $2,5 \text{ MHz} \leq \Delta f < 2,7 \text{ MHz}$ | $2,515\text{MHz} \leq f_{offset} < 2,715\text{MHz}$ | -14 dBm | 30 kHz |
| $2,7 \text{ MHz} \leq \Delta f < 3,5 \text{ MHz}$ | $2,715\text{MHz} \leq f_{offset} < 3,515\text{MHz}$ | $-14\text{dBm} - 15 \cdot \left(\frac{f_{offset}}{\text{MHz}} - 2,715 \right) \text{dB}$ | 30 kHz |
| | $3,515\text{MHz} \leq f_{offset} < 4,0\text{MHz}$ | -26 dBm | 30 kHz |
| $3,5 \text{ MHz} \leq \Delta f \leq f_{max}$ | $4,0\text{MHz} \leq f_{offset} < f_{offset_{max}}$ | -13 dBm | 1 MHz |

Table 9.2: Spectrum emission mask values, maximum output power $39 \leq P < 43$ dBm

| Frequency offset of measurement filter – 3dB point, Δf | Frequency offset of measurement filter centre frequency, f_{offset} | Maximum level | Measurement bandwidth |
|--|---|---|-----------------------|
| $2,5 \text{ MHz} \leq \Delta f < 2,7 \text{ MHz}$ | $2,515\text{MHz} \leq f_{offset} < 2,715\text{MHz}$ | -14 dBm | 30 kHz |
| $2,7 \text{ MHz} \leq \Delta f < 3,5 \text{ MHz}$ | $2,715\text{MHz} \leq f_{offset} < 3,515\text{MHz}$ | $-14\text{dBm} - 15 \cdot \left(\frac{f_{offset}}{\text{MHz}} - 2,715 \right) \text{dB}$ | 30 kHz |
| (see note) | $3,515\text{MHz} \leq f_{offset} < 4,0\text{MHz}$ | -26 dBm | 30 kHz |
| $3,5 \text{ MHz} \leq \Delta f < 7,5 \text{ MHz}$ | $4,0\text{MHz} \leq f_{offset} < 8,0\text{MHz}$ | -13 dBm | 1 MHz |
| $7,5 \text{ MHz} \leq \Delta f \leq f_{max}$ | $8,0\text{MHz} \leq f_{offset} < f_{offset_{max}}$ | $P - 56 \text{ dB}$ | 1 MHz |

Table 9.3: Spectrum emission mask values, maximum output power $31 \leq P < 39$ dBm

| Frequency offset of measurement filter – 3dB point, Δf | Frequency offset of measurement filter centre frequency, f_{offset} | Maximum level | Measurement bandwidth |
|--|--|--|-----------------------|
| $2,5 \text{ MHz} \leq \Delta f < 2,7 \text{ MHz}$ | $2,515\text{MHz} \leq f_{\text{offset}} < 2,715\text{MHz}$ | P - 53 dB | 30 kHz |
| $2,7 \text{ MHz} \leq \Delta f < 3,5 \text{ MHz}$ | $2,715\text{MHz} \leq f_{\text{offset}} < 3,515\text{MHz}$ | $P - 53\text{dB} - 15 \cdot \left(\frac{f_{\text{offset}}}{\text{MHz}} - 2,715 \right) \text{dB}$ | 30 kHz |
| (see note) | $3,515\text{MHz} \leq f_{\text{offset}} < 4,0\text{MHz}$ | P-65 dB | 30 kHz |
| $3,5 \text{ MHz} \leq \Delta f < 7,5 \text{ MHz}$ | $4,0\text{MHz} \leq f_{\text{offset}} < 8,0\text{MHz}$ | P - 52 dB | 1 MHz |
| $7,5 \text{ MHz} \leq \Delta f \leq f_{\text{max}}$ | $8,0\text{MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$ | P - 56 dB | 1 MHz |

Table 9.4: Spectrum emission mask values, maximum output power $P < 31$ dBm

| Frequency offset of measurement filter – 3dB point, Δf | Frequency offset of measurement filter centre frequency, f_{offset} | Maximum level | Measurement bandwidth |
|--|--|--|-----------------------|
| $2,5 \text{ MHz} \leq \Delta f < 2,7 \text{ MHz}$ | $2,515\text{MHz} \leq f_{\text{offset}} < 2,715\text{MHz}$ | -22 dBm | 30 kHz |
| $2,7 \text{ MHz} \leq \Delta f < 3,5 \text{ MHz}$ | $2,715\text{MHz} \leq f_{\text{offset}} < 3,515\text{MHz}$ | $-22\text{dBm} - 15 \cdot \left(\frac{f_{\text{offset}}}{\text{MHz}} - 2,715 \right) \text{dB}$ | 30 kHz |
| (see note) | $3,515\text{MHz} \leq f_{\text{offset}} < 4,0\text{MHz}$ | -34 dBm | 30 kHz |
| $3,5 \text{ MHz} \leq \Delta f < 7,5 \text{ MHz}$ | $4,0\text{MHz} \leq f_{\text{offset}} < 8,0\text{MHz}$ | -21 dBm | 1 MHz |
| $7,5 \text{ MHz} \leq \Delta f \leq f_{\text{max}}$ | $8,0\text{MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$ | -25 dBm | 1 MHz |

NOTE: This frequency range ensures that the range of values of f_{offset} is continuous.

9.2 Spurious emissions

Spurious emissions are emissions which are caused by unwanted transmitter effects such as harmonics emission, parasitic emission, intermodulation products and frequency conversion products, but exclude out of band emissions. This is measured at the repeaters RF output port.

Unless otherwise stated, all requirements are measured as mean power.

9.2.1 General Requirements

The requirements of either subclause 9.2.1.1 or subclause 9.2.1.2 shall apply whatever the type of repeater considered (one or several operating bands). It applies for all configurations foreseen by the manufacturer's specification.

Either requirement applies at frequencies within the specified frequency ranges that are more than 12,5 MHz below the centre frequency of the first 5 MHz channel or more than 12,5 MHz above the centre frequency of the last 5 MHz channel in the operating band.

9.2.1.1 Minimum Requirement (Category A)

The following requirements shall be met in cases where Category A limits for spurious emissions, as defined in ITU-R Recommendation SM.329 [1], are applied.

At maximum repeater gain, with WCDMA signals in the operating band of the repeater, at levels that produce the maximum rated output power per channel, the power of any spurious emission shall not exceed the limits specified in table 9.5. The requirements shall also apply at maximum gain without WCDMA signals in the operating band.

When the power in all channels is increased by 10 dB, compared to the input level producing the maximum rated output power, the requirement shall still be met.

Table 9.5: Up-link and down-link: General spurious emissions limits, Category A

| Band | Maximum level | Measurement Bandwidth | Note |
|------------------|---------------|-----------------------|--|
| 9kHz – 150kHz | -13 dBm | 1 kHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| 150kHz – 30MHz | | 10 kHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| 30MHz – 1GHz | | 100 kHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| 1GHz – 12,75 GHz | | 1 MHz | Upper frequency as in ITU-R SM.329 [1], s2.5 table 1 |

9.2.1.2 Minimum Requirement (Category B)

The following requirements shall be met in cases where Category B limits for spurious emissions, as defined in ITU-R Recommendation SM.329 [1], are applied.

At maximum repeater gain, with WCDMA signals in the operating band of the repeater, at levels that produce the maximum rated power output per channel, the power of any spurious emission shall not exceed the limits specified in tables 9.6 and 9.7 for the down- and up-link, respectively. The requirements shall also apply at maximum gain without WCDMA signals in the operating band.

When the power in all channels is increased by 10 dB, compared to the input level producing the maximum rated output power, the requirement shall still be met.

Table 9.6: Down-link: General spurious emissions limits, Category B

| Band | Maximum Level | Measurement Bandwidth | Note |
|---|---------------|-----------------------|--|
| 9kHz ↔ 150kHz | -36 dBm | 1 kHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| 150kHz ↔ 30MHz | -36 dBm | 10 kHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| 30MHz ↔ 1GHz | -36 dBm | 100 kHz | Bandwidth as in ITU-R SM.329, s4.1 |
| 1GHz ↔ Fc1 - 60 MHz or 2100 MHz <i>whichever is the higher</i> | -30 dBm | 1 MHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| Fc1 – 60 MHz or 2100 MHz <i>whichever is the higher</i> ↔ Fc1 – 50 MHz or 2100 MHz <i>whichever is the higher</i> | -25 dBm | 1 MHz | Specification in accordance with ITU-R SM.329 [1], s4.3 and Annex 7 |
| Fc1 – 50 MHz or 2100 MHz <i>whichever is the higher</i> ↔ Fc2 + 50 MHz or 2180 MHz <i>whichever is the lower</i> | -15 dBm | 1 MHz | Specification in accordance with ITU-R SM.329 [1], s4.3 and Annex 7 |
| Fc2 + 50 MHz or 2180 MHz <i>whichever is the lower</i> ↔ Fc2 + 60 MHz or 2180 MHz <i>whichever is the lower</i> | -25 dBm | 1 MHz | Specification in accordance with ITU-R SM.329 [1], s4.3 and Annex 7 |
| Fc2 + 60 MHz or 2180 MHz <i>whichever is the lower</i> ↔ 12,75 GHz | -30 dBm | 1 MHz | Bandwidth as in ITU-R SM.329 [1], s4.1. Upper frequency as in ITU-R SM.329 [1], s2.5 table 1 |

Table 9.7: Up-link: General spurious emissions limits, Category B

| Band | Maximum Level | Measurement Bandwidth | Note |
|---|---------------|-----------------------|--|
| 9kHz ↔ 150kHz | -36 dBm | 1 kHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| 150kHz ↔ 30MHz | - 36 dBm | 10 kHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| 30MHz ↔ 1GHz | -36 dBm | 100 kHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| 1GHz ↔ Fc1 - 60 MHz or 1910 MHz <i>whichever is the higher</i> | -30 dBm | 1 MHz | Bandwidth as in ITU-R SM.329 [1], s4.1 |
| Fc1 – 60 MHz or 1910 MHz <i>whichever is the higher</i> ↔ Fc1 – 50 MHz or 1910 MHz <i>whichever is the higher</i> | -25 dBm | 1 MHz | Specification in accordance with ITU-R SM.329 [1], s4.3 and Annex 7 |
| Fc1 – 50 MHz or 1910 MHz <i>whichever is the higher</i> ↔ Fc2 + 50 MHz or 1990 MHz <i>whichever is the lower</i> | -15 dBm | 1 MHz | Specification in accordance with ITU-R SM.329 [1], s4.3 and Annex 7 |
| Fc2 + 50 MHz or 1990 MHz <i>whichever is the lower</i> ↔ Fc2 + 60 MHz or 1990 MHz <i>whichever is the lower</i> | -25 dBm | 1 MHz | Specification in accordance with ITU-R SM.329 [1], s4.3 and Annex 7 |
| Fc2 + 60 MHz or 1990 MHz <i>whichever is the lower</i> ↔ 12,75 GHz | -30 dBm | 1 MHz | Bandwidth as in ITU-R SM.329 [1], s4.1. Upper frequency as in ITU-R SM.329 [1], s2.5 table 1 |

Fc1: Centre frequency of emission of the first 5 MHz channel in an operating band.

Fc2: Centre frequency of emission of the last 5 MHz channel in an operating band.

9.2.2 Co-location with UTRA-FDD BS

This requirement may be applied for the protection of UTRA-FDD BS receivers when UTRA-FDD Repeater and UTRA-FDD BS are co-located. The requirement applies only to the down-link direction of the repeater.

9.2.2.1 Minimum Requirement

The power of any spurious emission shall not exceed:

Table 9.8: UTRA Repeater spurious emissions limits for protection of co-located UTRA FDD BS receiver

| Band | Maximum Level | Measurement Bandwidth | Note |
|---|---------------|-----------------------|------|
| 1920 - 1980MHz For operation in Frequency Bands defined in sub-clause 5.2(a) | -96 dBm | 100 kHz | |
| 1850-1910 MHz For operation in Frequency Bands defined in sub-clause 5.2(b) | -96 dBm | 100kHz | |

9.2.3 Co-existence with GSM 900

9.2.3.1 Operation in the same geographic area

This requirement may be applied for the protection of GSM 900 MS in geographic areas in which both GSM 900 and UTRA-FDD Repeaters are deployed.

9.2.3.1.1 Minimum Requirement

The power of any spurious emission shall not exceed:

Table 9.9: UTRA Repeater spurious emissions limits in geographic coverage area of GSM 900 MS receiver

| Band | Maximum Level | Measurement Bandwidth | Note |
|---------------|---------------|-----------------------|------|
| 921 - 960 MHz | -79 dBm | 100 kHz | |

9.2.3.2 Co-located Repeaters and GSM 900 base stations

This requirement may be applied for the protection of GSM 900 BTS receivers when GSM 900 BTS and UTRA-FDD Repeaters are co-located.

9.2.3.2.1 Minimum Requirement

The power of any spurious emission shall not exceed:

Table 9.10: UTRA Repeater spurious emissions limits for Repeater co-located with GSM 900 BTS receiver

| Band | Maximum Level | Measurement Bandwidth | Note |
|-------------|---------------|-----------------------|------|
| 876-915 MHz | -98 dBm | 100 kHz | |

9.2.4 Co-existence with DCS 1800

9.2.4.1 Operation in the same geographic area

This requirement may be applied for the protection of DCS 1800 MS in geographic areas in which both DCS 1800 and UTRA-FDD Repeaters are deployed.

9.2.4.1.1 Minimum Requirement

The power of any spurious emission shall not exceed:

Table 9.11: UTRA Repeater spurious emissions limits in geographic coverage area of DCS 1800 MS receiver

| Band | Maximum Level | Measurement Bandwidth | Note |
|-----------------|---------------|-----------------------|------|
| 1805 - 1880 MHz | -71 dBm | 100 kHz | |

9.2.4.2 Co-located Repeaters and DCS 1800 base stations

This requirement may be applied for the protection of DCS 1800 BTS receivers when DCS 1800 BTS and UTRA-FDD Repeaters are co-located.

9.2.4.2.1 Minimum Requirement

The power of any spurious emission shall not exceed:

Table 9.12: UTRA Repeater spurious emissions limits for Repeater co-located with DCS 1800 BTS

| Band | Maximum Level | Measurement Bandwidth | Note |
|-----------------|---------------|-----------------------|------|
| 1710 - 1785 MHz | -98 dBm | 100 kHz | |

9.2.5 Co-existence with PHS

This requirement may be applied for the protection of PHS in geographic areas in which both PHS and UTRA-FDD Repeaters are deployed.

9.2.5.1 Minimum Requirement

The power of any spurious emission shall not exceed:

Table 9.13: UTRA Repeater spurious emissions limits for in geographic coverage area of PHS

| Band | Maximum Level | Measurement Bandwidth | Note |
|---------------------|---------------|-----------------------|------|
| 1893,5 - 1919,6 MHz | -41 dBm | 300 kHz | |

9.2.6 Co-existence with UTRA-TDD

9.2.6.1 Operation in the same geographic area

This requirement may be applied to geographic areas in which both UTRA-TDD and UTRA-FDD Repeaters are deployed. The requirement applies only to the down-link direction of the repeater.

9.2.6.1.1 Minimum Requirement

The power of any spurious emission shall not exceed:

Table 9.14: UTRA Repeater spurious emissions limits in geographic coverage area of UTRA-TDD

| Band | Maximum Level | Measurement Bandwidth | Note |
|-----------------|---------------|-----------------------|------|
| 1900 - 1920 MHz | -52 dBm | 1 MHz | |
| 2010 - 2025 MHz | -52 dBm | 1 MHz | |

9.2.6.2 Co-located Repeaters and UTRA-TDD base stations

This requirement may be applied for the protection of UTRA-TDD BS receivers when UTRA-TDD BS and UTRA-FDD Repeater are co-located. The requirement applies only to the down-link direction of the repeater.

9.2.6.2.1 Minimum Requirement

The power of any spurious emission shall not exceed:

Table 9.15: UTRA Repeater Spurious emissions limits for protection of co-located UTRA TDD BS receiver

| Band | Maximum Level | Measurement Bandwidth | Note |
|-----------------|---------------|-----------------------|------|
| 1900 - 1920 MHz | -86 dBm | 1 MHz | |
| 2010 - 2025 MHz | -86 dBm | 1 MHz | |

10 Modulation accuracy

10.1 Error Vector Magnitude

The modulation accuracy is defined by the Error Vector Magnitude (EVM), which is a measure of the difference between the theoretical waveform and a modified version of the measured waveform. This difference is called the error vector. The measured waveform is modified by first passing it through a matched root raised cosine filter with bandwidth 3.84 MHz and roll-off $\alpha=0.22$. The waveform is then further modified by selecting the frequency, absolute phase, absolute amplitude and chip clock timing so as to minimise the error vector. The EVM result is defined as root of the ratio of the mean error vector power to the mean reference signal power expressed as a %.

The measurement interval is one power control group (timeslot). The repeater shall operate with an ideal WCDMA signal in the operating band of the repeater at a level, which produce the maximum rated output power per channel, as specified by the manufacturer.

10.1.1 Minimum requirement

The Error Vector Magnitude shall not be worse than 12,5 %.

10.2 Peak code domain error

The peak code domain error is computed by projecting the power of the error vector (as defined in subclause 10.1) onto the code domain at a specified spreading factor. The code domain error for every code in the domain is defined as the ratio of the mean power of the projection onto that code, to the mean power of the composite reference waveform. This ratio is expressed in dB. The peak code domain error is defined as the maximum value for the code domain error for all codes. The measurement interval is one power control group (timeslot).

10.2.1 Minimum requirement

The peak code domain error shall not exceed -35 dB at spreading factor 256.

11 Input Intermodulation

The input intermodulation is a measure of the capability of the repeater to inhibit the generation of interference in the operating band, in the presence of interfering signals on frequencies other than the operating band.

11.1 General Requirement

The following requirement applies for interfering signals in the frequency bands defined in sub-clause 5.1(a) or 5.1(b), depending on the repeaters operating band. The requirement shall be met with the repeater operating at maximum gain.

11.1.1 Minimum requirement

For the parameters specified in table 11.1, the power in the operating band, shall not increase with more than 10 dB at the output of the repeater as measured in the centre of the operating band, compared to the level obtained without interfering signals applied.

The frequency separation between the two interfering signals shall be adjusted so that the 3rd order intermodulation product is positioned in the centre of the operating band.

Table 11.1 specifies the parameters for two interfering signals, where:

- f_{offset} is the separation between the centre frequency of first or last 5 MHz channel in the operating band and one the interfering signals.

Table 11.1: Input intermodulation requirement

| f_{offset} | Interfering Signal Levels | Type of signals | Measurement bandwidth |
|---------------------|---------------------------|-----------------|-----------------------|
| 3,5 MHz | -40 dBm | 2 CW carriers | 1 MHz |

11.2 Co-location with GSM 900 and/or DCS 1800

The following requirement may be applied when GSM 900 BTS and/or DCS 1800 BTS and UTRA-FDD Repeaters are co-located. The requirement shall be met with the repeater operating at maximum gain.

11.2.1 Minimum requirements

For the parameters specified in table 11.2, the power in the operating band shall not increase with more than 10 dB at the output of the repeater as measured in the centre of the operating band, compared to the level obtained without interfering signals applied.

The frequency separation between the two interfering signals shall be adjusted so that the lowest order intermodulation product is positioned in the centre of the operating band.

NOTE 1: The lowest intermodulation products corresponds to the 4th and 3rd order for the GSM 900 and DCS 1800 bands, respectively.

Table 11.2: Input intermodulation requirements for interfering signals in the GSM 900 and DCS 1800 bands

| Frequency of interfering signals | Interfering Signal Levels | Type of signals | Measurement bandwidth |
|----------------------------------|---------------------------|-----------------|-----------------------|
| 921 - 960 MHz | +16 dBm | 2 CW carriers | 1 MHz |
| 1805 - 1880 MHz | +16 dBm | 2 CW carriers | 1 MHz |

11.3 Co-existence with GSM 900 and/or DCS 1800

The following requirement may be applied when GSM 900 BTS and/or DCS 1800 BTS and UTRA-FDD Repeaters are co-located. The requirement shall be met with the repeater operating at maximum gain.

11.3.1 Minimum requirements

For the parameters specified in table 11.3, the power in the operating band shall not increase with more than 10 dB at the output of the repeater as measured in the centre of the operating band, compared to the level obtained without interfering signals applied.

The frequency separation between the two interfering signals shall be adjusted so that the lowest order intermodulation product is positioned in the centre of the operating band.

NOTE 1: The lowest intermodulation products corresponds to the 4th and 3rd order for the GSM 900 and DCS 1800 bands, respectively.

Table 11.3: Input intermodulation requirements for interfering signals in the GSM 900 and DCS 1800 bands

| Frequency of interfering signals | Interfering Signal Levels | Type of signals | Measurement bandwidth |
|----------------------------------|---------------------------|-----------------|-----------------------|
| 876 - 915 MHz | -15 dBm | 2 CW carriers | 1 MHz |
| 1710 - 1785 MHz | -15 dBm | 2 CW carriers | 1 MHz |

12 Output intermodulation

The output intermodulation requirement is a measure of the ability of the repeater to inhibit the generation of intermodulation products signals created by the presence of an interfering signal reaching the repeater via the output port.

The output intermodulation level is the power of the intermodulation products when a WCDMA modulated interference signal is injected into the output port at a level of 30 dB lower than that of the wanted signal. The frequency of the interference signal shall be ± 5 MHz, ± 10 MHz and ± 15 MHz offset from the wanted signal, but within the frequency band allocated for UTRA FDD downlink as specified in subclause 4.1.

The requirement is applicable for downlink signals.

12.1 Minimum requirement

The output intermodulation level shall not exceed the out of band emission or the spurious emission requirements of section 9.1 and 9.2.

Annex A (informative): Change History

Table A.1: Document history

| | | |
|--------|------------|--|
| V0.0.1 | 2000-05-25 | Document R4-000356 with a suggestion to V0.0.1 of this current specification approved at RAN WG4 #12 |
| V1.0.0 | 2000-09-13 | Inclusion of the text proposals approved by RAN WG4 #13 and submitted to RAN #9 for information. |
| V1.1.0 | 2000-11-24 | Inclusion of the text proposals approved by RAN WG4 #14 |
| V1.2.0 | 2001-01-31 | Inclusion of the text proposals approved by RAN WG4 #15 |
| V1.3.0 | 2001-02-26 | Inclusion of the text proposals approved by RAN WG4 #16 |
| V2.0.0 | 2001-03-08 | Submitted to TSG_RAN#11 for approval |
| V4.0.0 | 2001-03-30 | Approved by TSG RAN #11 |

Table A.2: CRs approved by TSG RAN#13

| RAN Tdoc | Spec | CR | R | Ph | Title | Cat | Curr | New |
|-----------|--------|----|---|-------|---|-----|-------|-------|
| RP-010628 | 25.106 | 1 | | Rel-4 | Editorial changes | F | 4.0.0 | 4.1.0 |
| RP-010628 | 25.106 | 2 | | Rel-4 | Clarification in spectrum emission mask | F | 4.0.0 | 4.1.0 |

Table A.3: Release 5 CR approved by TSG RAN#15

| RAN Tdoc | Spec | CR | R | Ph | Title | Cat | Curr | New | Work Item |
|-----------|--------|----|---|-------|---|-----|-------|-------|------------|
| RP-020033 | 25.106 | 4 | | Rel-5 | Correction to units in Spectrum emission mask | F | 4.2.0 | 5.0.0 | RInImp-REP |

Table A.4: Release 5 CRs approved by TSG RAN#16

| RAN Tdoc | Spec | CR | R | Ph | Title | Cat | Curr | New | Work Item |
|-----------|--------|----|---|-------|--|-----|-------|-------|------------|
| RP-020292 | 25.106 | 6 | | Rel-5 | Introduction of output intermodulation requirement | A | 5.0.0 | 5.1.0 | RInImp-REP |
| RP-020303 | 25.106 | 7 | | Rel-5 | Correction of ITU-R SM.329 references | F | 5.0.0 | 5.1.0 | TEI5 |

Table A.5: Release 5 CR approved by TSG RAN#17

| RAN Tdoc | Spec | CR | R | Ph | Title | Cat | Curr | New | Work Item |
|-----------|--------|----|---|-------|------------------|-----|-------|-------|------------|
| RP-020483 | 25.106 | 9 | 1 | Rel-5 | Out of band gain | A | 5.1.0 | 5.2.0 | RInImp-REP |

Table A.6: Release 5 CRs approved by TSG RAN#18

| RAN Tdoc | Spec | CR | R | Ph | Title | Cat | Curr | New | Work Item |
|-----------|--------|-----|---|-------|--|-----|-------|-------|----------------------|
| RP-020861 | 25.106 | 010 | | Rel-5 | EVM Test: Change requirement for the use of HSDPA. | A | 5.2.0 | 5.3.0 | RInImp-REP, HSDPA-RF |
| RP-020795 | 25.106 | 012 | 1 | Rel-5 | Input intermodulation: Correction of co-location and addition of co-existence | A | 5.2.0 | 5.3.0 | RInImp-REP |
| RP-020785 | 25.106 | 016 | | Rel-5 | Aligning of the requirement for "Output power" in extreme conditions with TS25.143 | A | 5.2.0 | 5.3.0 | RInImp-REP |
| RP-020794 | 25.106 | 018 | | Rel-5 | Out of band gain | A | 5.2.0 | 5.3.0 | RInImp-REP |

History

| Document history | | |
|-------------------------|----------------|-------------|
| V5.0.0 | March 2002 | Publication |
| V5.1.0 | June 2002 | Publication |
| V5.2.0 | September 2002 | Publication |
| V5.3.0 | December 2002 | Publication |
| | | |