

ETSI TS 125 327 V10.0.0 (2014-01)



Technical Specification

**Universal Mobile Telecommunications System (UMTS);
High Speed Packet Access (HSPA);
Requirements on User Equipments (UEs)
supporting a release-independent frequency band
and multi-carrier configuration
(3GPP TS 25.327 version 10.0.0 Release 10)**



Reference

RTS/TSGR-0225327va00

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations	5
3.1 Definitions	5
3.2 Abbreviations	5
4 DB-DC-HSDPA configurations independent of release	6
4.1 Void.....	6
4.2 Void.....	6
5 4C-HSDPA configurations independent of release	6
5.1 Single-band contiguous configurations	6
5.1.1 4C-HSDPA configuration II-3	6
5.1.1.1 RF requirements	6
5.1.1.2 Signalling requirements	6
5.1.2 4C-HSDPA configuration II-4	6
5.1.2.1 RF requirements	7
5.1.2.2 Signalling requirements	7
5.2 Dual-band configurations	7
5.2.1 4C-HSDPA configuration I-2-VIII-2.....	7
5.2.1.1 RF requirements	7
5.2.1.2 Signalling requirements	7
5.2.2 4C-HSDPA configuration I-1-VIII-2.....	8
5.2.2.1 RF requirements	8
5.2.2.2 Signalling requirements	8
5.2.3 4C-HSDPA configuration II-1-V-2	8
5.2.3.1 RF requirements	8
5.2.3.2 Signalling requirements	9
Annex A (informative): Change history	10
History	11

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies requirements on UEs supporting a DB-DC-HSDPA and 4C-HSDPA configuration that is independent of release. TSG-RAN has agreed that the standardisation of new configurations may be independent of a release. However, in order to implement a UE that conforms to a particular release but supports a configuration that is specified in a later release, it is necessary to specify some extra requirements.

For example, Band I-XI combination for DB-DC-HSDPA (referred to as DB-DC-HSDPA configuration 4 in [2]) is contained in the Release 10 specifications. In order to implement a UE conforming to Release 9 but supporting this configuration, it is necessary for the UE to additionally conform to some parts of the Release 10 specifications, such as the radio frequency and radio resource management requirements for the configuration.

Similarly, 4C-HSDPA configuration I-3 is contained in the Release 11 specification [3]. In order to implement a UE conforming to Release 10, but supporting this configuration, it is necessary for the UE to additionally conform to some parts of the Release 11 specifications.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

[2] 3GPP TS 25.101 (Release 10): "User Equipment (UE) radio transmission and reception (FDD)".

[3] 3GPP TS 25.101 (Release 11): "User Equipment (UE) radio transmission and reception (FDD)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

DB-DC-HSDPA Dual Band Dual Cell HSDPA
4C-HSDPA Four-carrier HSDPA

4 DB-DC-HSDPA configurations independent of release

4.1 Void

4.2 Void

5 4C-HSDPA configurations independent of release

5.1 Single-band contiguous configurations

5.1.1 4C-HSDPA configuration II-3

4C-HSDPA configuration II-3, i.e. 3 adjacent carriers in Band II, is specified in Release 11 in [3] but is defined as a release-independent configuration. This approach aligns 4C-HSDPA configuration II-3 with other 4C-HSDPA configurations when considering features that have to be supported in different releases.

UEs that conform to Release 10 and support 4C-HSDPA configuration II-3 shall support the following requirements of Release 11.

5.1.1.1 RF requirements

The UE shall comply with the RF requirements for 4C-HSDPA configuration II-3, as specified in [3]. These requirements are:

Table 5.1.1.1-1: RF Requirements for 4C-HSDPA Configuration II-3 UE

Section / Clause	Description
5.2	Frequency bands
6.2.1	UE maximum transmit power
7.3	Reference sensitivity level
7.4	Maximum input level
7.5	Adjacent channel selectivity
7.6	Blocking characteristics
7.7	Spurious response
7.8	Intermodulation characteristics

5.1.1.2 Signalling requirements

There are no additional signaling requirements of later releases.

5.1.2 4C-HSDPA configuration II-4

4C-HSDPA configuration II-4, i.e. 4 adjacent carriers in Band II, is specified in Release 11 in [3] but is defined as a release-independent configuration. This approach aligns 4C-HSDPA configuration II-4 with other 4C-HSDPA configurations when considering features that have to be supported in different releases.

UEs that conform to Release 10 and support 4C-HSDPA configuration II-4 shall support the following requirements of Release 11.

5.1.2.1 RF requirements

The UE shall comply with the RF requirements for 4C-HSDPA configuration II-4, as specified in [3]. These requirements are:

Table 5.1.2.1-1: RF Requirements for 4C-HSDPA Configuration II-4 UE

Section / Clause	Description
5.2	Frequency bands
6.2.1	UE maximum transmit power
7.3	Reference sensitivity level
7.4	Maximum input level
7.5	Adjacent channel selectivity
7.6	Blocking characteristics
7.7	Spurious response
7.8	Intermodulation characteristics

5.1.2.2 Signalling requirements

There are no additional signaling requirements of later releases.

5.2 Dual-band configurations

5.2.1 4C-HSDPA configuration I-2-VIII-2

4C-HSDPA configuration I-2-VIII-2, i.e. 2+2 carriers in Band I-VIII combination, is specified in Release 11 in [3] but is defined as a release-independent configuration. This approach aligns 4C-HSDPA configuration I-2-VIII-2 with other 4C-HSDPA configurations when considering features that have to be supported in different releases.

UEs that conform to Release 10 and support 4C-HSDPA configuration I-2-VIII-2 shall support the following requirements of Release 11.

5.2.1.1 RF requirements

The UE shall comply with the RF requirements for 4C-HSDPA configuration I-2-VIII-2, as specified in [3]. These requirements are:

Table 5.2.1.1-1: RF Requirements for 4C-HSDPA Configuration I-2-VIII-2 UE

Section / Clause	Description
5.2	Frequency bands
6.2.1	UE maximum transmit power
7.3	Reference sensitivity level
7.4	Maximum input level
7.5	Adjacent channel selectivity
7.6	Blocking characteristics
7.7	Spurious response
7.8	Intermodulation characteristics
7.10	Reference input power adjustment for a dual band device

5.2.1.2 Signalling requirements

There are no additional signaling requirements of later releases.

5.2.2 4C-HSDPA configuration I-1-VIII-2

4C-HSDPA configuration I-1-VIII-2, i.e. 1+2 carriers in Band I-VIII combination, is specified in Release 11 in [3] but is defined as a release-independent configuration. This approach aligns 4C-HSDPA configuration I-1-VIII-2 with other 4C-HSDPA configurations when considering features that have to be supported in different releases.

UEs that conform to Release 10 and support 4C-HSDPA configuration I-1-VIII-2 shall support the following requirements of Release 11.

5.2.2.1 RF requirements

The UE shall comply with the RF requirements for 4C-HSDPA configuration I-1-VIII-2, as specified in [3]. These requirements are:

Table 5.2.2.1-1: RF Requirements for 4C-HSDPA Configuration I-1-VIII-2 UE

Section / Clause	Description
5.2	Frequency bands
6.2.1	UE maximum transmit power
7.3	Reference sensitivity level
7.4	Maximum input level
7.5	Adjacent channel selectivity
7.6	Blocking characteristics
7.7	Spurious response
7.8	Intermodulation characteristics
7.10	Reference input power adjustment for a dual band device

5.2.2.2 Signalling requirements

There are no additional signaling requirements of later releases.

5.2.3 4C-HSDPA configuration II-1-V-2

4C-HSDPA configuration II-1-V-2, i.e. 1+2 carriers in Band II-V combination, is specified in Release 11 in [3] but is defined as a release-independent configuration. This approach aligns 4C-HSDPA configuration II-1-V-2 with other 4C-HSDPA configurations when considering features that have to be supported in different releases.

UEs that conform to Release 10 and support 4C-HSDPA configuration II-1-V-2 shall support the following requirements of Release 11.

5.2.3.1 RF requirements

The UE shall comply with the RF requirements for 4C-HSDPA configuration II-1-V-2, as specified in [3]. These requirements are:

Table 5.2.3.1-1: RF Requirements for 4C-HSDPA Configuration II-1-V-2 UE

Section / Clause	Description
5.2	Frequency bands
6.2.1	UE maximum transmit power
7.3	Reference sensitivity level
7.4	Maximum input level
7.5	Adjacent channel selectivity
7.6	Blocking characteristics
7.7	Spurious response
7.8	Intermodulation characteristics
7.10	Reference input power adjustment for a dual band device

5.2.3.2 Signalling requirements

There are no additional signaling requirements of later releases.

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2013-11					Skeleton report based on 25.317 contents	-	1.0.0
2013-12	RP-62	RP-131629			TS 25.327 approved by RAN #62	1.0.0	9.0.0
	RP-62	RP-131980	0001	1	Introduction of TS 25.327	9.0.0	10.0.0

History

Document history		
V10.0.0	January 2014	Publication