
# ETSI TS 126 115 V5.0.0 (2002-06)

**Technical Specification** 

Universal Mobile Telecommunications System (UMTS); Echo control for speech and multi-media services (3GPP TS 26.115 version 5.0.0 Release 5)



Reference RTS/TSGS-0426115v500

> Keywords UMTS

#### ETSI

#### 650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at http://portal.etsi.org/tb/status/status.asp

> If you find errors in the present document, send your comment to: editor@etsi.fr

#### **Copyright Notification**

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

> © European Telecommunications Standards Institute 2002. All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup> and **UMTS**<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**<sup>TM</sup> and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under www.etsi.org/key .

# Contents

Intelle	ectual Property Rights	2
Forew	vord	2
Forew	vord	4
Introd	luction	4
1	Scope	5
2	References	5
3	Abbreviations	5
4	Interfaces	5
5 5.1	Narrow Band Speech Telephony Network Echo Control GSTN Network Echo Cancellation	6 6
Anne	x A (informative): Change history	7
Histor	ry	8

### Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

### Introduction

The present document specifies minimum performance requirements for the transmission planning aspects of 3G speech and multi-media services.

The objective is to reach a quality as close as possible to ITU-T standards for PSTN circuits. However, due to technical and economic factors, there cannot be full compliance with the general characteristics of international telephone connections and circuits recommended by the ITU-T.

The performance requirements are specified the main body of the text; the test methods and considerations are described in [tbd].

#### 1 Scope

The present document specifies minimum performance requirements for the gateway echo control of 3G speech and multi-media services. The present document is applicable to any narrow band speech telephony or multimedia service.

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] ITU-T Recommendation G.114 (2000): "One-way transmission time".
- [2] ITU-T Recommendation G.168 (2000): "Digital network echo cancellers".
- [3] ITU-T Recommendation G.131 (1996): "Control of talker echo".
- [4] ITU-T Recommendation G.703 (1998): "Physical/electrical characteristics of hierarchical digital interfaces".
- [5] ITU-T Recommendation G.711 (1988): "Pulse code modulation (PCM) of voice frequencies".

#### 3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

Analogue to Digital Converter
Digital to Analogue Converter
Discontinuous Transmission
Echo Canceller
Electrical Echo Control
Echo Loss
Echo Return Loss
Echo Return Loss Enhancement
Pulse Code Modulation
Point of Interconnection (with PSTN)
Public Switched Telephone Network
Terminal Coupling Loss
Transmission

## 4 Interfaces

The POI with the public switched telephone network (PSTN) will generally be at the 2 048 kbits/ level at an interface in accordance with ITU-T Recommendation G.703 [4]/G.704 or STM1 155Mbit/s. At this point, which is considered to have a relative level of 0 dBr, the analogue signals will be represented by 8-bit A-law or  $\mu$ -law according to ITU-T Recommendation G.711 [5]. Analogue measurements may be made at this point using a standard send and receive side, as defined in ITU-T Recommendations.

## 5 Narrow Band Speech Telephony Network Echo Control

#### 5.1 GSTN Network Echo Cancellation

Narrow band speech calls from the 3G mobile system to the public GSTN are terminated on local switch line cards where two to four wire conversion takes place. The hybrid used to carry out this function is never perfect and echo is generated which degrades the speech call quality for the 3G mobile user. To overcome this situation an echo cancellation device should be used at the gateway from the 3G mobile network to the GSTN. This echo control device shall conform to ITU-T G.168 [2].

NOTE: Acoustic Echo Control: Narrow band speech calls from the 3G mobile network to the public GSTN involve a high delay. The only echo path that is audible to the GSTN user is the acoustic echo path in the UE. To overcome this echo a Terminal Coupling Loss (TCL) of 46dB should be achieved by the terminal. This provides adequate echo protection for calls up to a delay of 300ms as defined by ITU-T Recommendation G.131 [3].

# Annex A (informative): Change history

	Change history					
TSG SA#	Version	CR	Tdoc SA	New Version	Subject/Comment	
SA07	3.0.0	-	SP-000020	3.0.0	Approved at TSG SA #7 and placed under Change Control	

	Change history						
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
03-2001	11				Version for Release 4		4.0.0
06-2002	16				Version for Release 5	4.0.0	5.0.0

# History

	Document history					
V5.0.0	June 2002	Publication				