

ETSI TS 129 277 V8.3.0 (2009-10)

Technical Specification

Universal Mobile Telecommunications System (UMTS); LTE; Optimized Handover Procedures and Protocols between EUTRAN Access and 1xRTT Access (3GPP TS 29.277 version 8.3.0 Release 8)



Reference

RTS/TSGC-0429277v830

Keywords

LTE, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations	5
3.1 Definitions	5
3.2 Abbreviations	5
4 General	6
4.1 Introduction	6
4.2 S102 Requirements.....	6
5 S102 Header	6
6 S102 Messages and Message Formats	6
6.1 Introduction	6
6.1 Message Formats.....	6
6.2 S102 Messages	6
6.2.1 A21-1x Air Interface Signalling message.....	6
6.2.2 A21-Ack message.....	7
6.2.3 A21-Event Notification.....	7
6.3 Reliable Delivery of Signalling Messages.....	7
6.4 Information Elements	7
6.4.1 Information Element Assignments	7
6.4.1.1 A21 Message Type.....	7
6.4.1.2 Correlation ID	8
6.4.1.3 Mobile Identity.....	8
6.4.1.4 Void.....	8
6.4.1.5 Authentication Challenge Parameter (RAND)	8
6.4.1.6 A21 Mobile Subscription Information	8
6.4.1.7 Cause.....	8
6.4.1.8 A21-Event	9
6.4.1.9 GCSNA PDU	9
6.4.1.10 GCSNA Status	9
6.4.1.11 Reference Cell ID.....	9
6.4.1.12 Pilot List.....	9
7 Error Handling.....	9
7.1 Protocol Errors	9
7.2 Restoration and Recovery	9
8 Security provided to Communication over the S102 Interface	10
9 S102 Parameters	10
9.1 Timers	10
9.1.1 Introduction.....	10
9.1.2 Acknowledgement Timer (Tack).....	10
Annex 1 (informative): Change history	11
History	12

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies the stage 3 of the Evolved Packet System S102 interface between the MME and the 1x CS IWS to relay the 1xCS signalling messages documented in 3GPP TS 23.216 [2]. 1x CS signalling messages are those messages that are defined for A21 interface as described in 3GPP2 A.S0008-C [3]. The S102 interface messages shall be based on A21 messages.

The S102 interface is used to support UEs that do not transmit and receive on both the LTE and 1x radio interfaces simultaneously. S102 protocol aspects for SRVCC from E-UTRAN access to 3GPP2 1xCS is covered in this specification. Handling of non-voice component and protocol aspects for SRVCC from 3GPP2 1xCS to E-UTRAN direction is not specified in this release.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.216: "Single Radio Voice Call Continuity (SRVCC)".
- [3] 3GPP2 A.S0008-C: "Interoperability Specification (IOS) for High Rate Packet Data (HRPD) Radio Access Network Interfaces with Session Control in the Access Network".
- [4] 3GPP TS 23.272: "Circuit Switched Fallback in Evolved Packet System"

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

1xCS IWS	1xCS Interworking Solution
GCSNA	Generic Circuit Services Notification Application
IMSI	International Mobile Station Identity
IP	Internet Protocol
MEID	Mobile Equipment Identity
MME	Mobility Management Entity

PDU	Protocol Data Unit
SRVCC	Single Radio Voice Call Continuity
UDP	User Datagram Protocol

4 General

4.1 Introduction

The S102 application is based on UDP/IP transport medium.

S102 (MME-to-IWS) /udp/xxxx - This is the registered destination UDP port number to be used for signalling interconnection between an MME and an IWS.

Editor's Note: The port number needs to be allocated by IANA

The S102 interface allows CS fallback to 1xRTT to establish voice call in the CS domain through support of registration over EPS procedures as specified in 3GPP TS 23.272[4].

4.2 S102 Requirements

There are no additional requirements to those defined in 3GPP TS 23.216 [2] and 3GPP2 A.S0008-C [3].

5 S102 Header

The S102 message header shall be a fixed length header. The S102 header shall be at least 7 octets long. Octet 1 consists of A21 Message type and Octets 2-7 contain the Correlation Identifier.

Detailed information about the coding and format of the header fields of the A21 messages is specified in 3GPP2 A.S0008-C [3].

6 S102 Messages and Message Formats

6.1 Introduction

The S102 application defines a set of messages between the MME and 1xCS IWS to provide SR VCC and CSFB. The messages to be used are described in the following sections.

The S102 messages shall be based on A21 messages. The following A21 messages shall be used to support interworking and CS fallback to 1x RTT procedures between MME and 1xCS IWS.

6.1 Message Formats

6.2 S102 Messages

6.2.1 A21-1x Air Interface Signalling message

This message is A21-1x air interface signalling message specified in 3GPP2 A.S0008-C [3]. This message shall be sent from an MME or 1xCS IWS to transport 1x air interface message to the peer 1xCS IWS or MME.

The MME shall be provisioned to be able to reach a 1XCS IWS over the S102 interface. The IWS shall then decide which MSC to contact. The MME selects the 1XCS IWS based on the Reference Cell ID that it receives via the eNodeB.

This message shall be used by the MME or 1xCS IWS during Registration, paging, handover (SRVCC) procedures, and mobile originated and mobile terminated SMS procedures.

When the MME receives a 1x air interface message from the UE that is to be sent to 1xCS IWS, the MME encapsulates the 1x air interface message in a A21-1x air interface signalling message and sends it to the 1xCS IWS via the S102 interface. To support CS fallback to 1xRTT registration procedures, it contains the CDMA 2000 sector ID.

When sent from the 1xCS IWS to the MME, the 1xCS IWS encapsulates the 1x handoff direction message or 1xRTT CS paging request (after successful registration for CS fallback to 1xRTT) into A21-1x air interface signalling message.

Details about Information Element contents of A21-1x Air Interface signalling messages are found in 3GPP2 A.S0008-C [3] section 5.1.6.1.

6.2.2 A21-Ack message

This message is A21-Ack message specified in 3GPP2 A.S0008-C [3]. This message shall be sent from an MME or 1xCS IWS to acknowledge receipt of some A21 message to the peer 1xCS IWS or MME.

The Correlation ID in a A21-Ack message shall be copied from the request message that the MME or 1xCS IWS is replying to.

Details about Information Element contents of S102-Ack message are found in 3GPP2 A.S0008-C [3] section 5.1.6.2.

6.2.3 A21-Event Notification

This message is A21-Event Notification message specified in 3GPP2 A.S0008-C [3]. This message shall be sent by either MME or 1xCS IWS to notify the peer node of a specific event.

To support S102 tunnel redirection in case of MME relocation, "S102 Redirection" value shall be used.

To support notifying the 1xCS IWS, specifically if the UE switches off or if the MME changes the UE EMM state to EMM-DEREGISTERED, i.e. if the UE becomes unreachable, the "Power Down/Connection Closed Event" value shall be used.

Details about Information Element contents of S102-Event Notification message are found in 3GPP2 A.S0008-C [3] section 5.1.6.4.

6.3 Reliable Delivery of Signalling Messages

The A21 messages are transmitted using best-effort service.

6.4 Information Elements

6.4.1 Information Element Assignments

An A21 message may contain several information elements. Detailed information about the contents of the A21 messages is specified in 3GPP2 A.S0008-C [3]. The following sections highlight the relevant S102 specific parameters.

6.4.1.1 A21 Message Type

This IE is used to indicate the type of message on S102 interface. Typical values of this IE are as follows:

Table 6.4.1.1-1: A21 Message Type on S102 interface

Message Type	A21 Message Name
01H	A21-1x Air Interface Signalling message
02H	A21-Ack message
04H	A21-Event Notification message

6.4.1.2 Correlation ID

This IE is used to correlate the A21 messages transported across the S102 interface. Details of format and content of this IE are specified in 3GPP2 A.S0008-C [3].

6.4.1.3 Mobile Identity

This IE is used to identify the UE's identity. Details of format of this IE are specified in 3GPP2 A.S0008-C [3]. Typical values of this IE relevant for S102 are as follows.

Table 6.4.1.3-1: Mobile identity

Binary Values	MN-Id
"001"	MEID
"110"	IMSI
All other values are reserved	

ESN value shall not be used for S102 messages.

6.4.1.4 Void

6.4.1.5 Authentication Challenge Parameter (RAND)

This IE contains information used for authentication over S102 interface. Details of format and contents of this IE are specified in 3GPP2 A.S0008-C [3].

6.4.1.6 A21 Mobile Subscription Information

This IE includes mobile subscription information records. Details of format and contents of this IE are specified in 3GPP2 A.S0008-C [3].

6.4.1.7 Cause

In a response, the Cause Value indicates the acceptance or the rejection of the corresponding request. The Cause value shall be included in the response message. Typical values of IE relevant for S102 are as follows:

Table 6.4.1.7: Cause values for the corresponding request

Values	Cause value meaning
00H	Unknown mobile
01H	Unknown cell identifier(s)
02H	Tunnelling of 1x messages not available
03H	Resources not available
07H	Unspecified
08H	Rejection
0AH	Abort handoff from LTE to 1x
0BH	Version not supported
All other values are reserved	

6.4.1.8 A21-Event

This IE contains the value used to indicate the event that has occurred. Typical values of IE relevant for S102 are as follows:

6.4.1.8-1: A21-Event values

Values	Cause value meaning
03H	UE Power Down/Connection Closed
04H	Handoff Rejected
0BH	S102 Redirection
All other values are reserved	

6.4.1.9 GCSNA PDU

This IE contains the GCSNA header and GCSNA information, which can be 1x LAC encapsulated PDU or any other GCSNA information including 3G1x parameters, to be transported over the S102 interface. The IE is passed transparently for the MME. Details of inclusion rules, format and contents of this IE are specified in 3GPP2 A.S0008-C [3].

6.4.1.10 GCSNA Status

This IE contains the GCSNA status information to be transported over the S102 interface. The IE is passed transparently for the MME. Details of inclusion rules, format and contents of this IE are specified in 3GPP2 A.S0008-C [3].

6.4.1.11 Reference Cell ID

This IE contains the CDMA2000 Sector ID received from S1AP and passed to the MME from the eNB. Details of inclusion rules, format and contents of this IE are specified in 3GPP2 A.S0008-C [3].

6.4.1.12 Pilot List

This IE contains the 1xRTT Pilot List passed to the MME from the eNodeB. It is included by the MME whenever the MME receives the 1xRTT Pilot List from the eNodeB. Details of format and contents of this IE are specified in 3GPP2 A.S0008-C [3].

7 Error Handling

7.1 Protocol Errors

A protocol error is defined as a message with unknown, unforeseen or erroneous content. When the Tack timer expires, the sender may resend the request to the receiver and restart the Tack timer a configurable number of times. A cause value of "Unspecified" as indicated in section 6.4.1.7 shall be included in the response message to indicate protocol errors.

Detailed error handling procedures specific to each A21 message are found in 3GPP2 A.S0008-C [3] section 2.8.2

7.2 Restoration and Recovery

There are no new specific Restoration and recovery requirements to be supported over S102 interface.

8 Security provided to Communication over the S102 Interface

Protection of A21 communication over S102 interface shall be provided according to security mechanisms defined in 3GPP2 A.S0008-C [3]

9 S102 Parameters

9.1 Timers

9.1.1 Introduction

The parameters defined here and their recommended values shall not be fixed, but shall be possible to configure as described in section "Reliable delivery of messages".

The method used for retry sending of messages on S102 shall be based on the A21 retry method. In 3GPP2 A.S0008-C [3] section 2.8.2, the procedures for each of the A21 messages have a "Failure Operation" section where there are references to the use of timers and retries. In addition, there are flows in section 4.6.

9.1.2 Acknowledgement Timer (Tack)

This timer is started when the MME or 1xCS IWS sends an A21-1x Air interface signalling message or a A21 Event Notification message and is stopped when the corresponding A21-Ack message is received from the peer 1xCS IWS or MME.

Further details about recommended timer values and specifics are found in 3GPP2 A.S0008-C [3] section 5.3

Annex 1 (informative): Change history

:Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2008-09	CT#41	CP-080478			V2.0.0 approved in CT#41	2.0.0	8.0.0
2008-12	CT#42	CP-080689	0001		S102 Redirection	8.0.0	8.1.0
2009-06	CT#44	CP-090293	0003		Correlation ID Length	8.1.0	8.2.0
		CP-090293	0004	1	UDP Port Value		
		CP-090293	0005	1	Support for 03H (Power Down/Connection Closed) Event Value		
2009-09	CT#45	CP-090530	0007	1	Power Down/Connection Closed Event	8.2.0	8.3.0
		CP-090536	0008	1	Generic Circuit Services Notification Application on S102		
		CP-090536	0009	1	Reference Cell ID on S102		
		CP-090536	0010	1	Pilot List on S102		

History

Document history		
V8.1.0	January 2009	Publication
V8.2.0	June 2009	Publication
V8.3.0	October 2009	Publication