

# ETSI TS 129 333 V7.1.0 (2007-10)

---

*Technical Specification*

**Universal Mobile Telecommunications System (UMTS);  
Multimedia Resource Function Controller (MRFC) -  
Multimedia Resource Function  
Processor (MRFP) Mp interface;  
Stage 3  
(3GPP TS 29.333 version 7.1.0 Release 7)**

---



---

Reference

RTS/TSGC-0429333v710

---

Keywords

UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2007.  
All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup> and **UMTS**<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members.  
**TIPHON**<sup>TM</sup> and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.  
**3GPP**<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

# Contents

|   |    |
|---|----|
| Intellectual Property Rights .....                      | 2  |
| Foreword.....   | 2  |
| Foreword.....   | 6  |
| 1 Scope .....   | 7  |
| 2 References .....                                      | 7  |
| 3 Definitions and symbols .....                         | 8  |
| 3.1 Definitions .....                                   | 8  |
| 3.2 Symbols.....  | 8  |
| 4. Abbreviations .....                                  | 9  |
| 5 Profile Description .....                             | 9  |
| 5.1 Profile Identification.....                         | 9  |
| 5.2 Summary .....                                       | 9  |
| 5.3 Gateway Control Protocol Version .....              | 10 |
| 5.4 Connection Model .....                              | 10 |
| 5.5 Context Attributes .....                            | 10 |
| 5.6 Terminations.....                                   | 10 |
| 5.6.1 Termination Names.....                            | 10 |
| 5.6.1.1 General .....                                   | 10 |
| 5.6.1.2 ASN.1 encoding .....                            | 11 |
| 5.6.1.3 ABNF encoding .....                             | 11 |
| 5.6.2 Multiplexed Terminations.....                     | 11 |
| 5.7 Descriptors .....                                   | 11 |
| 5.7.1 Stream Descriptor .....                           | 11 |
| 5.7.1.1 LocalControl Descriptor.....                    | 11 |
| 5.7.2 Events Descriptor.....                            | 12 |
| 5.7.3 EventBuffer Descriptor.....                       | 13 |
| 5.7.4 Signals Descriptor.....                           | 13 |
| 5.7.5 DigitMap Descriptor .....                         | 14 |
| 5.7.6 Statistics Descriptor .....                       | 14 |
| 5.7.7 ObservedEvents Descriptor .....                   | 14 |
| 5.7.8 Topology Descriptor .....                         | 14 |
| 5.7.9 Error Descriptor .....                            | 15 |
| 5.8 Command API.....                                    | 15 |
| 5.8.1 Add .....   | 15 |
| 5.8.2 Modify .....                                      | 15 |
| 5.8.3 Subtract.....                                     | 15 |
| 5.8.4 Move.....   | 16 |
| 5.8.5 AuditValue.....                                   | 16 |
| 5.8.6 AuditCapabilities .....                           | 16 |
| 5.8.7 Notify.....                                       | 16 |
| 5.8.8 ServiceChange .....                               | 17 |
| 5.8.9 Manipulating and Auditing Context Attributes..... | 18 |
| 5.9 Generic Command Syntax and Encoding.....            | 18 |
| 5.10 Transactions .....                                 | 18 |
| 5.11 Messages .....                                     | 19 |
| 5.12 Transport .....                                    | 19 |
| 5.13 Security .....                                     | 20 |
| 5.14 Packages.....                                      | 20 |
| 5.14.1 Mandatory Packages .....                         | 20 |
| 5.14.2 Optional Packages .....                          | 21 |
| 5.14.3 Package Usage Information .....                  | 22 |
| 5.14.3.1 Generic Package.....                           | 22 |
| 5.14.3.2 Base Root Package.....                         | 23 |

|           |  |    |
|-----------|--|----|
| 5.14.3.3  | Overload Control Package .....                                 | 24 |
| 5.14.3.4  | Network Package .....  | 24 |
| 5.14.3.5  | RTP Package.....   | 25 |
| 5.14.3.6  | DTMF Detection Package.....                                    | 26 |
| 5.14.3.7  | Call Progress Tones Generator Package .....                    | 27 |
| 5.14.3.8  | Basic Services Tones Generator Package .....                   | 28 |
| 5.14.3.9  | Expanded Call Progress Tones Generator Package.....            | 29 |
| 5.14.3.10 | Basic Announcement Syntax Package .....                        | 29 |
| 5.14.3.11 | Voice Variable Syntax Package .....                            | 30 |
| 5.14.3.12 | Announcement Set Syntax Package.....                           | 30 |
| 5.14.3.13 | General Text Variable Type Package.....                        | 31 |
| 5.14.3.14 | Advanced Audio Server Base Package .....                       | 31 |
| 5.14.3.15 | Basic Call Progress Tones Generator with Directionality.....   | 32 |
| 5.14.3.16 | AAS Recording Package.....                                     | 33 |
| 5.14.3.17 | Multimedia Play Package.....                                   | 34 |
| 5.14.3.18 | Generic Announcement Package .....                             | 34 |
| 5.14.3.19 | Intrusion Tones Generator Package .....                        | 35 |
| 5.14.3.20 | Business Tones Generation Package.....                         | 36 |
| 5.14.3.21 | Conferencing Tones Generation Package .....                    | 36 |
| 5.14.3.22 | Inactivity Timer Package .....                                 | 37 |
| 5.14.3.23 | MGC Information Package .....                                  | 37 |
| 5.14.3.24 | Advanced audio server base package for TTS enhancement .....   | 38 |
| 5.14.3.25 | ASR Package.....   | 39 |
| 5.14.3.26 | Multimedia Recording Package .....                             | 40 |
| 5.15      | Mandatory Support of SDP and Annex C Information Elements..... | 40 |
| 5.16      | Optional support of SDP and Annex C information elements.....  | 42 |
| 5.17      | Procedures .....   | 43 |
| 5.17.1    | Formats and Codes .....  | 43 |
| 5.17.2    | Call Related Procedures.....                                   | 45 |
| 5.17.2.1  | General .....  | 45 |
| 5.17.2.2  | Reserve IMS Termination .....                                  | 47 |
| 5.17.2.3  | Configure Remote IMS Resources.....                            | 47 |
| 5.17.2.4  | Reserve IMS Termination & Configure Remote IMS Resources ..... | 48 |
| 5.17.2.5  | Release IMS Termination .....                                  | 48 |
| 5.17.2.6  | Send Tone .....  | 49 |
| 5.17.2.7  | Stop Tone .....  | 49 |
| 5.17.2.8  | Tone Completed.....  | 50 |
| 5.17.2.9  | Start Announcement.....  | 50 |
| 5.17.2.10 | Stop Announcement .....  | 51 |
| 5.17.2.11 | Announcement Completed.....                                    | 51 |
| 5.17.2.12 | Play TTS .....   | 52 |
| 5.17.2.13 | Stop TTS .....   | 52 |
| 5.17.2.14 | TTS Completed .....  | 52 |
| 5.17.2.15 | Start Audio Record.....  | 53 |
| 5.17.2.16 | Stop Audio Record.....   | 54 |
| 5.17.2.17 | Audio Record Complete.....                                     | 54 |
| 5.17.2.18 | Detect DTMF .....  | 55 |
| 5.17.2.19 | Report DTMF.....   | 55 |
| 5.17.2.20 | Stop DTMF Detection.....                                       | 56 |
| 5.17.2.21 | ASR Request.....   | 56 |
| 5.17.2.22 | ASR Completed .....  | 57 |
| 5.17.2.23 | Stop ASR .....   | 58 |
| 5.17.2.24 | Start Playing Multimedia .....                                 | 58 |
| 5.17.2.25 | Stop Playing Multimedia.....                                   | 59 |
| 5.17.2.26 | Playing Multimedia Completed .....                             | 59 |
| 5.17.2.27 | Start Multimedia Record .....                                  | 60 |
| 5.17.2.28 | Stop Multimedia Record .....                                   | 61 |
| 5.17.2.29 | Multimedia Record Completed .....                              | 61 |
| 5.17.2.30 | Adhoc Audio Conference.....                                    | 62 |
| 5.17.2.31 | Multi-Media Conferencing.....                                  | 62 |
| 5.17.3    | Non-Call Related Procedures.....                               | 62 |
| 5.17.3.1  | General .....  | 62 |

|  |  |           |
|--|--|-----------|
| 5.17.3.2   | MRFP Out Of Service .....                            | 63        |
| 5.17.3.3   | MRFP Communication Up .....                          | 63        |
| 5.17.3.4   | MRFP Register .....                                  | 64        |
| 5.17.3.5   | MRFC Restoration .....                               | 64        |
| 5.17.3.6   | MRFP Re-Register .....                               | 65        |
| 5.17.3.7   | MRFC Ordered Re-register .....                       | 65        |
| 5.17.3.8   | Audit Value .....                                    | 66        |
| 5.17.3.9   | Audit Capabilities .....                             | 66        |
| 5.17.3.10  | Capability Update .....                              | 67        |
| 5.17.3.11  | MRFC Out of Service .....                            | 67        |
| 5.17.3.12  | MRFP Resource Congestion Handling – Activate .....   | 68        |
| 5.17.3.13  | MRFP Resource Congestion Handling – Indication ..... | 68        |
| 5.17.3.14  | Command Rejected .....                               | 68        |
| 5.17.3.15  | MRFP Restoration .....                               | 69        |
| <b>Annex A (normative): The W3C SSML Profile for TTS function.....</b> |  | <b>70</b> |
| A.1  | Introduction .....                                   | 70        |
| A.2  | TTS Profile .....                                    | 70        |
| <b>Annex B (normative): The W3C SRGS Profile for ASR function.....</b> |  | <b>73</b> |
| B.1  | Introduction .....                                   | 73        |
| B.2  | SRGS Profile .....                                   | 73        |
| <b>Annex C (informative): Change history .....</b>                     |  | <b>75</b> |
| History .....  |  | 76        |

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present document describes the protocol to be used on the Multimedia Resource Function Controller (MRFC) – Multimedia Resource Function Processor (MRFP) interface (Mp interface). The IMS architecture is described in 3GPP TS 23.228 [1], the functional requirements are described in 3G TS 23.333 [25]

This specification defines a profile of the Gateway Control Protocol (H.248.1), for controlling Multimedia Resource Function Processor supporting in-band user interaction, conferencing and transcoding for multimedia-services.

The present document is valid for a 3<sup>rd</sup> generation PLMN (UMTS) complying with Release 7 and later.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".
- [2] 3GPP TS 23.002: "Network architecture".
- [3] ITU-T Recommendation H.248.1 (05/2002), Gateway control protocol: Version 2 + Corrigendum 1 (03/2004).
- [4] ITU-T Recommendation H.248.4 (11/2000), Gateway control protocol: Transport over Stream Control Transmission Protocol (SCTP) + Corrigendum 1 (03/2004).
- [5] ITU-T Recommendation H.248.7 (03/2004), Gateway control protocol: Generic announcement package.
- [6] ITU-T Recommendation H.248.9 (03/2002), Gateway control protocol: Advanced media server package.
- [7] ITU-T Recommendation H.248.11 (11/2002), Gateway control protocol: Media gateway overload control package.
- [8] IETF RFC 2960: "Stream Control Transmission Protocol".
- [9] ITU-T Recommendation H.248.14 (03/2002), Gateway control protocol: Inactivity timer package.
- [10] ITU-T Recommendation H.248.16 (11/2002), Gateway control protocol: Enhanced digit collection packages and procedures + Corrigendum 1 (03/2004).
- [11] ITU-T Recommendation H.248.19 (03/2004) Gateway control protocol: Decomposed Multipoint Control Unit, Audio, Video and Data Conferencing package
- [12] ITU-T Recommendation H.248.27 (07/2003), Gateway control protocol: Supplemental Tones package
- [13] ITU-T Recommendation Q.1950 (12/2002), Bearer independent call bearer control protocol.
- [14] ITU-T Recommendation G.711 (11/1988), Pulse code modulation (PCM) of voice frequencies.



- [15] ITU-T Recommendation G.711 Appendix I (09/1999), A high quality low-complexity algorithm for packet loss concealment with G.711.
- [16] ITU-T Recommendation G.711 Appendix I (09/1999), A comfort noise payload definition for ITU-T G.711 use in packet-based multimedia communication systems.
- [17] ITU-T Recommendation E.180 (03/1998), Technical characteristics of tones for the telephone service.
- [18] TS 183 022: Telecommunication and Internet converged Services and Protocols for Advanced Networking (TISPAN); MGC Information Package.
- [19] ES 201 970 Access and Terminals (AT); Public Switched Telephone Networks (PSTN); Harmonized specification of physical and electrical characteristics at a 2-wire analogue presented Network Termination Point (NTP).
- [20] IETF RFC 2327 (1998), SDP: Session Description Protocol.
- [21] IETF RFC 3551(2003), RTP Profile for Audio and Video Conferences with Minimal Control.
  
- [22] IETF RFC 2833 (2000), RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals.
- [23] IETF RFC 4040 (2005), RTP payload format for a 64 kbit/s transparent call.
- [24] IETF RFC 3555 (2003), MIME Type Registration of RTP Payload Formats.
- [25] 3GPP TS 23.333: "Multimedia Resource Function Controller (MRFC) – Multimedia Resource Function Processor (MRFP) Mp interface: Procedures Descriptions."
- [26] ITU-T Recommendation H.248.9a1 (03/2007), "Gateway control protocol: Advanced media server package (draft work in progress)".
- [27] 3GPP TS 29.163: "Interworking between the IM CN subsystem and CS networks – Stage 3".
- [28] W3C Recommendation (September 2004): "Speech Synthesis Markup Language (SSML) Version 1.0".
- [29] W3C Recommendation (September 2004): "Speech Recognition Grammar Specification (SRGS) Version 1.0".

---

## 3 Definitions and symbols

### 3.1 Definitions

For the purposes of the present document, the [following] terms and definitions [given in ... and the following] apply.

**Media Gateway:** See Recommendation H.248.1 [3].

**Media Gateway Controller:** See Recommendation H.248.1 [3].

**MultiMedia Resource Function Controller:** See 3GPP TS 23.002 [2].

**MultiMedia Resource Function Processor:** See 3GPP TS 23.002 [2].

### 3.2 Symbols

None.

## 4. Abbreviations

For the purposes of the present document, the following abbreviations apply:

|       |   |
|-------|---|
| CDR   | Call Data Record                          |
| CN    | Comfort Noise                             |
| CRC   | Cyclic Redundancy Check                   |
| DNS   | Domain Name System                        |
| DTMF  | Dual Tone Multi Frequency                 |
| FEC   | Forward Error Correction                  |
| IP    | Internet Protocol                         |
| IPsec | IP Security                               |
| MGC   | Media Gateway Controller                  |
| MGW   | Media Gateway MID    Message Identifier   |
| MID   | Message Identifier                        |
| MRFC  | MultiMedia Resource Function Controller   |
| MRFP  | MultiMedia Resource Function Processor    |
| OAM   | Operation, Administration and Maintenance |
| OoS   | Out of Service                            |
| PLC   | Packet Loss Concealment                   |
| PT    | Payload Type                              |
| QoS   | Quality of Service                        |
| SCTP  | Stream Control Transmission Protocol      |
| SDP   | Session Description Protocol              |
| SPNE  | Signal Processing Network Equipment       |
| SSRC  | Synchronisation Source                    |
| TCP   | Transmission Control Protocol             |
| TLS   | Transport Layer Security                  |
| TTL   | Time To Live                              |
| UDP   | User Datagram Protocol                    |
| VBD   | Voiceband Data                            |

## 5 Profile Description

**Editor's Note:** this is a draft version of the profile and the settings within the profile have not been fully agreed, further approval is required.

### 5.1 Profile Identification

*The name and version of the profile that is sent in the service change command are:*

**Table 5.1.1: Profile Identification**

|                      |     |
|----------------------|-----|
| <b>Profile name:</b> | MRF |
| <b>Version:</b>      | 1   |

### 5.2 Summary

The profile defined in the present document enables the control of media resource function processors (MRFP) supporting in-band user interaction, conferencing and transcoding for multimedia services.

This Profile describes the minimum mandatory settings and procedures required to fulfil the Media Gateway control requirements for the MRF.

In addition optional settings and procedures are described which fulfil optional features and where supported, the minimum mandatory settings within the optional procedures and packages are identified that must be supported in order to support that feature.

"Optional" or "O" means that it is optional for either the sender or the receiver to implement an element. If the receiving entity receives an optional element that it has not implemented it should send an Error Code (e.g. 445 "Unsupported or Unknown Property", 501 "Not Implemented", etc.). "Mandatory" or "M" means that it is mandatory for the receiver to implement an element. Whether it is mandatory for the sender to implement depends on specific functions; detail of whether elements of the core protocol are mandatory to be sent are defined in the stage 2 procedures, stage 3 procedures and/or the descriptions of individual packages.

The setting or modification of elements described in the profile under the heading "Used in Command" has the meaning that the property can be set/modified with that command. The property may be present in other commands (in order to preserve its value in accordance with ITU-T H.248.1[9]) when those commands are used for other procedures that affect the same descriptor.

## 5.3 Gateway Control Protocol Version

**Version 2** shall be the minimum version supported. Support of this version implies conformance to ITU-T Recommendation H.248 Version 2 [3].

## 5.4 Connection Model

Media Resource Function Processors shall support ephemeral terminations that sink and source IP traffic. This type of H.248 Termination is denoted IP in the following clauses.

**Table 5.4.1: Connection Model**

|   |                         |
|---|-------------------------|
| <b>Maximum number of contexts:</b>  | Provisioned<br>(NOTE 1) |
| <b>Maximum number of terminations per context:</b>  | Unspecified(NOTE 2)     |
| <b>Allowed terminations type combinations in a context:</b>   | Not Applicable          |
| NOTE 1: The actual number of supported contexts can be audited by the MRFC using the MaxNrOfContexts property defined in the Base Root Package.   |                         |
| NOTE 2: Support of 1 termination in a context is the basic requirement for the MRFP e.g. for voice record. 2 terminations in a context is required for transcoding or any inband media detection or insertion whilst an unspecified number terminations may be required if conferencing is supported. |                         |

## 5.5 Context Attributes

**Table 5.5.1: Context Attributes**

| Context Attribute          | Supported | Values Supported |
|----------------------------|-----------|------------------|
| <b>Topology</b>            | Yes       | See § 5.7.8      |
| <b>Priority Indicator</b>  | TBD       | 0-15             |
| <b>Emergency Indicator</b> | No        | Not Applicable   |

## 5.6 Terminations

### 5.6.1 Termination Names

#### 5.6.1.1 General

The Termination ID structure is provisioned in the MRFC and MRFP and is known by the MRFP and the MRFC at or before start up.

With ephemeral IP endpoint bearer types the internal structure of Termination ID is irrelevant for MRFC and MRFP and therefore Termination ID is only a numeric identifier for the termination.

### 5.6.1.2 ASN.1 encoding

The following general structure of TerminationID shall be used:

4 octets shall be used for the termination ID. The following defines the general structure for the termination ID:

**Table 5.6.1.2.1: Termination ID**

|                  |   |
|------------------|---|
| Termination type | X |
|------------------|---|

Termination type:

Length 3 bits

Values:

000 Reserved

001 Ephemeral termination

011 - 110 Reserved

111 Reserved for ROOT termination Id (ROOT Termination Id = 0xFFFFFFFF)

X:

Length 29 bits.

For IP termination, its usage is un-specified.

### 5.6.1.3 ABNF encoding

The following general structure of termination ID shall be used:

TerminationID = "ROOT" / pathName / "\$" / "\*" ; according to ITU-T H.248.1 [xx] Annex B.

## 5.6.2 Multiplexed Terminations

**Table 5.6.2.1: Multiplexed Terminations**

|                                   |    |
|-----------------------------------|----|
| Multiplex Terminations Supported? | NO |
|-----------------------------------|----|

## 5.7 Descriptors

### 5.7.1 Stream Descriptor

**Table 5.7.1.1: Stream Descriptor**

|  |   |                    |
|--|---|--------------------|
| Maximum number of streams per termination type | ALL   | Unspecified (NOTE) |
| NOTE:  | At least 1 stream for each media (e.g. video+audio = 2 streams). If only one stream is applicable, then the MRFC may omit the Stream Descriptor and the MRFP shall assume that StreamID =1. |                    |

#### 5.7.1.1 LocalControl Descriptor

The following tables specify the level of support required with regard to the properties in the local control descriptor.

Table 5.7.1.1.1: Reserve Group and Reserve Value

|   |            | Termination Type | Stream Type  |
|---|------------|------------------|--------------|
| <b>Reserve group used:</b>  | NO (NOTE)  | -                | -            |
| <b>Reserve value used:</b>  | YES(NOTE1) | IP               | Audio, Video |
| NOTE: Support of Reserve Group in case of multiple p-time values requires further studies   |            |                  |              |
| NOTE1: Used for audio streams where RFC2833 is also specified and for conference where participants are invited to join the conference. |            |                  |              |

Table 5.7.1.1.2: Stream Mode

| Termination Type | Stream Type | Allowed StreamMode Values                 |
|------------------|-------------|---|
| ALL except ROOT  | Any         | Send, Receive, Send and Receive, Inactive |

## 5.7.2 Events Descriptor

Table 5.7.2.1: Events Descriptor

|   |                 |                         |                    |
|---|-----------------|-------------------------|--------------------|
| <b>Events settable on termination types and stream types:</b> | Yes             |                         |                    |
| <i>If yes</i>   | <b>Event ID</b> | <b>Termination Type</b> | <b>Stream Type</b> |
|   | g/*             | IP                      | Audio, Video       |
|   | nt/*l           | IP                      | Audio, Video       |
|   | rtp/*           | IP                      | Audio, Video       |
|   | aasrec/*        | IP                      | Audio, Video       |
|   | aasb/*          | IP                      | Audio, Video       |
|   | dd/d0-dd        | IP                      | Audio              |
|   | it/*            | ROOT                    | Not Applicable     |
|   | ocp/mg_overload | ROOT                    | Not Applicable     |
|   | aastts/*        | IP                      | Audio              |
|   | asr/*           | IP                      | Audio              |
|   | mrp/*           | IP                      | Audio              |
|   | mpp/*           | IP                      | Audio              |
|   | vavsp/*         | IP                      | Audio, Video       |

Table 5.7.2.2: Event Buffer Control

|                                   |    |
|-----------------------------------|----|
| <b>Event Buffer Control used:</b> | No |
|-----------------------------------|----|

Table 5.7.2.3: Keep Active

|                                   |     |
|-----------------------------------|-----|
| <b>Keepactive used on events:</b> | Yes |
|-----------------------------------|-----|

Table 5.7.2.4: Embedding in event

|   |    |
|---|----|
| <b>Embedded events in an event descriptor:</b>  | No |
| <b>Embedded signals in an event descriptor:</b> | No |

Table 5.7.2.5: Notify Behaviour

|  |                         |
|--|-------------------------|
| <b>NotifyBehaviour used on events:</b> | NO                      |
| <i>If yes,</i>                         | <b>Supported values</b> |
|  | Not Applicable          |

### 5.7.3 EventBuffer Descriptor

Table 5.7.3.1: Event Buffer

|                                      |    |
|--------------------------------------|----|
| <b>Event Buffer descriptor used:</b> | No |
|--------------------------------------|----|

### 5.7.4 Signals Descriptor

Table 5.7.4.1: Signals dependant on termination or streams

|  |                  |                         |                         |
|--|------------------|-------------------------|-------------------------|
| <b>Signals settable dependant on termination or streams types:</b> | Yes              |                         |                         |
| <i>If yes</i>  | <b>Signal ID</b> | <b>Termination Type</b> | <b>Stream Type / ID</b> |
|  | cg/*             | IP                      | Audio                   |
|  | svrtn/*          | IP                      | Audio                   |
|  | xcg/*            | IP                      | Audio                   |
|  | an/apf           | IP                      | Audio, Video            |
|  | int/*            | IP                      | Audio                   |
|  | biztn/*          | IP                      | Audio                   |
|  | aasrec/*         | IP                      | Audio, Video            |
|  | Aasdc            | IP                      | Audio, Video            |
|  | aasb/*           | IP                      | Audio, Video            |
|  | conftn/*         | All except ROOT         | Audio                   |
|  | Tonegen/*        | IP                      | Audio                   |
|  | bcg/*            | IP                      | Audio                   |
|  | aastts/*         | IP                      | Audio                   |
|  | asr/*            | IP                      | Audio                   |
|  | mrp/*            | IP                      | Audio, video            |
|  | mpp/*            | IP                      | Audio, video            |

Table 5.7.4.2: Signal Lists

|                                 |  |              |
|---------------------------------|--|--------------|
| <b>Signals Lists supported:</b> | Yes  |              |
| <i>If yes</i>                   | <b>Termination Type Supporting Lists</b>         | IP           |
|                                 | <b>Stream Type Supporting lists</b>              | Audio, Video |
|                                 | <b>Maximum number of signals per signal list</b> | Provisioned  |

Table 5.7.4.3: Signal type and duration

|  |                  |                                  |
|--|------------------|----------------------------------|
| <b>Signal type and duration supported?</b> | Yes              |                                  |
| <i>If yes</i>                              | <b>Signal ID</b> | <b>Type or duration override</b> |
|  | ALL              | Both                             |

Table 5.7.4.4: Signal Direction

|                                    |    |
|------------------------------------|----|
| <b>Signal Direction supported:</b> | No |
|------------------------------------|----|

Table 5.7.4.5: Notify completion

|                                     |  |                                     |
|-------------------------------------|--|-------------------------------------|
| <b>Notify completion supported:</b> | Yes  |                                     |
| <i>If yes</i>                       | <b>Signal ID</b>   | <b>Type of completion supported</b> |
|                                     | , svrtn/*, xcg/*, an/*, int/*, biztn/*, conftn/*, tonegen/*, bcg/*, aasb/* | ALL                                 |

Table 5.7.4.6: RequestID Parameter

|                                |     |
|--------------------------------|-----|
| RequestID Parameter Supported: | Yes |
|--------------------------------|-----|

Table 5.7.4.7: Signals played simultaneously

|                                |   |   |
|--------------------------------|---|---|
| Signals played simultaneously: | No  |   |
| If yes                         | Signal Ids that can be played simultaneously: | - |

Table 5.7.4.8: Keep Active

|                             |     |
|-----------------------------|-----|
| Keepactive used on signals: | Yes |
|-----------------------------|-----|

## 5.7.5 DigitMap Descriptor

Table 5.7.5.1: DigitMap Descriptor

|                      |               |           |        |
|----------------------|---------------|-----------|--------|
| DigitMaps supported: | NO            |           |        |
| If yes               | DigitMap Name | Structure | Timers |
|                      |               |           |        |

## 5.7.6 Statistics Descriptor

Table 5.7.6.1: Statistics Descriptor

|                          |      |
|--------------------------|------|
| Statistics supported on: | NONE |
|--------------------------|------|

Table 5.7.6.2: Statistics reported on Subtract

|                                  |                        |                  |             |
|----------------------------------|------------------------|------------------|-------------|
| Statistics reported on Subtract: | No                     |                  |             |
| If yes                           | Statistic IDs Reported | Termination Type | Stream Type |
|                                  |                        |                  |             |

## 5.7.7 ObservedEvents Descriptor

Table 5.7.7.1: ObservedEvents Descriptor

|                                 |     |
|---------------------------------|-----|
| Event detection time supported: | Yes |
|---------------------------------|-----|

## 5.7.8 Topology Descriptor

Table 5.7.8.1: Topology Descriptor

|                  |   |
|------------------|---|
| Allowed triples: | (T1,T2, isolate)<br>(T1,T2, oneway)<br>(T1,T2, bothway) |
|------------------|---|

## 5.7.9 Error Descriptor

**Table 5.7.9.1: Error codes sent by the MRFC**

|   |   |
|---|---|
| <b>Supported H.248.8 Error Codes:</b>             | 400-403, 406, 410, 411, 421, 422, 430, 431, 442, 443, 444, 446, 458, 501-506, 533 |
| <b>Supported Error Codes defined in packages:</b> | All error codes defined in supported packages are supported.                      |

**Table 5.7.9.2: Error codes sent by the MRFP**

|   |   |
|---|---|
| <b>Supported H.248.8 Error Codes:</b>             | 400-411, 412, 421,422,430, 431, 432-435,440,441,442, 471, 500-517, 522-539. |
| <b>Supported Error Codes defined in packages:</b> | All error codes defined in supported packages are supported.                |

## 5.8 Command API

### 5.8.1 Add

**Table 5.8.1.1: Descriptors used by Add request**

|   |   |
|---|---|
| <b>Descriptors used by Add request:</b> | Events, Signals, Media (TerminationState, LocalControl, Local and Remote) |
|---|---|

**Table 5.8.1.2: Descriptors used by Add reply**

|                                       |  |
|---------------------------------------|--|
| <b>Descriptors used by Add reply:</b> | Events, Signals, Media (TerminationState, LocalControl, Local and Remote)Error |
|---------------------------------------|--|

### 5.8.2 Modify

**Table 5.8.2.1: Descriptors used by Modify request**

|  |   |
|--|---|
| <b>Descriptors used by Modify request:</b> | Events, Signals, Media (TerminationState, LocalControl, Local and Remote) |
|--|---|

**Table 5.8.2.2: Descriptors used by Modify reply**

|  |   |
|--|---|
| <b>Descriptors used by Modify reply:</b> | Events, Signals, Media (TerminationState, LocalControl, Local and Remote),Error |
|--|---|

### 5.8.3 Subtract

**Table 5.8.3.1: Descriptors used in Subtract request**

|  |                       |
|--|-----------------------|
| <b>Descriptors used by Subtract request:</b> | Audit (empty) or None |
|--|-----------------------|

**Table 5.8.3.2: Descriptors used in Subtract reply**

|  |      |
|--|------|
| <b>Descriptors used by Subtract reply:</b> | None |
|--|------|



## 5.8.4 Move

**Table 5.8.4.1: Command Move**

|                           |     |
|---------------------------|-----|
| <b>Move command used:</b> | Yes |
|---------------------------|-----|

**Table 5.8.4.2: Descriptor used by Move command**

|  |  |
|--|--|
| <b>Descriptors used by Move Request:</b> | Events, Signals, Media (TerminationState, LocalControl, Local and Remote)        |
| <b>Descriptors used by Move Reply:</b>   | Events, Signals, Media (TerminationState, LocalControl, Local and Remote), Error |

## 5.8.5 AuditValue

**Table 5.8.5.1: Auditvalue**

| <b>Audited Properties:</b>  | <b>Property Name and Identity</b>   | <b>Descriptor</b>            |
|---|---|------------------------------|
| Termination ID  | individual termination<br>- Root (MGW Audit)<br><br>The ServiceState property within the TerminationState descriptor shall not take the value "Test". | Termination State Descriptor |
| Termination ID  | ALL   | Media Descriptor             |
| Termination ID  | MGC information (mgcinfo)   | LocalControl Descriptor      |
| Termination ID  | For Packages:<br>- Root<br>-individualtermination (NOTE1)   | Packages Descriptor (NOTE2)  |
| Termination ID  | None (MGW Audit) :<br>- Root  | Audit (empty) Descriptor     |
| <b>Audited Statistics:</b>  | None  |                              |
| <b>Audited Signals:</b>   | ALL   |                              |
| <b>Audited Events:</b>  | ALL   |                              |
| <b>Package Audit possible:</b>  | Yes   |                              |
| NOTE1: The purpose to audit an individual Termination is to retrieve MGC Information if supported or to determine whether the Hanging Termination Detection package is supported. |   |                              |
| NOTE2: Optional   |   |                              |

## 5.8.6 AuditCapabilities

**Table 5.8.6.1: AuditCapabilities**

| <b>Audited Properties:</b> | <b>Property Name and Identity</b> | <b>Descriptor</b> |
|----------------------------|-----------------------------------|-------------------|
|                            | FFS                               | FFS               |
| <b>Audited Statistics:</b> | None                              |                   |
| <b>Audited Signals:</b>    | None                              |                   |
| <b>Audited Events:</b>     | None                              |                   |

## 5.8.7 Notify

**Table 5.8.7.1: Notify**

|  |                       |
|--|-----------------------|
| <b>Descriptors used by Notify Request or Reply:</b>              | ObservedEvents, Error |
| NOTE : The Error Descriptor shall not be used in Notify Request. |                       |

## 5.8.8 ServiceChange

:

**Table 5.8.8.1: Service Change Methods and Reason sent by MRFC**

| Service Change Methods Supported:   | ServiceChange Reasons supported:                               |
|---|--|
| Restart (NOTE 1)  | "900 Service Restored"<br>"901 Cold Boot",<br>"902 Warm Boot". |
| Graceful (NOTE 1)   | "905 Termination Taken Out Of Service"                         |
| Forced (NOTE 1)   | "905 Termination Taken Out Of Service"                         |
| Handoff (NOTE 1, NOTE 2)  | "903 MGC Directed Change"                                      |
| NOTE : When a Service Change command on the Root termination with a method other than Graceful is sent, the command shall always be sent as the only command in a message. The sending node shall always wait for the reply to a Service Change command on the Root termination with a method other than Graceful before sending further command requests. A Service Change command on the Root termination with method Graceful may be combined with other commands in a single message. |  |
| NOTE 1: ROOT Only.  |  |
| NOTE 2: Not involving more than 1 MRFC. No support of handoff relates to a network deployment scenario with "primary H.248 systems only", which translates to no geographic redundancy of the MRFC.   |  |

**Table 5.8.8.2: Service Change Methods and Reason sent by MRFP:**

| Service Change Methods Supported:   | ServiceChange Reasons supported:                                |
|---|---|
| Restart (NOTE 1)  | "900 Service Restored",<br>"901 Cold Boot",<br>"902 Warm Boot". |
| Graceful (NOTE 1)   | "908 MG Impending Failure "                                     |
| Forced (NOTE 1)   | "905 Termination Taken Out Of Service"                          |
| Handoff (NOTE 1, NOTE 2)  | "903 MGC Directed Change"                                       |
| Failover (NOTE 3)   | "909 MGC Impending Failure"                                     |
| Disconnected (NOTE 1)   | "900 Service Restored"  |
| NOTE : When a Service Change command on the Root termination with a method other than Graceful is sent, the command shall always be sent as the only command in a message. The sending node shall always wait for the reply to a Service Change command on the Root termination with a method other than Graceful before sending further command requests. A Service Change command on the Root termination with method Graceful may be combined with other commands in a single message. |   |
| NOTE 1: ROOT only.  |   |
| NOTE 2: In response to a MGC Ordered Re-Register  |   |
| NOTE 3: Only for TISPAN NGN MRF. Not involving more than 1 MRFP. No support of handoff relates to a network deployment scenario with "primary H.248 systems only", which translates to no geographic redundancy of the MGW.   |   |

**Table 5.8.8.3: Service Change Address**

|                            |    |
|----------------------------|----|
| ServiceChangeAddress used: | No |
|----------------------------|----|

**Table 5.8.8.4: Service Change Delay**

|                          |                      |
|--------------------------|----------------------|
| ServiceChangeDelay used: | No                   |
| If yes                   | Valid time period: - |

**Table 5.8.8.5: Service Change Incomplete Flag**

|                                     |    |
|-------------------------------------|----|
| ServiceChange Incomplete Flag used: | No |
|-------------------------------------|----|

**Table 5.8.8.6: Service Change Version**

|  |   |
|--|---|
| <b>Version used in ServiceChangeVersion:</b> | 2 |
|--|---|

**Table 5.8.8.7: Profile negotiation**

|   |    |
|---|----|
| <b>Profile negotiation as per H.248.18:</b> | No |
|---|----|

## 5.8.9 Manipulating and Auditing Context Attributes

**Table 5.8.9.1: Manipulating and Auditing Context Attributes**

|  |   |
|--|---|
| <b>Context Attributes Manipulated:</b> | ALL supported attributes (See table 5.5/1.) |
| <b>Context Attributes Audited:</b>     | ALL supported attributes (See table 5.5/1)  |

## 5.9 Generic Command Syntax and Encoding

**Table 5.9.1: Encoding**

|                             |   |
|-----------------------------|---|
| <b>Supported Encodings:</b> | Binary (optional)<br>Text (optional)<br>The receiver shall support: <ul style="list-style-type: none"> <li>• Short Token Notation</li> <li>• Long Token Notation</li> </ul> |
|-----------------------------|---|

## 5.10 Transactions

**Table 5.10.1: Transactions**

|   |    |
|---|----|
| <b>Maximum number of Transaction Requests / Replies / TransResponseAcks / Segment Replies per message:</b>  | 10 |
| NOTE : When more than one element are conveyed in one message, it is recommended that this message comprises a Transaction Request / Transaction Reply / Transaction Pending plus a Transaction Response Ack. |    |

**Table 5.10.2: Segmentation**

|  |  |
|--|--|
| <b>Segmentation Supported:</b>   | UDP : No<br>SCTP : Inherent in transport |
| NOTE: The H.248 Segmentation Package according Annex E.14 of H.248.1 Version 3 is intended for H.248 transport technologies without the capability of automatic message segmentation. This method is not required for UDP- or SCTP-based H.248 signalling transport in this Profile. |  |

**Table 5.10.3: Commands per Transaction Request**

|  |           |
|--|-----------|
| <b>Maximum number of commands per Transaction request:</b> | Unlimited |
|--|-----------|

**Table 5.10.4: Commands per Transaction Reply**

|  |           |
|--|-----------|
| <b>Maximum number of commands per Transaction reply:</b> | Unlimited |
|--|-----------|

Table 5.10.5: Optional Commands

|  |     |
|--|-----|
| <b>Commands able to be marked "Optional":</b>  | ALL |
| NOTE: The meaning of this table is that if one of the listed commands failed then the possibly present subsequent command within the same transaction will be processed. |     |

Table 5.10.6: Transaction Timers

| Transaction Timer:               | Value       |
|----------------------------------|-------------|
| NormalMGExecutionTime            | Provisioned |
| NormalMGCExecutionTime           | Provisioned |
| MGOriginatedPendingLimit         | Provisioned |
| MGCOriginatedPendingLimit        | Provisioned |
| MGProvisionalResponseTimerValue  | Provisioned |
| MGCProvisionalResponseTimerValue | Provisioned |

## 5.11 Messages

It is recommended that MRFP and MRFC names are in the form of fully qualified domain name. For example the domain name of the MRFC may be of the form MRFC1.whatever.net and the name of the MRFP may be of the form mg1.whatever.net.

The fully qualified domain name will be used by the MRFP and MRFC as part of the "Message Identifier" in the H.248 messages which identifies the originator of the message.

The MRFC domain name is provisioned in the MRFP or retrieved from the DNS using SRV records.

The use of a domain name provides the following benefits:

- MRFPs and MRFCs are identified by their domain name, not their network addresses. Several addresses can be associated with a domain name. If a command cannot be forwarded to one of the network addresses, implementations shall retry the transmission using another address.
- MRFPs and MRFCs may move to another platform. The association between a logical name (domain name) and the actual platform are kept in the Domain Name Service (DNS). MRFP and MRFC shall keep track of the record's time-to-live read from the DNS. They shall query the DNS to refresh the information if the time-to-live has expired.

The domain name may be used by MRFC/MRFP for authentication purposes.

## 5.12 Transport

Table 5.12.1: Transport

|   |  |
|---|--|
| <b>Supported Transports:</b>  | <p>Transport over UDP shall be supported. Support of SCTP is optional and shall conform to Recommendation H.248.4 [4]. Choosing one option or the other is a network operator's decision, based on the network configuration.</p> <ul style="list-style-type: none"> <li>• SCTP(recommended) (NOTE1).</li> <li>• UDP(optional).</li> </ul> |
| <p>NOTE: If using SCTP as defined in IETF RFC 2960 [8], the MRFP shall always be the node to perform the "Initiation".</p> <p>NOTE1: H.248 is "SCTP user" in this case of H.248/SCTP/IP based transport according ITU-T Rec. H.248.4. The number of used SCTP Streams for traffic of the H.248 Control Association must be defined, see § 8/H.248.4. A single SCTP Stream is the default assumption ("Single-Stream Mode") in this Profile.</p> |  |

Table 5.12.2: Segmentation

|                         |    |
|-------------------------|----|
| Segmentation Supported: | No |
|-------------------------|----|

Table 5.12.3: Control Association Monitoring

|   |   |
|---|---|
| Control Association Monitoring Supported: | <p>Monitoring mechanism is dependent on used H.248 transport</p> <ul style="list-style-type: none"> <li>• <b>SCTP</b>: inherent capability of SCTP (NOTE)</li> <li>• <b>UDP</b>: <ol style="list-style-type: none"> <li>1. H.248.14 (MRFP-driven monitoring)</li> <li>2. Empty AuditValue on ROOT (MRFC-driven monitoring)</li> </ol> </li> </ul> |
| NOTE: Use of H.248.14 for this is FFS.    |   |

## 5.13 Security

Table 5.13.1: Security

|  |      |
|--|------|
| Supported Security:  | None |
| NOTE: Both the MRFC and MRFP are assumed to be within a secure IP zone of a single operator. |      |

## 5.14 Packages

Editor's Note: the following mandatory and optional packages are not finalised.

### 5.14.1 Mandatory Packages

Table 5.14.1: Mandatory packages

| Mandatory Packages       |            |         |
|--------------------------|------------|---------|
| Package Name / Reference | Package ID | Version |
| Generic (H.248.1, [3])   | g          | 1       |
| Base Root (H.248.1, [3]) | root       | 2       |
| Network (H.248.1, [3])   | nt         | 1       |

## 5.14.2 Optional Packages

Table 5.14.2: Optional packages

| Optional Packages  |              |         |   |
|--|--------------|---------|---|
| Package Name / Reference   | Package ID   | Version | Support dependent on:   |
| DTMF Detection Package (see ITU-T Recommendation H.248.1 [9] Annex E.6); | dd, (0x0006) | 1       | Support is mandatory if DTMF Detection is supported.  |
| Call Progress Tones Generator (H.248.1,3)                                | cg           | 1       | If CS type Services provided by network   |
| Basic Services Tones Generator (Q.1950, [13])                            | srvtn        | 1       | If CS type Services provided by network   |
| Expanded Call Progress Tones Generator (Q.1950, [13])                    | xcg          | 1       | If CS type Services provided by network   |
| Basic Announcement Syntax (H.248.9, [6])                                 | banssyx      | 1       | Support is optional if playing announcement is supported.   |
| Voice Variable Syntax (H.248.9, [6])                                     | vvsyx        | 1       | Support is optional if playing announcement is supported.   |
| Announcement Set Syntax (H.248.9, [6])                                   | setsyx       | 2       | Support is optional if playing announcement is supported.   |
| General text Variable type (H.248.9, [6])                                | phrsyx       | 2       | Support is optional if playing announcement is supported.   |
| Advanced Audio Server Base ( (H.248.9 a1,[26])                           | aasb         | 2       | Support is optional if playing announcement is supported.   |
| AAS Recording package (H.248.9, [6])                                     | aasrec       | 1       | Support is optional if Audio Record is supported.   |
| AAS segment management (H.248.9, [6])                                    | aassm        | 1       |   |
| Generic Announcement (H.248.7, [5])                                      | an           | 2       | Support is mandatory if playing announcement is supported.  |
| Intrusion Tones Generation (Q.1950, [13])                                | int          | 1       | If CS type Services provided by network   |
| Business Tones Generation (Q.1950, [13])                                 | biztn        | 1       | If CS type Services provided by network   |
| Conferencing Tones Generation (H.248.27, [12])                           | conftn       | 1       | Support is optional and may be used if Audio Conference is supported.   |
| Inactivity Timer (H.248.14, [9])   | it           | 1       | Support is mandatory if UDP transport is enabled for H.248 messages.  |
| MGC Information (TS 183 022, [18])                                       | MGC Info     | 1       | This package may be supported as an operator option. For this profile the information string shall be limited to 32 octets in length. |
| Advanced audio server base package for TTS enhancement (H.248.9 a1 [26]) | aastts       | 1       | Support is mandatory if Text to Speech is supported.  |
| ASR package(H.248.9 a1,[26])   | asr          | 1       | Support is mandatory if Automatic Speech Recognition is supported.  |
| Multimedia Recording Package (H.248.9 a1 [26])                           | mrp          | 1       | Support is mandatory if Multimedia recording is supported.  |
| multimedia play package(H.248.9 a1,[26])                                 | Mpp          | 1       | Support is mandatory if Multimedia announcement file is supported.  |
| Overload Control Package (H.248.11, [6])                                 | ocp          | 1       |   |
| RTP Package (H.248.1, [3])   | rtp          | 1       |   |

## 5.14.3 Package Usage Information

## 5.14.3.1 Generic Package

Table 5.14.3.1.1: Package Usage Information for Generic Package

| Properties                                     | Mandatory/<br>Optional                     | Used in command:               | Supported Values:  | Provisioned Value:                     |
|--|--|--------------------------------|--|--|
| None   | -  | -                              | -  | -                                      |
| <b>Signals</b>                                 | <b>Mandatory/<br/>Optional</b>             | <b>Used in command:</b>        |  | <b>Duration Provisioned<br/>Value:</b> |
| None   | -  | -                              | -  | -                                      |
|  | <b>Signal Parameters</b>                   | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b>   | <b>Duration Provisioned<br/>Value:</b> |
|  | -  | -                              | -  | -                                      |
| <b>Events</b>                                  | <b>Mandatory/<br/>Optional</b>             | <b>Used in command:</b>        |  |  |
| Cause (g/cause,<br>0x0001/0x0001)              | M  | ADD, MOD, NOTIFY               |  |  |
|  | <b>Event<br/>Parameters</b>                | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b>   | <b>Provisioned Value:</b>              |
|  | None                                       | -                              | -  | -                                      |
|  | <b>ObservedEvent<br/>Parameters</b>        | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b>   | <b>Provisioned Value:</b>              |
|  | General Cause<br>(Generalcause,<br>0X0001) | M                              | "NR" Normal<br>Release (0x0001)<br>"UR" Unavailable<br>Resources (0x0002)<br>"FT" Failure,<br>Temporary (0x0003)<br>"FP" Failure,<br>Permanent (0x0004)<br>"IW" Interworking<br>Error (0x0005)<br>"UN" Unsupported<br>(0x0006) | -                                      |
|  | Failure Cause<br>(FailureCause,<br>0x0002) | O                              | Octet String   | -                                      |
| Signal Completion.<br>(g/sc,<br>0x0001/0x0002) | M  | ADD, MOD, MOVE, NOTIFY         |  |  |
|  | <b>Event<br/>Parameters</b>                | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b>   | <b>Provisioned Value:</b>              |
|  | None                                       | -                              | -  | -                                      |
|  | <b>ObservedEvent<br/>Parameters</b>        | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b>   | <b>Provisioned Value:</b>              |
|  | Signal Identity<br>(SigID,<br>0x0001)      | M                              | pkgdName syntax  | -                                      |
|  | Termination Method<br>(Meth,<br>0x0002)    | M                              | "TO" (0x0001) Signal<br>timed out or<br>otherwise completed<br>on its own<br>"EV" (0x0002)<br>Interrupted by event<br>"SD" (0x0003)<br>Halted by new<br>Signals descriptor<br>"NC" (0x0004) Not<br>completed, other<br>cause   | -                                      |
|  | Signal List Id                             | O                              | Integer  | Not Applicable                         |
|  | Request ID, RID                            | O                              | String indicating the<br>Request ID  | -                                      |

| Statistics  | Mandatory/<br>Optional | Used in command: | Supported Values: |
|-------------|------------------------|------------------|-------------------|
| None        | -                      | -                | -                 |
| Error Codes | Mandatory/ Optional    |                  |                   |
| None        | -                      |                  |                   |

## 5.14.3.2 Base Root Package

Table 5.14.3.2.1: Package Usage Information for Base Root Package

| Properties  | Mandatory/<br>Optional      | Used in<br>command:    | Supported Values:   | Provisioned<br>Value:             |
|---|-----------------------------|------------------------|---|-----------------------------------|
| maxNumberOfContexts<br>(root/maxNumberOfContexts,<br>0x0002/0x0001)                               | M                           | AuditValue             | 1 and up  | Implementation<br>Specific        |
| maxTerminationPerContext<br>(root/maxTerminationsPerContext,<br>0x0002/0x0002)                    | O                           | AuditValue             | See 5.4   | Implementation<br>Specific        |
| normalMGExecutionTime<br>(root/normalMGExecutionTime,<br>0x0002/0x0003)                           | O                           | AuditValue             | Integer   | Operator<br>Defined               |
| normalMGCExecutionTime<br>(root/normalMGCExecutionTime,<br>0x0002/0x0004)                         | O                           | AuditValue             | Integer   | Operator<br>Defined               |
| MGProvisionalResponseTimerValue<br>(root/<br>MGProvisionalResponseTimerValue,<br>0x0002/0x0005)   | O                           | AuditValue             | Integer(NormalMGExecutionTime<br>+ networkdelay)                | Operator<br>Defined               |
| MGCProvisionalResponseTimerValue<br>(root/<br>MGCProvisionalResponseTimerValue,<br>0x0002/0x0006) | O                           | AuditValue             | Integer (initially<br>NormalMGCExecutionTime +<br>networkdelay) | Operator<br>Defined               |
| MGCOriginatedPendingLimit<br>(root/ MGCOriginatedPendingLimit,<br>0x0002/0x0007)                  | O                           | AuditValue             | Integer   | Operator<br>Defined               |
| MGOOriginatedPendingLimit<br>(root/ MGOOriginatedPendingLimit,<br>0x0002/0x0008)                  | O                           | AuditValue             | Integer   | Operator<br>Defined               |
| Signals   | Mandatory/<br>Optional      | Used in command:       |   | Duration<br>Provisioned<br>Value: |
| None  | -                           | -                      |   | < -                               |
|   | Signal<br>Parameters        | Mandatory/<br>Optional | Supported<br>Values:  | Duration<br>Provisioned<br>Value: |
|   | -                           | -                      | -   | -                                 |
| Events  | Mandatory/<br>Optional      | Used in command:       |   |                                   |
| None  | -                           | -                      |   |                                   |
|   | Event<br>Parameters         | Mandatory/<br>Optional | Supported<br>Values:  | Provisioned<br>Value:             |
|   | -                           | -                      | -   | -                                 |
|   | ObservedEvent<br>Parameters | Mandatory/<br>Optional | Supported<br>Values:  | Provisioned<br>Value:             |
|   | >-                          | -                      | -   | -                                 |
| Statistics  | Mandatory/<br>Optional      | Used in command:       | Supported Values:   |                                   |
| None  | -                           | -                      | -   |                                   |
| Error Codes   | Mandatory/ Optional         |                        |   |                                   |
| None  | -                           |                        |   |                                   |



## 5.14.3.3 Overload Control Package

Table 5.14.3.3.1: Package Usage Information for Overload Control Package

| Properties  | Mandatory/<br>Optional      | Used in command:       | Supported Values:    | Provisioned Value:             |
|---|-----------------------------|------------------------|----------------------|--------------------------------|
| None  | -                           | -                      | -                    | -                              |
| Signals   | Mandatory/<br>Optional      | Used in command:       |                      | Duration Provisioned<br>Value: |
| None  | -                           | -                      |                      | -                              |
|   | Signal Parameters           | Mandatory/<br>Optional | Supported<br>Values: | Duration Provisioned<br>Value: |
|   | -                           | -                      | -                    | -                              |
| Events  | Mandatory/<br>Optional      | Used in command:       |                      |                                |
| MG_Overload.<br>(ocp/<br>mg_overload,<br>0x0051/0x0001) | M                           | ADD, MOD, NOTIFY       |                      |                                |
|   | Event<br>Parameters         | Mandatory/<br>Optional | Supported<br>Values: | Provisioned Value:             |
|   | -                           | -                      | -                    | -                              |
|   | ObservedEvent<br>Parameters | Mandatory/<br>Optional | Supported<br>Values: | Provisioned Value:             |
|   | -                           | -                      | -                    | -                              |
| Statistics  | Mandatory/<br>Optional      | Used in command:       | Supported Values:    |                                |
| None  | -                           | -                      | -                    |                                |
| Error Codes   | Mandatory/ Optional         |                        |                      |                                |
| None  | -                           |                        |                      |                                |

## 5.14.3.4 Network Package

Table 5.14.3.4.1: Package Usage Information for Network Package

| Properties   | Mandatory/<br>Optional      | Used in command:       | Supported Values:    | Provisioned Value:             |
|--|-----------------------------|------------------------|----------------------|--------------------------------|
| Maximum Jitter<br>Buffer (nt /jit,<br>0x000b/0x0007) | M                           | ADD, MOD, MOVE         | ALL                  | -                              |
| Signals  | Mandatory/<br>Optional      | Used in command:       |                      | Duration Provisioned<br>Value: |
| None   | -                           | -                      |                      | -                              |
|  | Signal Parameters           | Mandatory/<br>Optional | Supported<br>Values: | Duration Provisioned<br>Value: |
|  | -                           | -                      | -                    | -                              |
| Events   | Mandatory/<br>Optional      | Used in command:       |                      |                                |
| network failure(nt /<br>netfail,<br>0x000b/0x0005)   | M                           | ADD, MOD, MOVE, NOTIFY |                      |                                |
|  | Event<br>Parameters         | Mandatory/<br>Optional | Supported<br>Values: | Provisioned Value:             |
|  | none                        | -                      | -                    | -                              |
|  | ObservedEvent<br>Parameters | Mandatory/<br>Optional | Supported<br>Values: | Provisioned Value:             |
|  | cause(cs,0x0001)            | M                      | ALL                  | -                              |
| quality alert (nt /<br>qualert,<br>0x000b/0x0006)    | M                           | ADD, MOD, MOVE, NOTIFY |                      |                                |
|  | Event<br>Parameters         | Mandatory/<br>Optional | Supported<br>Values: | Provisioned Value:             |
|  | Threshold(th,0x0001)        | M                      | 0 to 99              | -                              |
|  | ObservedEvent<br>Parameters | Mandatory/<br>Optional | Supported<br>Values: | Provisioned Value:             |
|  | Threshold(th,0x0001)        | M                      | 0 to 99              | -                              |

| Statistics                                    | Mandatory/<br>Optional     | Used in command: | Supported Values: |
|---|----------------------------|------------------|-------------------|
| Duration(nt / dur,<br>0x000b/0x0001)          | M                          | AUDITVALUE       | ALL               |
| Octets Sent<br>(nt / os,<br>0x000b/0x0002)    | M                          | AUDITVALUE       | ALL               |
| Octets<br>Received(nt / or,<br>0x000b/0x0003) | M                          | AUDITVALUE       | ALL               |
| <b>Error Codes</b>                            | <b>Mandatory/ Optional</b> |                  |                   |
| -   | -                          |                  |                   |

## 5.14.3.5 RTP Package

Table 5.14.3.5.1: Package Usage Information for RTP Package

| Properties   | Mandatory/<br>Optional                                   | Used in command:                              | Supported Values:                       | Provisioned Value:                     |
|--|--|---|---|--|
| <name and<br>Identity e.g.<br>Packets Sent<br>(rtp/ps,<br>0x00c/0x0004),<br>ALL or None><br>None | <M/O>-   | <ADD, MOD, MOVE,<br>AUDITVALUE,<br>AUDITCAP>- | <Values / ALL >-                        | <Value / Not Applicable>-              |
| <b>Signals</b>   | <b>Mandatory/<br/>Optional</b>                           | <b>Used in command:</b>                       |   | <b>Duration Provisioned<br/>Value:</b> |
| <name and<br>Identity > None   | <M/O>-   | <ADD, MOD, MOVE, AUDITVALUE,<br>AUDITCAP>-    |   | <Value / Not Applicable>-              |
|  | <b>Signal Parameters</b>                                 | <b>Mandatory/<br/>Optional</b>                | <b>Supported<br/>Values:</b>            | <b>Duration Provisioned<br/>Value:</b> |
|  | <name and<br>Identity>-                                  | <M/O>-  | <Values / ALL>-                         | <Value / Not Applicable>-              |
| <b>Events</b>  | <b>Mandatory/<br/>Optional</b>                           | <b>Used in command:</b>                       |   |  |
| <name and<br>Identity > Payload<br>Transition,<br>(rtp/pltrans,<br>0x000C/0x0001)                | <M   | <ADD, MOD, MOVE, NOTIFY                       |   |  |
|  | <b>Event<br/>Parameters</b>                              | <b>Mandatory/<br/>Optional</b>                | <b>Supported<br/>Values:</b>            | <b>Provisioned Value:</b>              |
|  | <name and<br>Identity>None                               | <M/O>-  | <Values / ALL>-                         | <Value / Not Applicable>-              |
|  | <b>ObservedEvent<br/>Parameters</b>                      | <b>Mandatory/<br/>Optional</b>                | <b>Supported<br/>Values:</b>            | <b>Provisioned Value:</b>              |
|  | <name and<br>Identity> rtppayload<br>(rtppltype, 0x0001) | <M  | <Values / ALL> A<br>valid encoding name | <Value / Not Applicable>-              |

| Statistics                                      | Mandatory/<br>Optional     | Used in command:               | Supported Values: |
|---|----------------------------|--------------------------------|-------------------|
| Packets Sent,<br>(rtp/ps,<br>0x000C/0x0004)     | O                          | AUDITVALUE, SUBTRACT<br>REPLY  | ALL               |
| Packets Received,<br>(rtp/pr,<br>0x000C/0x0005) | O                          | AUDITVALUE , SUBTRACT<br>REPLY | ALL               |
| Packet Loss,<br>(rtp/pl,<br>0x000C/0x0006)      | O                          | AUDITVALUE , SUBTRACT<br>REPLY | ALL               |
| Jitter,<br>(rtp/jit,<br>0x000C/0x0007)          | O                          | AUDITVALUE , SUBTRACT<br>REPLY | ALL               |
| Delay,<br>(rtp/delay,<br>0x000C/0x0008)         | O                          | AUDITVALUE , SUBTRACT<br>REPLY | ALL               |
| <b>Error Codes</b>                              | <b>Mandatory/ Optional</b> |                                |                   |
| None  | -                          |                                |                   |

### 5.14.3.6 DTMF Detection Package

**Table 5.14.3.6.1: Package Usage Information for DTMF Detection Package**

| Properties                                | Mandatory/<br>Optional      | Used in command:       | Supported Values:    | Provisioned Value:             |
|---|-----------------------------|------------------------|----------------------|--------------------------------|
| None                                      | -                           | -                      | -                    | -                              |
| Signals                                   | Mandatory/<br>Optional      | Used in command:       |                      | Duration Provisioned<br>Value: |
| None                                      | -                           | -                      |                      | -                              |
|   | Signal<br>Parameters        | Mandatory/<br>Optional | Supported<br>Values: | Duration Provisioned<br>Value: |
|   | -                           | -                      | -                    | -                              |
| Events                                    | Mandatory/<br>Optional      | Used in command:       |                      |                                |
| DTMF character 0<br>(dd/d0,0x0006/0x0010) | M                           | ADD, MOD, NOTIFY       |                      |                                |
| DTMF character 1<br>(dd/d1,0x0006/0x0011) | Event<br>Parameters         | Mandatory/<br>Optional | Supported<br>Values: | Provisioned Value:             |
| DTMF character 2<br>(dd/d2,0x0006/0x0012) | -                           | -                      | -                    | -                              |
|   | ObservedEvent<br>Parameters | Mandatory/<br>Optional | Supported<br>Values: | Provisioned Value:             |

|   |                                |                         |   |                          |
|---|--------------------------------|-------------------------|---|--------------------------|
| DTMF character 3<br>(dd/d3,0x0006/0x0013)<br>DTMF character 4<br>(dd/d4,0x0006/0x0014)<br>DTMF character 5<br>(dd/d5,0x0006/0x0015)<br>DTMF character 6<br>(dd/d6,0x0006/0x0016)<br>DTMF character 7<br>(dd/d7,0x0006/0x0017)<br>DTMF character 8<br>(dd/d8,0x0006/0x0018)<br>DTMF character 9<br>(dd/d9,0x0006/0x0019)<br>DTMF character *<br>(dd/ds,0x0006/0x0020)<br>DTMF character #<br>(dd/do,0x0006/0x0021)<br>DTMF character A<br>(dd/da,0x0006/0x001a)<br>DTMF character B<br>(dd/db,0x0006/0x001b)<br>DTMF character C<br>(dd/dc,0x0006/0x001c)<br>DTMF character D<br>(dd/dd,0x0006/0x001d) | -                              | -                       | - | -                        |
| <b>Statistics</b>   | <b>Mandatory/<br/>Optional</b> | <b>Used in command:</b> |   | <b>Supported Values:</b> |
| None  | -                              | -                       |   | -                        |
| <b>Error Codes</b>  | <b>Mandatory/ Optional</b>     |                         |   |                          |
| None  | -                              |                         |   |                          |

5.14.3.7 Call Progress Tones Generator Package

Table 5.14.3.7.1: Package Usage Information for Call Progress Tones Generator Package

| Properties                             | Mandatory/<br>Optional         | Used in command:               | Supported Values:            | Provisioned Value:                     |
|--|--------------------------------|--------------------------------|------------------------------|--|
| None                                   | -                              | -                              | -                            | -                                      |
| <b>Signals</b>                         | <b>Mandatory/<br/>Optional</b> | <b>Used in command:</b>        |                              | <b>Duration Provisioned<br/>Value:</b> |
| Dial Tone,<br>(cg/dt,<br>0x0007/0x030) | M                              | ADD, MOD, MOVE                 |                              | Value                                  |
|  | <b>Signal Parameters</b>       | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b> | <b>Duration Provisioned<br/>Value:</b> |

|  |                                 |                           |                          |                           |
|--|---------------------------------|---------------------------|--------------------------|---------------------------|
| Ringing Tone, (cg/rt, 0x0007/0x031)<br>Busy Tone, (cg/bt, 0x0007/0x032)<br>Congestion Tone, (cg/ct, 0x0007/0x033)<br>Special Information Tone, (cg/sit, 0x0007/0x034)<br>Warning Tone, (cg/wt, 0x0007/0x035)<br>Payphone Recognition Tone, (cg/pt, 0x0007/0x036)<br>Call Waiting Tone, (cg/cw, 0x0007/0x037)<br>Caller Waiting Tone, (cg/cr, 0x0007/0x038) | -                               | -                         | -                        | -                         |
| <b>Events</b>  | <b>Mandatory/Optional</b>       | <b>Used in command:</b>   |                          |                           |
| None   | -                               | -                         |                          |                           |
|  | <b>Event Parameters</b>         | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|  | -                               | -                         | -                        | -                         |
|  | <b>ObservedEvent Parameters</b> | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|  | -                               | -                         | -                        | -                         |
| <b>Statistics</b>  | <b>Mandatory/Optional</b>       | <b>Used in command:</b>   |                          | <b>Supported Values:</b>  |
| None   | -                               | -                         |                          | -                         |
| <b>Error Codes</b>   | <b>Mandatory/Optional</b>       |                           |                          |                           |
| None   | -                               |                           |                          |                           |

5.14.3.8 Basic Services Tones Generator Package

Table 5.14.3.8.1: Package Usage Information for Basic Services Tones Generator Package

| Properties   | Mandatory/Optional           | Used in command:          | Supported Values:        | Provisioned Value:                 |
|--|------------------------------|---------------------------|--------------------------|------------------------------------|
| None   | -                            | -                         | -                        | -                                  |
| <b>Signals</b>   | <b>Mandatory/Optional</b>    | <b>Used in command:</b>   |                          | <b>Duration Provisioned Value:</b> |
|  | <b>O</b>                     | <b>ADD, MOD, MOVE</b>     |                          | <b>Value</b>                       |
| Recall Dial Tone (srvtn/rdt,0x0025/0x004f)<br>Confirmation Tone (srvtn/conf,0x0025/0x0050)<br>Held Tone (srvtn/ht,0x0025/0x0051)<br>Message Waiting Tone (srvtn/mwt,0x0025/0x0052) | <b>Signal Parameters</b>     | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
|  | Tone Direction (btd, 0x0001) | M                         | Internal / External      | Default=External                   |
| <b>Events</b>  | <b>Mandatory/Optional</b>    | <b>Used in command:</b>   |                          |                                    |

|                    |                                 |                            |                          |                           |
|--------------------|---------------------------------|----------------------------|--------------------------|---------------------------|
| None               | -                               | -                          |                          |                           |
|                    | <b>Event Parameters</b>         | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|                    | -                               | -                          | -                        | -                         |
|                    | <b>ObservedEvent Parameters</b> | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
| -                  | -                               | -                          | -                        |                           |
| <b>Statistics</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    | <b>Supported Values:</b> |                           |
| None               | -                               | -                          | -                        |                           |
| <b>Error Codes</b> | <b>Mandatory/ Optional</b>      |                            |                          |                           |
| None               | -                               |                            |                          |                           |

5.14.3.9 Expanded Call Progress Tones Generator Package

Table 5.14.3.9.1: Package Usage Information for Expanded Call Progress Tones Generator Package

|  |                                 |                            |                          |                                    |
|--|---------------------------------|----------------------------|--------------------------|------------------------------------|
| <b>Properties</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| None   | -                               | -                          | -                        | -                                  |
| <b>Signals</b>   | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          | <b>Duration Provisioned Value:</b> |
| Comfort Tone<br>(xcg/cmft,0x0024/0x004a)                 | O                               | ADD, MOD, MOVE             |                          | Value                              |
| Off-hook warning Tone<br>(xcg/roh, 0x0024/0x004b)        | <b>Signal Parameters</b>        | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
| Negative Acknowledgement<br>(xcg/nack,0x0024/0x004c)     | Tone Direction<br>(btd, 0x0001) | M                          | Internal / External      | Default=External                   |
| Vacant Number Tone<br>(xcg/vac, 0x0024/0x004d)           |                                 |                            |                          |                                    |
| Special Conditions Dial Tone<br>(xcg/spec,0x0024/0x004e) |                                 |                            |                          |                                    |
| <b>Events</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          |                                    |
| None   | -                               | -                          |                          |                                    |
| None   | <b>Event Parameters</b>         | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|  | -                               | -                          | -                        | -                                  |
|  | <b>ObservedEvent Parameters</b> | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|  | -                               | -                          | -                        | -                                  |
| <b>Statistics</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    | <b>Supported Values:</b> |                                    |
| None   | -                               | -                          | -                        |                                    |
| <b>Error Codes</b>                                       | <b>Mandatory/ Optional</b>      |                            |                          |                                    |
| None   | -                               |                            |                          |                                    |

5.14.3.10 Basic Announcement Syntax Package

Table 5.14.3.10.1: Package Usage Information for Basic Announcement Syntax Package

|                   |                            |                            |                          |                                    |
|-------------------|----------------------------|----------------------------|--------------------------|------------------------------------|
| <b>Properties</b> | <b>Mandatory/ Optional</b> | <b>Used in command:</b>    | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| None              | -                          | -                          | -                        | -                                  |
| <b>Signals</b>    | <b>Mandatory/ Optional</b> | <b>Used in command:</b>    |                          | <b>Duration Provisioned Value:</b> |
| None              | -                          | -                          |                          | -                                  |
| None              | <b>Signal Parameters</b>   | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
|                   |                            |                            |                          |                                    |

|                    |                                 |                           |                          |                           |
|--------------------|---------------------------------|---------------------------|--------------------------|---------------------------|
|                    | -                               | -                         | -                        | -                         |
| <b>Events</b>      | <b>Mandatory/Optional</b>       | <b>Used in command:</b>   |                          |                           |
| None               | -                               | -                         |                          |                           |
|                    | <b>Event Parameters</b>         | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|                    | -                               | -                         | -                        | -                         |
|                    | <b>ObservedEvent Parameters</b> | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|                    | -                               | -                         | -                        | -                         |
| <b>Statistics</b>  | <b>Mandatory/Optional</b>       | <b>Used in command:</b>   | <b>Supported Values:</b> |                           |
| None               | -                               | -                         | -                        |                           |
| <b>Error Codes</b> | <b>Mandatory/ Optional</b>      |                           |                          |                           |
| None               | -                               |                           |                          |                           |

## 5.14.3.11 Voice Variable Syntax Package

Table 5.14.3.11.1: Package Usage Information for Voice Variable Syntax Package

|                    |                                 |                           |                          |                                    |
|--------------------|---------------------------------|---------------------------|--------------------------|------------------------------------|
| <b>Properties</b>  | <b>Mandatory/Optional</b>       | <b>Used in command:</b>   | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| None               | -                               | -                         | -                        | -                                  |
| <b>Signals</b>     | <b>Mandatory/Optional</b>       | <b>Used in command:</b>   |                          | <b>Duration Provisioned Value:</b> |
| None               | -                               | -                         |                          | -                                  |
|                    | <b>Signal Parameters</b>        | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
|                    | -                               | -                         | -                        | -                                  |
| <b>Events</b>      | <b>Mandatory/Optional</b>       | <b>Used in command:</b>   |                          |                                    |
| None               | -                               | -                         |                          |                                    |
|                    | <b>Event Parameters</b>         | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|                    | -                               | -                         | -                        | -                                  |
|                    | <b>ObservedEvent Parameters</b> | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|                    | -                               | -                         | -                        | -                                  |
| <b>Statistics</b>  | <b>Mandatory/Optional</b>       | <b>Used in command:</b>   | <b>Supported Values:</b> |                                    |
| None               | -                               | -                         | -                        |                                    |
| <b>Error Codes</b> | <b>Mandatory/ Optional</b>      |                           |                          |                                    |
| None               | -                               |                           |                          |                                    |

## 5.14.3.12 Announcement Set Syntax Package

Table 5.14.3.12.1: Package Usage Information for Announcement Set Syntax Package

|                   |                           |                           |                          |                                    |
|-------------------|---------------------------|---------------------------|--------------------------|------------------------------------|
| <b>Properties</b> | <b>Mandatory/Optional</b> | <b>Used in command:</b>   | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| None              | -                         | -                         | -                        | -                                  |
| <b>Signals</b>    | <b>Mandatory/Optional</b> | <b>Used in command:</b>   |                          | <b>Duration Provisioned Value:</b> |
| None              | -                         | -                         |                          | -                                  |
|                   | <b>Signal Parameters</b>  | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
|                   | -                         | -                         | -                        | -                                  |
| <b>Events</b>     | <b>Mandatory/Optional</b> | <b>Used in command:</b>   |                          |                                    |
| None              | -                         | -                         |                          |                                    |
|                   | <b>Event Parameters</b>   | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|                   | -                         | -                         | -                        | -                                  |

|                    |                                 |                            |                          |                           |
|--------------------|---------------------------------|----------------------------|--------------------------|---------------------------|
|                    | <b>ObservedEvent Parameters</b> | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|                    | -                               | -                          | -                        | -                         |
| <b>Statistics</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          | <b>Supported Values:</b>  |
| None               | -                               | -                          |                          | -                         |
| <b>Error Codes</b> | <b>Mandatory/ Optional</b>      |                            |                          |                           |
| None               | -                               |                            |                          |                           |

## 5.14.3.13 General Text Variable Type Package

Table 5.14.3.13.1: Package Usage Information for General Text Variable Type Package

|                    |                                 |                            |                          |                                    |
|--------------------|---------------------------------|----------------------------|--------------------------|------------------------------------|
| <b>Properties</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| None               | -                               | -                          | -                        | -                                  |
| <b>Signals</b>     | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          | <b>Duration Provisioned Value:</b> |
| None               | -                               | -                          |                          | -                                  |
|                    | <b>Signal Parameters</b>        | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
|                    | -                               | -                          | -                        | -                                  |
| <b>Events</b>      | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          |                                    |
| None               | -                               | -                          |                          |                                    |
|                    | <b>Event Parameters</b>         | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|                    | -                               | -                          | -                        | -                                  |
|                    | <b>ObservedEvent Parameters</b> | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|                    | -                               | -                          | -                        | -                                  |
| <b>Statistics</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    | <b>Supported Values:</b> |                                    |
| None               | -                               | -                          | -                        |                                    |
| <b>Error Codes</b> | <b>Mandatory/ Optional</b>      |                            |                          |                                    |
| None               | -                               |                            |                          |                                    |

## 5.14.3.14 Advanced Audio Server Base Package

Table 5.14.3.14.1: Package Usage Information for Advanced Audio Server Base Package

|   |                                      |                             |                          |                                    |
|---|--------------------------------------|-----------------------------|--------------------------|------------------------------------|
| <b>Properties</b>   | <b>Mandatory/ Optional</b>           | <b>Used in command:</b>     | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| None  | -                                    | -                           | -                        | -                                  |
| <b>Signals</b>  | <b>Mandatory/ Optional</b>           | <b>Used in command:</b>     |                          | <b>Duration Provisioned Value:</b> |
|   | M                                    | ADD, MOD, MOVE, AUDITVALUE, |                          | -                                  |
|   | <b>Signal Parameters</b>             | <b>Mandatory/ Optional</b>  | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
| Play<br>(aasb/play,<br>0x0033/0x0001)                           | Announcement<br>(an, 0x0001)         | M                           | ALL                      | -                                  |
|   | Iterations<br>(it,0x0002)            | O                           | ALL                      | 1                                  |
|   | Interval(iv,0x0003)                  | O                           | 0 upwords                | -                                  |
|   | Announcement<br>Direction(di,0x0006) | M                           | Ext (0x01)<br>Int (0x02) | Default=External                   |
| <b>Events</b>   | <b>Mandatory/ Optional</b>           | <b>Used in command:</b>     |                          |                                    |
|   | M                                    | NOTIFY                      |                          |                                    |
|   | <b>Event Parameters</b>              | <b>Mandatory/ Optional</b>  | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| Audio operation<br>failure<br>(aasb/audfail,<br>0x0033 /0x0001) | -                                    | -                           | -                        | -                                  |



|                    |                                 |                            |                          |                           |
|--------------------|---------------------------------|----------------------------|--------------------------|---------------------------|
|                    | <b>ObservedEvent Parameters</b> | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|                    | Return Code(rc, 0x0001)         | M                          | FFS                      | -                         |
| <b>Statistics</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          | <b>Supported Values:</b>  |
| None               | -                               | -                          |                          | -                         |
| <b>Error Codes</b> | <b>Mandatory/ Optional</b>      |                            |                          |                           |
| None               | -                               |                            |                          |                           |

### 5.14.3.15 Basic Call Progress Tones Generator with Directionality

**Table 5.14.3.15.1: Package Usage Information For Basic Call Progress Tones Generator with Directionality Package**

|  |  |                                 |   |  |
|--|--|---------------------------------|---|--|
| <b>Properties</b>                                  | <b>Mandatory/ Optional</b>                               | <b>Used in command:</b>         | <b>Supported Values:</b>                        | <b>Provisioned Value:</b>                              |
| None   | -  | -                               | -   | -  |
| <b>Signals</b>                                     | <b>Mandatory/ Optional</b>                               | <b>Used in command:</b>         |   | <b>Duration Provisioned Value:</b>                     |
| Dial Tone (bcg/bdt, 0x0023/0x0040)                 | O  | ADD, MOD, MOVE                  |   | Value  |
| Ringing Tone (bcg/brt, 0x0023/0x0041)              | <b>Signal Parameters</b><br>Tone Direction (btd, 0x0001) | <b>Mandatory/ Optional</b><br>M | <b>Supported Values:</b><br>Internal / External | <b>Duration Provisioned Value:</b><br>Default=External |
| Busy Tone (bcg/bbt, 0x0023/0x0042)                 |  |                                 |   |  |
| Congestion Tone (bcg/bct, 0x0023/0x0043)           |  |                                 |   |  |
| Special Information Tone (bcg/bsit, 0x0023/0x0044) |  |                                 |   |  |
| Warning Tone (bcg/bwt, 0x0023/0x0045)              |  |                                 |   |  |
| Payphone Recognition Tone (bcg/bpt, 0x0023/0x0046) |  |                                 |   |  |
| Call Waiting Tone (bcg/bcw, 0x0023/0x0047)         |  |                                 |   |  |
| Caller Waiting Tone (bcg/bcr, 0x0023/0x0048)       |  |                                 |   |  |
| Pay Tone (bcg/bpy, 0x0023/0x0049)                  |  |                                 |   |  |
| <b>Events</b>                                      |  |                                 |   |  |
| None   | -  | -                               |   |  |
|  | <b>Event Parameters</b>                                  | <b>Mandatory/ Optional</b>      | <b>Supported Values:</b>                        | <b>Provisioned Value:</b>                              |
|  | -  | -                               | -   | -  |
|  | <b>ObservedEvent Parameters</b>                          | <b>Mandatory/ Optional</b>      | <b>Supported Values:</b>                        | <b>Provisioned Value:</b>                              |
|  | -  | -                               | -   | -  |
| <b>Statistics</b>                                  | <b>Mandatory/ Optional</b>                               | <b>Used in command:</b>         |   | <b>Supported Values:</b>                               |
| None   | -  | -                               |   | -  |
| <b>Error Codes</b>                                 | <b>Mandatory/ Optional</b>                               |                                 |   |  |
| None   | -  |                                 |   |  |

## 5.14.3.16 AAS Recording Package

Table 5.14.3.16.1: Package Usage Information for AAS Recording Package

| Properties   | Mandatory/<br>Optional                | Used in<br>command:            | Supported<br>Values:         | Provisioned Value:                     |
|--|---------------------------------------|--------------------------------|------------------------------|--|
| Maximum temporary<br>record life<br>(aasrec/maxtrl<br>0x0035/0x0003) | M                                     | ADD, MOD, MOVE                 | ALL                          | -                                      |
| <b>Signals</b>   | <b>Mandatory/<br/>Optional</b>        | <b>Used in command:</b>        |                              | <b>Duration Provisioned<br/>Value:</b> |
| PlayRecord<br>(aasrec/playrec,<br>0x0035/0x0002)                     | M                                     | ADD, MOD, MOVE                 |                              | -                                      |
|  | <b>Signal<br/>Parameters</b>          | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b> | <b>Duration Provisioned<br/>Value:</b> |
|  | Record Length<br>Timer(rlt, 0x0008)   | O                              | ALL                          | -                                      |
|  | Recording Identifier<br>(rid, 0x0009) | M                              | ALL                          | -                                      |
|  | EndInputKey(eik,<br>0x0010)           | M                              | ALL                          | -                                      |
| Make persistent<br>(aasrec/makepers,<br>0x0035/0x0003)               | O                                     | ADD, MOD, MOVE                 |                              | -                                      |
|  | <b>Signal<br/>Parameters</b>          | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b> | <b>Duration Provisioned<br/>Value:</b> |
| Recording Identifier<br>(rid, 0x0001)                                | M                                     | ALL                            | -                            | -                                      |
| <b>Events</b>  | <b>Mandatory/<br/>Optional</b>        | <b>Used in command:</b>        |                              |  |
| Audio operation failure<br>(aasrec/audfail,<br>0x0035/0x0001)        | M                                     | NOTIFY                         |                              |  |
|  | <b>Event<br/>Parameters</b>           | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b> | <b>Provisioned Value:</b>              |
|  | None                                  | -                              | -                            | -                                      |
|  | <b>ObservedEvent<br/>Parameters</b>   | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b> | <b>Provisioned Value:</b>              |
|  | Return Code(rc,<br>0x0001)            | M                              | ALL                          | -                                      |
| PlayRecord<br>success(aasrec/precsucc,<br>0x0035/0x0002))            | M                                     | NOTIFY                         |                              |  |
|  | <b>Event<br/>Parameters</b>           | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b> | <b>Provisioned Value:</b>              |
|  | None                                  | -                              | -                            | -                                      |
|  | <b>ObservedEvent<br/>Parameters</b>   | <b>Mandatory/<br/>Optional</b> | <b>Supported<br/>Values:</b> | <b>Provisioned Value:</b>              |
|  | Recording result<br>(res,0x0003)      | M                              | ALL                          | -                                      |
|  | Recording id<br>(ri, 0x0004))         | M                              | ALL                          | -                                      |
|  | Record duration<br>(rdur,0x0005)      | M                              | ALL                          | -                                      |
| <b>Statistics</b>  | <b>Mandatory/<br/>Optional</b>        | <b>Used in command:</b>        |                              | <b>Supported Values:</b>               |
| None   | -                                     | -                              |                              | -                                      |
| <b>Error Codes</b>   | <b>Mandatory/ Optional</b>            |                                |                              |  |
| None   | -                                     |                                |                              |  |

## 5.14.3.17 Multimedia Play Package

Table 5.14.3.17.1: Package Usage Information for Multimedia Play Package

| Properties                           | Mandatory/<br>Optional                    | Used in command:       | Supported Values:        | Provisioned Value:             |
|--------------------------------------|---|------------------------|--------------------------|--------------------------------|
| None                                 | -   | -                      | -                        | -                              |
| Signals                              | Mandatory/<br>Optional                    | Used in command:       |                          | Duration Provisioned<br>Value: |
| Play<br>(mpp/play,<br>0x00a9/0x0001) | M   | ADD, MOD, MOVE         |                          | -                              |
|                                      | Signal Parameters                         | Mandatory/<br>Optional | Supported<br>Values:     | Duration Provisioned<br>Value: |
|                                      | Announcement<br>(an,0x0001)               | M                      | ALL                      | -                              |
|                                      | Iterations<br>(it,0x0002)                 | M                      | ALL                      | -                              |
|                                      | Interval<br><br>(iv,0x0003)               | O                      | ALL                      | -                              |
|                                      | Announcement<br>Direction<br>(di, 0x0006) | M                      | Ext (0x01)<br>Int (0x02) | Default=External               |
| Events                               | Mandatory/<br>Optional                    | Used in command:       |                          |                                |
| None                                 | -   | -                      |                          |                                |
|                                      | Event<br>Parameters                       | Mandatory/<br>Optional | Supported<br>Values:     | Provisioned Value:             |
|                                      | -   | -                      | -                        | -                              |
|                                      | ObservedEvent<br>Parameters               | Mandatory/<br>Optional | Supported<br>Values:     | Provisioned Value:             |
| -                                    | -   | -                      | -                        |                                |
| Statistics                           | Mandatory/<br>Optional                    | Used in command:       | Supported Values:        |                                |
| None                                 | -   | -                      | -                        |                                |
| Error Codes                          | Mandatory/ Optional                       |                        |                          |                                |
| None                                 | -   |                        |                          |                                |

## 5.14.3.18 Generic Announcement Package

Table 5.14.3.18.1: Package Usage Information for Generic Announcement Package

| Properties  | Mandatory/<br>Optional                    | Used in command:       | Supported Values:        | Provisioned Value:             |
|---|---|------------------------|--------------------------|--------------------------------|
| None  | -   | -                      | -                        | -                              |
| Signals   | Mandatory/<br>Optional                    | Used in command:       |                          | Duration Provisioned<br>Value: |
| Fixed:<br>Announcement<br>play<br>(an/apf,<br>x001d/0x0001) | M   | ADD, MOD, MOVE         |                          | -                              |
|   | Signal Parameters                         | Mandatory/<br>Optional | Supported<br>Values:     | Duration Provisioned<br>Value: |
|   | Announcement<br>name<br>(an ,0x0001)      | <M                     | ALL                      | -                              |
|   | Number of cycles<br>(noc ,0x0002)         | O                      | Any                      | -                              |
|   | Announcement<br>Variant<br>(av ,0x0003)   | O                      | ALL                      | -                              |
|   | Announcement<br>Direction<br>(di ,0x0004) | M                      | Ext (0x01)<br>Int (0x02) | Default=External               |

|                    |                                 |                            |                          |                           |
|--------------------|---------------------------------|----------------------------|--------------------------|---------------------------|
| <b>Events</b>      | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          |                           |
| None               | -                               | -                          |                          |                           |
|                    | <b>Event Parameters</b>         | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|                    | -                               | -                          | -                        | -                         |
|                    | <b>ObservedEvent Parameters</b> | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
| -                  | -                               | -                          | -                        |                           |
| <b>Statistics</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          | <b>Supported Values:</b>  |
| None               | -                               | -                          |                          | -                         |
| <b>Error Codes</b> | <b>Mandatory/ Optional</b>      |                            |                          |                           |
| None               | -                               |                            |                          |                           |

5.14.3.19 Intrusion Tones Generator Package

Table 5.14.3.19.1: Package Usage Information for Intrusion Tones Generator Package

|   |   |                            |  |   |
|---|---|----------------------------|--|---|
| <b>Properties</b>                               | <b>Mandatory/ Optional</b>                        | <b>Used in command:</b>    | <b>Supported Values:</b>                 | <b>Provisioned Value:</b>                       |
| None  | -   | -                          | -  | -   |
| <b>Signals</b>                                  | <b>Mandatory/ Optional</b>                        | <b>Used in command:</b>    |  | <b>Duration Provisioned Value:</b>              |
| Intrusion Pending Tone (int/pend,0x0027/0x0057) | O   | ADD, MOD, MOVE             |  | Value   |
| Intrusion Tone (int/int,0x0027/0x0058)          | Signal Parameters<br>Tone Direction (btd, 0x0001) | Mandatory/ Optional        | Supported Values:<br>Internal / External | Duration Provisioned Value:<br>Default=External |
| Intrusion Reminder Tone (int/rem,0x0027/0x0059) |   |                            |  |   |
| Toll Break-In Tone (int/tbi,0x0027/0x005a)      |   |                            |  |   |
| Intrusion Queue Tone (int/intque,0x0027/0x005b) |   |                            |  |   |
| Busy Verification Tone (int/bv,0x0027/0x005c)   |   |                            |  |   |
| <b>Events</b>                                   | <b>Mandatory/ Optional</b>                        | <b>Used in command:</b>    |  |   |
| None  | -   | -                          |  |   |
|   | <b>Event Parameters</b>                           | <b>Mandatory/ Optional</b> | <b>Supported Values:</b>                 | <b>Provisioned Value:</b>                       |
|   | -   | -                          | -  | -   |
|   | <b>ObservedEvent Parameters</b>                   | <b>Mandatory/ Optional</b> | <b>Supported Values:</b>                 | <b>Provisioned Value:</b>                       |
| -   | -   | -                          | -  |   |
| <b>Statistics</b>                               | <b>Mandatory/ Optional</b>                        | <b>Used in command:</b>    |  | <b>Supported Values:</b>                        |
| None  | -   | -                          |  | -   |
| <b>Error Codes</b>                              | <b>Mandatory/ Optional</b>                        |                            |  |   |
| None  | -   |                            |  |   |

## 5.14.3.20 Business Tones Generation Package

Table 5.14.3.20.1: Package Usage Information for Business Tones Generation Package

| Properties   | Mandatory/<br>Optional       | Used in command:       | Supported Values:   | Provisioned Value:          |
|--|------------------------------|------------------------|---------------------|-----------------------------|
| None   | -                            | -                      | -                   | -                           |
| Signals  | Mandatory/<br>Optional       | Used in command:       |                     | Duration Provisioned Value: |
| Off-Hook Queuing Tone<br>(biztn/ofque,0x0028/0x005d)       | O                            | ADD, MOD, MOVE         |                     | Value                       |
| Expensive Route Warning Tone<br>(biztn/erwt,0x0028/0x005e) | Signal Parameters            | Mandatory/<br>Optional | Supported Values:   | Duration Provisioned Value: |
| Distinctive Dial Tone<br>(biztn/ddt,0x0028/0x005f)         | Tone Direction (btd, 0x0001) | M                      | Internal / External | Default=External            |
| Internal Dial Tone<br>(biztn/idt,0x0028/0x0060)            |                              |                        |                     |                             |
| Events   | Mandatory/<br>Optional       | Used in command:       |                     |                             |
| None   | -                            | -                      |                     |                             |
|  | Event Parameters             | Mandatory/<br>Optional | Supported Values:   | Provisioned Value:          |
|  | -                            | -                      | -                   | -                           |
|  | ObservedEvent Parameters     | Mandatory/<br>Optional | Supported Values:   | Provisioned Value:          |
|  | -                            | -                      | -                   | -                           |
| Statistics   | Mandatory/<br>Optional       | Used in command:       | Supported Values:   |                             |
| None   | -                            | -                      | -                   |                             |
| Error Codes  | Mandatory/ Optional          |                        |                     |                             |
| None   | -                            |                        |                     |                             |

## 5.14.3.21 Conferencing Tones Generation Package

Table 5.14.3.21.1: Package Usage Information for Conferencing Tones Generation Package

| Properties  | Mandatory/<br>Optional       | Used in command:       | Supported Values:   | Provisioned Value:          |
|---|------------------------------|------------------------|---------------------|-----------------------------|
| None  | -                            | -                      | -                   | -                           |
| Signals   | Mandatory/<br>Optional       | Used in command:       |                     | Duration Provisioned Value: |
| Conf. Entrance Tone<br>(confn/enter, 0x0038/0x0061)       | O                            | ADD, MOD, MOVE         |                     | Value                       |
| Conf. Exit Tone<br>(confn/exit, 0x0038/0x0062)            | Signal Parameters            | Mandatory/<br>Optional | Supported Values:   | Duration Provisioned Value: |
| Conf. Lock Tone<br>(confn/lock, 0x0038/0x0063)            | Tone Direction (btd, 0x0001) | M                      | Internal / External | Default=External            |
| Conf. Unlock Tone<br>(confn/unlock, 0x0038/0x0064)        |                              |                        |                     |                             |
| Time Limit Warning Tone<br>(confn/timelim, 0x0038/0x0065) |                              |                        |                     |                             |
| Events  | Mandatory/<br>Optional       | Used in command:       |                     |                             |
| None  | -                            | -                      |                     |                             |
|   | Event Parameters             | Mandatory/<br>Optional | Supported Values:   | Provisioned Value:          |
|   | -                            | -                      | -                   | -                           |

|                    |                                 |                           |                          |                           |
|--------------------|---------------------------------|---------------------------|--------------------------|---------------------------|
|                    | -                               | -                         | -                        | -                         |
|                    | <b>ObservedEvent Parameters</b> | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|                    | -                               | -                         | -                        | -                         |
| <b>Statistics</b>  | <b>Mandatory/Optional</b>       | <b>Used in command:</b>   | <b>Supported Values:</b> |                           |
| None               | -                               | -                         | -                        |                           |
| <b>Error Codes</b> | <b>Mandatory/ Optional</b>      |                           |                          |                           |
| None               | -                               |                           |                          |                           |

## 5.14.3.22 Inactivity Timer Package

Table 5.14.3.22.1: Package Usage Information for Inactivity Timer Package

|   |                                      |                           |                          |                                    |
|---|--------------------------------------|---------------------------|--------------------------|------------------------------------|
| <b>Properties</b>                         | <b>Mandatory/Optional</b>            | <b>Used in command:</b>   | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| None                                      | -                                    | -                         | -                        | -                                  |
| <b>Signals</b>                            | <b>Mandatory/Optional</b>            | <b>Used in command:</b>   |                          | <b>Duration Provisioned Value:</b> |
| None                                      | -                                    | -                         |                          | -                                  |
|   | <b>Signal Parameters</b>             | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
|   | -                                    | -                         | -                        | -                                  |
| <b>Events</b>                             | <b>Mandatory/Optional</b>            | <b>Used in command:</b>   |                          |                                    |
| Inactivity Timeout(it/ito, 0x0045/0x0001) | M                                    | MOD, NOTIFY               |                          |                                    |
|   | <b>Event Parameters</b>              | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|   | Maximum Inactivity Time(mit, 0x0001) | M                         | Any integer              | -                                  |
|   | <b>ObservedEvent Parameters</b>      | <b>Mandatory/Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|   | None                                 | -                         | -                        | -                                  |
| <b>Statistics</b>                         | <b>Mandatory/Optional</b>            | <b>Used in command:</b>   | <b>Supported Values:</b> |                                    |
| None                                      | -                                    | -                         | -                        |                                    |
| <b>Error Codes</b>                        | <b>Mandatory/ Optional</b>           |                           |                          |                                    |
| None                                      | -                                    |                           |                          |                                    |

## 5.14.3.23 MGC Information Package

Table 5.14.3.23.1: Package Usage Information for MGC Information Package

|                                       |                           |                           |                           |                                    |
|---------------------------------------|---------------------------|---------------------------|---------------------------|------------------------------------|
| <b>Properties</b>                     | <b>Mandatory/Optional</b> | <b>Used in command:</b>   | <b>Supported Values:</b>  | <b>Provisioned Value:</b>          |
| Data Block(MGCInfo/db, 0x00a0/0x0001) | M                         | ADD, MOD, AUDITVALUE      | A range of 0 to 32 octets | An empty string                    |
| <b>Signals</b>                        | <b>Mandatory/Optional</b> | <b>Used in command:</b>   |                           | <b>Duration Provisioned Value:</b> |
| None                                  | -                         | -                         |                           | -                                  |
|                                       | <b>Signal Parameters</b>  | <b>Mandatory/Optional</b> | <b>Supported Values:</b>  | <b>Duration Provisioned Value:</b> |
|                                       | -                         | -                         | -                         | -                                  |
| <b>Events</b>                         | <b>Mandatory/Optional</b> | <b>Used in command:</b>   |                           |                                    |
| None                                  | -                         | -                         |                           |                                    |
|                                       | <b>Event Parameters</b>   | <b>Mandatory/Optional</b> | <b>Supported Values:</b>  | <b>Provisioned Value:</b>          |
|                                       | -                         | -                         | -                         | -                                  |

|                    |                                 |                            |                          |                           |
|--------------------|---------------------------------|----------------------------|--------------------------|---------------------------|
|                    | <b>ObservedEvent Parameters</b> | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b> |
|                    | -                               | -                          | -                        | -                         |
| <b>Statistics</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          | <b>Supported Values:</b>  |
| None               | -                               | -                          |                          | -                         |
| <b>Error Codes</b> | <b>Mandatory/ Optional</b>      |                            |                          |                           |
| None               | -                               |                            |                          |                           |

## 5.14.3.24 Advanced audio server base package for TTS enhancement

Table 5.14.3.24.1: Package Usage Information for TTS enhancement package

| <b>Properties</b>                                       | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
|---|---------------------------------|----------------------------|--------------------------|------------------------------------|
| None  | -                               | -                          | -                        | -                                  |
| <b>Signals</b>  | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          | <b>Duration Provisioned Value:</b> |
| Play Segment Identifier (aastts/playsid, 0x00a8/0x0001) | M                               | ADD, MOD, MOVE             |                          | -                                  |
|   | <b>Signal Parameters</b>        | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
| Announcement (an,0x0001)                                | M                               | M                          | ALL                      | -                                  |
| Iterations (it, 0x0003)                                 | M                               | M                          | ALL                      | -                                  |
| Interval (iv,0x0004)                                    | O                               | O                          | ALL                      | -                                  |
| Direction (di,0x0005)                                   | M                               | M                          | Ext (0x01)<br>Int(0x02)  | Default=External                   |
| Play script (aastts/playscript, 0x00a8/0x0002)          | M                               | ADD, MOD, MOVE             |                          | -                                  |
|   | <b>Signal Parameters</b>        | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Duration Provisioned Value:</b> |
| Script (script,0x0001)                                  | M                               | M                          | (NOTE 1)                 | -                                  |
| Iterations (it,0x0003)                                  | M                               | M                          | ALL                      | -                                  |
| Interval (iv, 0x0004)                                   | O                               | O                          | ALL                      | -                                  |
| Direction (di,0x0005)                                   | M                               | M                          | Ext (0x01)<br>Int(0x02)  | Default=External                   |
| <b>Events</b>   | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          |                                    |
| TTS operation failure(aastts/ttsfail, 0x00a8/0x0001)    | M                               | ADD, MOD, NOTIFY           |                          |                                    |
|   | <b>Event Parameters</b>         | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| None  | -                               | -                          | -                        | -                                  |
|   | <b>ObservedEvent Parameters</b> | <b>Mandatory/ Optional</b> | <b>Supported Values:</b> | <b>Provisioned Value:</b>          |
| Return Code (rc ,0x0001)                                | M                               | M                          | ALL                      | -                                  |
| <b>Statistics</b>                                       | <b>Mandatory/ Optional</b>      | <b>Used in command:</b>    |                          | <b>Supported Values:</b>           |
| None  | -                               | -                          |                          | -                                  |
| <b>Error Codes</b>                                      | <b>Mandatory/ Optional</b>      |                            |                          |                                    |
| None  | -                               |                            |                          |                                    |

NOTE 1: The value shall comply with the Annex X : "The W3C SSML Profile for TTS function".

## 5.14.3.25 ASR Package

Table 5.14.3.25.1: Package Usage Information for ASR Package

| Properties  | Mandatory/<br>Optional                                    | Used in command:       | Supported Values:                     | Provisioned Value:             |
|---|---|------------------------|---------------------------------------|--------------------------------|
| None  | -   | -                      | -                                     | -                              |
| Signals   | Mandatory/<br>Optional                                    | Used in command:       |                                       | Duration Provisioned<br>Value: |
| ASR recognition with<br>grammar<br>script(asr/asrws,<br>0x00a6/0x0001)                | M   | ADD, MOD, MOVE         |                                       | -                              |
|   | Signal Parameters   | Mandatory/<br>Optional | Supported<br>Values:                  | Duration Provisioned<br>Value: |
|   | grammar file<br>(rgsf, 0x0002)                            | M                      | (NOTE 1)                              | -                              |
|   | Recognition<br>grammar script<br>format<br>(rgsf, 0x0004) | M                      | ABNF (0x0001) □<br>XML (0x0002)       | -                              |
|   | recognition mode<br>(rm, 0x0005)                          | M                      | Normal (0x0001) □<br>Hotword (0x0002) | -                              |
|   | End Input Key<br>(eik, 0x0006)                            | M                      | ALL                                   | -                              |
| ASR recognition with<br>grammar<br>identifier(asr/asrid,<br>0x00a6/0x0002)            | M   | ADD, MOD, MOVE         |                                       | -                              |
|   | Signal Parameters   | Mandatory/<br>Optional | Supported<br>Values:                  | Duration Provisioned<br>Value: |
|   | Recognition<br>grammar identifier<br>(rgid, 0x0002)       | M                      | ALL                                   | -                              |
|   | Recognition<br>grammar script type<br>(rgst, 0x0003)      | M                      | SRGS (0x0001)                         | -                              |
|   | Recognition<br>grammar script<br>format<br>(rgsf, 0x0004) | M                      | ABNF (0x0001) □<br>XML (0x0002)       | -                              |
|   | recognition mode<br>(rm, 0x0005)                          | M                      | Normal (0x0001) □<br>Hotword (0x0002) | -                              |
| End Input Key<br>(eik, 0x0006)  | M   | ALL                    | -                                     |                                |
| Events  | Mandatory/<br>Optional                                    | Used in command:       |                                       |                                |
| ASR failure<br>(asr/asrfail,<br>0x00a6/0x0001)  | M   | ADD, MOD, NOTIFY       |                                       |                                |
|   | Event<br>Parameters                                       | Mandatory/<br>Optional | Supported<br>Values:                  | Provisioned Value:             |
|   | None  | -                      | -                                     | -                              |
|   | ObservedEvent<br>Parameters                               | Mandatory/<br>Optional | Supported<br>Values:                  | Provisioned Value:             |
| Return Code<br>(rc, 0x0001)   | M   | ALL                    | -                                     |                                |
| ASR<br>success(asr/asrsucc,<br>0x00a6/0x0002)   | M   | ADD, MOD, NOTIFY       |                                       |                                |
|   | Event<br>Parameters                                       | Mandatory/<br>Optional | Supported<br>Values:                  | Provisioned Value:             |
|   | None  | -                      | -                                     | -                              |
|   | ObservedEvent<br>Parameters                               | Mandatory/<br>Optional | Supported<br>Values:                  | Provisioned Value:             |
| ASR result<br>(asrr, 0x0001)  | M   | ALL                    | -                                     |                                |
| Statistics  | Mandatory/<br>Optional                                    | Used in command:       | Supported Values:                     |                                |
| None  | -   | -                      | -                                     |                                |
| Error Codes   | Mandatory/ Optional                                       |                        |                                       |                                |
| None  | -   |                        |                                       |                                |
| NOTE 1: The value shall comply with Annex X. "the W3C SRGS Profile for ASR function". |   |                        |                                       |                                |



## 5.14.3.26 Multimedia Recording Package

Table 5.14.3.26.1: Package Usage Information for Multimedia Recording Package

| Properties                                    | Mandatory/<br>Optional                | Used in command:       | Supported Values:           | Provisioned Value:             |
|---|---------------------------------------|------------------------|-----------------------------|--------------------------------|
| None  | -                                     | -                      | -                           | -                              |
| Signals                                       | Mandatory/<br>Optional                | Used in command:       |                             | Duration Provisioned<br>Value: |
| PlayRecord<br>(mrp/playrec,<br>0x00??/0x0002) | M                                     | ADD, MOD, MOVE         |                             | -                              |
|   | Signal Parameters                     | Mandatory/<br>Optional | Supported<br>Values:        | Duration Provisioned<br>Value: |
|   | Record Length<br>Timer(rlt, 0x0008)   | M                      | ALL                         | -                              |
|   | Recording Identifier<br>(rid, 0x0009) | M                      | ALL                         | -                              |
|   | record direction<br>(rd,0x0011)       | M                      | Ext□0x0001□,<br>Int(0x0002) | -                              |
| Events  | Mandatory/<br>Optional                | Used in command:       |                             |                                |
| none  | -                                     | -                      |                             |                                |
|   | Event<br>Parameters                   | Mandatory/<br>Optional | Supported<br>Values:        | Provisioned Value:             |
|   | -                                     | -                      | -                           | -                              |
|   | ObservedEvent<br>Parameters           | Mandatory/<br>Optional | Supported<br>Values:        | Provisioned Value:             |
|   | -                                     | -                      | -                           | -                              |
| Statistics                                    | Mandatory/<br>Optional                | Used in command:       | Supported Values:           |                                |
| None  | -                                     | -                      | -                           |                                |
| Error Codes                                   | Mandatory/ Optional                   |                        |                             |                                |
| None  | -                                     |                        |                             |                                |

## 5.15 Mandatory Support of SDP and Annex C Information Elements

The v=, o=, s=, m=, c=, t=, a= and b= lines of the SDP [20] syntax shall be supported. All other lines should be ignored if received.

Table 5.15.1

| Supported Annex C and SDP information elements: |                 |             |
|---|-----------------|-------------|
| Information Element                             | Annex C Support | SDP Support |
|   |                 |             |

|                          |          |  |
|--------------------------|----------|--|
| Protocol version (v=)    | "SDP_V " | <p>The protocol version (v=) line contains a single field:<br/>v= &lt;version&gt;</p> <p>and shall be used in accordance with RFC 2327 [20] (i.e. v=0).</p>  |
| Origin (o=)              | "SDP_O " | <p>The origin line consists of 6 fields:<br/>o= &lt;user name&gt; &lt;session ID&gt; &lt;version&gt; &lt;network type&gt;<br/>&lt;address type&gt; &lt;address&gt;.</p> <p>The MRFC is not required to supply this line but shall accept it.</p> <p>The MRFP should populate this line as follows or use the value received from the MRFC:</p> <ul style="list-style-type: none"> <li>- &lt;user name&gt; should contain an hyphen</li> <li>- &lt;session ID&gt; and &lt;version&gt; should contain one or more digits as described in RFC 2327 [20]</li> <li>- &lt;network type&gt; shall be set to IN</li> <li>- &lt;address type&gt; shall be set to IP4 or IP6 The Address Type shall be set to "IP4" or "IP6" depending on the addressing scheme used by the network to which the MRFP is connected.</li> <li>- &lt;address&gt; should contain the fully qualified domain name of the gateway.</li> </ul>   |
| Session Name (s=)        | "SDP_S"  | <p>The session name (s=) line contains a single field:<br/>s= &lt;session-name&gt;.</p> <p>The MRFC is not required to supply a session name but shall accept one. This line may be used to convey correlation information for use in CDRs.</p> <p>The MRFP shall use an hyphen "-" as a session name or the value received from the MRFC.</p>   |
| Connection data (c=)     | "SDP_C " | <p>The connection data line consists of 3 fields:<br/>c= &lt;network-type&gt; &lt;address-type&gt; &lt;connection-address&gt;</p> <ul style="list-style-type: none"> <li>- The &lt;network-type&gt; shall be set to "IN".</li> <li>- The &lt;address-type&gt; shall be set to "IP4" or "IP6" depending on the addressing scheme used by the network to which the MRFP is connected.</li> <li>- The &lt;connection-address&gt; sent by the MRFC in the remote descriptor is the address to which the MRFP shall send the media flows.</li> <li>- The &lt;connection-address&gt; sent by the MRFC in local descriptors may be a unicast IPv4 or IPv6 address or it may be wildcarded to allow the MRFP to choose an address. In the second case, MGs shall fill this field with a unicast IP address at which they will receive the media stream. Thus a TTL value shall not be present and a "number of addresses" value shall not be present. The field shall not be filled with a fully-qualified domain name instead of an IP address.</li> </ul> <p>When the &lt;connection address&gt; is wildcarded (i.e. choose wildcard) by the MRFC, the MRFP allocates an IP address based on the address type. The addressing space for which this address is taken may depend on the termination ID supplied by the MRFC.</p> |
| Media announcements (m=) | "SDP_M " | <p>Media Announcements (m=) lines consist of 3 fields:<br/>m= &lt;media&gt; &lt;port&gt; &lt;transport&gt; &lt;format&gt;</p> <ul style="list-style-type: none"> <li>- The &lt;media&gt; field shall be set to "audio" or "video"</li> <li>- The &lt;port&gt; field in remote descriptors is provided by the MRFC and represents the port to which the MRFP shall send the media flows.</li> <li>- The &lt;port&gt; field in local descriptors may be provided by the MRFC or wildcarded (i.e. choose wildcard) to allow the MRFP to choose a value for the port on which it wishes to receive the</li> </ul>  |

|                 |          |  |
|-----------------|----------|--|
|                 |          | <p>media stream</p> <ul style="list-style-type: none"> <li>- The &lt;transport&gt; field shall be set to "RTP/AVP".</li> <li>- The &lt;format&gt; field may be explicitly supplied by the MRFC, wildcarded or overspecified. If the MRFC wishes to request the MRFP to choose which media formats it wishes to use for the call then the MRFC shall provide a "\$" wildcard. If the MRFC wishes to suggest that the MRFP selects a media format from a list of possible media formats then it shall provide a list of appropriate media types in accordance with SDP. All conforming gateways shall support at least format "8" for RTP/AVP (i.e. G.711 A-Law).</li> </ul> <p>Dynamic payloads shall not be used when a static RTP/AVP payload value is defined in RFC 3551[21].</p> |
| Bandwidth (b=)  | "SDP_B " | <p>The Bandwidth (b=) line consists of 2 fields:<br/> <i>b= &lt;modifier&gt;: &lt;bandwidth-value&gt;</i></p> <p>Bandwidth information shall be supplied by the MRFC if the required bandwidth cannot be immediately derived from the information contained in the m= line. If absent, the MRFP shall assume a reasonable default bandwidth value for well-known codecs and shall provide this value in the response sent to the MRFC. The Modifier field shall be set to "AS".</p> <p>The Bandwidth Value field shall be set to the maximum bandwidth requirement of the media stream in kbit/s. The bandwidth value shall take into account all headers down to the IP layer, including a 5% bandwidth for RTCP packets.</p>   |
| Time (t=)       | "SDP_T " | <p>The time (t=) line consists of two fields:<br/> <i>t= &lt;start-time&gt; &lt;stop-time&gt;</i>.</p> <p>This line is ignored by both the MRFC and the MRFP if received in local and remote descriptors.</p> <p>The MRFC is not required to supply a time description but shall accept one.</p> <p>When supplied, this line shall be set to 0 0.</p>  |
| Attributes (a=) | "SDP_A " | <p>Attributes (a=) lines consist of two fields:<br/> <i>a= &lt;attribute&gt;: &lt;value&gt;</i></p> <p>One or more of the "a" attribute lines specified below may be included, depending on the payload type. An attribute line not specified below should not be used. Only the following attributes are understood by the MRFP. Other attributes are ignored.</p> <p><i>a= rtpmap: &lt;payload type&gt; &lt;encoding name&gt;/&lt;clock rate&gt; [/&lt;encoding parameters&gt;]</i><br/> <i>a= fmp: &lt;format&gt; &lt;format specific parameters&gt;</i><br/> <i>a= ptime: &lt;time&gt;</i></p>   |

## 5.16 Optional support of SDP and Annex C information elements

*Specifies what SDP attributes and Annex C information elements may be supported.*

**Table 5.16.1:**

| Optional Annex C and SDP information elements: |                    |             |                       |
|--|--------------------|-------------|-----------------------|
| Information Element                            | Annex C Support    | SDP Support | Support Dependent on: |
| <name>   | <Annex C property> | <Describe>  | <Describe>            |

## 5.17 Procedures

### 5.17.1 Formats and Codes

Table 5.17.1.1 shows the parameters which are required for the procedures defined in the following clauses.

The coding rules applied in ITU-T Recommendation H.248.1 [10] for the applicable coding technique shall be followed for the UMTS capability set.

The binary encoding rules which are applicable to the defined Abstract Syntaxes are the Basic Encoding Rules for Abstract Syntax Notation One, defined in ITU-T Recommendation X.690 [41]. Specifically in accordance with ITU-T Recommendation X.690 [41] section 7.3, alternative encodings based on the definite and indefinite form of length are permitted by the basic encoding rules as a sender's option. Receivers shall support both alternatives.

Unsupported values of parameters or properties may be reported by the MGW and shall be supported by the MSC as such by using H.248.1 error code #449 "Unsupported or Unknown Parameter or Property Value". **Error Text in the error Descriptor:** The unsupported or unknown value is included in the error text in the error descriptor.

Table 5.17.1.1: Information Elements Used in Procedures

| Signalling Object             | H.248 Descriptor                      | Coding   |
|-------------------------------|---------------------------------------|--|
| Announcement Cause            | Events<br>ObservedEvents              | The "Meth" parameter in g/sc event per ITU-T Recommendation H.248.1 [3] Annex E.1.2  |
| Announcement Completed        | Events<br>ObservedEvents              | The g/sc event per ITU-T Recommendation H.248.1 [3] Annex E.1.2  |
| Announcement Cycles           | Signal                                | The "noc" parameter as per ITU-T Recommendation H.248.7 [5], Clause 4.3.1  |
| Announcement Variant          | Signal                                | The "av" parameter as per ITU-T Recommendation H.248.7 [5], Clause 4.3.1   |
| ASR Cause                     | Events<br>ObservedEvents              | TBD  |
| Cause                         | Events<br>ObservedEvents              | Encoded as "Meth" parameter in g/sc event per ITU-T Recommendation H.248.1 [3] Annex E.1.2   |
| Codec List                    | Local Descriptor or Remote Descriptor | <fmt list> in a single SDP m-line.<br>For a static RTP payload type, the codec type should be implied by the RTP payload type, if not then each codec type shall be provided in a separate SDP "a=rtpmap"-line and possibly additional SDP "a=fmtp"-line(s). See Clause 10.2.<br>For a dynamic RTP payload type, for each codec information on the codec type shall be provided in a separate SDP "a=rtpmap"-line and possibly additional SDP "a=fmtp"-line(s). See Clause 10.2. |
| Confidence Score              | ObservedEvents                        | TBD  |
| Context ID                    | NA                                    | Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A.<br>Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B.  |
| Digit                         | Observed Events                       | Encoding as per ITU-T Recommendation H.248.1 Annex E.6.2.<br>Digits are reported individually by the MRFP.   |
| DTMFTrigger                   | Signal Descriptor                     | "endinputkey, eik" see H,249a1 [26] Clause 16.3.1.1.16.  |
| End of Recording Notification | Events<br>ObservedEvents              | Enables the MRFC to be informed of the end of a recording.<br>Corresponds to aasrec/audfail (mrp/audfail) and aasrec/precsucc, (mrp/precsucc) events see ITU-T Recommendation H.248.9a1 [26] 12.2.   |
| Input Time                    | Signal Descriptor                     | "waiting time for input, wit" parameter in ITU-T Recommendation H.248.9a1 [26] Clause 12.3.1.1.5.  |
| IP Address                    | Local Descriptor or Remote Descriptor | <connection address> in SDP "c-line"   |
| Maximum Record Time           | Signal                                | "Record Length Timer, rlt" parameter in H,249a1 [26] Clause 16.3.1.1.8   |
| Media Identifier              | Signal                                | TBD  |
| Mediatype                     | Local Descriptor or Remote Descriptor | <media> in sdp m-line<br>"audio" for voice service, and "image" for T.38 service.  |
| Multimedia file format        |                                       | To Be Defined  |
| Port                          | Local Descriptor or Remote Descriptor | <port> in SDP m-line.<br><transport> in SDP m-line shall be set to value "RTP/AVP" for voice service   |
| Recognition Result            | ObservedEvents                        | "asrr" parameter to "asrsucc" event in H,249a1 [26] Clause 12.2.2.2.1  |
| Record File Format            | Signal                                | To Be Defined  |
| Record File Identifier        | Signal                                | "rid" parameter in playrec signal H,249a1 [26] Clause 16.3.1.1.9   |
| Reserve_Value                 | Local Control                         | ITU-T Recommendation H.248.1 [9] Mode property.<br>Binary Encoding: Encoding as per ITU-T Recommendation H.248.1 Annex A "reserveValue"<br>Textual Encoding: Encoding as per ITU-T Recommendation H.248.1 Annex B "reservedValueMode".   |
| Result Interpretation         | Events<br>ObservedEvents              | TBD  |
| RtcpbwRS                      | Local Descriptor or Remote Descriptor | <bandwidth> in SDP "b:RS"-line.  |
| RtcpbwRR                      | Local Descriptor or Remote Descriptor | <bandwidth> in SDP "b:RR"-line.  |
| RTPpayload                    | Local Descriptor or Remote Descriptor | <fmt list> in SDP m-line   |

|                |                          |   |
|----------------|--------------------------|---|
| SRGS Grammar   | Signal                   | "grammar file, gf" parameter in asr/asr signal in H,249a1 [26] Clause 12.3.1.1.2  |
| SSML           | Signal                   | "an" parameter in the aasts/play signal in H,249a1 [26] Clause 14.3.1.1.1   |
| Stream Number  | Stream                   | Encoding as per ITU-T Recommendation H.248.1 Annex B "Stream"/"ST".<br>For a single stream, this may be omitted by the MRFC.            |
| Termination ID | NA                       | Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A.<br>Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B. |
| Text Token     | Events<br>ObservedEvents | "asrr" parameter in "asr/asrsucc" in H,249a1 [26] Clause 12.2.2.2.1   |
| Timing         | Events                   | As in dd package H.248.1 [3] Annex E.6.2, (end tone detected shall be used)   |
| Tone Completed | Events<br>ObservedEvents | "g/sc" see H.248.1 [3] Annex E.1.2  |
| Tone Duration  | Signal                   | As in the respective tone package   |
| Tone Identity  | Signal                   | Encoding as per ITU-T Recommendation H.248.1 Annex B and the package which defines the tone (Tone Signal Ids only).                     |
| Transaction ID | NA                       | Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A.<br>Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B. |
| TTS Completed  | Events<br>ObservedEvents | "g/sc" see H.248.1 [3] Annex E.1.2 if successful, aasts/ttsfail H,249a1 [26] Clause 14.2.1 if not successful.                           |

## 5.17.2 Call Related Procedures

### 5.17.2.1 General

This section describes the various call related procedures performed by the MRFP, which are listed in table 15.17.2.1.

Table 5.17.2.1.1: MRFP Call Related Procedures

| Transaction defined in 3GPP TS 23.333 [25]                  | Transaction used from TS 29.163 [xx]                        | Supported | Comment      |
|---|---|-----------|--------------|
| Reserve IMS Connection point                                | Reserve IMS Connection point                                | Mandatory | See 5.17.2.2 |
| Configure IMS Resources                                     | Configure IMS Resources                                     | Mandatory | See 5.17.2.3 |
| Reserve IMS Connection Point and configure remote resources | Reserve IMS Connection Point and configure remote resources | Mandatory | See 5.17.2.4 |
| Release IMS termination                                     | Release IMS termination                                     | Mandatory | See 5.17.2.5 |
| Detect DTMF   | Detect IMS RTP Tel Event                                    | Optional  | See 5.17.2.5 |
| Stop DTMF Detection   | End IMS RTP Tel Event                                       | Optional  | See 5.17.2.5 |
| Report DTMF   | Notify IMS RTP Tel Event                                    | Optional  | See 5.17.2.5 |
| Start Playing Multimedia                                    | n.a for re-use  |           |              |
| Stop Playing Multimedia                                     | n.a for re-use  |           |              |
| Playing Multimedia Completed                                | n.a for re-use  |           |              |
| Send Tone   | n.a for re-use  | Optional  | See 5.17.2.5 |
| Stop Tone   | IMS Stop Tone   | Optional  | See 5.17.2.5 |
| Tone Completed  | IMS Tone Completed  | Optional  | See 5.17.2.5 |
| Start Announcement  | n.a for re-use  |           |              |
| Stop Announcement   | Stop Announcement   |           |              |
| Announcement Completed                                      | Announcement Completed                                      |           |              |
| Start Audio Record  | n.a for re-use  |           |              |
| Stop Audio Record   | n.a for re-use  |           |              |
| Audio Record Complete                                       | n.a for re-use  |           |              |
| Start Multimedia Record                                     | n.a for re-use  |           |              |
| Stop Multimedia Record                                      | n.a for re-use  |           |              |
| Multimedia Record Completed                                 | n.a for re-use  |           |              |
| Start TTS   | n.a for re-use  |           |              |
| Stop TTS  | n.a for re-use  |           |              |
| TTS Completed   | n.a for re-use  |           |              |
| Start ASR   | n.a for re-use  |           |              |
| Stop ASR  | n.a for re-use  |           |              |
| ASR Completed   | n.a for re-use  |           |              |

NOTE 1: A procedure defined in this table can be combined with another procedure in the table. This means that they can share the same contextID and termination ID(s) and that they can be combined in the same H.248 command.

### 5.17.2.2 Reserve IMS Termination

The MRFC sends an ADD request command as in Table 5.17.2.2.1.

**Table 5.17.2.2.1: Reserve IMS Termination Request**

| Address Information                                     | Control information  | Bearer information                                    |
|---|--|---|
| Local Descriptor {<br>Port = \$<br>IP Address = \$<br>} | Transaction ID = x<br>Context ID= \$<br>Termination ID = \$<br>If Stream Number specified:-<br>Stream Number<br>If Resources for multiple Codecs<br>required:<br>Reserve_Value | Local Descriptor {<br>Codec List<br>RTP Payloads<br>} |

On reserving the IMS termination, the MRFP responds as in Table 5.17.2.2.2.

**Table 5.17.2.2.2: Reserve IMS Termination Request Acknowledge**

| Address Information                           | Control information   | Bearer information                                    |
|---|---|---|
| Local Descriptor {<br>Port<br>IP Address<br>} | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>Stream Number | Local Descriptor {<br>Codec List<br>RTP Payloads<br>} |

### 5.17.2.3 Configure Remote IMS Resources

The MRFC sends a MODIFY request command as in Table 5.17.2.3.1.

**Table 5.17.2.3.1: Configure Remote IMS Resources Request**

| Address Information  | Control information  | Bearer information   |
|--|--|--|
| If local resources are modified:<br>Local Descriptor {<br>Port<br>IP Address<br>}<br>If remote resources are modified:<br>Remote Descriptor {<br>Port<br>IP Address<br>} | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>If Stream Number specified:<br>Stream Number<br><br>If Resources for multiple Codecs<br>required:<br>Reserve_Value | If local resources are modified:<br>Local Descriptor {<br>Codec List<br>RTP Payloads<br>}<br>If remote resources are modified:<br>Remote Descriptor {<br>Codec List<br>RTP Payloads<br>} |

The MRFP responds as in 5.17.2.3.2.



**Table 5.17.2.3.2: Configure Remote IMS Resources Request Acknowledge**

| Address Information   | Control information  | Bearer information  |
|---|--|---|
| If local resources were provided in request:<br>Local Descriptor {<br>Port<br>IP Address<br>} | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>If Stream Number Specified:<br>Stream Number | If local resources were provided in request:<br>Local Descriptor {<br>Codec List<br>RTP Payloads<br>} |

#### 5.17.2.4 Reserve IMS Termination & Configure Remote IMS Resources

The MRFC sends an ADD request command as in Table 5.17.2.4.1.

**Table 5.17.2.4.1: Reserve IMS Connection Point and configure remote resources Request**

| Address Information   | Control information   | Bearer information  |
|---|---|---|
| Local Descriptor {<br>Port = \$<br>IP Address = \$<br>}<br>Remote Descriptor {<br>Port<br>IP Address<br>} | Transaction ID = x<br>Context ID = \$<br>Termination ID = \$<br><br>If Stream Number Specified:<br>Stream Number<br>If Resources for multiple Codecs<br>shall be reserved:<br>Reserve_Value | Local Descriptor {<br>Codec List<br>RTP Payloads<br>}<br>Remote Descriptor {<br>Codec List<br>RTP Payloads<br>} |

The MRFP responds as in Table 5.17.2.4.2.

**Table 5.17.2.4.2: Reserve IMS Termination & Configure Remote IMS Resources Request Acknowledge**

| Address Information                           | Control information   | Bearer information                                    |
|---|---|---|
| Local Descriptor {<br>Port<br>IP Address<br>} | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>Stream Number | Local Descriptor {<br>Codec List<br>RTP Payloads<br>} |

#### 5.17.2.5 Release IMS Termination

The MRFC sends a SUBTRACT command as in Table 5.17.2.5.1.

**Table 5.17.2.5.1: Release IMS Termination Request**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

On releasing the IMS termination, the MRFP responds as in Table 5.17.2.5.2

**Table 5.17.2.5.2: Release IMS Termination Request Acknowledge**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.6 Send Tone

This procedure is used to play a tone.

The MRFC sends an ADD or MODIFY command as in table 5.17.2.6.1.

**Table 5.17.2.6.1: Send Tone**

| Address information   | Control information  | Bearer information |
|---|--|--------------------|
|   | Transaction ID = x<br>If context already exists:<br>Context ID = C1<br>Else<br>Context = \$<br>If Termination exists:<br>Termination ID = T1<br>Else<br>Termination ID = \$<br><br>If Stream Number specified:<br>Stream Number<br><br>Signal ID = Tone Identity<br>If override Signal Direction<br>Direction = Signal Direction<br><br>If DTMF override<br>Override = DTMFTrigger<br><br>If MRFC wishes to override the<br>default tone duration:<br>Tone Duration<br><br>If MRFC requires to be informed<br>of the end of the tone :-<br>Request End Of Signal<br>Notification |                    |
| NOTE1: Signal Direction shall be either "internal" or "external".<br>NOTE2: Only the Tone Signal Ids shall be used, not the Tone Ids within the PlayTone Signal Id. |  |                    |

The MRFP responds as shown in Table 5.17.2.6.2.

**Table 5.17.2.6.2: SendTone Acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>If local resources were provided in<br>request:<br>Stream Number |                    |

### 5.17.2.7 Stop Tone

This procedure is used to stop a tone. This procedure is the same as the procedure Start Tone however the signal descriptor shall not include the started tone signal. Note that a tone may also be stopped by releasing the IMS termination.

### 5.17.2.8 Tone Completed

This procedure is used to report that a tone has ended.

The MRFP sends a NOTIFY to the MRFC as shown in table 5.17.2.q.1.

**Table 5.17.2.8.1: Tone Completed**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>End Of Signal Notification = Tone Completed<br>Cause |                    |

The MRFC responds as shown in Table 5.17.2.8.2.

**Table 5.17.2.8.2: Tone Completed Ack**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.9 Start Announcement

This procedure is used to play an announcement, which may be fixed or variable.

The MRFC sends an ADD or MODIFY command as in Table 5.17.2.9.1.

**Table 5.17.2.9.1: Start Announcement**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>If context already exists:<br>Context ID = C1<br>Else<br>Context = \$<br>If Termination exists:<br>Termination ID = T1<br>Else<br>Termination ID = \$<br><br>If Stream number specified:<br>Stream Number<br><br>Announcement Identity<br>If override Signal Direction<br>Direction = Signal Direction<br><br>If DTMF override<br>Override = DTMFTrigger<br><br>If MRFC wishes to override the<br>default number of cycles:<br>Announcement Cycles<br><br>If MRFC wishes to override the |                    |

|   |   |  |
|---|---|--|
|   | default announcement variant:<br>Announcement Variant<br><br>If MRFC requires to be informed<br>of the end of the fixed<br>announcement :-<br>Request End Of Signal<br>Notification |  |
| NOTE1: Signal Direction shall be either "internal" or "external".<br>NOTE2: Stream mode may be maintained as for the ongoing call or may be changed be restricted to<br>"send only".<br>NOTE3: Signal Lists shall be supported. |   |  |

The MRFP responds as shown in Table 5.17.2.9.2.

**Table 5.17.2.9.2: Start Announcement Acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>If local resources were provided in<br>request:<br>Stream Number |                    |

### 5.17.2.10 Stop Announcement

This procedure is used to stop an announcement. This procedure is the same as the procedure Start Announcement however the signal descriptor shall not include the started announcement signal. Note that an announcement may also be stopped by releasing the IMS termination.

### 5.17.2.11 Announcement Completed

This procedure is used to report that an announcement has ended.

The MRFP sends a NOTIFY to the MRFC as shown in table 5.17.2.11.1.

**Table 5.17.2.11.1: Announcement Completed**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>End Of Signal Notification =<br>Announcement Completed<br>Cause = Announcement Cause |                    |

The MRFC responds as shown in Table 5.17.2.11.2.

**Table 5.17.2.11.2: Announcement Completed Ack**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.12 Play TTS

This procedure is used to play out a text file as speech.

The MRFC sends an ADD or MODIFY command as in Table 5.17.2.12.1.

**Table 5.17.2.12.1: Play TTS request**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>If context already exists:<br>Context ID = C1<br>Else<br>Context = \$<br>If Termination exists:<br>Termination ID = T1<br>Else<br>Termination ID = \$<br><br>If Stream number specified:<br>Stream Number<br>If override Direction<br>TTS Direction = Signal Direction<br><br>If DTMF override<br>DTMF Stop TTS =DTMFTrigger<br><br>Text Block = SSML<br><br>If MRFC requires to be informed<br>of the end of TTS:-<br>Request End Of Signal<br>Notification |                    |

The MRFP responds as shown in Table 5.17.2.12.2.

**Table 5.17.2.12.2: Play TTS Acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>If local resources were provided in<br>request:<br>Stream Number |                    |

### 5.17.2.13 Stop TTS

This procedure is used to stop TTS play. This procedure is the same as the procedure Start TTS however the signal descriptor shall not include the started TTS signal. Note that an TTS play may also be stopped by releasing the IMS termination.

### 5.17.2.14 TTS Completed

This procedure is used to report that an TTS play has ended.

The MRFP sends a NOTIFY to the MRFC as shown in table 5.17.2.14.1.

**Table 5.17.2.14.1: TTS Completed**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>End Of Signal Notification = TTS Completed<br>Cause |                    |

The MRFC responds as shown in Table 5.17.2.14.2.

**Table 5.17.2.14.2: TTS Completed Ack**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.15 Start Audio Record

This procedure enables a caller to leave/record a voice message (e.g. in a voice mail application).

The MRFC sends an ADD or MODIFY command as in table 5.17.2.15.1.

**Table 5.17.2.15.1: Start Audio Record**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>If context already exists:<br>Context ID = C1<br>Else<br>Context = \$<br>If Termination exists:<br>Termination ID = T1<br>Else<br>Termination ID = \$<br><br>If Stream Number specified:<br>Stream Number<br><br>If specific record file<br>Recording File Identity =<br>Record File Identifier<br><br>If request record file identity<br>Recording File Identity = ?<br><br>If maximum record time<br>Maximum Recording Length =<br>Maximum Record Time<br>If MRFC requires to be informed<br>of the end of the recording :-<br>End Of Recording<br>Notification |                    |

The MRFP responds as shown in table 5.17.2.15.2.

**Table 5.17.2.15.2: Start Audio Record acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>If local resources were provided in request:<br>Stream Number<br>If requested record file identity<br>Recording File Identity = Record File Identifier |                    |

**5.17.2.16 Stop Audio Record**

This procedure is used to stop recording of audio. Note that Audio Record may also be stopped by releasing the IMS termination.

**Table 5.17.2.16.1: Stop Audio Record**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>Stop Audio Record Indication<br><br>If End of Audio Record Notification previously requested :<br>Stop End of Record Notification |                    |

The MRFP responds as shown in Table 5.17.2.16.2.

**Table 5.17.2.16.2: Stop Audio Record Response**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

**5.17.2.17 Audio Record Complete**

This procedure enables the MRFP to inform the MRFC when an audio recording is complete.

The MRFP sends a NOTIFY command as in table 5.17.2.17.1.

**Table 5.17.2.17.1: Audio Record Complete**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>End Of Recording Notification |                    |

The MRFC responds as shown in table 5.17.2.17.2.

**Table 5.17.2.17.2: Audio Record Complete Acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.18 Detect DTMF

This procedure is used to collect DTMF digits.

The MRFP applies the procedures defined in RFC 4733 [22] to receive DTMF digits at the user plane, however only complete single digits shall be reported, i.e. the MRFP shall wait until E-bit is set to 1 before reporting the digit to the MRFC.

The MRFC sends an ADD or MODIFY command as in Table 5.17.2.18.1.

**Table 5.17.2.18.1: Detect DTMF**

| Address information  | Control information   | Bearer information |
|--|---|--------------------|
|  | Transaction ID = x<br>If context already exists:<br>Context ID = C1<br>Else<br>Context = \$<br>If Termination exists:<br>Termination ID = T1<br>Else<br>Termination ID = \$<br><br>If Stream Number specified:<br>Stream Number<br><br>NotificationRequested (Event ID = x, "Report_DTMF (Digit,Timing)") |                    |
| NOTE1: Only "end tone detected" shall be requested by the MRFC.<br>NOTE2: All digits shall be requested i.e. Toneld shall be wildcarded. |   |                    |

The MRFP responds as shown in Table 5.17.2.18.2.

**Table 5.17.2.18.2: Detect DTMF acknowledge**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>If local resources were provided in request:<br>Stream Number |                    |

### 5.17.2.19 Report DTMF

This procedure is used to notify the MRFC of detected DTMF digits.

The MRFP sends a NOTIFY command as in Table 5.17.2.19.1.



**Table 5.17.2.19.1: Report DTMF**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>Digit Notification = digit |                    |

The MRFC responds as shown in Table 5.17.2.19.2.

**Table 5.17.2.19.2: Report DTMF Digit Acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.20 Stop DTMF Detection

This procedure is used to stop DTMF digit detection.

The MRFC sends a MODIFY command as in Table 5.17.2.20.1.

**Table 5.17.2.20.1: Stop DTMF Detection**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>Stop DTMF Digit Collection |                    |

The MRFP responds as shown in Table 5.17.2.20.2.

**Table 5.17.2.20.2: Stop DTMF Digit Detection acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.21 ASR Request

This procedure enables the MRFC to request the MRFP to perform automatic speech recognition; an advanced interaction with the user involving guidance announcements and collection of user input via speech and also possibly DTMF. In turn, the MRFP attempts to recognize and match the detected speech to the specified grammar file and report this to the MRFC.

The MRFC sends an ADD or MODIFY command as in table 5.17.2.21.1.

**Table 5.17.2.21.1: ASR request**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>If context already exists:<br>Context ID = C1<br>Else<br>Context = \$<br>If Termination exists:<br>Termination ID = T1<br>Else<br>Termination ID = \$<br><br>If Stream Number specified:<br>Stream Number<br><br>ASR Grammar File = SRGS<br>grammar<br><br>If MRFC requires to be informed<br>of the end of the ASR :-<br>NotificationRequested (Event ID<br>= x, "Notify ASR Completion<br>(ASR Cause, recognition result,<br>text token, result interpretation,<br>confidence score, input time)") |                    |

The MRFP responds as shown in table 5.17.2.21.2.

**Table 5.17.2.21.2: ASR request acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>If local resources were provided in<br>request:<br>Stream Number |                    |

### 5.17.2.22 ASR Completed

This procedure enables the MRFP to inform the MRFC of the result of an ASR request.

The MRFP sends a NOTIFY command as in table 5.17.2.22.1.

**Table 5.17.2.22.1: ASR Completed**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>ASR Cause<br><br>Optionally:<br>recognition result<br>text token,<br>result interpretation<br>confidence score<br>input time |                    |

The MRFP responds as shown in table 5.17.2.22.2.

**Table 5.17.2.22.2: ASR Completed acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.23 Stop ASR

This procedure is used to stop the ASR procedure.

The MRFC sends a MODIFY command as in Table 5.17.2.23.1.

**Table 5.17.2.23.1: Stop ASR**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>Stop ASR |                    |

The MRFP responds as shown in Table 5.17.2.23.2.

**Table 5.17.2.23.2: Stop ASR acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.24 Start Playing Multimedia

This procedure enables a caller to be connected to a playback of previously recorded multimedia segments. This procedure is similar to that of 5.17.2.9 with the difference that multiple H.248 streams will be used to reflect the multimedia content to be played out.

The MRFC sends an ADD or MODIFY command as in Table 5.17.2.24.1.

**Table 5.17.2.24.1: Start Playing Multimedia**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>If context already exists:<br>Context ID = C1<br>Else<br>Context = \$<br>If Termination exists:<br>Termination ID = T1<br>Else<br>Termination ID = \$ |                    |

|  |  |  |
|--|--|--|
|  | <p>If multiple media sources<br/>Stream NumberX: Media IdentifierX<br/>Stream numberY: Media IdentifierY<br/>Else<br/>Stream NumberX, Stream NumberY: Media Identifier</p> <p>If override multimedia format<br/>Format = Multimedia File Format</p> <p>If override Signal Direction<br/>Direction = Signal Direction</p> <p>If DTMF override<br/>Multimedia Override = DTMFTrigger</p> <p>If MRFC wishes to override the default number of cycles:<br/>play Cycles= iteration</p> <p>If MRFC wishes to override the default announcement variant:<br/>Announcement Variant</p> <p>If MRFC requires to be informed of the end of the multimedia play<br/>Request End Of Signal Notification</p> |  |
| <p>NOTE1: Signal Direction shall be either "internal" or "external".</p> <p>NOTE2: Stream mode may be maintained as for the ongoing call or may be changed be restricted to "send only".</p> <p>NOTE3: Signal Lists shall be supported</p> |  |  |

The MRFP responds as shown in Table 5.17.2.24.2.

**Table 5.17.2.24.2: Start Playing Multimedia Acknowledge**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | <p>Transaction ID = x<br/>Context ID = C1<br/>Termination ID = T1</p> <p>If local resources were provided in request:<br/>Stream Number</p> |                    |

**5.17.2.25 Stop Playing Multimedia**

This procedure is used to stop an announcement. This procedure is the same as the procedure Start Playing Multimedia however the signal descriptor shall not include the started multimedia signal. Note that playing multimedia may also be stopped by releasing the IMS termination.

**5.17.2.26 Playing Multimedia Completed**

This procedure is used to report that a playing multimedia has ended.

The MRFP sends a NOTIFY to the MRFC as shown in table 5.17.2.26.1.

**Table 5.17.2.26.1: Playing Multimedia Completed**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>End Of Signal Notification =<br>Playing Multimedia Completed<br>Cause = Announcement Cause |                    |

The MRFC responds as shown in Table 5.17.2.26.2.

**Table 5.17.2.26.2: Playing Multimedia Completed Ack**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.27 Start Multimedia Record

This procedure enables a caller to leave/record a multimedia message. This procedure is similar to that of Audio Record (5.17.2.15) with the difference that multiple H.248 streams will be used and both audio and video codecs are specified for each participant in the conference. Any prompting "announcements" are played out in the appropriate format by the MRFP based on the fact that multimedia codecs are specified by the MRFC in the Remote Descriptor. Similarly, the MRFP records all received media streams that are consistent with the Local Descriptor of the termination.

The MRFC sends an ADD or MODIFY command as in table 5.17.2.27.1.

**Table 5.17.2.27.1 – Start Multimedia Record**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>If context already exists:<br>Context ID = C1<br>Else<br>Context = \$<br>If Termination exists:<br>Termination ID = T1<br>Else<br>Termination ID = \$<br><br>If Stream Number specified:<br>Stream Number<br><br>If specific record file<br>Recording File Identity =<br>Record File Identifier<br><br>If override multimedia format<br>Format = Multimedia File<br>Format<br><br>If maximum record time<br>Maximum Recording Length =<br>Maximum Record Time<br><br>If MRFC requires to be informed<br>of the end of the recording :-<br>End Of Recording<br>Notification |                    |

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | If request record file identity<br>Recording File Identity = ? |                    |

The MRFP responds as shown in table 5.17.2.27.2.

**Table 5.17.2.27.2: Start Multimedia Record acknowledge**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br>If local resources were provided in request:<br>Stream Number<br><br>If requested record file indentity<br>Recording File Identity = Record File Identifier |                    |

### 5.17.2.28 Stop Multimedia Record

This procedure is used to stop recording of multimedia. Note that Audio Record may also be stopped by releasing the IMS termination.

**Table 5.17.2.28.1: Stop Multimedia Record**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>Stop Multimedia Record Indication<br><br>If End of Multimedia Record Notification previously requested :<br>Stop End of Record Notification |                    |

The MRFP responds as shown in Table 5.17.2.28.2.

**Table 5.17.2.28.2: Stop Multimedia Record Response**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.29 Multimedia Record Completed

This procedure enables the MRFP to inform the MRFC when multimedia recording is complete.

The MRFP sends a NOTIFY command as in table 5.17.2.29.1.

**Table 5.17.2.29.1: Multimedia Record Completed**

| Address information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1<br><br>End Of Recording Notification |                    |

The MRFC responds as shown in table 5.17.2.29.2.

**Table 5.17.2.29.2: Multimedia Record Completed Acknowledge**

| Address information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = C1<br>Termination ID = T1 |                    |

### 5.17.2.30 Adhoc Audio Conference

This includes support for N-party conferences plus the support of audio transcoding. In this case, up to N ephemeral terminations may be placed in a context and appropriate audio transcoding performed by the MRFP between any codec differences between the terminations. In terms of the media mixing, the MRFP mixes audio from terminations N-1, N-2 etc plays to termination N and so forth.

This procedure consists of the creation of the first ephemeral termination of a conference within a context using procedure "Reserve IMS Connection Point and configure remote resources" and then subsequent parties are added using procedures "Reserve IMS Connection Point" and "Configure IMS Resources".

### 5.17.2.31 Multi-Media Conferencing

This is similar to audio conferencing (5.17.2.y) with the difference that multiple H.248 streams will be used and both audio and video codecs are specified for each participant in the conference. The MRFP shall only transcode and mix between streams of the same media type.

## 5.17.3 Non-Call Related Procedures

### 5.17.3.1 General

This section describes the various non-call related procedures which are listed in table 5.17.3.1.1

**Table 5.17.3.1.1: MRFP Non-Call Related Procedures**

| Transaction defined in 3GPP TS 23.333 [25]     | Support   | Comment   |
|--|-----------|---|
| MRFP Out of service                            | Mandatory | 5.17.3.2  |
| MRFP Communication Up                          | Mandatory | 5.17.3.3  |
| MRFP Register                                  | Mandatory | 5.17.3.4  |
| MRFP Re-register                               | Mandatory | 5.17.3.5  |
| MRFC Ordered Re-register                       | Mandatory | 5.17.3.6  |
| MRFC Restoration                               | Optional  | 5.17.3.7  |
| MRFC Out of Service                            | Optional  | 5.17.3.8  |
| Audit Value                                    | Mandatory | 5.17.3.9  |
| Audit Capability                               | Optional  | 5.17.3.10   |
| Capability Update                              | Optional  | 5.17.3.11   |
| MRFP Resource Congestion Handling – Activate   | Mandatory | 5.17.3.12   |
| MRFP Resource Congestion Handling – Indication | Mandatory | 5.17.3.13   |
| Command Rejected                               | Mandatory | 5.17.3.14<br><br>The "Command Rejected" procedure may be used in response both to call-related and non-call-related ITU-T Recommendation H.248 Commands |
| MRFP Restoration                               | Mandatory | 5.17.3.15   |

### 5.17.3.2 MRFP Out Of Service

The MRFP sends a SERVICE CHANGE request command as in Table 5.17.3.2.1.

**Table 5.17.3.2.1: MRFP Out Of Service Request**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>SC Method = FORCED or GRACEFUL<br>SC Reason = 905 Termination Taken OOS or 908, MG Impending Failure |                    |

The MRFC responds as in table 5.17.3.2.2.

**Table 5.17.3.2.2: MRFP Out Of Service Request Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT |                    |

### 5.17.3.3 MRFP Communication Up

The MRFP sends a SERVICE CHANGE request command as in Table 5.17.3.3.1 to the MRFC address to which the control link association was previously established.



**Table 5.17.3.3.1: MRFP Communication Up**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>SC Method = DISCONNECTED<br>SC Reason = 900 , Service Restored |                    |

The MRFC may respond as in table 5.17.3.3.2. If a response is received, the control link association is re-established and the inactivity timer would be restarted.

**Table 5.17.3.3.2: MRFP Communication Up Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT |                    |

#### 5.17.3.4 MRFP Register

The MRFP sends a SERVICE CHANGE request command as in Table 5.17.3.4.1.

**Table 5.17.3.4.1: MRFP Register**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>SC Method = RESTART<br>SC Reason =901Cold Boot or 902, Warm Boot<br>H248 Profile Identity<br>H248 Protocol Version |                    |

The MRFC responds as in table 5.17.3.4.2.

**Table 5.17.3.4.2: MRFP Register Ack**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT<br>H248 Protocol Version<br>If applicable:-<br>H248 Profile Identity |                    |

#### 5.17.3.5 MRFC Restoration

When the MRFC has recovered, the MRFC sends a SERVICE CHANGE as in Table 5.17.3.3.1,

The MRFP may respond as in Table 5.17.3.5.2.

The MRFC sends a SERVICE CHANGE as in Table 5.17.3.5.1

**Table 5.17.3.5.1: MRFC Restoration**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>SC Method = RESTART<br>SC Reason = 901, Cold Boot OR<br>902, Warm Boot |                    |

The MRFP responds as in table 5.17.3.5.2.

**Table 5.17.3.5.2: MRFC Restoration Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT |                    |

### 5.17.3.6 MRFP Re-Register

The MRFP sends a SERVICE CHANGE request command as in Table 5.17.3.6.1.

**Table 5.17.3.6.1: Re-Registration**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>SC Method = Handoff<br>SC Reason = 903, MGC Directed<br>Change<br>H248 Profile Identity<br>H248 Protocol Version |                    |

The MRFC responds as in table 5.17.3.6.2.

**Table 5.17.3.6.2: Re-Registration Ack**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT<br>H248 Protocol Version<br>If applicable:-<br>H248 Profile Identity |                    |

### 5.17.3.7 MRFC Ordered Re-register

The MRFC sends a SERVICE CHANGE request command as in Table 5.17.3.7.1.

**Table 5.17.3.7.1: MRFC Ordered Re-Register**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>SC Method = HANDOFF<br>SC Reason = 903, MGC Directed Change |                    |

The MRFP responds as in table 5.17.3.7.2.

**Table 5.17.3.7.2: MRFC Ordered Re-Register Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT |                    |

The MRFP then performs an MRFP Re-Register procedure according to Clause 5.17.3.6.

### 5.17.3.8 Audit Value

The MRFC sends an AUDIT VALUE request command as in Table 5.17.3.8.1.

**Table 5.17.3.8.1: Audit Value**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>Audit Packages |                    |

The MRFP responds as in table 5.17.3.8.2.

**Table 5.17.3.8.2: Audit Value Ack**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT<br>Packages List |                    |

### 5.17.3.9 Audit Capabilities

The MRFC sends an AUDIT CAPABILITY request command as in Table 5.17.3.9.1.

**Table 5.17.3.9.1: Audit Capability Request**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>Audited Capabilities |                    |

The MRFP responds as in table 5.17.3.9.2.

**Table 5.17.3.8.2.2: Audit Capability Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT<br>Capabilities |                    |

### 5.17.3.10 Capability Update

The MRFP sends a SERVICE CHANGE request command as in Table 5.17.3.10.1.

**Table 5.17.3.10.1: Capability Update**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT<br>SC Method = RESTART<br>SC Reason = 917, Capability<br>Change<br>H248 Profile Identity<br>H248 Protocol Version |                    |

The MRFC responds as in table 5.17.3.10.2.

**Table 5.17.3.10.2 Capability Update Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT |                    |

### 5.17.3.11 MRFC Out of Service

The MRFC sends a SERVICE CHANGE request command as in Table 5.17.3.11.1.

**Table 5.17.3.11.1: MRFC Out Of Service**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT<br>SC Method = FORCED or<br>GRACEFUL<br>SC Reason = 905, Termination<br>Taken OOS |                    |

The MRFP responds as in table 5.17.3.11.2.

**Table 5.17.3.11.2: MRFC Out Of Service Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT |                    |

### 5.17.3.12 MRFP Resource Congestion Handling – Activate

The MRFC sends a MODIFY request command as in Table 5.17.3.12.1.

**Table 5.17.3.12.1: MRFP Resource Congestion Handling – Activate**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>If required :<br>Set Inactivity Timer<br>Request Overload Notification |                    |

The MRFP responds as in table 5.17.3.12.2.

**Table 5.17.3.12.2: MRFP Resource Congestion Handling – Activate Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT |                    |

### 5.17.3.13 MRFP Resource Congestion Handling – Indication

The MRFP sends a NOTIFY request command as in Table 5.17.3.13.1.

**Table 5.17.3.13.1: MRFP Resource Congestion Handling – Indication**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>Overload Notification |                    |

The MRFC responds as in table 5.17.3.13.2.

**Table 5.17.3.13.2: MRFP Resource Congestion Handling – Indication Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT |                    |

### 5.17.3.14 Command Rejected

When the procedure "Command Reject" is required the following procedure is initiated:

The MGW/MGC sends .resp to any command.req with the following information.

**Table 5.17.3.14.1: NYcommand.resp (command reject ) MRFP/MRFC to MRFC/MRFP**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = z<br>Context ID = c1 or no context<br><br>Reason=Error |                    |

### 5.17.3.15 MRFP Restoration

When the MRFP has recovered, the MRFP sends a SERVICE CHANGE as in Table 5.17.3.15.1,

The MRFC may respond as in Table 5.17.3.15.2.

The MRFP sends a SERVICE CHANGE as in Table 5.17.3.15.1

**Table 5.17.3.15.1: MRFC Restoration**

| Address Information | Control information  | Bearer information |
|---------------------|--|--------------------|
|                     | Transaction ID = x<br>Context ID= -<br>Termination ID = ROOT<br>SC Method = RESTART<br>SC Reason = 900, Service Restored |                    |

The MRFC responds as in table 5.17.3.15.2.

**Table 5.17.3.15.2: MRFC Restoration Ack**

| Address Information | Control information   | Bearer information |
|---------------------|---|--------------------|
|                     | Transaction ID = x<br>Context ID = -<br>Termination ID = ROOT |                    |

# Annex A (normative): The W3C SSML Profile for TTS function

## A.1 Introduction

This annex contains a profile to the W3C Speech Synthesis Markup Language (SSML) specification [28]. The SSML specification is a W3C Recommendation, and is designed to provide a rich, XML-based markup language for assisting the generation of synthetic speech in Web and other applications. The essential role of the markup language is to provide authors of synthesizable content a standard way to control aspects of speech such as pronunciation, volume, pitch, rate, etc. across different synthesis-capable platforms.

This annex provides a profile for SSML according to the stage 2 specification of the Mp interface. This profile is referenced by the advanced audio server base package for TTS enhancement.

## A.2 TTS Profile

**Table A.2.1: The profile of SSML**

| Element or attribute     | Description  | Support    |
|--------------------------|--|------------|
| <b>speak</b>             | This is the root element that can contain text to be rendered and the following elements: <b>audio</b> , <b>break</b> , <b>emphasis</b> , <b>lexicon</b> , <b>mark</b> , <b>meta</b> , <b>metadata</b> , <b>p</b> , <b>phoneme</b> , <b>say-as</b> , <b>sub</b> , <b>s</b> , <b>voice</b>  | Mandatory. |
| <b>xml:lang</b>          | This attribute defines the language that applied to the element, subelements and its attributes. The <b>phoneme</b> , <b>emphasis</b> , <b>break</b> , <b>p</b> , and <b>s</b> elements are language specific dependent  | Mandatory  |
| <b>xml:base</b>          | This attribute defines the base URI for resolving relative URI that may be used for the following elements:<br>- The optional <b>src</b> attribute of <b>audio</b> element<br>- The <b>uri</b> attribute of <b>lexicon</b> element   | Optional   |
| <b>lexicon</b>           | An SSML document may reference one or more external pronunciation documents, the <b>lexicon</b> element is used to identified the URI of this external document.<br><br>A lexicon document contains pronunciation for tokens that can appear in a text to be spoken. A <b>lexicon</b> element shall contain an uri.  | Mandatory  |
| <b>meta and metadata</b> | The <b>metadata</b> and <b>meta</b> elements are containers in which information about the document can be placed  | Optional   |
| <b>p and s</b>           | A <b>p</b> element represents a paragraph and <b>s</b> element represents a sentence.<br><br>The use of <b>p</b> and <b>s</b> elements is optional. Where text occurs without an enclosing <b>p</b> or <b>s</b> element the <a href="#">synthesis processor</a> should attempt to determine the structure using language-specific knowledge of the format of plain text.<br><br>The <b>p</b> element can only contain text to be rendered and the following elements: <a href="#">audio</a> , <a href="#">break</a> , <a href="#">emphasis</a> , <a href="#">mark</a> , <a href="#">phoneme</a> , <a href="#">prosody</a> , <a href="#">say-as</a> , <a href="#">sub</a> , <a href="#">s</a> , <a href="#">voice</a> .<br><br>The <b>s</b> element can only contain text to be rendered and the following elements: <a href="#">audio</a> , <a href="#">break</a> , <a href="#">emphasis</a> , <a href="#">mark</a> , <a href="#">phoneme</a> , <a href="#">prosody</a> , <a href="#">say-as</a> , <a href="#">sub</a> , <a href="#">voice</a> . | Optional   |

|                 |   |          |
|-----------------|---|----------|
| <b>say-as</b>   | <p>The <a href="#">say-as</a> element allows the author to indicate information on the type of text construct contained within the element and to help specify the level of detail for rendering the contained text. For example for English when "\$200" appears in a document it may be spoken as "two hundred dollars", similarly, "1/2" may be spoken as "half", "one of two"..</p> <p>Defining a comprehensive set of text format types is difficult because of the variety of languages that have to be considered and because of the innate flexibility of written languages. SSML only specifies the <a href="#">say-as</a> element, its attributes, and their purpose. It does not enumerate the possible values for the attributes. The Working Group expects to produce a separate document that will define standard values and associated normative behavior for these values.</p> <p>The <b>say-as</b> element has three attributes: interpret-as, format and detail</p> <p>The <b>say-as</b> element can only contains text to be rendered</p> | Optional |
| <b>phoneme</b>  | <p>The <a href="#">phoneme</a> element provides a phonemic/phonetic pronunciation for the contained text.</p> <p>The <b>ph</b> attribute is a required attribute that specifies the phoneme/phone string.</p> <p>The <b>alphabet</b> attribute is an optional attribute that specifies the phonemic/phonetic alphabet. An alphabet in this context refers to a collection of symbols to represent the sounds of one or more human languages. The only valid values for this attribute are "<b>ipa</b>" (see the next paragraph) and vendor-defined strings of the form "<b>x-organization</b>" or "<b>x-organization-alphabet</b>".</p> <p>Example:</p> <pre>&lt;phoneme alphabet="ipa" ph="t&amp;#x259;mei&amp;#x325;&amp;#x27E;ou&amp;#x325;"&gt; tomato &lt;/phoneme&gt;</pre>   | Optional |
| <b>sub</b>      | <p>The <a href="#">sub</a> element is employed to indicate that the text in the alias attribute value replaces the contained text for pronunciation. The required alias attribute specifies the string to be spoken instead of the enclosed string. The <a href="#">sub</a> element can only contain text (no elements).</p> <p>Example:</p> <pre>&lt;sub alias="World Wide Web Consortium"&gt;W3C&lt;/sub&gt;</pre>  | Optional |
| <b>Voice</b>    | <p>The <b>voice</b> element indicates the characteristics of the voice rendering.</p> <p>The <b>voice</b> element is commonly used to change the language</p> <p>The following attributes are used:</p> <ul style="list-style-type: none"> <li>- gender: male, female or neutral</li> <li>- age</li> <li>- variant: indicates a preferred variant of the other voice characteristics</li> <li>- name indicates the processor-specific voice name</li> </ul>   | Optional |
| <b>emphasis</b> | <p>The <a href="#">emphasis</a> element requests that the contained text be spoken with emphasis (also referred to as prominence or stress).</p> <p>the optional level attribute indicates the strength of emphasis to be applied. Defined values are "strong", "moderate", "none" and "reduced".</p> <p>The <a href="#">emphasis</a> element can only contain text to be rendered and the following elements: <a href="#">audio</a>, <a href="#">break</a>, <a href="#">emphasis</a>, <a href="#">mark</a>, <a href="#">phoneme</a>, <a href="#">prosody</a>, <a href="#">say-as</a>, <a href="#">sub</a>, <a href="#">voice</a>.</p>  | Optional |
| <b>break</b>    | <p>The <a href="#">break</a> element is an empty element that controls the pausing or other prosodic boundaries between words.</p> <p>The <b>break</b> element is most often used to override the typical automatic behaviour</p>   | Optional |



of a synthesis processor.

The following attributes are used on the break element:

- **strength:** "none", "x-weak", "weak", "medium", "strong", or "x-strong". It indicates the strength of the prosodic break in the speech output. For example, the breaks between paragraphs are typically much stronger than the breaks between words within a sentence.
- **Time:** the time attribute is an option attribute indicating the duration of a pause to be inserted in the output in seconds or milliseconds e.g. "250ms", "3s"

|                |   |          |
|----------------|---|----------|
| <b>prosody</b> | <p>The <b>prosody</b> element permits control of the pitch, speaking rate and volume of the speech output, the optional attributes are:</p> <ul style="list-style-type: none"> <li>- <b>pith:</b> this attribute indicates the baseline pitch. legal value are: a number followed by "Hz", a relative change (+10Hz or +5st, a semitone is half of a tone on the standard diatonic scale), or a "x-low", "low", "medium", "high", "x-high", or "default". The exact meaning of baseline pitch may vary across synthesis processors</li> <li>- <b>pitch contour:</b> the pitch contour is a set of the form (time position,target), the first value is a percentage of the period of the contained text (a <a href="#">number</a> followed by "%") and the second value is the value of the pitch attribute. e.g. (20%, "+10Hz) (40%, "+20Hz) means increase the pitch of 10Hz at 20% of the period of the contained text and 20Hz at 40% of the text duration.</li> <li>- <b>Range:</b> the pitch range although the exact meaning may vary across synthesis processor. The same value as for pitch are legal value from SSML.</li> <li>- <b>Rate:</b> change the speaking rate. Legal values are: a relative change or "x-slow", "slow", "medium", "fast", "x-fast" or "default".</li> <li>- <b>Duration:</b> a value in seconds or milliseconds for the desired time to take to read the element contents.</li> <li>- <b>Volume:</b> the volume for the contained text in the range 0.0 to 100.0. Legal values are: a number, a relative change or "silent", "x-soft", "soft", "medium", "loud", "x-loud", or "default".</li> </ul> | Optional |
| <b>audio</b>   | <p>The <b>audio</b> element supports the insertion of recorded audio files.</p>   | Optional |
| <b>Mark</b>    | <p>The <b>mark</b> element is an empty element that places a marker into the text/tag sequence that the environment will be informed to detect the corresponding position within the rendered output and may report an event when encountered.</p> <p>This element has a <b>name</b> attribute.</p>   | Optional |
| <b>Desc</b>    | <p>The <b>desc</b> element can only occur within the content of the audio element.</p> <p>It describes the textual content of the audio source that may be used when text-only output is being produced by the synthesis processor.</p>   | Optional |

## Annex B (normative): The W3C SRGS Profile for ASR function

### B.1 Introduction

This annex contains a profile to the W3C Speech Recognition Grammar Specification (SRGS) [29]. The SRGS are intended for use by speech recognizers and other grammar processors so that developers can specify the words and patterns of words to be listened for by a speech recognizer.

This annex provides a profile for SRGS according to the stage 2 specification of the Mp interface. This profile is referenced by the ASR Package.

### B.2 SRGS Profile

**Table B.2.1: The profile of SRGS**

| Declaration Item | Description   | Support or not |
|------------------|---|----------------|
| Language         | <p>The <b>language</b> declaration of a grammar provides the <a href="#">language identifier</a> that indicates the primary language contained by the document and optionally indicates a country or other variation. Additionally, any legal rule expansion may be <a href="#">labeled with a language identifier</a>.</p> <p>The language declaration is required for all speech recognition grammars.</p>  | Mandatory      |
| Mode             | <p>The mode of a grammar indicates the type of input that the user agent should be detecting. The default mode is "<b>voice</b>" for speech recognition grammars. An alternative input mode is "<b>dtmf</b>" input.</p> <p>For the Mp interface, only voice mode is supported.</p>  | Mandatory      |
| Root rule        | <p>Both the XML Form and ABNF Form permit the grammar header to optionally declare a single rule to be the root rule of the grammar. The rule declared as the root rule must be defined within the scope of the grammar. The rule declared as the root rule may be <a href="#">scoped</a> as either <b>public</b> or <b>private</b>.</p>  | Mandatory      |
| Tag format       | <p>The <b>tag-format</b> declaration is an optional declaration of a tag-format identifier that indicates the content type of all <a href="#">rule tags</a> and <a href="#">header tags</a> contained within a grammar.</p> <p>The tag-format identifier is a <a href="#">URI</a>. It is recommended that the tag format identifier indicate both the content type and a version. Tags typically contain content for a <a href="#">semantic interpretation</a> processor and in such cases the identifier, if present, should indicate the semantic processor to use.</p> <p>Tag-format identifier values beginning with the string "semantics/x.y" (where x and y are digits) are reserved for use by the W3C Semantic Interpretation for Speech Recognition specification <a href="#">[SEM]</a> or future</p> | Mandatory      |

versions of the specification.

|                       |  |                |
|-----------------------|--|----------------|
| Base URI              | <p>Relative URIs are resolved according to a base URI, which may come from a variety of sources. The base URI declaration allows authors to specify a document's base URI explicitly.</p> <p>The path information specified by the base URI declaration only affects URIs in the document where the element appears.</p> <p>The base URI declaration is permitted but optional in both the XML Form and the ABNF Form.</p>   | Optional       |
| Pronunciation lexicon | <p>A grammar may optionally reference one or more external pronunciation lexicon documents. A lexicon document is identified by a <a href="#">URI</a> with an optional <a href="#">media type</a>.</p> <p>The pronunciation information contained within a lexicon document is used only for tokens defined within the enclosing grammar.</p> <p>The W3C Voice Browser Working Group is developing the Pronunciation Lexicon Markup Language <a href="#">[LEX]</a>. The specification will address the matching process between tokens and lexicon entries and the mechanism by which a speech recognizer handles multiple pronunciations from internal and grammar-specified lexicons. Pronunciation handling with proprietary lexicon formats will necessarily be specific to the speech recognizer.</p> <p>Pronunciation lexicons are necessarily language-specific. Pronunciation lookup in a lexicon and pronunciation inference for any token may use an algorithm that is language-specific. (See <a href="#">Section 2.1</a> for additional information on token handling and pronunciations.)</p> | Mandatory      |
| Metadata              | <p>Grammar documents let authors specify metadata — information about a document rather than document content — in a number of ways.</p> <p>A <a href="#">meta declaration</a> in either the ABNF Form or XML Form may be used to express metadata information in both XML Form and ABNF Form grammars or to reference metadata available in an external resource. The XML Form also supports a <a href="#">metadata element</a> that provides a more general and powerful treatment of metadata information than <b>meta</b>. Since <b>metadata</b> requires an XML metadata schema which cannot be expressed in ABNF, there is no equivalent of <b>metadata</b> in the ABNF Form of grammars.</p>  | Not Applicable |
| Tag                   | <p>A grammar may optionally specify one or more <b>tag</b> declarations in the header. The content of a <b>tag</b> in the header, just like a <a href="#">tag in rule expansions</a>, is an arbitrary string which may be used for <a href="#">semantic interpretation</a>.</p>  | Mandatory      |

---

## Annex C (informative): Change history

| Change history |       |           |      |     |   |       |       |
|----------------|-------|-----------|------|-----|---|-------|-------|
| Date           | TSG # | TSG Doc.  | CR   | Rev | Subject/Comment   | Old   | New   |
| 06-2007        | CT#36 | CP-070336 |      |     | V7.0.0 approved in CT#36  | 1.0.0 | 7.0.0 |
| 09-2007        | CT#37 | CP-070539 | 0001 | 2   | Alignment of stage 3 to proposed stage 2 changes for Audio Record and Multimedia Record | 7.0.0 | 7.1.0 |
| 09-2007        | CT#37 | CP-070539 | 0002 | 1   | Completion of formats and codes   | 7.0.0 | 7.1.0 |
| 09-2007        | CT#37 | CP-070539 | 0003 | 1   | Corrections to Stage 3 Profile  | 7.0.0 | 7.1.0 |
| 09-2007        | CT#37 | CP-070539 | 0004 | 1   | Editorial corrections   | 7.0.0 | 7.1.0 |

---

## History

| <b>Document history</b> |              |             |
|-------------------------|--------------|-------------|
| V7.0.0                  | June 2007    | Publication |
| V7.1.0                  | October 2007 | Publication |
|                         |              |             |
|                         |              |             |
|                         |              |             |