

# ETSI TS 132 172 V6.0.0 (2004-12)

*Technical Specification*

**Digital cellular telecommunications system (Phase 2+);  
Universal Mobile Telecommunications System (UMTS);  
Telecommunication management;  
Subscription Management (SuM)  
Network Resource Model (NRM)  
Integration Reference Point (IRP): Information Service (IS)  
(3GPP TS 32.172 version 6.0.0 Release 6)**



---

Reference

DTS/TSGS-0532172v600

---

Keywords

GSM, UMTS

***ETSI***

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***

Individual copies of the present document can be downloaded from:  
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at  
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
[http://portal.etsi.org/chaircor/ETSI\\_support.asp](http://portal.etsi.org/chaircor/ETSI_support.asp)

---

***Copyright Notification***

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.  
All rights reserved.

**DECT™, PLUGTESTS™ and UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.  
**TIPHON™** and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.  
**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under  
<http://webapp.etsi.org/key/queryform.asp>.

---

## Contents

Intellectual Property Rights .....	2
Foreword.....	2
Foreword.....	5
Introduction .....	5
1    Scope .....	6
2    References .....	6
3    Definitions and abbreviations.....	6
3.1    Definitions.....	6
3.2    Abbreviations .....	6
4    Compliance rules.....	7
5    Modelling approach.....	7
6    Information Object Classes .....	7
6.1    Imported information entities and local labels .....	7
6.2    Class diagram .....	7
6.2.1    Attributes and relationships .....	7
6.2.2    Inheritance .....	8
6.3    Information Object Class definitions .....	9
6.3.1    SuMService.....	9
6.3.1.1    Definition .....	9
6.3.1.2    Attributes.....	10
6.3.2    CSService .....	10
6.3.2.1    Definition .....	10
6.3.2.2    Attributes.....	11
6.3.2.3    Attribute constraints.....	11
6.3.3    PSService.....	12
6.3.3.1    Definition .....	12
6.3.3.2    Attributes.....	12
6.3.3.3    Attribute constraints.....	12
6.3.4    IMSService .....	13
6.3.4.1    Definition .....	13
6.3.4.2    Attributes.....	13
6.3.4.3    Attribute constraints.....	13
6.3.5    SuMSubscribedService .....	13
6.3.5.1    Definition .....	13
6.3.5.2    Attributes.....	13
6.3.6    CSSubscribedService .....	14
6.3.6.1    Definition .....	14
6.3.6.2    Attributes.....	15
6.3.6.3    Attribute constraints.....	15
6.3.7    PSSubscribedService .....	16
6.3.7.1    Definition .....	16
6.3.7.2    Attributes.....	16
6.3.7.3    Attribute constraints.....	16
6.3.8    IMSSubscribedService.....	17
6.3.8.1    Definition .....	17
6.3.8.2    Attributes.....	17
6.3.8.3    Attribute constraints.....	17
6.3.9    SuMSubscriberProfile.....	17
6.3.9.1    Definition .....	17
6.3.9.2    Attributes.....	18
6.3.10    SuMSubscriptionProfile.....	18

6.3.10.1	Definition .....	18
6.3.10.2	Attributes.....	18
6.3.10.3	Attribute constraints.....	18
6.3.11	SuMServiceProfile.....	18
6.3.11.1	Definition .....	18
6.3.11.2	Attributes.....	18
6.3.12	CSServiceProfile.....	18
6.3.12.1	Definition .....	18
6.3.12.2	Attributes.....	20
6.3.12.3	Attribute constraints.....	21
6.3.13	PSServiceProfile .....	22
6.3.13.1	Definition .....	22
6.3.13.2	Attributes.....	23
6.3.13.3	Attribute constraints.....	24
6.3.14	IMSServiceProfile .....	24
6.3.14.1	Definition .....	24
6.3.14.2	Attributes.....	25
6.3.14.3	Attribute constraints.....	25
6.3.15	ServiceProviderFunction .....	25
6.3.15.1	Definition .....	25
6.3.15.2	Attributes.....	25
6.3.16	SubscriptionFunction.....	25
6.3.16.1	Definition .....	25
6.3.16.2	Attributes.....	26
6.4	Information relationship definitions .....	26
6.4.1	Agreement.....	26
6.4.1.1	Definition .....	26
6.4.1.2	Roles .....	26
6.4.1.3	Constraints .....	26
6.4.2	Description.....	26
6.4.2.1	Definition .....	26
6.4.2.2	Roles .....	26
6.4.2.3	Constraints .....	26
6.5	Information attribute definitions.....	27
6.5.1	Definitions and legal values.....	27
<b>Annex A (informative):</b>	<b>Change history .....</b>	<b>31</b>
History .....		32

---

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x the first digit:

- 1 presented to TSG for information;
- 2 presented to TSG for approval;
- 3 or greater indicates TSG approved document under change control.

y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Introduction

The interface Itf-N, defined in 3GPP TS 32.102 [2], is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2].

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project: Technical Specification Group Services and System Aspects; Telecommunication management, as identified below:

TS 32.140: "Subscription Management (SuM) requirements".

TS 32.141: "Subscription Management (SuM) architecture".

TS 32.171: "Subscription Management (SuM) Network Resource Model (NRM) Integration Reference Point (IRP): Requirements".

**TS 32.172:** "**Subscription Management (SuM) Network Resource Model (NRM) Integration Reference Point (IRP): Information Service (IS)**".

TS 32.175: "Subscription Management (SuM) Network Resource Model (NRM) Integration Reference Point (IRP): eXtensible Markup Language (XML) definition".

---

## 1 Scope

The present document defines the Network Resources Model (NRM) for the SuM IRP.

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.140: "Telecommunication management; Subscription Management (SuM) Requirements".
- [4] 3GPP TS 32.141: "Telecommunication management; Subscription Management (SuM) Architecture."
- [5] 3GPP TS 32.171: "Telecommunication management; Subscription Management (SuM) Network Resource Model (NRM) Integration Reference Point (IRP): Requirements".
- [6] 3GPP TS 32.622: "Telecommunication management; Configuration Management (CM); Generic network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [7] 3GPP TS 23.008: "Organization of subscriber data".

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply. For terms and definitions not found here, please refer to 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.140 [3] and TS 32.141 [4].

**Subscription Profile:** see 3GPP TS 32.140 [3].

**Subscription Profile Component:** see 3GPP TS 32.140 [3].

**Subscription Profile Component Definition:** specifies a Subscription Profile Component.

**Subscriber Profile:** see 3GPP TS 32.140 [3].

### 3.2 Abbreviations

For the purposes of the present document the following and the abbreviations in 32.101 [1], 32.102 [2], 32.140 [3] and 32.141 [4] apply.

EM	Element Manager
----	-----------------

IOC	Information Object Class
IRP	Integration Reference Point
MOC	Managed Object Class
NE	Network Element
SuM	Subscription Management

## 4 Compliance rules

The following defines the meaning of Mandatory and Optional IOC attributes and associations between IOCs, in Solution Sets to the IRP defined by the present document.

Solution Sets to the SuM IRP:

- The IRPManager shall support all Mandatory attributes/associations. The IRPManager shall be prepared to receive information related to Mandatory as well as Optional attributes/associations without failure; however the IRPManager does not have to support handling of the Optional attributes/associations.
- The IRPAgent shall support all Mandatory attributes/associations. It may support Optional attributes/associations.

An IRPAgent that incorporates vendor-specific extensions shall support normal communication with a 3GPP SA5-compliant IRPManager with respect to all Mandatory and Optional Managed Object Classes (MOCs), attributes, associations, operations, parameters and notifications without requiring the IRPManager to have any knowledge of the extensions.

## 5 Modelling approach

The modelling approach adopted and used in this IRP is described in 3GPP TS 32.622 [6].

## 6 Information Object Classes


### 6.1 Imported information entities and local labels

Label reference	Local label
32.622 [6], information object class, ManagedFunction	ManagedFunction
32.622 [6], information object class, ManagedElement	ManagedElement

### 6.2 Class diagram

#### 6.2.1 Attributes and relationships


This clause depicts the set of IOCs that encapsulate information relevant for this service. This sub-clause provides the overview of all information object classes in UML. Subsequent clauses provide more detailed specification of various aspects of these Information Object Classes (IOCs).






NOTE: The listed cardinality numbers represent transient as well as steady-state numbers, and reflect all managed object creation and deletion scenarios.

**Figure 1: SuM NRM Containment/Naming and Association diagram**

## 6.2.2 Inheritance



**Figure 2a: SuM NRM Inheritance Hierarchy 1**

**Figure 2b: SuM NRM Inheritance Hierarchy 2****Figure 2c: SuM NRM Inheritance Hierarchy 3****Figure 2d: SuM NRM Inheritance Hierarchy 4**

## 6.3 Information Object Class definitions

### 6.3.1 SuMService

#### 6.3.1.1 Definition

This is an abstract IOC provided for sub-classing only. It provides attribute(s) that are common to Services IOCs.

### 6.3.1.2 Attributes

**Attributes of SuMService**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
agreement-contract	+	M	M	O

### 6.3.2 CSService

#### 6.3.2.1 Definition

In this management context:

- a) This class represents a CS service (see 3GPP TS 23.008 [7]) provided by a service provider
- b) This class contains the valid parameters that define the CS service from subscription point of view.

### 6.3.2.2 Attributes

**Attributes of CSService**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
cSServiceId	+	M	M	-
networkAccessMode	+	M	M	M
basicMSISDNIndicator	+	O	M	M
mSISDNAlertIndicator	+	O	M	M
subscriptionRestriction	+	O	M	M
rSZIlists	+	O	M	M
lSAIdentity	+	O	M	M
lSAPriority	+	O	M	M
lSAPreferentialAccessIndicator	+	O	M	M
lSAActiveModeSupportIndicator	+	O	M	M
lSAOnlyAccessIndicator	+	O	M	M
lSAActiveModeIndicator	+	O	M	M
vPLMNIIdentifier	+	O	M	M
accessRestrictionData	+	O	M	M
privacyExceptionList	+	O	M	M
gMLCNumbers	+	O	M	M
mOLRList	+	O	M	M
serviceTypes	+	O	M	M
mobileStationCategory	+	M	M	M
lMUIIdentifier	+	M	M	M
subscriptionRestriction	+	M	M	M
subscriberStatus	+	M	M	M
gsmSCFAddresslistForODB	+	M	M	M
provisionOfBearerService	+	M	M	M
provisionOfTeleservice	+	M	M	M
bCAssignment	+	O	M	M
barringOfOutgoingCalls	+	O	M	M
barringOfIncomingCalls	+	O	M	M
barringOfRoaming	+	O	M	M
barringOfPremiumRateCalls	+	O	M	M
barringOfSupplementaryServiceManagement	+	O	M	M
barringOfRegistrationOfCallForwarding	+	O	M	M
barringOfInvocationOfCallTransfer	+	O	M	M
operatorDeterminedBarringPLMNspecificData	+	O	M	M
vGCSGroupMembershipList	+	O	M	M
vBSGroupMembershipList	+	O	M	M
broadcastCallInitiationAllowedList	+	O	M	M
originatingCAMELSubscriptionInformationOCSI	+	O	M	M
terminatingCAMELSubscriptionInformationTCSI	+	O	M	M
vMSCTerminatingCAMELSubscriptionInformationVTCSI	+	O	M	M
locationInformationSubscriberStateInformation	+	O	M	M
uSSDCAMELSubscriptionInformationUCSI	+	O	M	M
sSInvocationNotificationSSCSI	+	O	M	M
translationInformationFlagTIFCSI	+	O	M	M
dialledServiceCAMELSubscriptionInformationDCSI	+	O	M	M
uSSDGGeneralCAMELServiceInformationUGCSI	+	O	M	M
shortMessageServiceCAMELSubscriptionInformationMOSMSCSI	+	O	M	M
shortMessageServiceCAMELSubscriptionInformationMTSMSCSI	+	O	M	M
mTSMSCSIVLRNegotiatedCAMELCapabilityHandling	+	O	M	M
gsmSCFAddressforCSI	+	O	M	M
iSTAlertTimer	+	O	M	M
cSAllocationRetentionpriority	+	O	M	M

### 6.3.2.3 Attribute constraints

The optional attributes shall be supported for the following criteria: The NE supports the parameter (see TS 23.008 [7]).

### 6.3.3 PSService

#### 6.3.3.1 Definition

In this management context:

- a) This class represents a PS service (see 3GPP TS 23.008 [7]) provided by a service provider
- b) This class contains the valid parameters that define the PS service from subscription point of view.

#### 6.3.3.2 Attributes

**Attributes of PSService**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
pSServiceId	+	M	M	-
networkAccessMode	+	M	M	M
basicMSISDNIndicator	+	O	M	M
mSISDNAlertIndicator	+	O	M	M
subscriptionRestriction	+	O	M	M
rSZIlists	+	O	M	M
lSAIdentity	+	O	M	M
lSAPriority	+	O	M	M
lSAReferentialAccessIndicator	+	O	M	M
lSAActiveModeSupportIndicator	+	O	M	M
lSAOnlyAccessIndicator	+	O	M	M
lSAActiveModeIndicator	+	O	M	M
vPLMNIIdentifier	+	O	M	M
accessRestrictionData	+	O	M	M
privacyExceptionList	+	O	M	M
gMLCNumbers	+	O	M	M
mOLRList	+	O	M	M
serviceTypes	+	O	M	M
gGSNNumber	+	O	M	M
provisionofTeleservice	+	O	M	M
transferofSMoption	+	M	M	M
barringofPacketOrientedServices	+	O	M	M
pDPType	+	O	M	M
pDPAddress	+	O	M	M
accessPointName	+	O	M	M
vPLMNAddressAllowed	+	O	M	M
qualityofServiceSubscribed	+	O	M	M
pDPContextChargingCharacteristics	+	O	M	M
gPRSCAMELSubscriptionInformationGPRSCSI	+	O	M	M
mOShortMessageServiceCAMELSubscriptionInformationMOSMSCSI	+	O	M	M
mTShortMessageServiceCAMELSubscriptionInformationMTSMSCSI	+	O	M	M
mOSMSCSISGSNNegotiatedCAMELCapabilityHandling	+	O	M	M
mTSMSCSISGSNNegotiatedCAMELCapabilityHandling	+	O	M	M
mobilityManagementforGPRSeventnotificationMGCSI	+	O	M	M
mGCSINegotiatedCAMELCapabilityHandling	+	O	M	M
gsmSCFaddressforCSI	+	O	M	M
subscribedChargingCharacteristics	+	O	M	M

#### 6.3.3.3 Attribute constraints

The optional attributes shall be supported for the following criteria: The NE supports the parameter (See TS 23.008 [7]).

## 6.3.4 IMSService

### 6.3.4.1 Definition

In this management context:

- a) This class represents a IMS service (see 3GPP TS 23.008 [7]) provided by a service provider
- b) This class contains the valid parameters that define the ims service from subscription point of view.

### 6.3.4.2 Attributes

**Attributes of IMSService**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
iMSServiceId	+	M	M	-
barringIndication	+	M	M	M
listofauthorizedvisitednetworkidentifiers	+	M	M	M
registrationStatus	+	M	M	M
sCSCFName	+	M	M	M
serverCapabilities	+	O	M	M
subscribedMediaProfileIdentifier	+	O	M	M
initialFilterCriteria	+	O	M	M
applicationServerInformation	+	O	M	M
serviceIndication	+	M	M	M
primaryEventChargingFunctionName	+	O	M	M
secondaryEventChargingFunctionName	+	O	M	M
primaryChargingCollectionFunctionName	+	M	M	M
secondaryChargingCollectionFunctionName	+	O	M	M
gsmSCFaddressforIMCSI	+	O	M	M
oIMCSI	+	O	M	M
vTIMCSI	+	O	M	M
dIMCS	+	O	M	M

### 6.3.4.3 Attribute constraints

The optional attributes shall be supported for the following criteria: The NE supports the parameter (See TS 23.008 [7]).

## 6.3.5 SuMSubscribedService

### 6.3.5.1 Definition

This is an abstract IOC provided for sub-classing only. It provides attribute(s) that are common to Subscribed Services IOCs.

### 6.3.5.2 Attributes

**Attributes of SuMSubscribedService**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
description-service	+	M	M	O
agreement-offer	+	M	M	O

## 6.3.6 CSSubscribedService

### 6.3.6.1 Definition

In this management context:

- a) This class represents subscription to a CS service (see 3GPP TS 23.008 [7]) for a subscriber. The entire set of CS subscribed services owned by a subscriber constitutes the subscriber's Subscribed Services Profile for CS services.
- b) This class contains the agreed (between the Subscriber and the Service Provider) parameter settings for a CS service that a Subscriber subscribes to.

### 6.3.6.2 Attributes

**Attributes of CSSubscribedService**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
cSSubscribedServiceId	+	M	M	-
networkAccessMode	+	M	M	M
basicMSISDNIndicator	+	O	M	M
mSISDNAlertIndicator	+	O	M	M
subscriptionRestriction	+	O	M	M
rSZIlists	+	O	M	M
lSAIdentity	+	O	M	M
lSAPriority	+	O	M	M
lSAPreferentialAccessIndicator	+	O	M	M
lSAActiveModeSupportIndicator	+	O	M	M
lSAOnlyAccessIndicator	+	O	M	M
lSAActiveModeIndicator	+	O	M	M
vPLMNIdentifier	+	O	M	M
accessRestrictionData	+	O	M	M
privacyExceptionList	+	O	M	M
gMLCNumbers	+	O	M	M
mOLRList	+	O	M	M
serviceTypes	+	O	M	M
mobileStationCategory	+	M	M	M
lMUIIdentifier	+	M	M	M
subscriptionRestriction	+	M	M	M
subscriberStatus	+	M	M	M
gsmSCFAddresslistForODB	+	M	M	M
provisionOfBearerService	+	M	M	M
provisionOfTeleservice	+	M	M	M
bCAssignment	+	O	M	M
barringOfOutgoingCalls	+	O	M	M
barringOfIncomingCalls	+	O	M	M
barringOfRoaming	+	O	M	M
barringOfPremiumRateCalls	+	O	M	M
barringOfSupplementaryServiceManagement	+	O	M	M
barringOfRegistrationOfCallForwarding	+	O	M	M
barringOfInvocationOfCallTransfer	+	O	M	M
operatorDeterminedBarringPLMNspecificData	+	O	M	M
vGCSGroupMembershipList	+	O	M	M
vBSGroupMembershipList	+	O	M	M
broadcastCallInitiationAllowedList	+	O	M	M
originatingCAMELSubscriptionInformationOCSI	+	O	M	M
terminatingCAMELSubscriptionInformationTCSI	+	O	M	M
vMSCTerminatingCAMELSubscriptionInformationVTCSI	+	O	M	M
locationInformation/SubscriberStateInformation	+	O	M	M
uSSDCAMELSubscriptionInformationUCSI	+	O	M	M
sSInvocationNotificationSSCSI	+	O	M	M
translationInformationFlagTIFCSI	+	O	M	M
dialledServiceCAMELSubscriptionInformationDCSI	+	O	M	M
uSSDGGeneralCAMELServiceInformationUGCSI	+	O	M	M
shortMessageServiceCAMELSubscriptionInformationMOSMSCSI	+	O	M	M
shortMessageServiceCAMELSubscriptionInformationMTSMSCSI	+	O	M	M
mTSMSCSIVLRNegotiatedCAMELCapabilityHandling	+	O	M	M
gsmSCFAddressforCSI	+	O	M	M
iSTAlertTimer	+	O	M	M
cSAllocationRetentionpriority	+	O	M	M

### 6.3.6.3 Attribute constraints

The optional attributes shall be supported for the following criteria: The NE supports the parameter (See TS 23.008 [7]).

## 6.3.7 PSSubscribedService

### 6.3.7.1 Definition

In this management context:

- a) This class represents subscription to a PS service (see 3GPP TS 23.008 [7]) for a subscriber. The entire set of PS subscribed services owned by a subscriber constitutes the subscriber's Subscribed Services Profile for PS services.
- b) This class contains the agreed (between the Subscriber and the Service Provider) parameter settings for a PS service that a Subscriber subscribes to.

### 6.3.7.2 Attributes

**Attributes of PSSubscribedService**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
pSSubscribedServiceId	+	M	M	-
networkAccessMode	+	M	M	M
basicMSISDNIndicator	+	O	M	M
mSISDNAlertIndicator	+	O	M	M
subscriptionRestriction	+	O	M	M
rSZIlists	+	O	M	M
lSAIdentity	+	O	M	M
lSAPriority	+	O	M	M
lSAPreferentialAccessIndicator	+	O	M	M
lSAActiveModeSupportIndicator	+	O	M	M
lSAOnlyAccessIndicator	+	O	M	M
lSAActiveModeIndicator	+	O	M	M
vPLMNIdentifier	+	O	M	M
accessRestrictionData	+	O	M	M
privacyExceptionList	+	O	M	M
gMLCNumbers	+	O	M	M
mOLRList	+	O	M	M
serviceTypes	+	O	M	M
gGSNNumber	+	O	M	M
provisionofTeleservice	+	O	M	M
transferofSMoption	+	M	M	M
barringofPacketOrientedServices	+	O	M	M
pDPType	+	O	M	M
pDPAddress	+	O	M	M
accessPointName	+	O	M	M
vPLMNAliasAllowed	+	O	M	M
qualityofServiceSubscribed	+	O	M	M
pDPContextChargingCharacteristics	+	O	M	M
gPRSCAMELSubscriptionInformationGPRSCSI	+	O	M	M
mOSShortMessageServiceCAMELSubscriptionInformationMOSMSCSI	+	O	M	M
mTShortMessageServiceCAMELSubscriptionInformationMTSMSCSI	+	O	M	M
mOSMSCSISGSNNegotiatedCAMELCapabilityHandling	+	O	M	M
mTSMSCSISGSNNegotiatedCAMELCapabilityHandling	+	O	M	M
mobilityManagementforGPRSeventnotificationMGCSI	+	O	M	M
mGCSINegotiatedCAMELCapabilityHandling	+	O	M	M
gsmSCFaddressforCSI	+	O	M	M
subscribedChargingCharacteristics	+	O	M	M

### 6.3.7.3 Attribute constraints

The optional attributes shall be supported for the following criteria: The NE supports the parameter (See TS 23.008 [7]).

## 6.3.8 IMSSubscribedService

### 6.3.8.1 Definition

In this management context:

- a) This class represents subscription to an ims (see 3GPP TS 23.008 [7]) service for a subscriber. The entire set of ims subscribed services owned by a subscriber constitutes the subscriber's Subscribed Services Profile for PS services.
- b) This class contains the agreed (between the Subscriber and the Service Provider) parameter settings for an ims service that a Subscriber subscribes to.

### 6.3.8.2 Attributes

**Attributes of IMSSubscribedService**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
iMSSubscribedServiceId	+	M	M	-
barringIndication	+	M	M	M
listofauthorizedvisitednetworkidentifiers	+	M	M	M
registrationStatus	+	M	M	M
sCSCFName	+	M	M	M
serverCapabilities	+	O	M	M
subscribedMediaProfileIdentifier	+	O	M	M
initialFilterCriteria	+	O	M	M
applicationServerInformation	+	O	M	M
serviceIndication	+	M	M	M
primaryEventChargingFunctionName	+	O	M	M
secondaryEventChargingFunctionName	+	O	M	M
primaryChargingCollectionFunctionName	+	M	M	M
secondaryChargingCollectionFunctionName	+	O	M	M
gsmSCFaddressforIMCSI	+	O	M	M
oIMCSI	+	O	M	M
vTIMCSI	+	O	M	M
dIMCS	+	O	M	M

### 6.3.8.3 Attribute constraints

The optional attributes shall be supported for the following criteria: The NE supports the parameter (See TS 23.008 [7]).

## 6.3.9 SuMSubscriberProfile

### 6.3.9.1 Definition

In this management context:

- a) This class represents the Subscriber Profile.
- b) This class contains the Subscribed Services for a subscriber
- c) This class contains the users for a subscriber.

### 6.3.9.2 Attributes

**Attributes of SuMSubscriberProfile**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
suMSubscriberProfileId	+	M	M	-
suMSubscriberProfileInfo	+	M	M	O

### 6.3.10 SuMSubscriptionProfile

#### 6.3.10.1 Definition

In this management context:

- a) This class represents user's subscription profile of the services contracted by a subscriber.
- b) This class contains Service Profiles for the services contracted by a subscriber and assigned to a user.

#### 6.3.10.2 Attributes

**Attributes of SuMSubscriptionProfile**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
suMSubscriptionProfileId	+	M	M	-
iMSI	+	M	M	M
mSISDN	+	M	M	M
multinumberingMSISDNs	+	M	M	M
iMEISV	+	O	M	-
privateUserIdentity	+	M	M	M
publicIdentity	+	M	M	M

#### 6.3.10.3 Attribute constraints

The optional attributes shall be supported for the following criteria: The NE supports the parameter (See TS 23.008 [7]).

### 6.3.11 SuMServiceProfile

#### 6.3.11.1 Definition

This is an abstract IOC provided for sub-classing only. It provides attribute(s) that are common to Service Profiles IOCs.

#### 6.3.11.2 Attributes

**Attributes of SuMServiceProfile**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
description-specification	+	M	M	O

### 6.3.12 CSServiceProfile

#### 6.3.12.1 Definition

In this management context:

- a) This class represents for a subscribed CS service (see 3GPP TS 23.008 [7]) the service preferences and settings chosen for a user.

### 6.3.12.2 Attributes

**Attributes of CSServiceProfile**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
cSServiceProfileId	+	M	M	O
networkAccessMode	+	M	M	M
basicMSISDNIndicator	+	O	M	M
mSISDNAlertIndicator	+	O	M	M
vLRNumber	+	M	M	-
mSCNumber	+	M	M	-
subscriptionRestriction	+	O	M	M
rSZIlists	+	O	M	M
mSCAreaRestrictedFlag	+	M	M	-
oDBinducedBarringData	+	O	M	-
roamingRestrictionDueToUnsupportedFeature	+	M	M	-
lSAIdentity	+	O	M	M
lSAPriority	+	O	M	M
lSAPreferentialAccess Indicator	+	O	M	M
lSAActiveModeSupportIndicator	+	O	M	M
lSAOnlyAccessIndicator	+	O	M	M
lSAActiveModeIndicator	+	O	M	M
vPLMNIdentifier	+	O	M	M
accessRestrictionData	+	O	M	M
privacyExceptionList	+	O	M	M
gMLCNumbers	+	O	M	M
mOLRList	+	O	M	M
serviceTypes	+	O	M	M
ageIndicator	+	O	M	-
lMSI	+	M	M	-
mobileStationCategory	+	M	M	M
lMUIentifier	+	M	M	M
mSCNumber	+	M	M	-
subscriptionRestriction	+	M	M	M
mSCAreaRestrictedFlag	+	M	M	-
oDBinducedBarringData	+	M	M	-
roamingRestrictionDueToUnsupportedFeature	+	M	M	-
mNRR	+	M	M	-
subscriberStatus	+	M	M	M
notificationToCSEFlagForODB	+	M	M	-
gsmSCFaddresslistForODB	+	M	M	M
messagesWaitingData	+	M	M	-
mobileStationNotReachableFlag	+	M	M	-
memoryCapacityExceededFlag	+	M	M	-
traceReference	+	O	M	-
traceType	+	O	M	-
operationsSystemsIdentity	+	O	M	-
hLRTtraceType	+	O	M	-
mAPErrorOnTrace	+	O	M	-
traceActivatedInVLR	+	O	M	-
provisionOfBearerService	+	M	M	M
provisionOfTeleservice	+	M	M	M
bCAlocation	+	O	M	M
checkSSIndicator	+	M	M	-
mSPurgedForNonGPRSFlag	+	M	M	-
barringOfOutgoingCalls	+	O	M	M
barringOfIncomingCalls	+	O	M	M
barringOfRoaming	+	O	M	M
barringOfPremiumRateCalls	+	O	M	M
barringOfSupplementaryServiceManagement	+	O	M	M
barringOfRegistrationOfCallForwarding	+	O	M	M
barringOfInvocationOfCallTransfer	+	O	M	M
operatorDeterminedBarringPLMNspecificData	+	O	M	M
vGCSGroupMembershipList	+	O	M	M

vBSGroupMembershipList	+	O	M	M
broadcastCallInitiationAllowedList	+	O	M	M
originatingCAMELSubscriptionInformationOCSI	+	O	M	M
terminatingCAMELSubscriptionInformationTCSI	+	O	M	M
vMSCTerminatingCAMELSubscriptionInformationVTCSI	+	O	M	M
locationInformationSubscriberStateInformation	+	O	M	M
uSSDCAMELSubscriptionInformationUCSI	+	O	M	M
sSInvocationNotificationSSCSI	+	O	M	M
translationInformationFlagTIFCSI	+	O	M	M
dialledServiceCAMELSubscriptionInformationDCSI	+	O	M	M
uSSDGeneralCAMELServiceInformationUGCSI	+	O	M	M
oCSINegotiatedCAMELCapabilityHandling	+	O	M	-
sSCSINegotiatedCAMELCapabilityHandling	+	O	M	-
vTCSINegotiatedCAMELCapabilityHandling	+	O	M	-
shortMessageServiceCAMELSubscriptionInformationMOSMSCSI	+	O	M	M
shortMessageServiceCAMELSubscriptionInformationMTSMSCSI	+	O	M	M
mOSMSCSIVLRNegotiatedCAMELCapabilityHandling	+	O	M	-
mTSMSCSIVLRNegotiatedCAMELCapabilityHandling	+	O	M	M
mCSINegotiatedCAMELCapabilityHandling	+	O	M	-
vLRSupportedCAMELPhases	+	O	M	-
gsmSCFaddressforCSI	+	O	M	M
vLROfferedCAMEL4CSIs	+	O	M	-
iSTAAlertTimer	+	O	M	M
cSAllocationRetentionpriority	+	O	M	M

### 6.3.12.3 Attribute constraints

The optional attributes:

```

accessRestrictionData
ageIndicator
barringOfIncomingCalls
barringOfInvocationOfCallTransfer
barringOfOutgoingCalls
barringOfPremiumRateCalls
barringOfRegistrationOfCallForwarding
barringOfRoaming
barringOfSupplementaryServiceManagement
basicMSISDNIndicator
bCAlocation
bCAlocation
broadcastCallInitiationAllowedList
cSAllocationRetentionpriority
dialledServiceCAMELSubscriptionInformationDCSI
gMLCNumbers
gsmSCFaddressforCSI
iSTAAlertTimer
locationInformationSubscriberStateInformation
lSAActiveModeIndicator
lSAActiveModeSupportIndicator
lSAIdentity
lSAOnlyAccessIndicator
lSAPreferentialAccess Indicator
lSAPriority
mCSINegotiatedCAMELCapabilityHandling
mOLRList
mOSMSCSIVLRNegotiatedCAMELCapabilityHandling
mSISDNAlertIndicator
mTSMSCSIVLRNegotiatedCAMELCapabilityHandling
oCSINegotiatedCAMELCapabilityHandling
oDBinducedBarringData
operatorDeterminedBarringPLMNspecificData

```

```
originatingCAMELSubscriptionInformationOCSI
privacyExceptionList
rSZIlists
serviceTypes
shortMessageServiceCAMELSubscriptionInformationMOSMSCSI
shortMessageServiceCAMELSubscriptionInformationMTSMSCSI
sSCSINegotiatedCAMELCapabilityHandling
sSInvocationNotificationSSCSI
subscriptionRestriction
terminatingCAMELSubscriptionInformationTCSI
translationInformationFlagTIFCSI
uSSDCAMELSubscriptionInformationUCSI
uSSDGeneralCAMELServiceInformationUGCSI
vBSSGroupMembershipList
vGCSGroupMembershipList
vLROfferedCAMEL4CSIs
vLRSupportedCAMELPhases
vMSCTerminatingCAMELSubscriptionInformationVTCSI
vPLMNIdentifier
vTCSSINegotiatedCAMELCapabilityHandling
```

shall be supported for the following criteria: the NE supports the parameter (See TS 23.008 [7]).

### 6.3.13 PSServiceProfile

#### 6.3.13.1 Definition

In this management context:

- a) This class represents for a subscribed PS service (see 3GPP TS 23.008 [7]) the service preferences and settings chosen for a user.

### 6.3.13.2 Attributes

**Attributes of PSServiceProfile**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
pSServiceProfileId	+	M	M	O
networkAccessMode	+	M	M	M
basicMSISDNIndicator	+	O	M	M
mSISDNAlertIndicator	+	O	M	M
vLRNumber	+	M	M	-
mSCNumber	+	M	M	-
subscriptionRestriction	+	O	M	M
rSZIlists	+	O	M	M
mSCAreaRestrictedFlag	+	M	M	-
oDBinducedBarringData	+	O	M	-
roamingRestrictionDueToUnsupportedFeature	+	M	M	-
1SAIdentity	+	O	M	M
1SAPriority	+	O	M	M
1SAPreferentialAccessIndicator	+	O	M	M
1SAActiveModeSupportIndicator	+	O	M	M
1SAOnlyAccessIndicator	+	O	M	M
1SAActiveModeIndicator	+	O	M	M
vPLMNIIdentifier	+	O	M	M
accessRestrictionData	+	O	M	M
privacyExceptionList	+	O	M	M
gMLCNumbers	+	O	M	M
mOLRList	+	O	M	M
serviceTypes	+	O	M	M
ageIndicator	+	O	M	-
sGSNNumber	+	M	M	-
gGSNNumber	+	O	M	M
sGSNarearestrictedflag	+	M	M	-
roamingRestrictedintheSGSNduetounsupportedfeature	+	M	M	-
mNRG	+	M	M	-
traceActivatedinSGSN	+	O	M	-
provisionofTeleservice	+	O	M	M
transferofSMoption	+	M	M	M
mSpurgedforGPRSflag	+	M	M	-
barringofPacketOrientedServices	+	O	M	M
pDPType	+	O	M	M
pDPAddress	+	O	M	M
accessPointName	+	O	M	M
vPLMNAddressAllowed	+	O	M	M
gGSNlist	+	M	M	-
qualityofServiceSubscribed	+	O	M	M
pDPContextIdentifier	+	O	M	-
pDPContextChargingCharacteristics	+	O	M	M
gPRSCAMELSubscriptionInformationGPRCSI	+	O	M	M
mOShortMessageServiceCAMELSubscriptionInformationMOSMSCSI	+	O	M	M
mTShortMessageServiceCAMELSubscriptionInformationMTSMSCSI	+	O	M	M
mOSMSCSISGSNNegotiatedCAMELCapabilityHandling	+	O	M	M
mTSMSCSISGSNNegotiatedCAMELCapabilityHandling	+	O	M	M
mobilityManagementforGPRSeventnotificationMGCSI	+	O	M	M
mGCSINegotiatedCAMELCapabilityHandling	+	O	M	M
gPRCSIINegotiatedCAMELCapabilityHandling	+	O	M	-
sGSNSupportedCAMELPhases	+	O	M	-
sGSNOfferedCAMEL4CSIs	+	O	M	-
gsmSCFaddressforCSI	+	O	M	M
subscribedChargingCharacteristics	+	O	M	M

### 6.3.13.3 Attribute constraints

The optional attributes:

```

accessPointName
accessRestrictionData
ageIndicator
barringofPacketOrientedServices
basicMSISDNIndicator
gGSNNNumber
gMLCNumbers
gPRSCAMELSubscriptionInformationGPRSCSI
gPRSCSINegotiatedCAMELCapabilityHandling
gsmSCFaddressforCSI
lSAActiveModeIndicator
lSAActiveModeSupportIndicator
lSAIdentity
lSAOnlyAccessIndicator
lSAPreferentialAccessIndicator
lSAPriority
mGCSINegotiatedCAMELCapabilityHandling
mobilityManagementforGPRSeventnotificationMGCSI
mOLRList
mOShortMessageServiceCAMELSubscriptionInformationMOSMSCSI
mOSMSCSISGSNNegotiatedCAMELCapabilityHandling
mSISDNAlertIndicator
mTShortMessageServiceCAMELSubscriptionInformationMTSMSCSI
mTSMSCSISGSNNegotiatedCAMELCapabilityHandling
oDBinducedBarringData
pDPAddress
pDPContextChargingCharacteristics
pDPContextIdentifier
pDPType
privacyExceptionList
provisionofTeleservice
qualityofServiceSubscribed
rSZIlists
serviceTypes
SGSNOfferedCAMEL4CSIs
SGSNSupportedCAMELPhases
subscribedChargingCharacteristics
subscriptionRestriction
vPLMNAddressAllowed
vPLMNIentifier

```

shall be supported for the following criteria: the NE supports the parameter (See TS 23.008 [7]).

### 6.3.14 IMSServiceProfile

#### 6.3.14.1 Definition

In this management context:

- a) This class represents for a subscribed ims (see 3GPP TS 23.008 [7]) service the service preferences and settings chosen for a user.

### 6.3.14.2 Attributes

**Attributes of IMSServiceProfile**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
iMSServiceProfileId	+	M	M	O
barringIndication	+	M	M	M
listofauthorizedvisitednetworkidentifiers	+	M	M	M
registrationStatus	+	M	M	M
sCSCFName	+	M	M	M
diameterClientAddressofSCSCF	+	M	M	-
serverCapabilities	+	O	M	M
subscribedMediaProfileIdentifier	+	O	M	M
initialFilterCriteria	+	O	M	M
applicationServerInformation	+	O	M	M
serviceIndication	+	M	M	M
primaryEventChargingFunctionName	+	O	M	M
secondaryEventChargingFunctionName	+	O	M	M
primaryChargingCollectionFunctionName	+	M	M	M
secondaryChargingCollectionFunctionName	+	O	M	M
gsmSCFaddressforIMCSI	+	O	M	M
iMSSFaddressforIMCSI	+	O	M	-
oIMCSI	+	O	M	M
vTIMCSI	+	O	M	M
dIMCS	+	O	M	M

### 6.3.14.3 Attribute constraints

The optional attributes shall be supported for the following criteria: The NE supports the parameter (See TS 23.008 [7]).

## 6.3.15 ServiceProviderFunction

### 6.3.15.1 Definition

In this management context:

- a) This class represents service provider functionality.
- b) All managed elements related with providing services have this functionality.
- c) It carries references to all services to be provided.
- d) It inherits from ManagedFunction (defined in 32.622 [6]).

### 6.3.15.2 Attributes

**Attributes of ServiceProviderFunction**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
serviceProviderFunctionId	+	M	M	-
userLabel	+	M	M	M

## 6.3.16 SubscriptionFunction

### 6.3.16.1 Definition

In this management context:

- a) This class represents subscription functionality.
- b) All managed elements related with the subscription of services have this functionality.
- c) It carries references to all subscription profile data.
- d) It carries references to all Subscriber data
- e) It inherits from ManagedFunction (defined in 32.622 [6]).

### 6.3.16.2 Attributes

**Attributes of SubscriptionFunction**

Attribute name	Visibility	Support Qualifier	Read Qualifier	Write Qualifier
subscriptionFunctionId	+	M	M	-
userLabel	+	M	M	M

## 6.4 Information relationship definitions

### 6.4.1 Agreement

#### 6.4.1.1 Definition

This represents the agreement relationship between SuMService and SuMSubscribedService.

#### 6.4.1.2 Roles

Name	Definition
contract	The SuMSubscribedService represents an agreed contract for a SuMService.
offer	The SuMService represents an offer of an agreement to a SuMSubscribedService.

#### 6.4.1.3 Constraints

-

### 6.4.2 Description

#### 6.4.2.1 Definition

This represents the content relationship between SuMSubscriptionProfile and SuMServiceProfile.

#### 6.4.2.2 Roles

Name	Definition
specification	SuMSubscribedService acts as the specification for the description of SuMServiceProfile.
service	SuMServiceProfile acts as the service specified in the description.

#### 6.4.2.3 Constraints

-

## 6.5 Information attribute definitions

### 6.5.1 Definitions and legal values

The following table defines the attributes that are present in several IOCs of the present document.

**Table 6.5.1: Attributes**

Attribute Name	Definition	Legal Values
iMSServiceId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the IMSService object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	
cSServiceId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the CSService object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	
pSServiceId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the PSService object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	
cSServiceProfileId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the CSServiceProfile object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	
pSServiceProfileId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the PSServiceProfile object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	
iMSServiceProfileId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the IMSServiceProfile object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	
cSSubscribedServiceId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the CSSubscribedService object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	

pSSubscribedServiceId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the PSSubscribedService object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	
iMSSubscribedServiceId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the IMSSubscribedService object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	
suMSubscriptionProfileId	An attribute whose 'name+value' can be used as an RDN when naming an instance of the SuMSubscriptionProfile object class. This RDN uniquely identifies the object instance within the scope of its containing (parent) object instance.	
userLabel	A user-friendly (and user assigned) name of the associated object. Inherited from ManagedFunction.	
agreement-contract	Models the agreement relationship to a subscribed service. This attribute contains a list of the DN(s) of the related SuMSubscribedService instance(s).	
agreement-offer	Models the agreement relationship to a service. An attribute whose 'name+value' can be used as DN when referencing an instance of the SuMService object class.	
description-service	Models the description relationship to a service profile. This attribute contains a list of the DN(s) of the related SuMServiceProfile instance(s).	
description-specification	Models the description relationship to a subscribed service. An attribute whose 'name+value' can be used as DN when referencing an instance of the SuMSubscribedService object class.	
iMSI	23.008 clause 2.1.1.1	
networkAccessMode	23.008 clause 2.1.1.2	
mSISDN	23.008 clause 2.1.2	
multinumberingMSISDNs	23.008 clause 2.1.3	
basicCMSISDNIndicator	23.008 clause 2.1.3.1	
mSISDNAlertIndicator	23.008 clause 2.1.3.2	
lMSI	23.008 clause 2.1.8	
mobileStationCategory	23.008 clause 2.2.1	
lMUIIdentifier	23.008 clause 2.2.2	
iMEISV	23.008 clause 2.2.3	
subscriptionRestriction	23.008 clause 2.4.10	
rSZIlists	23.008 clause 2.4.11.1	
mSCAreaRestrictedFlag	23.008 clause 2.4.12	
sGSNarearestrictedflag	23.008 clause 2.4.14	
oDBinducedBarringData	23.008 clause 2.4.15.1	
roamingRestrictionDueToUnsupportedFeature	23.008 clause 2.4.15.2	

roamingRestrictedintheSGSNduetounsupportedfeature	23.008 clause 2.4.15.3	
lSAIdentity	23.008 clause 2.4.17.1	
lSAPriority	23.008 clause 2.4.17.2	
lSAPreferentialAccessIndicator	23.008 clause 2.4.17.2A	
lSAActiveModeSupportIndicator	23.008 clause 2.4.17.2B	
lSAOnlyAccessIndicator	23.008 clause 2.4.17.3	
lSAActiveModeIndicator	23.008 clause 2.4.17.4	
vPLMNIIdentifier	23.008 clause 2.4.17.5	
accessRestrictionData	23.008 clause 2.4.18	
vLRNumber	23.008 clause 2.4.5	
mSCNumber	23.008 clause 2.4.6	
sGSNNumber	23.008 clause 2.4.8.1	
gGSNNumber	23.008 clause 2.4.8.2	
provisionOfBearerService	23.008 clause 2.5.1	
provisionOfTeleservice	23.008 clause 2.5.2	
bCAllocation	23.008 clause 2.5.3	
transferofSMoption	23.008 clause 2.5.4	
mNRG	23.008 clause 2.7.2	
checkSSIIndicator	23.008 clause 2.7.4.4	
mSPurgedForNonGPRSFlag	23.008 clause 2.7.5	
mSpurgedforGPRSflag	23.008 clause 2.7.6	
subscriberStatus	23.008 clause 2.8.1	
barringOfOutgoingCalls	23.008 clause 2.8.2.1	
barringOfIncomingCalls	23.008 clause 2.8.2.2	
barringOfRoaming	23.008 clause 2.8.2.3	
barringOfPremiumRateCalls	23.008 clause 2.8.2.4	
barringOfSupplementaryServiceManagement	23.008 clause 2.8.2.5	
barringOfRegistrationOfCallForwarding	23.008 clause 2.8.2.6	
barringOfInvocationOfCallTransfer	23.008 clause 2.8.2.7	
barringofPacketOrientedServices	23.008 clause 2.8.2.8	
operatorDeterminedBarringPLMNspecificData	23.008 clause 2.8.3	
notificationToCSEFlagForODB	23.008 clause 2.8.4	
gsmSCFaddresslistForODB	23.008 clause 2.8.5	
messagesWaitingData	23.008 clause 2.10.1	
mobileStationNotReachableFlag	23.008 clause 2.10.2	
memoryCapacityExceededFlag	23.008 clause 2.10.3	
traceReference	23.008 clause 2.11.1	
traceType	23.008 clause 2.11.2	
operationsSystemsIdentity	23.008 clause 2.11.3	
hLRTtraceType	23.008 clause 2.11.4	
mAPErrorOnTrace	23.008 clause 2.11.5	
traceActivatedInVLR	23.008 clause 2.11.6	
traceActivatedinSGSN	23.008 clause 2.11.7	
vGCSGroupMembershipList	23.008 clause 2.12.1	
vBSGroupMembershipList	23.008 clause 2.12.2	
broadcastCallInitiationAllowedList	23.008 clause 2.12.2.1	
pDPType	23.008 clause 2.13.1	
gGSNlist	23.008 clause 2.13.11	
qualityofServiceSubscribed	23.008 clause 2.13.12	
pDPAddress	23.008 clause 2.13.2	
pDPContextIdentifier	23.008 clause 2.13.24	
pDPContextChargingCharacteristics	23.008 clause 2.13.25	
accessPointName	23.008 clause 2.13.6	
vPLMNAddressAllowed	23.008 clause 2.13.8	
originatingCAMELSubscriptionInformationOCSI	23.008 clause 2.14.1.1/3.1	
gPRSCAMELSubscriptionInformationGPRSCSI	23.008 clause 2.14.1.10/2.14.4.4	
dialledServiceCAMELSubscriptionInformationDCSI	23.008 clause 2.14.1.11/3.7	
mobilityManagementforGPRSeventnotificationMGCSI	23.008 clause 2.14.1.12/2.14.4.4	
terminatingCAMELSubscriptionInformationTCSI	23.008 clause 2.14.1.2	
vMSCTerminatingCAMELSubscriptionInformationVTCSI	23.008 clause 2.14.1.2/3.2	
locationInformationSubscriberStateInformation	23.008 clause 2.14.1.3	
uSSDCAMELSubscriptionInformationUCSI	23.008 clause 2.14.1.4	
sSInvocationNotificationSSCSI	23.008 clause 2.14.1.5/3.2	
translationInformationFlagTIFCSI	23.008 clause 2.14.1.6/3.6	
shortMessageServiceCAMELSubscriptionInformationMOSMSCSI	23.008 clause 2.14.1.8/2.14.3.5	

mOShortMessageServiceCAMELSubscriptionInformationMOSMSCSI	23.008 clause 2.14.1.8/2.14.4.1	
shortMessageServiceCAMELSubscriptionInformationMTSMSCSI	23.008 clause 2.14.1.9/2.14.3.6	
mTShortMessageServiceCAMELSubscriptionInformationMTSMSCSI	23.008 clause 2.14.1.9/2.14.4.2.	
gPRSCSINegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
mCSINegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
mGCSINegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
mOSMSCSISGSNNegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
mOSMSCSIVLRNegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
mTSMSCSISGSNNegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
mTSMSCSIVLRNegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
oCSINegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
sSCSINegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
vTCSINegotiatedCAMELCapabilityHandling	23.008 clause 2.14.2.1	
SGSNOfferedCAMEL4CSIs	23.008 clause 2.14.2.2A	
vLROfferedCAMEL4CSIs	23.008 clause 2.14.2.2A	
sGSNSupportedCAMELPhases	23.008 clause 2.14.2.3	
vLRSupportedCAMELPhases	23.008 clause 2.14.2.3	
gsmSCFaddressforCSI	23.008 clause 2.14.2.4	
uSSDGeneralCAMELServiceInformationUGCSI	23.008 clause 2.14.2.4	
iSTAlertTimer	23.008 clause 2.15.1	
privacyExceptionList	23.008 clause 2.16.1.1	
gMLCNumbers	23.008 clause 2.16.1.2	
mOLRList	23.008 clause 2.16.1.3	
serviceTypes	23.008 clause 2.16.1.4	
ageIndicator	23.008 clause 2.17.1	
cSAllocationRetentionpriority	23.008 clause 2.18.1	
subscribedChargingCharacteristics	23.008 clause 2.19.1	
privateUserIdentity	23.008 clause 3.1.1	
publicIdentity	23.008 clause 3.1.2	
barringIndication	23.008 clause 3.1.3	
listofauthorizedvisitednetworkidentifiers	23.008 clause 3.1.4	
registrationStatus	23.008 clause 3.2.1	
sCSCFName	23.008 clause 3.2.2	
diameterClientAddressofSCSCF	23.008 clause 3.2.3	
serverCapabilities	23.008 clause 3.4.1	
subscribedMediaProfileIdentifier	23.008 clause 3.5.1	
initialFilterCriteria	23.008 clause 3.5.2	
applicationServerInformation	23.008 clause 3.5.3	
serviceIndication	23.008 clause 3.5.4	
primaryEventChargingFunctionName	23.008 clause 3.7.1	
secondaryEventChargingFunctionName	23.008 clause 3.7.2	
primaryChargingCollectionFunctionName	23.008 clause 3.7.3	
secondaryChargingCollectionFunctionName	23.008 clause 3.7.4	
gsmSCFaddressforIMCSI	23.008 clause 3.8.4	
iMSSFaddressforIMCSI	23.008 clause 3.8.5	
oIMCSI	23.008 clause 3.8.1	
vTIMCSI	23.008 clause 3.8.2	
dimcs	23.008 clause 3.8.3	

---

## Annex A (informative): Change history

Change history							Old	New
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment			
Dec 2003	S_22	SP-030617	--	--	Submitted to TSG SA#22 for Information		1.0.0	
Sep 2004	S_25	SP-040546	--	--	Submitted to TSG SA#25 for Approval		2.0.0	
Dec 2004	S_26	SP-040830	--	--	Submitted to TSG SA#26 for Approval		2.7.0	6.0.0

---

## History

Document history		
V6.0.0	December 2004	Publication