ETSI TS 132 303 V6.2.0 (2004-12)

Technical Specification

Digital cellular telecommunications system (Phase 2+);

Universal Mobile Telecommunications System (UMTS);

Telecommunication management;

Configuration Management (CM);

Notification Integration Reference Point (IRP):

Common Object Request Broker Architecture (CORBA)

Solution Set (SS)

(3GPP TS 32.303 version 6.2.0 Release 6)



Reference
RTS/TSGS-0532303v620

Keywords
GSM, UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**TM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**TM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Contents

Intell	lectual Property Rights	2
Fore	word	2
Fore	word	4
	duction	
1	Scope	
	References	
2		
3	Definitions and abbreviations	
3.1 3.2	Definitions	
	Abbreviations	
4	Architectural features	
4.1 4.1.1	Notification services	
4.1.2	Support of multiple notifications in one push operation	
5	Mapping	
5.1	Operation mapping	
5.2	Operation parameter mapping	
5.3	Notification parameter mapping	
6	IRPAgent's Behaviour	13
6.1	Subscription	
6.2	IRPAgent supports multiple categories of Notifications	
6.3	IRPAgent's integrity risk of attach_push_b Method	
6.4	Quality of Service Parameters	
Anno	ex A (normative): IDL specifications	16
A.1	IDL specification (file name "ManagedGenericIRPConstDefs.idl")	16
A.2	IDL specification (file name "ManagedGenericIRPSystem.idl")	17
A.3	IDL specification (file name "NotificationIRPConstDefs.idl")	18
A.4	IDL specification (file name "NotificationIRPSystem.idl")	19
A.5	IDL specification (file name "NotificationIRPNotifications.idl")	21
Anno	ex B (informative): Change history	23
Histo	•	24

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

32.301:	"Configuration Management (CM); Notification Integration Reference Point (IRP): Requirements".
32.302:	"Configuration Management (CM); Notification Integration Reference Point (IRP): Information Service (IS)".
32.303:	"Configuration Management (CM); Notification Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
32.304:	"Configuration Management (CM); Notification Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as a single action on a NE of the 3G network or as part of a complex procedure involving actions on many NEs.

The Itf-N interface is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [5] and 3GPP TS 32.102 [6].

Network Elements (NEs) under management and element managers generate notifications of events about occurrences within the network. Different kinds of events carry different kinds of information. For instance a new alarm as specified in Alarm IRP: Information Service [1], is one possible kind of event, an object creation as specified in Basic CM IRP: Information Service [8] is another possible kind of event.

Information of an event is carried in notification. An IRPAgent (typically an EM or a NE) emits notifications. IRPManager (typically a network management system) receives notifications. The purpose of Notification IRP is to define an interface through which an IRPManager can subscribe to IRPAgent for receiving notifications.

This IRP bases its design on work captured in ITU-T Recommendation X.734 [2], OMG Notification Service [4]. The central design ideas are:

- Separation of notification Consumers (IRPManagers) from Producers (IRPAgents);
- Notifications are sent to IRPManagers without the need for IRPManagers to periodically check for new notifications.

Common characteristics related to notifications in all other IRPs are gathered in one IRP.

1 Scope

The present document specifies the Common Object Request Broker Architecture (CORBA) Solution Set (SS) for the IRP whose semantics is specified in Notification IRP: Information Service (3GPP TS 32.302 [5]).

This Solution Set specification is related to 3GPP TS 32.302 V6.1.X.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] ITU-T Recommendation X.736: "Information technology Open Systems Interconnection Systems Management: Security alarm reporting function".
- [2] OMG TC Document telecom (98-11-01): "Summary of responses to real time survey".
- [3] OMG CORBA services: Common Object Services Specification, Update: November 22, 1996. (Clause 4 contains the Event Service Specification).
- [4] 3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP) management; Information Service (IS)".
- [5] 3GPP TS 32.302: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Information Service (IS)".
- [6] 3GPP TS 32.111-2: "Telecommunication management; Fault Management; Part 2: Alarm Integration Reference Point (IRP): Information Service (IS)".
- [7] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [8] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [9] 3GPP TS 32.301: "Telecommunication Management; Configuration Management (CM); Notification Integration Reference Point (IRP): Requirements".
- [10] 3GPP TS 32.111-3: "Telecommunication management; Fault Management; Part 3: Alarm Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
- [11] 3GPP TS 32.311: "Telecommunication management; Generic Integration Reference Point (IRP) management: Requirements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.101 [7], 3GPP TS 32.102 [8] and 3GPP TS 32.301 [9] and the following apply:

IRP document version number string (or "IRPVersion"): See 3GPP TS 32.311 [11].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM Configuration Management

CORBA Common Object Request Broker Architecture (OMG)

EC Event channel (OMG)
EM Element Manager

IDL Interface Definition Language (OMG)
IOR Interoperable Object Reference

IS Information Service

NC Notification Channel (OMG)

NE Network Element NV Name and Value pair OMG Object Management Group

QoS Quality of Service SS Solution Set

UML Unified Modelling Language (OMG)

4 Architectural features

The overall architectural feature of Notification IRP is specified in 3GPP TS 32.302 [5]. This clause specifies features that are specific to the CORBA Solution Set (SS).

4.1 Notification services

In the CORBA Solution Set, notifications are emitted by IRPAgent using CORBA Notification service (OMG TC Document telecom [2]).

CORBA Event service (OMG CORBA services [3]) provides event routing and distribution capabilities. CORBA Notification service provides, in addition to Event service, event filtering and support for Quality of Service (QoS) as well.

A subset of CORBA Notification services shall be used to support the implementation of notification. This CORBA Notification service subset, in terms of OMG Notification service (OMG TC Document telecom [2]) defined methods, is identified in the present.

4.1.1 Support of Push and Pull Interface

The IRPAgent shall support the OMG Notification push interface model. Additionally, it may support the OMG Notification pull interface model as well.

4.1.2 Support of multiple notifications in one push operation

For efficiency, IRPAgent uses the following OMG Notification Service (OMG TC Document telecom [2]) defined interface to pack multiple notifications and push them to IRPManager using one method push_structured_events. The method takes as input a parameter of type EventBatch as defined in the OMG CosNotification module (OMG TC Document telecom [2]). This data type is a sequence of Structured Events (see clause 4). Upon invocation, this parameter will contain a sequence of Structured Events being delivered to IRPManager by IRPAgent to which it is connected.

The maximum number of events that will be transmitted within a single invocation of this operation is controlled by IRPAgent wide configuration parameter. The amount of time IRPAgent will accumulate individual events into the sequence before invoking this operation is controlled by IRPAgent wide configuration parameter as well.

IRPAgent may push EventBatch with only one Structured Event.

The OMG Notification service (OMG TC Document telecom [2]) defined IDL module is shown below.

5 Mapping

5.1 Operation mapping

Notification IRP: IS (3GPP TS 32.302 [5]) defines semantics of operations visible across this IRP. These operations are the operations of the IOCs defined in 3GPP TS 32.302 [5].

Table 1 maps the operations defined in Notification IRP: IS (3GPP TS 32.302 [5]) to their equivalents (methods) in this Solution Set (SS). Specifically, the table 1 maps the operations of the IOCs defined in 3GPP TS 32.302 [5] to their equivalents in this SS. Since one of the IOCs, the NotificationIRP IOC, inherits from the ManagedGenericIRP IOC [4], the table 1 also maps the operations of ManagedGenericIRP IOC to their equivalents (methods) in this SS.

Table 1 also qualifies if a method is Mandatory (M) or Optional (O).

Table 1: Mapping from IS Operation to SS Equivalents

IS Operations in 3GPP TS 32.302 [5]	SS Methods	Qualifier
subscribe	attach_push, attach_push_b, attach_pull	M, O, O
unsubscribe	detach	M
getIRPVersion (see note.)	get_notification_IRP_versions	М
getSubscriptionStatus	get_subscription_status	0
getSubscriptionIds	get_subscription_ids	0
changeSubscriptionFilter	If subscription is established using attach_push method, the SS equivalent shall be change_subscription_filter. The IDL specification of this method is included in annex A. This method is Optional (O).	See box on the left.
	If subscription is established using attach_push_b method, the SS equivalent shall be modify_constraints. The method is defined in OMG Notification Service Filter Interface (OMG TC Document telecom [2]). The IDL specification of this method is not included in annex A. If IRPAgent supports the optional attach_push_b method, it shall support this method as mandatory.	
	If subscription is established using attach_pull method, the SS equivalent shall be modify_constraints. The method is defined by OMG Notification Service Filter Interface (OMG TC Document telecom [2]). The IDL specification of this method is not included in annex A. If IRPAgent supports the optional attach_pull method, it shall support this method as mandatory.	
suspendSubscription	If subscription is established using attach_push, there is no SS equivalent. In other words, IRPManager cannot suspend subscription.	See box on the left
	If subscription is established using attach_push_b, the SS equivalent shall be suspend_connection. This method is defined by OMG Notification Service (OMG TC Document telecom [2]). The IDL specification of this method is not included in annex A. If IRPAgent supports the optional attach_push_b method, it shall support this method as mandatory.	
	If subscription is established using attach_pull, there is no SS equivalent.	
resumeSubscription	If subscription is established using attach_push, there is no SS equivalent. In other words, IRPManager cannot resume subscription.	See box on the left
	If subscription is established using attach_push_b, the SS equivalent shall be resume_connection. This method is defined by OMG Notification Service (OMG TC Document telecom [2]). The IDL specification of this method is not included in annex A. If IRPAgent supports the optional attach_push_b method, it shall support this method as mandatory.	
	If subscription is established using attach_pull, there is no SS equivalent.	
getNotificationCategories	get_notification_categories	0
getOperationProfile (see note.)	get_notification_IRP_operations_profile	0
getNotificationProfile (see note.)	get_notification_IRP_notification_profile	0
	ons are operations of ManagedGenericIRP IOC specified in 3GPP TS 32.312 [4]. The OC of 3GPP TS 32.302 [5] inherits from it.	те

5.2 Operation parameter mapping

3GPP TS 32.302 [5] defines semantics of parameters carried in operations across the Notification IRP. Table 2 through table 14 indicate the mapping of these parameters, as per operation, to their equivalents defined in this SS.

Table 2: Mapping from IS subscribe parameters to SS attach_push equivalents

IS Opera	ation parameter	SS Method parameter	Qualifier
managerR	Reference	string manager_reference (see note 1)	М
timeTick		unsigned long time_tick	0
notification	n Categories	NotificationIRPConstDefs::NotificationCategorySet notification_categories	0
filter		ManagedGenericIRPConstDefs::StringTypeOpt filter (see note 2)	0
subscription	onld	Return value of type NotificationIRPConstDefs::SubscriptionId	М
status		Attach, ManagedGenericIRPSystem::ParameterNotSupported, ManagedGenericIRPSystem::InvalidParameter, AlreadySubscribed, AtLeastOneNotificationCategoryNotSupported	М
NOTE 1:	NOTE 1: IRPManager creates a CosNotifyComm::SequencePushConsumer object and invokes CORBA::ORB::object_to_string to obtain the stringified IOR, say s1. IRPManager stores the s1. IRPManager sends s1 as input parameter of attach_push to IRPAgent. IRPAgent receives s1, performs CORBA::ORB::string_to_object to obtain the IRPManager's IOR and uses it for its future methods. IRPAgent also stores the s1 for future comparisons. IRPManager later calls detach with s1. IRPAgent receives the stringified IOR s1, compares it with those stored stringified IORs (e.g. s1), finds a match, and performs the detach process. IRPAgent pushes sequence of Structured Events towards IRPManager via the CosNotifyComm::SequencePushConsumer_object push_structured_events method, depending on the supplied notification categories and filter.		
NOTE 2:	The grammar of t	the filter string is extended_TCL defined by OMG Notification Service (OMG Tm [2]). This SS and the Alarm IRP: CORBA SS [10] shall use this grammar or	

Table 3: Mapping from IS subscribe parameters to SS attach_push_b equivalents

IS Oper	ation parameter	SS Method parameter	Qualifier
managerF	Reference	string manager_reference (see note 1)	M
timeTick		unsigned long time_tick	0
notificatio	n Categories	NotificationIRPConstDefs::NotificationCategorySet notification_categories	0
filter		ManagedGenericIRPConstDefs::StringTypeOpt filter (see note 2)	0
subscripti	onld	Return value of type NotificationIRPConstDefs::SubscriptionId	М
Not specif	fied in IS	CosNotifyChannelAdmin::SequenceProxyPushSupplier system_reference (see note 3)	M
status		Attach, ManagedGenericIRPSystem::OperationNotSupported, ManagedGenericIRPSystem::ParameterNotSupported, ManagedGenericIRPSystem::InvalidParameter, AlreadySubscribed, AtLeastOneNotificationCategoryNotSupported	M
NOTE 1: IRPManager creates a CosNotifyComm::SequencePushConsumer object and invokes CORBA::ORB::object_to_string to obtain the stringified IOR, say s1. IRPManager stores the s1. IRPManager sends s1 as input parameter of attach_push_b to IRPAgent. IRPAgent receives s1 and stores the s1 for future comparisons. IRPManager later calls detach with s1. IRPAgent receives the stringified IORs s1, compares it with those stored stringified IORs (e.g. s1), finds a match, and performs the detach process		s1 and stores stringified IOR tach process.	
NOTE 2:	OTE 2: The grammar of the filter string is extended_TCL defined by OMG Notification Service (OMG TC Docume telecom [2]). This SS and the Alarm IRP: CORBA SS [10] shall use this grammar only.		C Document
NOTE 3:	OTE 3: IRPAgent provides this reference to which IRPManager can invoke methods to manage the subscription. Valid methods are not defined in this IRP. OMG CORBA Notification Service defines these methods. Read interface CosNotifyChannelAdmin::SequenceProxyPushSupplier and CosNotifyComm::SequencePushConsumer. IRPManager is expected to invoke connect_sequence_push_consumer method of this interface to connect its own cosNotifyComm::SequencePushConsummer with this reference. After successful connection, IRPAgent pushes sequence of Structured Events towards IRPManager.		thods. Read

Table 4: Mapping from IS subscribe parameters to SS attach_pull equivalents

IS Oper	ation parameter	SS Method parameter	Qualifier
managerF	Reference	string manager_reference (see note 1)	М
timeTick		unsigned long time_tick	0
notificatio	n Categories	NotificationIRPConstDefs::NotificationCategorySet notification_categories	0
filter		ManagedGenericIRPConstDefs::StringTypeOpt filter (see note 2)	0
subscripti	onld	Return value of type NotificationIRPConstDefs::SubscriptionId	М
Not specif	fied in IS.	CosNotifyChannelAdmin::SequenceProxyPullSupplier system_reference (see note 3)	M
status		Attach, ManagedGenericIRPSystem::OperationNotSupported, ManagedGenericIRPSystem::ParameterNotSupported, ManagedGenericIRPSystem::InvalidParameter, AlreadySubscribed, AtLeastOneNotificationCategoryNotSupported	M
	NOTE 1: IRPManager creates a CosNotifyComm::SequencePullConsumer object and invokes CORBA::ORB::object_to_string to obtain the stringified IOR, say s1. IRPManager stores the s1. IRPManager sends s1 as input parameter of attach_pull to IRPAgent. IRPAgent receives s1 and stores the s1 for future comparisons. IRPManager later calls detach with s1. IRPAgent receives the stringified IOR s1 compares it with those stored stringified IORs (e.g. s1), finds a match, and performs the detach process.		nd stores the gified IOR s1, n process.
NOTE 2:	E 2: The grammar of the filter string is extended_TCL defined by OMG Notification Service (OMG TC Docume telecom [2]). This SS and the Alarm IRP: CORBA SS [10] shall use this grammar only.		C Document
NOTE 3:	3: IRPAgent provides this reference to which IRPManager can invoke methods to manage the subscription. Valid methods are not defined in this IRP. OMG CORBA Notification Service defines these methods. Read interface CosNotifyChannelAdmin::SequenceProxyPullSupplier and CosNotifyComm::SequencePullConsumer. IRPManager is expected to invoke connect_sequence_pull_consumer method of this interface to connect its own CosNotifyComm::SequencePullConsummer with this reference. After successful connection, IRPManager pulls sequence of Structured Events from IRPAgent.		

Table 5: Mapping from IS unsubscribe parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
managerReference	string manager_reference	M
subscriptionId	NotificationIRPConstDefs::SubscriptionId subscription_id	0
status	DetachException, ManagedGenericIRPSystem::ParameterNotSupported,	M
	ManagedGenericIRPSystem::InvalidParameter	

Table 6: Mapping from IS getIRPVersion parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
versionNumberSet	Return value of type ManagedGenericIRPConstDefs::VersionNumberSet	М
status	GetNotificationIRPVersions	М

Table 7: Mapping from IS getSubscriptionStatus parameters to SS equivalents

IS Operation	SS Method parameter	Qualifier
parameter		
subscriptionId	NotificationIRPConstDefs::SubscriptionId subscription_id	M
notificationCategory	Return value of type NotificationIRPConstDefs::NotificationCategorySet	M
Set		
filterInEffect	ManagedGenericIRPConstDefs::StringTypeOpt filter_in_effect	0
subscriptionState	NotificationIRPConstDef::SubscriptionState subscription_state	0
timeTick	unsigned long time_tick	0
status	GetSubscriptionStatus, ManagedGenericIRPSystem::OperationNotSupported,	M
	ManagedGenericIRPSystem::InvalidParameter	

Table 8: Mapping from IS getSubscriptionIds parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
managerReference	string manager_reference	М
subscriptionIdSet	Return value of type NotificationIRPConstDefs::SubscriptionIdSet	M
status	GetSubscriptionIds, ManagedGenericIRPSystem::OperationNotSupported,	М
	ManagedGenericIRPSystem::InvalidParameter	

Table 9: Mapping from IS changeSubscriptionFilter parameters to SS equivalents

IS Operation	SS Method parameter	Qualifier
parameter		
subscriptionId	NotificationIRPConstDefs::SubscriptionId subscription_id	М
filter	string filter	М
status	ChangeSubscriptionFilter, ManagedGenericIRPSystem::OperationNotSupported, ManagedGenericIRPSystem::InvalidParameter	M

Table 10: Mapping from IS suspendSubscription parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
subscriptionId	If subscription is established using attach_push, there is no SS equivalent method. Therefore, there is no SS equivalent for this IS parameter. If subscription is established using attach_push_b, the SS equivalent method is suspend_connection. This method is defined by OMG Notification Service (OMG TC Document telecom [2]) and requires no parameter. Therefore, there is no SS equivalent for this IS parameter. If subscription is established using attach_pull, there is no SS equivalent	M
	method. Therefore, there is no SS equivalent for this IS parameter.	
status	If subscription is established using attach_push, there is no SS equivalent method. Therefore, there is no SS equivalent for this IS parameter. If subscription is established using attach_push_b, the SS equivalent method is suspend_connection. This method is defined by OMG Notification Service (OMG TC Document telecom [2]) and it returns a void. Therefore, there is no SS equivalent for this IS parameter. This suspend_connection method can raise OMG Notification Service (OMG TC Document telecom [2]) defined exception called ConnectionAlreadylnactive. If subscription is established using attach_pull, there is no SS equivalent method. Therefore, there is no SS equivalent for this IS parameter.	М

Table 11: Mapping from IS resumeSubscription parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
subscriptionId	If subscription is established using attach_push, there is no SS equivalent method. Therefore, there is no SS equivalent for this IS parameter. If subscription is established using attach_push_b, the SS equivalent method is resume_connection. This method is defined by OMG Notification Service (OMG TC Document telecom [2]) and requires no parameter. Therefore, there is no SS equivalent for this IS parameter. If subscription is established using attach_pull, there is no SS equivalent	M
	method. Therefore, there is no SS equivalent for this IS parameter.	
status	If subscription is established using attach_push, there is no SS equivalent method. Therefore, there is no SS equivalent for this IS parameter. If subscription is established using attach_push_b, the SS equivalent method is resume_connection. This method is defined by OMG Notification Service (OMG TC Document telecom [2]) and returns a void. Therefore, there is no SS equivalent for this IS parameter. This resume_connection method can raise OMG Notification Service (OMG TC Document telecom [2]) defined exception called ConnectionAlreadyActive. If subscription is established using attach_pull, there is no SS equivalent method. Therefore, there is no SS equivalent for this IS parameter.	M

Table 12: Mapping from IS getNotificationCategories parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
notificationCategoryList	Return value of type NotificationIRPConstDefs::NotificationCategorySet	M
Not specified in IS	NotificationIRPConstDefs::NotificationTypesSet notification_type_list	0
status	GetNotificationCategories,	М
	ManagedGenericIRPSystem::OperationNotSupported	

Table 13: Mapping from IS getOperationProfile parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
iRPVersion	ManagedGenericIRPConstDefs::VersionNumber notification_irp_version	M
operationNameProfile,ope	Return of type ManagedGenericIRPConstDefs::MethodList	M
rationParameterProfile		
status	GetNotificationIRPOperationsProfile,	
	ManagedGenericIRPSystem::OperationNotSupported,	
	ManagedGenericIRPSystem::InvalidParameter	

Table 14: Mapping from IS getNotificationProfile parameters to SS equivalents

IS Operation parameter	ter SS Method parameter			
iRPVersion	ManagedGenericIRPConstDefs::VersionNumber notification_irp_version	M		
notificationNameProfile,no	Return value of type ManagedGenericIRPConstDefs::MethodList	M		
tificationParameterProfile				
status	GetNotificationIRPNotificationProfile,	M		
	ManagedGenericIRPSystem::OperationNotSupported,			
	ManagedGenericIRPSystem::InvalidParameter			

5.3 Notification parameter mapping

Notification IRP: IS (3GPP TS 32.302 [5]) defines the semantics of common attributes carried in notifications. This SS does not provide the mapping of these attributes to their CORBA SS equivalents. Other IRPs such as Alarm IRP: IS (3GPP TS 32.111-2 [6]) identify and qualify these common attributes for use in their environment. Their corresponding SS documents define the mapping of these attributes to their SS equivalents.

6 IRPAgent's Behaviour

This clause describes some IRPAgent's behaviour not captured by IDL.

6.1 Subscription

IRPManager can invoke multiple attach_push, multiple attach_push_b or multiple attach_pull using different manager_reference(s). As far as IRPAgent is concerned, the IRPAgent will emit notifications to multiple "places" with their independent filter requirements. IRPAgent will not know if the notifications are going to the same IRPManager.

If IRPManager invokes multiple attach_push, attach_push_b or attach_pull using the same manager_reference and with an already subscribed notification_category, IRPAgent shall raise AlreadySubscribed exception to all invocations except one.

IRPManager can invoke multiple attach_push using the same manager_reference and with one or more not-yet-subscribed notification_categories. In this case, if IRPAgent supports all the notification categories requested, IRPAgent shall accept the invocation; otherwise, it raises

AtLeastOneNotificationCategoryNotSupported exception. IRPAgent shall have similar behaviour for attach_push_b and attach_pull.

When IRPManager is in subscription by invoking attach_push, IRPManager can change the filter constraint, using change_subscription_filter, applicable to the notification categories specified in the attach_push.

When IRPManager is in subscription by invoking attach_push_b, IRPManager can change the filter constraint during subscription using the OMG defined Notification Service Filter Interface. IRPManager shall not use change_subscription_filter; otherwise it shall get an exception.

6.2 IRPAgent supports multiple categories of Notifications

IRPAgent may emit multiple categories of Notifications. IRPAgent may have mechanism for IRPManager to pull for notifications of multiple categories.

IRPManager can query IRPAgent about the categories of notifications supported by using get_notification_categories.

IRPManager uses a parameter, notification_categories, in attach_push, attach_push_b and attach_pull to specify one or more categories of notifications wanted.

IRPManager uses a zero-length sequence in notification_categories of attach_push, attach_push_b and attach_pull to specify that all IRPAgent supported categories of notifications are wanted. If IRPManager uses attach_push with zero-length sequence in notification_categories and if the operation is successful, IRPAgent shall reject subsequent attach_push operation, regardless if the notification_categories contains a zero-length sequence or one or more specific notification categories. IRPAgent shall have similar behaviour for attach_push_b and attach_pull.

6.3 IRPAgent's integrity risk of attach_push_b Method

In the case that IRPAgent implements this method by extending or using OMG compliant Notification Service, the following IRPManager behaviour illustrates a risk to IRPAgent's integrity.

Given the object reference (IOR) of the SequenceProxyPushSupplier (as the mandatory output parameter of the subject method), IRPManager can invoke SequenceProxyPushSupplier.MyAdmin method.

IRPManager can then obtain the consumer admin object of the proxy. Then IRPManager can invoke ConsumerAdmin.MyChannel to get the IOR of the Notification Channel. IRPManager then can call EventChannel.MyFactory which will provide IRPManager the IOR of the EventChannelFactory itself. IRPManager can then able to invoke methods directly on the EventChannelFactory, like get_all_channels which lists all channel numbers and create_channel which allows IRPManager to create any number of additional channels.

A malicious IRPManager can, given access to the EventChannelFactory, get a list of existing channels and start connecting them together at random thus compromising the IRPAgent's integrity. Deployment of this attach_push_b needs strong authentication and authorisation mechanism in place.

The attach_push is mandatory. IRPAgent compliant to this IRP shall support it.

The attach_push_b is optional. It is recommended that IRPAgent concerned with integrity risk should not support the attach_push_b option.

6.4 Quality of Service Parameters

The OMG Notification Service [2] supports a variety of Quality of Service (QoS) properties, such as reliability and priority, that may be expressed to indicate the delivery characteristics of notifications. The following OMG Notification Service QoS parameter settings shall be required when the IRPAgent uses the OMG Notification Service to support this SS:

- 1. The order policy shall be set to FifoOrder (First-in, First-out) [2].
- 2. The message priority shall be set to 0, i.e. no priority [2].
- 3. The Start Time Supported shall be set to false, i.e. do not use Start Time [2].
- 4. The Stop Time Supported shall be set to false, i.e. do not use Stop Time [2].

When the OMG Notification Service is not used, the IRPAgent shall provide First-in, First-out notification ordering, not provide message priority and not provide the support of Start Time and Stop Time.

Annex A (normative): IDL specifications

A.1 IDL specification (file name "ManagedGenericIRPConstDefs.idl")

```
//File: ManagedGenericIRPConstDefs.idl
#ifndef _MANAGEDGENERICIRPCONSTDEFS_IDL_
#define _MANAGEDGENERICIRPCONSTDEFS_IDL_
#include "TimeBase.idl"
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
/* ## Module: ManagedGenericIRPConstDefs
This module contains definitions commonly used among all IRPs such as Alarm IRP.
______
* /
module ManagedGenericIRPConstDefs
  Definition imported from CosTime.
  The time refers to time in Greenwich Time Zone.
   It also consists of a time displacement factor in the form of minutes of
  displacement from the Greenwich Meridian.
  typedef TimeBase::UtcT IRPTime;
  enum Signal {OK, FAILURE, PARTIALFAILURE};
  The VersionNumber is a string that identifies the IRP specification name
   and its version number. See definition "IRP document version number
   string" or "IRPVersion".
   The VersionNumberSet is a sequence of such VersionNumber. It is returned
  by get_XXX_IRP_versions(). The sequence order has no significance.
   typedef string VersionNumber;
   typedef sequence <VersionNumber> VersionNumberSet;
   typedef string MethodName;
   typedef string ParameterName;
   typedef sequence <ParameterName> ParameterList;
  The Method defines the structure to be returned as part of
  get_supported_operations_profile(). The name shall be the actual method
  name (ex. "attach_push", "change_subscription_filter", etc.)
   The parameter_list contains a list of strings. Each string shall be
  the actual parameter name (ex. "manager_reference", "filter", etc.)
   struct Method
     MethodName name;
     ParameterList parameter_list;
  List of all methods and their associated parameters.
   typedef sequence <Method> MethodList;
  StringTypeOpt is a type carrying an optional parameter.
   If the boolean is TRUE, then the value is present.
   Otherwise the value is absent.
```

```
union StringTypeOpt switch (boolean)
   {
      case TRUE: string value;
   /*
   ShortTypeOpt is a type carrying an optional parameter. If the boolean is TRUE, then the value is present.
   Otherwise the value is absent.
   union ShortTypeOpt switch (boolean)
      case TRUE: short value;
   UnsignedShortTypeOpt is a type carrying an optional parameter.
   If the boolean is TRUE, then the value is present.
   Otherwise the value is absent.
   union UnsignedShortTypeOpt switch (boolean)
      case TRUE: unsigned short value;
   };
   LongTypeOpt is a type carrying an optional parameter.
   If the boolean is TRUE, then the value is present.
   Otherwise the value is absent.
   union LongTypeOpt switch (boolean)
   {
      case TRUE: long value;
   };
   UnsignedLongTypeOpt is a type carrying an optional parameter.
   If the boolean is TRUE, then the value is present.
   Otherwise the value is absent.
   union UnsignedLongTypeOpt switch (boolean)
      case TRUE: unsigned long value;
};
#endif // _MANAGEDGENERICIRPCONSTDEFS_IDL_
```

A.2 IDL specification (file name "ManagedGenericIRPSystem.idl")

```
The parameter shall be the actual parameter name.

*/
exception InvalidParameter { string parameter; };

/*
Exception thrown when a valid but unsupported parameter value is passed.
The parameter shall be the actual parameter name.

*/
exception ValueNotSupported { string parameter; };

/*
Exception thrown when an unsupported optional method is called.

*/
exception OperationNotSupported {};
};

#endif // _MANAGEDGENERICIRPSYSTEM_IDL_
```

A.3 IDL specification (file name "NotificationIRPConstDefs.idl")

```
//File: NotificationIRPConstDefs.idl
#ifndef _NOTIFICATIONIRPCONSTDEFS_IDL_
#define _NOTIFICATIONIRPCONSTDEFS_IDL_
#include "ManagedGenericIRPConstDefs.idl"
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
/* ## Module: NotificationIRPConstDefs
This module contains definitions specific for Notification IRP.
_
module NotificationIRPConstDefs
  Define the parameters (in the notification header) specified in
   the Notification IRP: IS.
   interface AttributeNameValue
     const string NOTIFICATION_ID = "a";
     const string EVENT_TIME = "b";
     const string SYSTEM_DN = "c";
     const string MANAGED_OBJECT_CLASS = "d";
     const string MANAGED_OBJECT_INSTANCE = "e";
   };
  It defines the notification categories.
  A notification category is identified by the IRP name and its version number.
  typedef ManagedGenericIRPConstDefs::VersionNumberSet NotificationCategorySet;
   It defines the notification types of a particular notification category.
   typedef sequence <string> NotificationTypePerNotificationCategory;
  This sequence identifies all notification types of all notification
   categories identified by NotificationCategorySet. The number of elements
   in this sequence shall be identical to that of NotificationCategorySet.
   typedef sequence <NotificationTypePerNotificationCategory>
      NotificationTypesSet;
```

```
It defines a sequence of SubscriptionIds.
   */
   typedef string SubscriptionId;
   typedef sequence <SubscriptionId> SubscriptionIdSet;

/*
   This indicates if the subscription is Active (not suspended), Suspended, or Invalid.
   */
   enum SubscriptionState {ACTIVE, SUSPENDED, INVALID};
};
#endif // _NOTIFICATIONIRPCONSTDEFS_IDL_
```

A.4 IDL specification (file name "NotificationIRPSystem.idl")

```
//File: NotificationIRPSystem.idl
#ifndef _NOTIFICATIONIRPSYSTEM_IDL_
#define _NOTIFICATIONIRPSYSTEM_IDL_
#include "CosNotifyChannelAdmin.idl"
#include "ManagedGenericIRPConstDefs.idl"
#include "ManagedGenericIRPSystem.idl"
#include "NotificationIRPConstDefs.idl'
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
/* ## Module: NotificationIRPSystem
This module implements capabilities of Notification IRP.
______
module NotificationIRPSystem
{
  System fails to complete the operation. System can provide reason
   to qualify the exception. The semantics carried in reason
   is outside the scope of this IRP.
  exception GetNotificationIRPVersions { string reason; };
   exception GetNotificationIRPOperationsProfile { string reason; };
   exception GetNotificationIRPNotificationProfile { string reason; };
  exception Attach { string reason; };
  exception DetachException { string reason; };
  exception GetSubscriptionStatus { string reason; };
   exception ChangeSubscriptionFilter { string reason; };
  exception GetNotificationCategories { string reason; };
  exception GetSubscriptionIds { string reason; };
   exception AlreadySubscribed {};
   exception AtLeastOneNotificationCategoryNotSupported {};
   interface NotificationIRP
     Return the list of all supported Notification IRP versions
     Each IRPVersion is defined by the rule in TS 32.311 clause titled
      "IRP document version number string"
     ManagedGenericIRPConstDefs::VersionNumberSet get_notification_IRP_versions
     raises (GetNotificationIRPVersions);
     Return the list of all supported operations and their supported
      parameters for a specific Notification IRP version.
     ManagedGenericIRPConstDefs::MethodList
         get_notification_IRP_operations_profile (
             in ManagedGenericIRPConstDefs::VersionNumber
```

```
notification_irp_version
raises (GetNotificationIRPOperationsProfile,
        {\tt ManagedGenericIRPSystem::OperationNotSupported,}
        ManagedGenericIRPSystem::InvalidParameter);
Return the list of all supported notifications.
Agent should always throw a ManagedGenericIRPSystem::OperationNotSupported
Similar method, such as get_alarm_IRP_notification_profile,
is supported in other IRP versions such as Alarm IRP.
ManagedGenericIRPConstDefs::MethodList
    get_notification_IRP_notification_profile (
        in ManagedGenericIRPConstDefs::VersionNumber
            {\tt notification\_irp\_version}
raises (GetNotificationIRPNotificationProfile,
        ManagedGenericIRPSystem::OperationNotSupported,
        ManagedGenericIRPSystem::InvalidParameter);
Obtain the list of all supported notification categories.
NotificationIRPConstDefs::NotificationCategorySet
    get_notification_categories (
        out NotificationIRPConstDefs::NotificationTypesSet
            notification_type_list
raises (GetNotificationCategories,
    ManagedGenericIRPSystem::OperationNotSupported);
{\tt NotificationIRPConstDefs::SubscriptionId\ attach\_push\ (}
   in string manager_reference,
   in unsigned long time_tick,
   in NotificationIRPConstDefs::NotificationCategorySet
       notification_categories,
   \hbox{in ManagedGenericIRPConstDefs::} String Type Opt \ filter
raises (Attach, ManagedGenericIRPSystem::ParameterNotSupported,
        ManagedGenericIRPSystem::InvalidParameter, AlreadySubscribed,
        AtLeastOneNotificationCategoryNotSupported);
NotificationIRPConstDefs::SubscriptionId attach_push_b (
   in string manager_reference,
   in unsigned long time_tick,
   in NotificationIRPConstDefs::NotificationCategorySet
       notification_categories,
   in ManagedGenericIRPConstDefs::StringTypeOpt filter,
   out CosNotifyChannelAdmin::SequenceProxyPushSupplier system_reference
raises (Attach, ManagedGenericIRPSystem::OperationNotSupported,
        ManagedGenericIRPSystem::ParameterNotSupported,
        ManagedGenericIRPSystem::InvalidParameter,
        {\tt AlreadySubscribed,\ AtLeastOneNotificationCategoryNotSupported);}
{\tt NotificationIRPConstDefs::SubscriptionId\ attach\_pull\ (}
   in string manager_reference,
   in unsigned long time_tick,
   in NotificationIRPConstDefs::NotificationCategorySet
       notification_categories,
   in ManagedGenericIRPConstDefs::StringTypeOpt filter,
   out CosNotifyChannelAdmin::SequenceProxyPullSupplier system_reference
raises (Attach, ManagedGenericIRPSystem::OperationNotSupported,
        ManagedGenericIRPSystem::ParameterNotSupported,
        ManagedGenericIRPSystem::InvalidParameter,
        AlreadySubscribed, AtLeastOneNotificationCategoryNotSupported);
Replace the present filter constraint with the one provided.
void change_subscription_filter (
   in NotificationIRPConstDefs::SubscriptionId subscription_id,
   in string filter
raises (ChangeSubscriptionFilter,
```

```
ManagedGenericIRPSystem::OperationNotSupported,
         ManagedGenericIRPSystem::InvalidParameter);
      Check the current state of the subscription.
      NotificationIRPConstDefs::NotificationCategorySet get_subscription_status
         in NotificationIRPConstDefs::SubscriptionId subscription_id,
         out ManagedGenericIRPConstDefs::StringTypeOpt filter_in_effect,
         out NotificationIRPConstDefs::SubscriptionState subscription_state,
         out unsigned long time_tick
      raises (GetSubscriptionStatus,
         ManagedGenericIRPSystem::OperationNotSupported,
         ManagedGenericIRPSystem::InvalidParameter);
     NotificationIRPConstDefs::SubscriptionIdSet get_subscription_ids (
         in string manager_reference
      raises (GetSubscriptionIds,
         ManagedGenericIRPSystem::OperationNotSupported,
         ManagedGenericIRPSystem::InvalidParameter);
      Terminates the subscription with the agent.
      void detach (
         in string manager_reference,
         in NotificationIRPConstDefs::SubscriptionId subscription_id
      raises (DetachException,
         ManagedGenericIRPSystem::ParameterNotSupported,
         ManagedGenericIRPSystem::InvalidParameter);
};
#endif // _NOTIFICATIONIRPSYSTEM_IDL_
```

A.5 IDL specification (file name "NotificationIRPNotifications.idl")

```
//File: NotificationIRPNotifications.idl
#ifndef _NOTIFICATIONIRPNOTIFICATIONS_IDL_
#define _NOTIFICATIONIRPNOTIFICATIONS_IDL_
#include <NotificationIRPConstDefs.idl>
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
module NotificationIRPNotifications
    interface Notify
          Notification IRP IS defines 6 attributes for the notification header.
          They are: objectClass, objectInstance, notificationId, eventTime,
          systemDN and notificationType.
          The first 2 attributes are mapped into 1 name-value pair. The name of
          the mapped IDL construct is {\tt MANAGED\_OBJECT\_INSTANCE} . The const
          string of this mapped IDL construct is defined here.
          The notificationId, eventTime and systemDN are respectively mapped
          into 3 name-value pairs. The const string(s) of these 3 mapped IDL
          constructs are defined here.
          The notificationType is not mapped into any name-value pair
          but is mapped into the type_name position-dependent
          field of the CORBA structured-event. There is no need for a const string
          definition for it.
```

Annex B (informative): Change history

	Change history						
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Jun 2001	S_12	SP-010283			Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0
Sep 2001	S_13	SP-010522	001		Eliminate guesses on IDL file names in Notification IRP: CORBA SS	4.0.0	4.1.0
Mar 2002	S_15	SP-020038	002		Addition of missing generic CORBA exception "ValueNotSupported" into CORBA module "ManagedGenericIRPSystem"	4.1.0	4.2.0
Mar 2002	S_15				Automatic upgrade to Rel-5 (no Rel-5 CR)	4.2.0	5.0.0
Sep 2002	S_17	SP-020482	004		Corrections to CORBA IDL specification "NotificationIRPSystem"	5.0.0	5.1.0
Sep 2002	S_17	SP-020479	005		Add optional parameters in CORBA Solution Set	5.0.0	5.1.0
Sep 2002					Corrected history box CR# & TS version#	5.1.0	5.1.1
Dec 2002					Cosmetics	5.1.1	5.1.2
Mar 2003	S_19	SP-030137	800		Remove unused suspend_subscription and resume_subscription methods	5.1.2	5.2.0
Mar 2003	S_19	SP-030137	009		Corrections of CORBA IDL syntax errors	5.1.2	5.2.0
Mar 2003	S_19	SP-030064	010		Update the usage IRP_VERSION in line with adopted release 5 policy - alignment with 32.111-3	5.1.2	5.2.0
Mar 2004	S_23	SP-040105			Automatic upgrade to Rel-6 (no CR)	5.2.0	6.0.0
Sep 2004	S_25	SP-040562	012		Update 32.303 using IDL Style Guide	6.0.0	6.1.0
Dec 2004	S_26	SP-040793	013		Remove filter requirement in IDL comments in the Notification IRP CORBA SS	6.1.0	6.2.0

History

Document history				
V6.2.0 December 2004 Publication		Publication		