

ETSI TS 132 633 V5.1.0 (2002-12)

Technical Specification

**Digital cellular telecommunications system (Phase 2+);
Universal Mobile Telecommunications System (UMTS);
Telecommunication management;
Configuration Management (CM);
Core network resources Integration Reference Point (IRP);
CORBA solution set
(3GPP TS 32.633 version 5.1.0 Release 5)**



Reference

RTS/TSGS-0532633v510

Keywords

GSM, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:
editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

All published ETSI deliverables shall include information which directs the reader to the above source of information.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp> .

Contents

| | |
|---|-----------|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Foreword..... | 4 |
| Introduction | 4 |
| 1 Scope | 5 |
| 2 References | 5 |
| 3 Definitions and abbreviations..... | 5 |
| 3.1 Definitions | 5 |
| 3.2 Abbreviations | 5 |
| 4 Architectural features | 6 |
| 4.1 Notifications | 6 |
| 5 Mapping | 6 |
| 5.1 General mappings..... | 6 |
| 5.2 Core Network NRM Managed Object Class (MOC) mapping..... | 6 |
| 5.2.1 MOC MscServerFunction..... | 6 |
| 5.2.2 MOC HlrFunction..... | 7 |
| 5.2.3 MOC VlrFunction..... | 7 |
| 5.2.4 MOC AucFunction | 7 |
| 5.2.5 MOC EirFunction | 7 |
| 5.2.6 MOC SmsIwmscFunction..... | 7 |
| 5.2.7 MOC SmsGmscFunction..... | 8 |
| 5.2.8 MOC SgsnFunction | 8 |
| 5.2.9 MOC GgsnFunction..... | 8 |
| 5.2.10 MOC BgFunction | 8 |
| 5.2.11 MOC GmscFunction..... | 9 |
| 5.2.12 MOC SmlcFunction..... | 9 |
| 5.2.13 MOC GmlcFunction | 9 |
| 5.2.14 MOC ScfFunction..... | 9 |
| 5.2.15 MOC SrfFunction | 9 |
| 5.2.16 MOC CbcFunction..... | 10 |
| 5.2.17 MOC CgfFunction | 10 |
| 5.2.18 MOC MgwFunction..... | 10 |
| 5.2.19 MOC GmscServerFunction | 10 |
| 5.2.20 MOC IwfFunction | 10 |
| 5.2.21 MOC MnpSrfFunction..... | 11 |
| 5.2.22 MOC NpdbFunction | 11 |
| 5.2.23 MOC SgwFunction | 11 |
| 5.2.24 MOC SsfFunction | 11 |
| 5.2.25 MOC BsFunction..... | 11 |
| 5.2.26 MOC IucsLink | 12 |
| 5.2.27 MOC IupsLink..... | 12 |
| 5.2.28 MOC IubcLink..... | 12 |
| 5.2.29 MOC ALink..... | 12 |
| 5.2.30 MOC GbLink..... | 13 |
| 5.2.31 MOC CsMgwFunction | 13 |
| 6 Rules for NRM extensions | 14 |
| 6.1 Allowed extensions | 14 |
| 6.2 Extensions not allowed..... | 14 |
| Annex A (normative): CORBA IDL, NRM Definitions | 15 |
| Annex B (informative): Change history | 23 |
| History | 24 |

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

1 Scope

The purpose of this *Core Network Resources IRP: CORBA Solution Set* is to define the mapping of the IRP information model (see TS 32.632 [3]) to the protocol specific details necessary for implementation of this IRP in a CORBA/IDL environment.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "3G Telecom Management principles and high level requirements".
- [2] 3GPP TS 32.102: "3G Telecom Management architecture".
- [3] 3GPP TS 32.632: "Configuration Management (CM); Core Network Resources Integration Reference Point (IRP); Network Resource Model (NRM)".
- [4] 3GPP TS 32.300: "Configuration Management (CM); Name convention for Managed Objects".
- [5] 3GPP TS 32.303: "Configuration Management (CM); Notification Integration Reference Point (IRP); CORBA solution set".

3 Definitions and abbreviations

3.1 Definitions

For terms and definitions please refer to TS 32.101 [1], TS 32.102 [2] and TS 32.632 [3].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|-------|---|
| CORBA | Common Object Request Broker Architecture |
| DN | Distinguished Name |
| IS | Information Service |
| IDL | Interface Definition Language (OMG) |
| IRP | Integration Reference Point |
| MO | Managed Object |
| MOC | Managed Object Class |
| NRM | Network Resource Model |
| OMG | Object Management Group |
| SS | Solution Set |

4 Architectural features

The overall architectural feature of Core Network Resources IRP is specified in TS 32.632[3]. This clause specifies features that are specific to the CORBA SS [3].

4.1 Notifications

Notifications are sent according to the Notification IRP: CORBA SS (see TS 32.303 [5]).

5 Mapping

5.1 General mappings

The IS parameter name managedObjectInstance is mapped into DN.

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MOReference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MOReferenceSet, which contains a sequence of MO references.

If a reference attribute is changed, an AttributeValueChange notification is emitted.

5.2 Core Network NRM Managed Object Class (MOC) mapping

5.2.1 MOC MscServerFunction

Table 1: Mapping from NRM MOC MscServerFunction attributes to SS equivalent MOC MscServerFunction attributes

| NRM Attributes of MOC MscFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|-----------------------------------|---|----------------|
| mscServerFunctionId | mscServerFunctionId | string | Read-Only, M |
| userLabel | userLabel | string | Read- Write, M |
| mccList | mccList | long | Read-Write, M |
| mncList | mncList | long | Read-Write, M |
| lacList | lacList | long | Read-Write, M |
| sacList | sacList | long | Read-Write, M |
| gcaList | gcaList | long | Read-Write, M |
| mscId | mscId | long | Read-Write, M |
| Associated With/ mscServerFunction-GSMcell | mscServerFunction-GSMcell | GenericNRIRPSystem::AttributeTypes::MOReference | Read-Only, M |
| Associated With/ mscServerFunction-ExternalGSMcell | mscServerFunction-ExternalGSMcell | GenericNRIRPSystem::AttributeTypes::MOReference | Read-Only, M |
| Associated With/ mscServerFunction-CsMgwFunction | mscServerFunction-CsMgwFunction | GenericNRIRPSystem::AttributeTypes::MOReference | Read-Only, M |

5.2.2 MOC HlrFunction

Table 2: Mapping from NRM MOC HlrFunction attributes to SS equivalent MOC HlrFunction attributes

| NRM Attributes of MOC HlrFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| hlrFunctionId | hlrFunctionId | string | Read-Only, M |
| userLabel | userLabel | string | Read- Write, M |

5.2.3 MOC VirFunction

Table 3: Mapping from NRM MOC VirFunction attributes to SS equivalent MOC VirFunction attributes

| NRM Attributes of MOC VirFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| virFunctionId | virFunctionId | string | Read-Only, M |
| userLabel | userLabel | string | Read- Write, M |

5.2.4 MOC AucFunction

Table 4: Mapping from NRM MOC AucFunction attributes to SS equivalent MOC AucFunction attributes

| NRM Attributes of MOC AucFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| aucFunctionId | aucFunctionId | string | Read-Only, M |
| userLabel | userLabel | string | Read- Write, M |

5.2.5 MOC EirFunction

Table 5: Mapping from NRM MOC EirFunction attributes to SS equivalent MOC EirFunction attributes

| NRM Attributes of MOC EirFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| EirFunctionId | eirFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.6 MOC SmsIwmscFunction

Table 6: Mapping from NRM MOC SmsIwmscFunction attributes to SS equivalent MOC SmsIwmscFunction attributes

| NRM Attributes of MOC SmsIwmscFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|--------------------|---------|----------------|
| smsIwmscFunctionId | smsIwmscFunctionId | string | Read-Only, M |
| userLabel | userLabel | string | Read- Write, M |

5.2.7 MOC SmsGmScFunction

Table 7: Mapping from NRM MOC SmsGmScFunction attributes to SS equivalent MOC SmsGmScFunction attributes

| NRM Attributes of MOC SmsGmScFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|-------------------|---------|----------------|
| SmsGmScFunctionId | smsGmScFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.8 MOC SgsnFunction

Table 8: Mapping from NRM MOC SgsnFunction attributes to SS equivalent MOC SgsnFunction attributes

| NRM Attributes of MOC SgsnFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|------------------------------|--|---------------|
| SgsnFunctionId | sgsnFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read-Write, M |
| mccList | mccList | long | Read-Write, M |
| mncList | mncList | long | Read-Write, M |
| lacList | lacList | long | Read-Write, M |
| racList | racList | long | Read-Write, M |
| sacList | sacList | long | Read-Write, M |
| sgsnId | sgsnId | long | Read-Write, M |
| Associated With/ sgsnFunction-GSMCell | sgsnFunction-GSMCell | GenericNRIRPSSystem::AttributeTypes::MOReference | Read-Only, M |
| Associated With/ sgsnFunction-ExternalGSMCell | sgsnFunction-ExternalGSMCell | GenericNRIRPSSystem::AttributeTypes::MOReference | Read-Only, M |

5.2.9 MOC GgsnFunction

Table 9: Mapping from NRM MOC GgsnFunction attributes to SS equivalent MOC GgsnFunction attributes

| NRM Attributes of MOC GgsnFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|----------------|---------|----------------|
| GgsnFunctionId | ggsnFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.10 MOC BgFunction

Table 10: Mapping from NRM MOC BgFunction attributes to SS equivalent MOC BgFunction attributes

| NRM Attributes of MOC BgFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|---------------|---------|----------------|
| BgFunctionId | bgFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.11 MOC GmscFunction

Table 11: Mapping from NRM MOC GmscFunction attributes to SS equivalent MOC GmscFunction attributes

| NRM Attributes of MOC GmscFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|----------------|---------|----------------|
| GmscFunctionId | gmscFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.12 MOC SmlcFunction

Table 12: Mapping from NRM MOC SmlcFunction attributes to SS equivalent MOC SmlcFunction attributes

| NRM Attributes of MOC SmlcFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|----------------|---------|----------------|
| SmlcFunctionId | smlcFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.13 MOC GmlcFunction

Table 13: Mapping from NRM MOC GmlcFunction attributes to SS equivalent MOC GmlcFunction attributes

| NRM Attributes of MOC GmlcFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|----------------|---------|----------------|
| GmlcFunctionId | gmlcFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.14 MOC ScfFunction

Table 14: Mapping from NRM MOC ScfFunction attributes to SS equivalent MOC ScfFunction attributes

| NRM Attributes of MOC ScfFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| ScfFunctionId | scfFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.15 MOC SrfFunction

Table 15: Mapping from NRM MOC SrfFunction attributes to SS equivalent MOC SrfFunction attributes

| NRM Attributes of MOC SrfFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| SrfFunctionId | srfFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.16 MOC CbcFunction

Table 16: Mapping from NRM MOC CbcFunction attributes to SS equivalent MOC CbcFunction attributes

| NRM Attributes of MOC CbcFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| CbcFunctionId | cbcFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.17 MOC CgfFunction

Table 17: Mapping from NRM MOC CgfFunction attributes to SS equivalent MOC CgfFunction attributes

| NRM Attributes of MOC CgfFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| CgfFunctionId | cgfFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.18 MOC MgwFunction

Table 18: Mapping from NRM MOC MgwFunction attributes to SS equivalent MOC MgwFunction attributes

| NRM Attributes of MOC MgwFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| MgwFunctionId | mgwFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.19 MOC GmscServerFunction

Table 19: Mapping from NRM MOC GmscServerFunction attributes to SS equivalent MOC GmscServerFunction attributes

| NRM Attributes of MOC GmscServerFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|----------------------|---------|----------------|
| GmscServerFunctionId | gmscServerFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.20 MOC IwfFunction

Table 20: Mapping from NRM MOC IwfFunction attributes to SS equivalent MOC IwfFunction attributes

| NRM Attributes of MOC IwfFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| IwfFunctionId | iwfFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.21 MOC MnpSrfFunction

Table 21: Mapping from NRM MOC MnpSrfFunction attributes to SS equivalent MOC lwfFunction attributes

| NRM Attributes of MOC MnpSrfFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|------------------|---------|----------------|
| MnpSrfFunctionId | mnpSrfFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.22 MOC NpdbFunction

Table 22: Mapping from NRM MOC NpdbFunction attributes to SS equivalent MOC NpdbFunction attributes

| NRM Attributes of MOC NpdbFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|----------------|---------|----------------|
| NpdbFunctionId | npdbFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.23 MOC SgwFunction

Table 23: Mapping from NRM MOC SgwFunction attributes to SS equivalent MOC SgwFunction attributes

| NRM Attributes of MOC SgwFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| sgwFunctionId | sgwFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.24 MOC SsfFunction

Table 24: Mapping from NRM MOC SsfFunction attributes to SS equivalent MOC SsfFunction attributes

| NRM Attributes of MOC SsfFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------|---------|----------------|
| SsfFunctionId | ssfFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.25 MOC BsFunction

Table 25: Mapping from NRM MOC BsFunction attributes to SS equivalent MOC BsFunction attributes

| NRM Attributes of MOC BsFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|---------------|---------|----------------|
| bsFunctionId | bsFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read- Write, M |

5.2.26 MOC IucsLink

Table 26: Mapping from NRM MOC IucsLink attributes to SS equivalent MOC IucsLink attributes

| NRM Attributes of MOC IucsLink in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|---------------|---|----------------|
| iucsLinkId | iucsLinkId | string | Read-Only, M |
| userLabel | userLabel | string | Read- Write, M |
| Connected To/connectedRnc | connectedRnc | GenericNRIRPSSystem::AttributeTypes::MOResource | Read-Only, M |
| Connected To/connectedBss | connectedBss | GenericNRIRPSSystem::AttributeTypes::MOResource | Read-Only, M |

5.2.27 MOC IupsLink

Table 27: Mapping from NRM MOC IupsLink attributes to SS equivalent MOC IupsLink attributes

| NRM Attributes of MOC IupsLink in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|---------------|---|----------------|
| iupsLinkId | iupsLinkId | string | Read-Only, M |
| userLabel | userLabel | string | Read- Write, M |
| Connected To/connectedRnc | connectedRnc | GenericNRIRPSSystem::AttributeTypes::MOResource | Read-Only, O |
| Connected To/connectedBss | connectedBss | GenericNRIRPSSystem::AttributeTypes::MOResource | Read-Only, O |

5.2.28 MOC IubcLink

Table 28: Mapping from NRM MOC IubcLink attributes to SS equivalent MOC IubcLink attributes

| NRM Attributes of MOC IubcLink in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|---------------|---|----------------|
| iubcLinkId | iubcLinkId | string | Read-Only, M |
| userLabel | userLabel | string | Read- Write, M |
| Connected To/connectedRnc | connectedRnc | GenericNRIRPSSystem::AttributeTypes::MOResource | Read-Only, M |

5.2.29 MOC ALink

Table 29: Mapping from NRM MOC ALink attributes to SS equivalent MOC ALink attributes

| NRM Attributes of MOC IucsLink in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|---------------|---|----------------|
| aLinkId | aLinkId | string | Read-Only, M |
| userLabel | userLabel | string | Read- Write, M |
| Connected To/connectedBss | connectedBss | GenericNRIRPSSystem::AttributeTypes::MOResource | Read-Only, M |

5.2.30 MOC GbLink

Table 30: Mapping from NRM MOC GbLink attributes to SS equivalent MOC GbLink attributes

| NRM Attributes of MOC IuCsLink in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|---|---------------|--|---------------|
| gbLinkId | gbLinkId | string | Read-Only, M |
| userLabel | userLabel | string | Read-Write, M |
| Connected To/connectedBss | connectedBss | GenericNRIRPSSystem::AttributeTypes::MORefERENCE | Read-Only, M |

5.2.31 MOC CsMgwFunction

Table 32: Mapping from NRM MOC CsMgwFunction attributes to SS equivalent MOC CsMgwFunction attributes

| NRM Attributes of MOC MgwFunction in TS 32.632 [3] | SS Attributes | SS Type | Qualifier |
|--|---------------------------------|--|---------------|
| CsMgwFunctionId | CsmgwFunctionId | string | Read-Only, M |
| UserLabel | userLabel | string | Read-Write, M |
| Associated With/csMgwFunction-mscServerFunction | csMgwFunction-mscServerFunction | GenericNRIRPSSystem::AttributeTypes::MOResourceReference | Read-Only, M |
| Connected To/csMgwFunction- iucsLink | csMgwFunction- iucsLink | GenericNRIRPSSystem::AttributeTypes::MOResourceReference | Read-Only, M |
| Connected To /csMgwFunction- ALink | csMgwFunction- ALink | GenericNRIRPSSystem::AttributeTypes::MOResourceReference | Read-Only, M |

6 Rules for NRM extensions

This clause discusses how the models and IDL definitions provided in the present document can be extended for a particular implementation and still remain compliant with 3GPP SA5's specifications.

6.1 Allowed extensions

Vendor-specific MOCs may be supported. The vendor-specific MOCs may support new types of attributes. The 3GPP SA5-specified notifications may be issued referring to the vendor-specific MOCs and vendor-specific attributes. New MOCs shall be distinguishable from 3GPP SA5 MOCs by name. 3GPP SA5-specified and vendor-specific attributes may be used in vendor-specific MOCs. Vendor-specific attribute names shall be distinguishable from existing attribute names.

NRM MOCs may be subclassed. Subclassed MOCs shall maintain the specified behaviour of the 3GPP SA5's superior classes. They may add vendor-specific behaviour with vendor-specific attributes. When subclassing, naming attributes cannot be changed. The subclassed MOC shall support all attributes of its superior class. Vendor-specific attributes cannot be added to 3GPP SA5 NRM MOCs without subclassing.

When subclassing, the 3GPP SA5-specified containment rules and their specified cardinality shall still be followed. As an example, ManagementNode (or its subclasses) shall be contained under SubNetwork (or its subclasses). Also, in Rel-4, there may only be 0 or 1 ManagementNode (or its subclasses) contained under SubNetwork (or its subclasses).

Managed Object Instances may be instantiated as CORBA objects. This requires that the MOCs be represented in IDL. 3GPP SA5's NRM MOCs are not currently specified in IDL, but may be specified in IDL for instantiation or subclassing purposes. However, management information models should not require that IRPManagers access the instantiated managed objects other than through supported methods in the present document.

Extension rules related to notifications (Notification categories, Event Types, Extended Event Types etc.) are for further study.

6.2 Extensions not allowed

The IDL specifications in the present document cannot be edited or altered. Any additional IDL specifications shall be specified in separate IDL files.

IDL interfaces (note: not MOCs) specified in the present document may not be subclassed or extended. New interfaces may be defined with vendor-specific methods.

Annex A (normative): CORBA IDL, NRM Definitions

```
#ifndef CoreNetworkResourcesNRMDefs_idl
#define CoreNetworkResourcesNRMDefs_idl

#pragma prefix "3gppsa5.org"

/***
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module CoreNetworkResourcesNRMDefs
{



    /**
     * Definitions for MO class MscServerFunction
     */
    interface MscServerFunction
    {
        const string CLASS = "MscServerFunction";

        // Attribute Names
        //
        const string mscServerFunctionId = "mscServerFunctionId";
        const string userLabel = "userLabel";
        const string mccList = "mccList";
        const string mncList = "mncList";
        const string lacList = "lacList";
        const string sacList = "sacList";
        const string gcaList = "gcaList";
        const string mscId = "mscId";
        const string mscServerFunctionGSMcell = "mscServerFunctionGSMcell";
        const string mscServerFunctionExternalGSMcell =
"mscServerFunctionExternalGSMcell";
        const string mscServerFunctionCsMgwFunction =
"mscServerFunctionCsMgwFunction";
    };

    /**
     * Definitions for MO class HlrFunction
     */
    interface HlrFunction
    {
        const string CLASS = "HlrFunction";

        // Attribute Names
        //
        const string hlrFunctionId = "hlrFunctionId";
        const string userLabel = "userLabel";
    };

    /**
     * Definitions for MO class VlrFunction
     */
    interface VlrFunction
    {
```

```
    const string CLASS = "VlrFunction";

    // Attribute Names
    //
    const string vlrFunctionId = "vlrFunctionId";
    const string userLabel = "userLabel";
};

/***
 *  Definitions for MO class AucFunction
 */
interface AucFunction
{
    const string CLASS = "AucFunction";

    // Attribute Names
    //
    const string aucFunctionId = "aucFunctionId";
    const string userLabel = "userLabel";
};

/***
 *  Definitions for MO class EirFunction
 */
interface EirFunction
{
    const string CLASS = "EirFunction";

    // Attribute Names
    //
    const string eirFunctionId = "eirFunctionId";
    const string userLabel = "userLabel";
};

/***
 *  Definitions for MO class SmsIwmscFunction
 */
interface SmsIwmscFunction
{
    const string CLASS = "SmsIwmscFunction";

    // Attribute Names
    //
    const string smsIwmscFunctionId = "smsIwmscFunctionId";
    const string userLabel = "userLabel";
};

/***
 *  Definitions for MO class SmsGmscFunction
 */
interface SmsGmscFunction
{
    const string CLASS = "SmsGmscFunction";

    // Attribute Names
    //
    const string smsGmscFunctionId = "smsGmscFunctionId";
    const string userLabel = "userLabel";
};
```

```

};

/*
 * Definitions for MO class SgsnFunction
 */
interface SgsnFunction
{
    const string CLASS = "SgsnFunction";

    // Attribute Names
    //
    const string sgsnFunctionId = "sgsnFunctionId";
    const string userLabel = "userLabel";
    const string mccList = "mccList";
    const string mncList = "mncList";
    const string lacList = "lacList";
    const string racList = "racList";
    const string sacList = "sacList";
    const string sgsnId = "sgsnId";
    const string sgsnFunctionGSMcell = "sgsnFunctionGSMcell";
    const string sgsnFunctionExternalGSMcell = "sgsnFunctionExternalGSMcell";
};

/*
 * Definitions for MO class GgsnFunction
 */
interface GgsnFunction
{
    const string CLASS = "GgsnFunction";

    // Attribute Names
    //
    const string ggsnFunctionId = "ggsnFunctionId";
    const string userLabel = "userLabel";
};

/*
 * Definitions for MO class BgFunction
 */
interface BgFunction
{
    const string CLASS = "BgFunction";

    // Attribute Names
    //
    const string bgFunctionId = "bgFunctionId";
    const string userLabel = "userLabel";
};

/*
 * Definitions for MO class GmscFunction
 */
interface GmscFunction
{
    const string CLASS = "GmscFunction";

    // Attribute Names
    //
    const string gmscFunctionId = "gmscFunctionId";

```

```
        const string userLabel = "userLabel";
    };

/***
 *  Definitions for MO class SmlcFunction
 */
interface SmlcFunction
{
    const string CLASS = "SmlcFunction";

    // Attribute Names
    //
    const string smlcFunctionId = "smlcFunctionId";
    const string userLabel = "userLabel";
};

/***
 *  Definitions for MO class GmlcFunction
 */
interface GmlcFunction
{
    const string CLASS = "GmlcFunction";

    // Attribute Names
    //
    const string gmlcFunctionId = "gmlcFunctionId";
    const string userLabel = "userLabel";
};

/***
 *  Definitions for MO class ScfFunction
 */
interface ScfFunction
{
    const string CLASS = "ScfFunction";

    // Attribute Names
    //
    const string scfFunctionId = "scfFunctionId";
    const string userLabel = "userLabel";
};

/***
 *  Definitions for MO class SrfFunction
 */
interface SrfFunction
{
    const string CLASS = "SrfFunction";

    // Attribute Names
    //
    const string srfFunctionId = "srfFunctionId";
    const string userLabel = "userLabel";
};

/***
```

```
* Definitions for MO class CbcFunction
*/
interface CbcFunction
{
    const string CLASS = "CbcFunction";

    // Attribute Names
    //
    const string cbcFunctionId = "cbcFunctionId";
    const string userLabel = "userLabel";
};

/***
 * Definitions for MO class CgfFunction
 */
interface CgfFunction
{
    const string CLASS = "CgfFunction";

    // Attribute Names
    //
    const string cgfFunctionId = "cgfFunctionId";
    const string userLabel = "userLabel";
};

/***
 * Definitions for MO class MgwFunction
 */
interface MgwFunction
{
    const string CLASS = "MgwFunction";

    // Attribute Names
    //
    const string mgwFunctionId = "mgwFunctionId";
    const string userLabel = "userLabel";
};

/***
 * Definitions for MO class GmscServerFunction
 */
interface GmscServerFunction
{
    const string CLASS = "GmscServerFunction";

    // Attribute Names
    //
    const string gmscServerFunctionId = "gmscServerFunctionId";
    const string userLabel = "userLabel";
};

/***
 * Definitions for MO class IwfFunction
 */
interface IwfFunction
{
    const string CLASS = "IwfFunction";
```

```
// Attribute Names
//
const string iwfFunctionId = "iwfFunctionId";
const string userLabel = "userLabel";
};

/***
 * Definitions for MO class MnpSrfFunction
 */
interface MnpSrfFunction
{
    const string CLASS = "MnpSrfFunction";

    // Attribute Names
    //
    const string mnpSrfFunctionId = "mnpSrfFunctionId";
    const string userLabel = "userLabel";
};

/***
 * Definitions for MO class NpdbcFunction
 */
interface NpdbcFunction
{
    const string CLASS = "NpdbcFunction";

    // Attribute Names
    //
    const string npdbcFunctionId = "npdbcFunctionId";
    const string userLabel = "userLabel";
};

/***
 * Definitions for MO class SgwFunction
 */
interface SgwFunction
{
    const string CLASS = "SgwFunction";

    // Attribute Names
    //
    const string sgwFunctionId = "sgwFunctionId";
    const string userLabel = "userLabel";
};

/***
 * Definitions for MO class SsfFunction
 */
interface SsfFunction
{
    const string CLASS = "SsfFunction";

    // Attribute Names
    //
    const string ssfFunctionId = "ssfFunctionId";
    const string userLabel = "userLabel";
};
```

```

    /**
     * Definitions for MO class BsFunction
     */
interface BsFunction
{
    const string CLASS = "BsFunction";

    // Attribute Names
    //
    const string bsFunctionId = "bsFunctionId";
    const string userLabel = "userLabel";
};

    /**
     * Definitions for MO class IucsLink
     */
interface IucsLink
{
    const string CLASS = "IucsLink";

    // Attribute Names
    //
    const string iucsLinkId = "iucsLinkId";
    const string userLabel = "userLabel";
    const string connectedRnc = "connectedRnc";
    const string connectedBss = "connectedBss";
};

    /**
     * Definitions for MO class IupsLink
     */
interface IupsLink
{
    const string CLASS = "IupsLink";

    // Attribute Names
    //
    const string iupsLinkId = "iupsLinkId";
    const string userLabel = "userLabel";
    const string connectedRnc = "connectedRnc";
    const string connectedBss = "connectedBss";
};

    /**
     * Definitions for MO class IubcLink
     */
interface IubcLink
{
    const string CLASS = "IubcLink";

    // Attribute Names
    //
    const string iubcLinkId = "iubcLinkId";
    const string userLabel = "userLabel";
    const string connectedRnc = "connectedRnc";
};

    /**

```

```
* Definitions for MO class ALink
*/
interface ALink
{
    const string CLASS = "ALink";

    // Attribute Names
    //
    const string aLinkId = "aLinkId";
    const string userLabel = "userLabel";
    const string connectedBss = "connectedBss";
};

/***
 * Definitions for MO class GbLink
 */
interface GbLink
{
    const string CLASS = "GbLink";

    // Attribute Names
    //
    const string gbLinkId = "gbLinkId";
    const string userLabel = "userLabel";
    const string connectedBss = "connectedBss";
};

/***
 * Definitions for MO class CsMgwFunction
 */
interface CsMgwFunction
{
    const string CLASS = "CsMgwFunction";

    // Attribute Names
    //
    const string csMgwFunctionId = "csMgwFunctionId";
    const string userLabel = "userLabel";
    const string csMgwFunctionMscServerFunction =
"csMgwFunctionMscServerFunction";
    const string csMgwFunctionIucsLink = "csMgwFunctionIucsLink";
    const string csMgwFunctionALink = "csMgwFunctionALink";
};

};

#endif
```

Annex B (informative): Change history

| Change history | | | | | | | | |
|----------------|-------|-----------|-----|-----|---|-------|-------|--|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New | |
| Jun 2001 | S_12 | SP-010283 | -- | -- | Approved at TSG SA #12 and placed under Change Control | 2.0.0 | 4.0.0 | |
| Jun 2002 | S_16 | SP-020302 | 001 | -- | Align with Rel-4 Network Architecture (23.002) by changing Roaming Signalling Gateway (R-SGW) to Signalling Gateway (SGW) | 4.0.0 | 4.1.0 | |
| Sep 2002 | S_17 | SP-020489 | 002 | -- | Upgrade to Rel-5 the CORBA SS for Core Network NRM (add Managed Object Classes (MOCs)) | 4.1.0 | 5.0.0 | |
| Dec 2002 | S_18 | SP-020747 | 003 | -- | Removal of faulty attribute uralList (alignment with Rel-5 32.632 Network Resource Model) | 5.0.0 | 5.1.0 | |
| | | | | | | | | |

History

| Document history | | |
|------------------|----------------|-------------|
| V5.0.0 | September 2002 | Publication |
| V5.1.0 | December 2002 | Publication |
| | | |
| | | |
| | | |