

# ETSI TS 132 634 V4.0.0 (2001-06)

*Technical Specification*

**Digital cellular telecommunications system (Phase 2+) (GSM);  
Universal Mobile Telecommunications System (UMTS);  
Telecommunication Management;  
Configuration Management;  
Core network resources IRP: CMIP solution set  
(3GPP TS 32.634 version 4.0.0 Release 4)**



---

Reference

DTS/TSGS-0532634Uv4

---

Keywords

GSM, UMTS

***ETSI***

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***

Individual copies of the present document can be downloaded from:  
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:  
[editor@etsi.fr](mailto:editor@etsi.fr)

---

***Copyright Notification***

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.

All rights reserved.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by the ETSI 3<sup>rd</sup> Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under [www.etsi.org/key](http://www.etsi.org/key).

---

# Contents

Foreword .....	5
Introduction.....	5
1    Scope.....	7
2    References.....	7
3    Definitions, symbols and abbreviations .....	7
3.1    Definitions.....	7
3.2    Abbreviations .....	8
4    Basic aspects .....	8
4.1    Explanation.....	8
4.2    Mapping .....	8
4.2.1    Mapping of MOCs .....	8
4.2.2    Mapping of Attributes.....	9
5    GDMO Definitions .....	10
5.1    Managed Object Classes.....	10
5.1.1    smlcFunction.....	10
5.1.2    gmlcFunction .....	10
5.1.3    scfFunction .....	10
5.1.4    srfFunction .....	11
5.1.5    cbcFunction.....	11
5.1.6    cfgFunction .....	11
5.1.7    mgwFunction .....	12
5.1.8    gmscFunction.....	12
5.1.9    iwfFunction.....	12
5.1.10    mnpSrfFunction .....	13
5.1.11    npdbFunction .....	13
5.1.12    rSgwFunction.....	14
5.1.13    ssfFunction.....	14
5.1.14    bsFunction.....	14
5.2    Attributes.....	15
5.2.1    smlcFunctionId .....	15
5.2.2    gmlcFunctionId .....	15
5.2.3    sfcFunctionId .....	15
5.2.4    srfFunctionId.....	16
5.2.5    CbcFunctionId .....	16
5.2.6    CfgFunctionId.....	16
5.2.7    mgwFunctionId .....	16
5.2.8    gmscFunctionId .....	17
5.2.9    iwfFunctionId .....	17
5.2.10    mnpSrfFunctionId .....	17
5.2.11    npdbFunctionId .....	17
5.2.12    rSgwFunctionId .....	18
5.2.13    ssfFunctionId .....	18
5.2.14    bsFunctionId .....	18
5.3    Name Binding.....	19
5.3.1    smlcFunction - managedElement.....	19
5.3.2    gmlcFunction - managedElement .....	19
5.3.3    sfcFunction - managedElement.....	19
5.3.4    srfFunction - managedElement .....	20
5.3.5    cbcFunction - managedElement.....	20
5.3.6    cfgFunction - managedElement .....	21
5.3.7    mgwFunction - managedElement .....	21
5.3.8    gmscFunction - managedElement .....	21
5.3.9    iwfFunction - managedElement .....	22

5.3.10	mnpSrfFunction - managedElement .....	22
5.3.11	npdbFunction - managedElement .....	22
5.3.12	rSgwFunction - managedElement.....	23
5.3.13	ssfFunction - managedElement.....	23
5.3.14	bsFunction - managedElement.....	24
6	ASN.1 Definitions .....	25
<b>Annex A (informative):</b>	<b>Change history.....</b>	<b>26</b>

---

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Introduction

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

Due to the growing number of specifications to model new services and Resource Models for Configuration Management (CM), as well as the expected growth in size of each of them from 3GPP Release 4 onwards, a new structure of the specifications is already needed in Release 4. This structure is needed for several reasons, but mainly to enable more independent development and release for each part, as well as a simpler document identification and version handling. Another benefit would be that it becomes easier for bodies outside 3GPP, such as the ITU-T, to refer to telecom management specifications from 3GPP. The new structure of the specifications does not lose any information or functionality supported by the Release 1999. The restructuring also includes defining new IRPs for the Network Resource Models (Generic, Core Network and UTRAN NRM).

Finally, the Name convention for Managed Objects (in Release 1999: 32.106-8) has been moved to a separate number series used for specifications common between several management areas (e.g. CM, FM, PM).

The following table shows an overview of the mapping between the old Release 1999 and new Release 4 CM specification structure.

**Table: Mapping between Release '99 and the new Rel-4 specifications**

R99 Old no.	Old (R99) specification title	Rel-4 New no.	New (Rel-4) specification title
32.106-1	3G Configuration Management: Concept and Requirements	32.600	<b>3G Configuration Management: Concept and High-level Requirements</b>
32.106-1	<Notification IRP requirements from 32.106-1 and 32.106-2>	32.301	<b>Notification IRP:</b> Requirements
32.106-2	Notification IRP: IS	32.302	Notification IRP: Information Service
32.106-3	Notification IRP: CORBA SS	32.303	Notification IRP: CORBA SS
32.106-4	Notification IRP: CMIP SS	32.304	Notification IRP: CMIP SS
32.106-8	Name convention for Managed Objects	32.300	<b>Name Convention for Managed Objects</b>
32.106-1	<Basic CM IRP IS requirements from 32.106-1 and 32.106-5>	32.601	<b>Basic CM IRP:</b> Requirements
32.106-5	Basic CM IRP IM (Intro & IS part)	32.602	Basic CM IRP: Information Service
32.106-6	Basic CM IRP CORBA SS (IS related part)	32.603	Basic CM IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (IS related part)	32.604	Basic CM IRP: CMIP SS
32.106-8	Name convention for Managed Objects	32.300	<b>Name Convention for Managed Objects</b>
-	-	32.611	<b>Bulk CM IRP:</b> Requirements
-	-	32.612	Bulk CM IRP: Information Service
-	-	32.613	Bulk CM IRP: CORBA SS
-	-	32.614	Bulk CM IRP: CMIP SS
		32.615	Bulk CM IRP: XML file format definition
32.106-1	<Basic CM IRP Generic NRM requirements from 32.106-1 and 32.106-5>	32.621	<b>Generic Network Resources IRP:</b> Requirements
32.106-5	Basic CM IRP IM (Generic NRM part)	32.622	Generic Network Resources IRP: NRM
32.106-6	Basic CM IRP CORBA SS (Generic NRM related part)	32.623	Generic Network Resources IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (Generic NRM related part)	32.624	Generic Network Resources IRP: CMIP SS
32.106-1	<Basic CM IRP CN NRM requirements from 32.106-1 and 32.106-5>	32.631	<b>Core Network Resources IRP:</b> Requirements
32.106-5	Basic CM IRP IM (CN NRM part)	32.632	Core Network Resources IRP: NRM
32.106-6	Basic CM IRP CORBA SS (CN NRM related part)	32.633	Core Network Resources IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (CN NRM related part)	32.634	<b>Core Network Resources IRP: CMIP SS</b>
32.106-1	<Basic CM IRP UTRAN NRM requirements from 32.106-1 and 32.106-5>	32.641	<b>UTRAN Network Resources IRP:</b> Requirements
32.106-5	Basic CM IRP IM (UTRAN NRM part)	32.642	UTRAN Network Resources IRP: NRM
32.106-6	Basic CM IRP CORBA SS (UTRAN NRM related part)	32.643	UTRAN Network Resources IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (UTRAN NRM related part)	32.644	UTRAN Network Resources IRP: CMIP SS
		32.651	<b>GERAN Network Resources IRP:</b> Requirements
		32.652	GERAN Network Resources IRP: NRM
		32.653	GERAN Network Resources IRP: CORBA SS
		32.654	GERAN Network Resources IRP: CMIP SS

## 1 Scope

The present document specifies the Common Management Information Protocol (CMIP) Solution Set (SS) for the CN Network Resource Integration Reference Point (IRP): Network Resource Model defined in 3GPP TS 32.632. In detail:

- Clause 4 contains an introduction to some concepts that are the base for some specific aspects of the CMIP interfaces.
- Clause 5 contains the GDMO definitions for the Alarm Management over the CMIP interfaces
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "3G Telecom Management principles and high level requirements".
- [2] 3GPP TS 32.102: "3G Telecom Management architecture".
- [3] 3GPP TS 32.304: "Telecommunication Management; Notification Management; Part 4: Notification Integration Reference Point; CMIP Solution Set".
- [4] 3GPP TS 32.632: "Telecommunication Management; Configuration Management: CN Network Resource Integration Reference Point: Network Resource Model".
- [5] ITU-T Recommendation X.710 (1991): "Common Management Information Service Definition for CCITT Applications".
- [6] ITU-T Recommendation X.721 (02/92): "Information Technology - Open Systems Interconnection – Structure of Management Information: Definition of Management Information".
- [7] ITU-T Recommendation X.730 (01/92): "Information Technology - Open Systems Interconnection – Systems Management: Object Management Function".
- [8] ITU-T Recommendation X.733 (02/92): "Information Technology - Open Systems Interconnection - Alarm Reporting Function".
- [9] ITU-T Recommendation M.3100 (07/95): "Maintenance Telecommunications Management Network – Generic Network Information Model".

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.600 and 3GPP TS 32.632 apply.

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CMIP	Common Management Information Protocol
DN	Distinguished Name
GDMO	Guidelines for the Definition of Managed Objects
IDL	Interface Definition Language
IEC	International Electro-technical Commission
ISO	International Standards Organization
ITU-T	International Telecommunication Union, Telecommunication Sector
MIB	Management Information Base
MIM	Management Information Model
MIT	Management Information Tree (or Naming Tree)
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NR	Network Resource
NRM	Network Resource Model
TMN	Telecommunications Management Network
UTRAN	UMTS Terrestrial Radio Access Network

## 4 Basic aspects

### 4.1 Explanation

A technology independent CN network resource model is defined in 3GPP TS 32.632 for 3G networks. This document provides an implementation of this CN network resource model by using CMIP technology.

### 4.2 Mapping

The semantic of the CN Network Resource Model is defined in 3GPP TS 32.632. The specification of the information object classes defined there is independent of any implementation technology and protocol.

This subclause maps these technology and protocol independent definitions onto the equivalencies of the CMIP Solution Set of the UTRAN Network Resource IRP.

#### 4.2.1 Mapping of MOCs

Table 2 maps the information object classes defined in the CN Network Resource Model onto the equivalent MOCs of the CMIP Solution Set.

**Table 1: Mapping of MOCs**

<b>Managed Objects of the CN NR IRP NRM</b>	<b>MOCs of this CMIP SS</b>
AucFunction	AucFunction (3GPP TS 32.106-7: 6.2001)
BgFunction	bgFunction (3GPP TS 32.106-7: 6.2001)
EirFunction	eirFunction (3GPP TS 32.106-7: 6.2001)
GgsnFunction	ggsnFunction (3GPP TS 32.106-7: 6.2001)
GmscFunction	gmscFunction (3GPP TS 32.106-7: 6.2001)
HlrFunction	hlrFunction (3GPP TS 32.106-7: 6.2001)
MscFunction	mscFunction (3GPP TS 32.106-7: 6.2001)
SgsnFunction	sgsnFunction (3GPP TS 32.106-7: 6.2001)
SmsGmscFunction	smsGmscFunction (3GPP TS 32.106-7: 6.2001)
SmsIwmscFunction	smsIwmscFunction (3GPP TS 32.106-7: 6.2001)
VlrFunction	vlrFunction (3GPP TS 32.106-7: 6.2001)
SmlcFunction	smlcFunction
GmlcFunction	gmlcFunction
SfcFunction	sfcFunction
SrfFunction	srfFunction
CbcFunction	cbcFunction
CqfFunction	cqfFunction
MgwFunction	mgwFunction
GmscFunction	gmscFunction
IwfFunction	iwfFunction
MnpSrfFunction	mnpSrfFunction
NpdbFunction	npdbFunction
RSgwFunction	rSgwFunction
SsfFunction	ssfFunction
BsFunction	bsFunction

#### 4.2.2 Mapping of Attributes

**Table 2: Mapping of Attributes**

<b>Attribute defined in 3GPP TS 32.632</b>	<b>Attribute defined in this CMIP SS</b>
UserLabel	userLabel (3GPP TS 32.106-7: 6.2001)
AucFunctionId	AucFunctionId (3GPP TS 32.106-7: 6.2001)
BgFunctionId	bgFunctionId (3GPP TS 32.106-7: 6.2001)
eirFunctionId	eirFunctionId (3GPP TS 32.106-7: 6.2001)
ggsnFunctionId	ggsnFunctionId (3GPP TS 32.106-7: 6.2001)
gmscFunctionId	gmscFunctionId (3GPP TS 32.106-7: 6.2001)
hlrFunctionId	hlrFunctionId (3GPP TS 32.106-7: 6.2001)
mscFunctionId	mscFunctionId (3GPP TS 32.106-7: 6.2001)
vlrFunctionId	vlrFunctionId (3GPP TS 32.106-7: 6.2001)
sgsnFunctionId	sgsnFunctionId (3GPP TS 32.106-7: 6.2001)
smsGmscFunctionId	smsGmscFunctionId (3GPP TS 32.106-7: 6.2001)
smsIwmscFunctionId	smsIwmscFunctionId (3GPP TS 32.106-7: 6.2001)
smlcFunctionId	smlcFunctionId
gmlcFunctionId	gmlcFunctionId
sfcFunctionId	sfcFunctionId
srfFunctionId	srfFunctionId
cbcFunctionId	cbcFunctionId
cqfFunctionId	cqfFunctionId
mgwFunctionId	mgwFunctionId
gmscFunctionId	gmscFunctionId
iwfFunctionId	iwfFunctionId
mnpSrfFunctionId	mnpSrfFunctionId
npdbFunctionId	npdbFunctionId
rSgwFunctionId	rSgwFunctionId
ssfFunctionId	ssfFunctionId
bsFunctionId	bsFunctionId

---

## 5 GDMO Definitions

### 5.1 Managed Object Classes

#### 5.1.1 smlcFunction

**smlcFunction** MANAGED OBJECT CLASS

DERIVED FROM “3GPP TS 32.106-7: 6.2001”: managedFunction;  
CHARACTERIZED BY

  smlcFunctionBasicPackage PACKAGE

  BEHAVIOUR **smlcFunctionBasicPackageBehaviour**;

  ATTRIBUTES

  smlcFunctionId GET;::

REGISTERED AS {ts32-621ObjectClass 1};

**smlcFunctionBasicPackageBehaviour** BEHAVIOUR

DEFINED AS

  " This Managed Object Class represents SMLC functionality. For more information about the SMLC, see 3GPP TS 23.002";

#### 5.1.2 gmlcFunction

**gmlcFunction** MANAGED OBJECT CLASS

DERIVED FROM “3GPP TS 32.106-7: 6.2001”: managedFunction;  
CHARACTERIZED BY

  gmlcFunctionBasicPackage PACKAGE

  BEHAVIOUR **gmlcFunctionBasicPackageBehaviour**;

  ATTRIBUTES

  gmlcFunctionId GET;::

REGISTERED AS {ts32-621ObjectClass 2};

**gmlcFunctionBasicPackageBehaviour** BEHAVIOUR

DEFINED AS

  " This Managed Object Class represents GMLC functionality. For more information about the GMLC, see 3GPP TS 23.002";

#### 5.1.3 scfFunction

**scfFunction** MANAGED OBJECT CLASS

DERIVED FROM “3GPP TS 32.106-7: 6.2001”: managedFunction;  
CHARACTERIZED BY

  scfFunctionBasicPackage PACKAGE

  BEHAVIOUR **scfFunctionBasicPackageBehaviour**;

  ATTRIBUTES

scfFunctionId GET;;;  
 REGISTERED AS {ts32-621ObjectClass 3};

### **scfFunctionBasicPackageBehaviour BEHAVIOUR**

#### DEFINED AS

" This Managed Object Class represents SCF functionality. For more information about the SCF, see 3GPP TS 23.002";

## 5.1.4 srfFunction

### **srfFunction MANAGED OBJECT CLASS**

DERIVED FROM "3GPP TS 32.106-7: 6.2001": managedFunction;

#### CHARACTERIZED BY

scfFunctionBasicPackage PACKAGE

BEHAVIOUR **srfFunctionBasicPackageBehaviour;**

#### ATTRIBUTES

srfFunctionId GET;;;

REGISTERED AS {ts32-621ObjectClass 4};

### **srfFunctionBasicPackageBehaviour BEHAVIOUR**

#### DEFINED AS

" This Managed Object Class represents SRF functionality. For more information about the SRF, see 3GPP TS 23.002";

## 5.1.5 cbcFunction

### **cbcFunction MANAGED OBJECT CLASS**

DERIVED FROM "3GPP TS 32.106-7: 6.2001": managedFunction;

#### CHARACTERIZED BY

cbcFunctionBasicPackage PACKAGE

BEHAVIOUR **cbcFunctionBasicPackageBehaviour;**

#### ATTRIBUTES

cbcFunctionId GET;;;

REGISTERED AS {ts32-621ObjectClass 5};

### **cbcFunctionBasicPackageBehaviour BEHAVIOUR**

#### DEFINED AS

" This Managed Object Class represents SBC functionality. For more information about the SBC, see 3GPP TS 23.002";

## 5.1.6 cfgFunction

### **cfgFunction MANAGED OBJECT CLASS**

DERIVED FROM "3GPP TS 32.106-7: 6.2001": managedFunction;

#### CHARACTERIZED BY

cfgFunctionBasicPackage PACKAGE

**BEHAVIOUR cfgFunctionBasicPackageBehaviour;**  
**ATTRIBUTES**  
cfgFunctionId GET;;;  
REGISTERED AS {ts32-621ObjectClass 6};

#### **cfgFunctionBasicPackageBehaviour BEHAVIOUR**

##### **DEFINED AS**

" This Managed Object Class represents CGF functionality. For more information about the CGF, see 3GPP TS 23.002";

### **5.1.7 mgwFunction**

#### **mgwFunction MANAGED OBJECT CLASS**

DERIVED FROM "3GPP TS 32.106-7: 6.2001": managedFunction;

##### **CHARACTERIZED BY**

mgwFunctionBasicPackage PACKAGE

**BEHAVIOUR mgwFunctionBasicPackageBehaviour;**

##### **ATTRIBUTES**

mgwFunctionId GET;;;

REGISTERED AS {ts32-621ObjectClass 7};

#### **mgwFunctionBasicPackageBehaviour BEHAVIOUR**

##### **DEFINED AS**

" This Managed Object Class represents MGW functionality. For more information about the MGW, see 3GPP TS 23.002";

### **5.1.8 gmscFunction**

#### **gmscFunction MANAGED OBJECT CLASS**

DERIVED FROM "3GPP TS 32.106-7: 6.2001": managedFunction;

##### **CHARACTERIZED BY**

scfFunctionBasicPackage PACKAGE

**BEHAVIOUR gmscFunctionBasicPackageBehaviour;**

##### **ATTRIBUTES**

gmscFunctionId GET;;;

REGISTERED AS {ts32-621ObjectClass 8};

#### **gmscFunctionBasicPackageBehaviour BEHAVIOUR**

##### **DEFINED AS**

" This Managed Object Class represents gmsc functionality. For more information about the gmsc, see 3GPP TS 23.002";

### **5.1.9 iwfFunction**

#### **iwfFunction MANAGED OBJECT CLASS**

DERIVED FROM "3GPP TS 32.106-7: 6.2001": managedFunction;

CHARACTERIZED BY  
 scfFunctionBasicPackage PACKAGE  
**BEHAVIOUR iwfFunctionBasicPackageBehaviour;**  
 ATTRIBUTES  
 iwfFunctionId GET;;;  
 REGISTERED AS {ts32-621ObjectClass 9};

#### **iwfFunctionBasicPackageBehaviour BEHAVIOUR**

DEFINED AS

" This Managed Object Class represents IWF functionality. For more information about the IWF, see 3GPP TS 23.002";

### 5.1.10 mnpSrfFunction

**mnpSrfFunction** MANAGED OBJECT CLASS  
 DERIVED FROM "3GPP TS 32.106-7: 6.2001": managedFunction;  
 CHARACTERIZED BY  
 scfFunctionBasicPackage PACKAGE  
**BEHAVIOUR mnpSrfFunctionBasicPackageBehaviour;**  
 ATTRIBUTES  
 mnpSrfFunctionId GET;;;  
 REGISTERED AS {ts32-621ObjectClass 10};

#### **mnpSrfFunctionBasicPackageBehaviour BEHAVIOUR**

DEFINED AS

" This Managed Object Class represents MNPSRF functionality. For more information about the MNPSRF, see 3GPP TS 23.002";

### 5.1.11 npdbFunction

**npdbFunction** MANAGED OBJECT CLASS  
 DERIVED FROM "3GPP TS 32.106-7: 6.2001": managedFunction;  
 CHARACTERIZED BY  
 scfFunctionBasicPackage PACKAGE  
**BEHAVIOUR npdbFunctionBasicPackageBehaviour;**  
 ATTRIBUTES  
 npdbFunctionId GET;;;  
 REGISTERED AS {ts32-621ObjectClass 11};

#### **npdbFunctionBasicPackageBehaviour BEHAVIOUR**

DEFINED AS

" This Managed Object Class represents NPDB functionality. For more information about the NPDB, see 3GPP TS 23.002";

### 5.1.12 rSgwFunction

#### **rSgwFunction** MANAGED OBJECT CLASS

DERIVED FROM “3GPP TS 32.106-7: 6.2001”: managedFunction;

CHARACTERIZED BY

scfFunctionBasicPackage PACKAGE

BEHAVIOUR **rSgwFunctionBasicPackageBehaviour**;

ATTRIBUTES

rSgwFunctionId GET;::

REGISTERED AS {ts32-621ObjectClass 12};

#### **rSgwFunctionBasicPackageBehaviour** BEHAVIOUR

DEFINED AS

“This Managed Object Class represents R-SGW functionality. For more information about the R-SGW, see 3GPP TS 23.002”;

### 5.1.13 ssfFunction

#### **ssfFunction** MANAGED OBJECT CLASS

DERIVED FROM “3GPP TS 32.106-7: 6.2001”: managedFunction;

CHARACTERIZED BY

scfFunctionBasicPackage PACKAGE

BEHAVIOUR **ssfFunctionBasicPackageBehaviour**;

ATTRIBUTES

ssfFunctionId GET;::

REGISTERED AS {ts32-621ObjectClass 13};

#### **ssfFunctionBasicPackageBehaviour** BEHAVIOUR

DEFINED AS

“This Managed Object Class represents SSF functionality. For more information about the SSF, see 3GPP TS 23.002”;

### 5.1.14 bsFunction

#### **bsFunction** MANAGED OBJECT CLASS

DERIVED FROM “3GPP TS 32.106-7: 6.2001”: managedFunction;

CHARACTERIZED BY

scfFunctionBasicPackage PACKAGE

BEHAVIOUR **bsFunctionBasicPackageBehaviour**;

ATTRIBUTES

bsFunctionId GET;::

REGISTERED AS {ts32-621ObjectClass 14};

#### **bsFunctionBasicPackageBehaviour** BEHAVIOUR

DEFINED AS

" This Managed Object Class represents BS functionality. For more information about the BS, see 3GPP TS 23.002";

## 5.2 Attributes

### 5.2.1 smlcFunctionId

#### **smlcFunctionId** ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
     smlcFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 1};

#### **smlcFunctionIdBehaviour** BEHAVIOUR

DEFINED AS

" This attribute identifies a smlcFunction instance. ";

### 5.2.2 gmlcFunctionId

#### **gmlcFunctionId** ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
     gmlcFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 2};

#### **gmlcFunctionIdBehaviour** BEHAVIOUR

DEFINED AS

" This attribute identifies a gmlcFunction instance. ";

### 5.2.3 sfcFunctionId

#### **sfcFunctionId** ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
     sfcFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 3};

#### **sfcFunctionIdBehaviour** BEHAVIOUR

DEFINED AS

" This attribute identifies a sfcFunction instance. ";

## 5.2.4 srfFunctionId

### **srfFunctionId** ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
   srfFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 4};

### **srfFunctionIdBehaviour** BEHAVIOUR

DEFINED AS

" This attribute identifies a srfFunction instance. ";

## 5.2.5 CbcFunctionId

### **CbcFunctionId** ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
   CbcFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 5};

### **CbcFunctionIdBehaviour** BEHAVIOUR

DEFINED AS

" This attribute identifies a CbcFunction instance. ";

## 5.2.6 CgfFunctionId

### **CgfFunctionId** ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
   CgfFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 6};

### **CgfFunctionIdBehaviour** BEHAVIOUR

DEFINED AS

" This attribute identifies a CgfFunction instance. ";

## 5.2.7 mgwFunctionId

### **mgwFunctionId** ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
   mgwFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 7};

**mgwFunctionIdBehaviour BEHAVIOUR**

DEFINED AS

" This attribute identifies a mgwFunction instance.";

**5.2.8 gmscFunctionId****gmscFunctionId ATTRIBUTE**

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

gmscFunctionIdBehaviour;

REGISTERED AS {ts32-621Attribute 8};

**gmscFunctionIdBehaviour BEHAVIOUR**

DEFINED AS

" This attribute identifies a gmscFunction instance.";

**5.2.9 iwfFunctionId****iwfFunctionId ATTRIBUTE**

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

iwfFunctionIdBehaviour;

REGISTERED AS {ts32-621Attribute 9};

**iwfFunctionIdBehaviour BEHAVIOUR**

DEFINED AS

" This attribute identifies a iwfFunction instance.";

**5.2.10 mnpSrfFunctionId****mnpSrfFunctionId ATTRIBUTE**

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

mnpSrfFunctionIdBehaviour;

REGISTERED AS {ts32-621Attribute 10};

**mnpSrfFunctionIdBehaviour BEHAVIOUR**

DEFINED AS

" This attribute identifies a mnpSrfFunction instance.";

**5.2.11 npdbFunctionId****npdbFunctionId ATTRIBUTE**

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
   npdbFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 11};

#### **npdbFunctionIdBehaviour BEHAVIOUR**

DEFINED AS

  " This attribute identifies a npdbFunction instance.";

### 5.2.12 rSgwFunctionId

#### **rSgwFunctionId ATTRIBUTE**

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
   rSgwFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 12};

#### **rSgwFunctionIdBehaviour BEHAVIOUR**

DEFINED AS

  " This attribute identifies a rSgwFunction instance.";

### 5.2.13 ssfFunctionId

#### **ssfFunctionId ATTRIBUTE**

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
   ssfFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 13};

#### **ssfFunctionIdBehaviour BEHAVIOUR**

DEFINED AS

  " This attribute identifies a ssfFunction instance.";

### 5.2.14 bsFunctionId

#### **bsFunctionId ATTRIBUTE**

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
   bsFunctionIdBehaviour;  
 REGISTERED AS {ts32-621Attribute 14};

#### **bsFunctionIdBehaviour BEHAVIOUR**

DEFINED AS

" This attribute identifies a bsFunction instance.";

## 5.3 Name Binding

### 5.3.1 smlcFunction - managedElement

#### **smlcFunction-managedElement** NAME BINDING

SUBORDINATE OBJECT CLASS rncFunction;

NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;

WITH ATTRIBUTE smlcFunctionId;

BEHAVIOUR

smlcFunction-managedElementBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-621NameBinding 1};

#### **smlcFunction-managedElementBehaviour** BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls a smlcFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

### 5.3.2 gmlcFunction - managedElement

#### **gmlcFunction-managedElement** NAME BINDING

SUBORDINATE OBJECT CLASS rncFunction;

NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;

WITH ATTRIBUTE gmlcFunctionId;

BEHAVIOUR

gmlcFunction-managedElementBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-621NameBinding 2};

#### **gmlcFunction-managedElementBehaviour** BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls a gmlcFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

### 5.3.3 sfcFunction - managedElement

#### **sfcFunction-managedElement** NAME BINDING

SUBORDINATE OBJECT CLASS rncFunction;

NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;

WITH ATTRIBUTE sfcFunctionId;

BEHAVIOUR

sfcFunction-managedElementBehaviour;  
 CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
 DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
 REGISTERED AS {ts32-621NameBinding 3};

#### **sfcFunction-managedElementBehaviour BEHAVIOUR**

##### DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls a sfcFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

### 5.3.4 srfFunction - managedElement

#### **srfFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;  
 NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;  
 WITH ATTRIBUTE srfFunctionId;  
 BEHAVIOUR  
   srfFunction-managedElementBehaviour;  
 CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
 DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
 REGISTERED AS {ts32-621NameBinding 4};

#### **srfFunction-managedElementBehaviour BEHAVIOUR**

##### DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls a srfFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

### 5.3.5 cbcFunction - managedElement

#### **cbcFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;  
 NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;  
 WITH ATTRIBUTE cbcFunctionId;  
 BEHAVIOUR  
   cbcFunction-managedElementBehaviour;  
 CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
 DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
 REGISTERED AS {ts32-621NameBinding 5};

#### **cbcFunction-managedElementBehaviour BEHAVIOUR**

##### DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls a cbcFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

### 5.3.6 cfgFunction - managedElement

#### **cfgFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;  
 NAMED BY SUPERIOR OBJECT CLASS “3GPP TS 32.620-4: 6.2001”: managedElement;  
 WITH ATTRIBUTE cfgFunctionId;  
 BEHAVIOUR  
   cfgFunction-managedElementBehaviour;  
 CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
 DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
 REGISTERED AS {ts32-621NameBinding 6};

#### **cfgFunction-managedElementBehaviour BEHAVIOUR**

DEFINED AS

“The name binding represents a relationship in which a managedElement contains and controls a cfgFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.”;

### 5.3.7 mgwFunction - managedElement

#### **mgwFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;  
 NAMED BY SUPERIOR OBJECT CLASS “3GPP TS 32.620-4: 6.2001”: managedElement;  
 WITH ATTRIBUTE mgwFunctionId;  
 BEHAVIOUR  
   mgwFunction-managedElementBehaviour;  
 CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
 DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
 REGISTERED AS {ts32-621NameBinding 7};

#### **mgwFunction-managedElementBehaviour BEHAVIOUR**

DEFINED AS

“The name binding represents a relationship in which a managedElement contains and controls a mgwFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.”;

### 5.3.8 gmscFunction - managedElement

#### **gmscFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;  
 NAMED BY SUPERIOR OBJECT CLASS “3GPP TS 32.620-4: 6.2001”: managedElement;  
 WITH ATTRIBUTE gmscFunctionId;  
 BEHAVIOUR  
   gmscFunction-managedElementBehaviour;  
 CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
 DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
 REGISTERED AS {ts32-621NameBinding 8};

**gmscFunction-managedElementBehaviour BEHAVIOUR****DEFINED AS**

"The name binding represents a relationship in which a managedElement contains and controls a gmscFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

**5.3.9 iwfFunction - managedElement****iwfFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;

NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;

WITH ATTRIBUTE iwfFunctionId;

**BEHAVIOUR**

    iwfFunction-managedElementBehaviour;

    CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

    DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-621NameBinding 9};

**iwfFunction-managedElementBehaviour BEHAVIOUR****DEFINED AS**

"The name binding represents a relationship in which a managedElement contains and controls a iwfFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

**5.3.10 mnpSrfFunction - managedElement****mnpSrfFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;

NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;

WITH ATTRIBUTE mnpSrfFunctionId;

**BEHAVIOUR**

    mnpSrfFunction-managedElementBehaviour;

    CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

    DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-621NameBinding 10};

**mnpSrfFunction-managedElementBehaviour BEHAVIOUR****DEFINED AS**

"The name binding represents a relationship in which a managedElement contains and controls a mnpSrfFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

**5.3.11 npdbFunction - managedElement****npdbFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;

NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;

WITH ATTRIBUTE npdbFunctionId;

**BEHAVIOUR**

npdbFunction-managedElementBehaviour;  
 CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
 DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
 REGISTERED AS {ts32-621NameBinding 11};

**npdbFunction-managedElementBehaviour BEHAVIOUR****DEFINED AS**

"The name binding represents a relationship in which a managedElement contains and controls a npdbFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

**5.3.12 rSgwFunction - managedElement****rSgwFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;  
 NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;  
 WITH ATTRIBUTE rSgwFunctionId;  
**BEHAVIOUR**  
 rSgwFunction-managedElementBehaviour;  
 CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
 DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
 REGISTERED AS {ts32-621NameBinding 12};

**rSgwFunction-managedElementBehaviour BEHAVIOUR****DEFINED AS**

"The name binding represents a relationship in which a managedElement contains and controls a rSgwFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

**5.3.13 ssfFunction - managedElement****ssfFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;  
 NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;  
 WITH ATTRIBUTE ssfFunctionId;  
**BEHAVIOUR**  
 ssfFunction-managedElementBehaviour;  
 CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
 DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
 REGISTERED AS {ts32-621NameBinding 13};

**ssfFunction-managedElementBehaviour BEHAVIOUR****DEFINED AS**

"The name binding represents a relationship in which a managedElement contains and controls a ssfFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

### 5.3.14 bsFunction - managedElement

#### **bsFunction-managedElement NAME BINDING**

SUBORDINATE OBJECT CLASS rncFunction;  
NAMED BY SUPERIOR OBJECT CLASS “3GPP TS 32.620-4: 6.2001”: managedElement;  
WITH ATTRIBUTE bsFunctionId;  
BEHAVIOUR  
    bsFunction-managedElementBehaviour;  
CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
DELETE ONLY-IF-NO-CONTAINED-OBJECTS;  
REGISTERED AS {ts32-621NameBinding 14};

#### **bsFunction-managedElementBehaviour BEHAVIOUR**

##### DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls a bsFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

---

## 6 ASN.1 Definitions

TS32-621TypeModule {ccitt (0) identified-organization (4) etsi (0)  
mobileDomain (0) umts-Operation-Maintenance (3) ts-32-621 (621)  
informationModel (0) asn1Module (2) version1 (1)}

DEFINITIONS IMPLICIT TAGS ::=

BEGIN

--EXPORTS everything

--IMPORTS

-- 3GPP TS 32.621-4 related Object Identifiers

baseNodeUMTS OBJECT IDENTIFIER ::= { itu-t(0) identified-organization(4) etsi(0) mobileDomain(0)  
umts-Operation-Maintenance(3)}

ts32-621 OBJECT IDENTIFIER ::= { baseNodeUMTS ts-32-621(621)}

ts32-621InfoModel OBJECT IDENTIFIER ::= { ts32-621 informationModel(0)}

ts32-621ObjectClass OBJECT IDENTIFIER ::= { ts32-621InfoModel managedObjectClass(3)}

ts32-621Package OBJECT IDENTIFIER ::= { ts32-621InfoModel package(4)}

ts32-621Parameter OBJECT IDENTIFIER ::= { ts32-621InfoModel parameter(5)}

ts32-621NameBinding OBJECT IDENTIFIER ::= { ts32-621InfoModel nameBinding(6)}

ts32-621Attribute OBJECT IDENTIFIER ::= { ts32-621InfoModel attribute(7)}

ts32-621Action OBJECT IDENTIFIER ::= { ts32-621InfoModel action(9)}

ts32-621Notification OBJECT IDENTIFIER ::= { ts32-621InfoModel notification(10)}

-- Start of 3gPP SA5 own definitions

END -- of TS32-621TypeModule

---

## Annex A (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New	
Jun 2001	S_12	SP-010283	--	--	Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0	

---

## History

<b>Document history</b>		
V4.0.0	June 2001	Publication