

ETSI TS 132 634 V6.1.0 (2005-03)

Technical Specification

**Digital cellular telecommunications system (Phase 2+);
Universal Mobile Telecommunications System (UMTS);
Telecommunication management;
Configuration Management (CM);
Core network resources Integration Reference Point (IRP):
Common Management Information Protocol (CMIP)
Solution Set (SS)
(3GPP TS 32.634 version 6.1.0 Release 6)**



Reference

RTS/TSGS-0532634v610

Keywords

GSM, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	8
Introduction	8
1 Scope	9
2 References	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Abbreviations	10
4 Basic aspects	10
4.1 Architectural Aspects	10
4.2 Mapping	10
4.2.1 Mapping of Information Object Classes	11
4.2.2 Mapping of Information Object Class Attributes.....	12
4.2.2.1 Attribute Mapping of the IOC <i>MscServerFunction</i>	12
4.2.2.2 Attribute Mapping of the IOC <i>HlrFunction</i>	12
4.2.2.3 Attribute Mapping of the IOC <i>VlrFunction</i>	12
4.2.2.4 Attribute Mapping of the IOC <i>AucFunction</i>	12
4.2.2.5 Attribute Mapping of the IOC <i>EirFunction</i>	12
4.2.2.6 Attribute Mapping of the IOC <i>SmsIwmscFunction</i>	13
4.2.2.7 Attribute Mapping of the IOC <i>SmsGmscFunction</i>	13
4.2.2.8 Attribute Mapping of the IOC <i>SgsnFunction</i>	13
4.2.2.9 Attribute Mapping of the IOC <i>GgsnFunction</i>	13
4.2.2.10 Attribute Mapping of the IOC <i>BgFunction</i>	13
4.2.2.11 Attribute Mapping of the IOC <i>GmscFunction</i>	14
4.2.2.12 Attribute Mapping of the IOC <i>SmlcFunction</i>	14
4.2.2.13 Attribute Mapping of the IOC <i>GmlcFunction</i>	14
4.2.2.14 Attribute Mapping of the IOC <i>ScfFunction</i>	14
4.2.2.15 Attribute Mapping of the IOC <i>SrfFunction</i>	14
4.2.2.16 Attribute Mapping of the IOC <i>CbcFunction</i>	14
4.2.2.17 Attribute Mapping of the IOC <i>CgfFunction</i>	15
4.2.2.18 Attribute Mapping of the IOC <i>ImsMgwFunction</i>	15
4.2.2.19 Attribute Mapping of the IOC <i>GmscServerFunction</i>	15
4.2.2.20 Attribute Mapping of the IOC <i>IwfFunction</i>	15
4.2.2.21 Attribute Mapping of the IOC <i>MnpSrfFunction</i>	15
4.2.2.22 Attribute Mapping of the IOC <i>NpdbFunction</i>	15
4.2.2.23 Attribute Mapping of the IOC <i>SgwFunction</i>	16
4.2.2.24 Attribute Mapping of the IOC <i>SsfFunction</i>	16
4.2.2.25 Attribute Mapping of the IOC <i>BsFunction</i>	16
4.2.2.26 Attribute Mapping of the IOC <i>IucsLink</i>	16
4.2.2.27 Attribute Mapping of the IOC <i>IupsLink</i>	16
4.2.2.28 Attribute Mapping of the IOC <i>IubcLink</i>	16
4.2.2.29 Attribute Mapping of the IOC <i>ALink</i>	17
4.2.2.30 Attribute Mapping of the IOC <i>GbLink</i>	17
4.2.2.31 Attribute Mapping of the IOC <i>CsMgwFunction</i>	17
4.2.2.32 Attribute Mapping of the IOC <i>SescfFunction</i>	17
4.2.2.33 Attribute Mapping of the IOC <i>PscsfFunction</i>	17
4.2.2.34 Attribute Mapping of the IOC <i>IcscfFunction</i>	18
4.2.2.35 Attribute Mapping of the IOC <i>SlfFunction</i>	18
4.2.2.36 Attribute Mapping of the IOC <i>BgcfFunction</i>	18
4.2.2.37 Attribute Mapping of the IOC <i>MrfcFunction</i>	18
4.2.2.38 Attribute Mapping of the IOC <i>AsFunction</i>	18
4.2.2.39 Attribute Mapping of the IOC <i>MgcfcFunction</i>	18

4.2.2.40	Attribute Mapping of the IOC <i>MrfpFunction</i>	19
4.2.3	Mapping of Name Containments	19
-- 5	GDMO Definitions.....	20
-- 5.1	Information Object Classes (IOCs)	20
-- 5.1.1	smlcFunction.....	20
-- 5.1.2	gmlcFunction	20
-- 5.1.3	scfFunction	20
-- 5.1.4	srfFunction	20
-- 5.1.5	cbcFunction.....	21
-- 5.1.6	cgfFunction	21
-- 5.1.7	imsMgwFunction.....	21
-- 5.1.8	gmscFunction.....	21
-- 5.1.9	iwfFunction	22
-- 5.1.10	mnpSrfFunction	22
-- 5.1.11	npdbFunction	22
-- 5.1.12	rSgwFunction.....	23
-- 5.1.13	ssfFunction.....	23
-- 5.1.14	bsFunction.....	23
-- 5.1.15	aucFunction.....	23
-- 5.1.16	bgFunction	24
-- 5.1.17	eirFunction	24
-- 5.1.18	ggsnFunction.....	24
-- 5.1.19	hlrFunction.....	24
-- 5.1.20	mscServerFunction	25
-- 5.1.21	sgsnFunction	25
-- 5.1.22	smsGmscFunction.....	25
-- 5.1.23	smsIwmscFunction	25
-- 5.1.24	vlrFunction.....	26
-- 5.1.25	gbLink.....	26
-- 5.1.26	aLink.....	26
-- 5.1.27	iucsLink	26
-- 5.1.28	iupsLink	27
-- 5.1.29	iubcLink.....	27
-- 5.1.30	csMgwFunction	27
-- 5.1.31	gmscServerFunction	28
-- 5.1.32	scscfFunction	28
-- 5.1.33	pcscfFunction.....	28
-- 5.1.34	icscfFunction.....	28
-- 5.1.35	slfFunction	29
-- 5.1.36	bgcfFunction.....	29
-- 5.1.37	mrfcFunction.....	29
-- 5.1.38	asFunction.....	29
-- 5.1.39	mgcfFunction.....	30
-- 5.1.40	mrfpFunction	30
-- 5.2	Packages.....	30
-- 5.2.1	smlcFunctionBasicPackage	30
-- 5.2.2	gmlcFunctionBasicPackage	30
-- 5.2.3	scfFunctionBasicPackage	31
-- 5.2.4	srfFunctionBasicPackage	31
-- 5.2.5	cbcFunctionBasicPackage	31
-- 5.2.6	cgfFunctionBasicPackage.....	31
-- 5.2.7	imsMgwFunctionBasicPackage.....	31
-- 5.2.8	gmscFunctionBasicPackage.....	32
-- 5.2.9	iwfFunctionBasicPackage.....	32
-- 5.2.10	mnpSrfFunctionBasicPackage	32
-- 5.2.11	npdbFunctionBasicPackage	32
-- 5.2.12	rSgwFunctionBasicPackage.....	32
-- 5.2.13	ssfFunctionBasicPackage.....	33
-- 5.2.14	bsFunctionBasicPackage	33
-- 5.2.15	aucFunctionBasicPackage	33
-- 5.2.16	bgFunctionBasicPackage	33

-- 5.2.17	eirFunctionBasicPackage	33
-- 5.2.18	ggsnFunctionBasicPackage	34
-- 5.2.19	hlrFunctionBasicPackage.....	34
-- 5.2.20	mscServerFunctionBasicPackage	34
-- 5.2.21	mscServerFunctionAssociationPackage	34
-- 5.2.22	sgsnFunctionBasicPackage	34
-- 5.2.23	sgsnFunctionAssociattionPackage	35
-- 5.2.24	smsGmscFunctionBasicPackage.....	35
-- 5.2.25	smsIwmscFunctionBasicPackage	35
-- 5.2.26	vlrFunctionBasicPackage.....	35
-- 5.2.27	gbLinkBasicPackage.....	36
-- 5.2.28	gbLinkAssociationPackage.....	36
-- 5.2.29	aLinkBasicPackage.....	36
-- 5.2.30	aLinkAssociationPackage	36
-- 5.2.31	iucsLinkBasicPackage	36
-- 5.2.32	iucsLinkAssociationPackage	37
-- 5.2.33	iupsLinkBasicPackage	37
-- 5.2.34	iupsLinkAssociationPackage	37
-- 5.2.35	iubcLinkBasicPackage.....	37
-- 5.2.36	iubcLinkAssociationPackage	37
-- 5.2.37	csMgwFunctionBasicPackage	38
-- 5.2.38	csMgwFunctionAssociationPackage	38
-- 5.2.39	gmscServerFunctionBasicPackage	38
-- 5.2.40	scscfFunctionBasicPackage	38
-- 5.2.41	pcscfFunctionBasicPackage.....	38
-- 5.2.42	icscfFunctionBasicPackage.....	39
-- 5.2.43	slffFunctionBasicPackage	39
-- 5.2.44	bgcfFunctionBasicPackage.....	39
-- 5.2.45	mrfcFunctionBasicPackage.....	39
-- 5.2.46	asFunctionBasicPackage.....	39
-- 5.2.47	mgcfFunctionBasicPackage.....	40
-- 5.2.48	mrfpFunctionBasicPackage	40
-- 5.3	Attributes.....	40
-- 5.3.1	smlcFunctionId	40
-- 5.3.2	gmlcFunctionId.....	40
-- 5.3.3	scfFunctionId	40
-- 5.3.4	srfFunctionId.....	41
-- 5.3.5	cbcFunctionId	41
-- 5.3.6	cgfFunctionId.....	41
-- 5.3.7	imsMgwFunctionId.....	41
-- 5.3.8	gmscFunctionId	41
-- 5.3.9	iwfFunctionId	42
-- 5.3.10	mnpSrfFunctionId.....	42
-- 5.3.11	npdbFunctionId.....	42
-- 5.3.12	rSgwFunctionId	42
-- 5.3.13	ssfFunctionId	43
-- 5.3.14	bsFunctionId	43
-- 5.3.15	aucFunctionId	43
-- 5.3.16	bgFunctionId.....	43
-- 5.3.17	eirFunctionId.....	43
-- 5.3.18	ggsnFunctionId	44
-- 5.3.19	hlrFunctionId	44
-- 5.3.20	mscServerFunctionId	44
-- 5.3.21	vlrFunctionId	44
-- 5.3.22	sgsnFunctionId.....	44
-- 5.3.23	smsGmscFunctionId	45
-- 5.3.24	smsIwmscFunctionId	45
-- 5.3.25	gbLinkId	45
-- 5.3.26	aLinkId.....	45
-- 5.3.27	iucsLinkId.....	45
-- 5.3.28	iupsLinkId.....	46
-- 5.3.29	iubcLinkId.....	46

-- 5.3.30	csMgwFunctionId	46
-- 5.3.31	gmscServerFunctionId	46
-- 5.3.32	mccList	47
-- 5.3.33	mncList	47
-- 5.3.34	lacList	47
-- 5.3.35	sacList	47
-- 5.3.36	uraList	47
-- 5.3.37	gcaList	47
-- 5.3.38	mscId	48
-- 5.3.39	mscServerFunction-GSMcell.....	48
-- 5.3.40	mscServerFunction-ExternalGSMcell	48
-- 5.3.41	mscServerFunction-CsMgwFunction	48
-- 5.3.42	racList	49
-- 5.3.43	sgsnId.....	49
-- 5.3.44	sgsnFunction-GSMcell	49
-- 5.3.45	sgsnFunction-ExternalGSMcell.....	49
-- 5.3.46	connectedBss	49
-- 5.3.47	connectedRnc.....	50
-- 5.3.48	csMgwFunction-MscServerFunction.....	50
-- 5.3.49	csMgwFunction-IucsLink.....	50
-- 5.3.50	csMgwFunction-Alink	50
-- 5.3.51	scscfFunctionId.....	51
-- 5.3.52	pcscfFunctionId	51
-- 5.3.53	icscfFunctionId	51
-- 5.3.54	slfFunctionId.....	51
-- 5.3.55	bgcfFunctionId.....	51
-- 5.3.56	mrfcFunctionId	52
-- 5.3.57	asFunctionId	52
-- 5.3.58	mgcfFunctionId.....	52
-- 5.3.59	mrfpFunctionId	52
-- 5.4	Name Binding	53
-- 5.4.1	smlcFunction - managedElement.....	53
-- 5.4.2	gmlcFunction - managedElement	53
-- 5.4.3	scfFunction - managedElement.....	53
-- 5.4.4	srfFunction - managedElement.....	54
-- 5.4.5	cbcFunction - managedElement.....	54
-- 5.4.6	cgfFunction - managedElement	54
-- 5.4.7	imsMgwFunction - managedElement	54
-- 5.4.8	gmscFunction - managedElement.....	55
-- 5.4.9	iwfFunction - managedElement.....	55
-- 5.4.10	mnpSrfFunction - managedElement	55
-- 5.4.11	npdbFunction - managedElement	56
-- 5.4.12	rSgwFunction - managedElement.....	56
-- 5.4.13	ssfFunction - managedElement.....	56
-- 5.4.14	bsFunction - managedElement.....	57
-- 5.4.15	aucFunction - managedElement.....	57
-- 5.4.16	bgFunction - managedElement	57
-- 5.4.17	eirFunction - managedElement	58
-- 5.4.18	ggsnFunction - managedElement.....	58
-- 5.4.19	hlrFunction - managedElement.....	58
-- 5.4.20	mscServerFunction - managedElement	59
-- 5.4.21	vlrFunction - managedElement.....	59
-- 5.4.22	sgsnFunction - managedElement	59
-- 5.4.23	smsGmscFunction - managedElement.....	59
-- 5.4.24	smsIwmscFunction - managedElement	60
-- 5.4.25	gbLink - managedElement.....	60
-- 5.4.26	aLink - managedElement	60
-- 5.4.27	iucsLink - managedElement	61
-- 5.4.28	iupsLink - managedElement	61
-- 5.4.29	iubcLink - managedElement	61
-- 5.4.30	gmscServerFunction - managedElement	62
-- 5.4.31	csMgwFunction - managedElement	62

-- 5.4.32	scscfFunction - managedElement	62
-- 5.4.33	pcscfFunction - managedElement	63
-- 5.4.34	icscfFunction - managedElement	63
-- 5.4.35	slfFunction - managedElement	63
-- 5.4.36	bgcfFunction - managedElement	64
-- 5.4.37	mrfcFunction - managedElement	64
-- 5.4.38	asFunction - managedElement	64
-- 5.4.39	mgcfFunction - managedElement	64
-- 5.4.40	mrfpFunction - managedElement	65
-- 6	ASN.1 Definitions	65
Annex A (informative):	List of assigned Object Identifiers.....	67
Annex B (informative):	Change history	73
History		74

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project Technical Specification Group Services and System Aspects, Telecommunication management; Configuration Management (CM); as identified below:

- 32.631: "Core network resources Integration Reference Point (IRP): Requirements";
- 32.632: "Core network resources Integration Reference Point (IRP): Network Resource Model (NRM)";
- 32.633: "Core network resources Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)";
- 32.634: "Core network resources Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".**
- 32.635: "Core network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition".

A 3G network is composed of a multitude of different network elements (NE). For a successful operation of the network the operator must be provided with mechanisms allowing him to manage the network. These management activities can be grouped into several areas: configuration management, fault management, performance management, and accounting management and security management.

The present document is part of a set of technical specifications defining the telecommunication management (TM) of 3G systems. The TM principles are described in 3GPP TS 32.101 [1]. The TM architecture is described in 3GPP TS 32.102 [2]. The other specifications define the interface (Itf-N) between the managing system (manager), which is in general the network manager (NM) and the managed system (agent), which is either an element manager (EM) or the managed NE itself. The Itf-N is composed of a number of integration reference points (IRPs) defining the information in the agent that is visible for the manager, the operations that the manager may perform on this information and the notifications that are sent from the agent to the manager. One of these IRPs is the Core Network Resources IRP.

Each IRP is specified by five TS: Requirements, IS, CORBA SS, CMIP SS and the XML file format definition.

1 Scope

The present document specifies the Common Management Information Protocol (CMIP) Solution Set (SS) for the CN Network Resource Integration Reference Point (IRP): Network Resource Model defined in 3GPP TS 32.632 [4]. In detail:

- Clause 4 contains an introduction to some concepts that are the base for some specific aspects of the CMIP interfaces.
- Clause 5 contains the GDMO definitions for the Alarm Management over the CMIP interfaces
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

This Solution Set specification is related to 3GPP TS 32.632 V6.2.X [4].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] Void.
- [4] 3GPP TS 32.632: "Telecommunication management; Configuration Management (CM); Core Network Resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [5] ITU-T Recommendation X.710 (1991): "Common Management Information Service Definition for CCITT Applications".
- [6] ITU-T Recommendation X.721 (02/92): "Information Technology - Open Systems Interconnection – Structure of Management Information: Definition of Management Information".
- [7] ITU-T Recommendation X.730 (01/92): "Information Technology - Open Systems Interconnection – Systems Management: Object Management Function".
- [8] ITU-T Recommendation X.733 (02/92): "Information Technology - Open Systems Interconnection - Alarm Reporting Function".
- [9] ITU-T Recommendation M.3100 (07/95): "Maintenance Telecommunications Management Network – Generic Network Information Model".
- [10] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.600 [10] and 3GPP TS 32.632 [4] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CMIP	Common Management Information Protocol
DN	Distinguished Name
GDMO	Guidelines for the Definition of Managed Objects
IDL	Interface Definition Language
IEC	International Electrotechnical Commission
IOC	Information Object Class
ISO	International Standards Organization
ITU-T	International Telecommunication Union, Telecommunication Sector
MGW	Media GateWay
MIB	Management Information Base
MIM	Management Information Model
MIT	Management Information Tree (or Naming Tree)
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NR	Network Resource
NRM	Network Resource Model
TMN	Telecommunications Management Network
UTRAN	UMTS Terrestrial Radio Access Network

4 Basic aspects

4.1 Architectural Aspects

A technology independent CN network resource model is defined in 3GPP TS 32.632 [4] for 3G networks. This document provides an implementation of this CN network resource model by using CMIP technology.

4.2 Mapping

The semantic of the CN Network Resource Model is defined in 3GPP TS 32.632 [4]. The specification of the information object classes defined there is independent of any implementation technology and protocol. This clause maps these technology and protocol independent definitions onto the equivalencies of the CMIP Solution Set of the UTRAN Network Resource IRP.

4.2.1 Mapping of Information Object Classes

Table 4.1 maps the Information Object Classes (IOCs) defined in the CN Network Resource Model onto the equivalent IOCs of the CMIP Solution Set.

Table 4.1: Mapping of IOCs

IS IOC	CMIP SS MOC
AucFunction	aucFunction
ALink	aLink
IucsLink	iucsLink
IupsLink	iupsLink
IubcLink	iubcLink
BgFunction	bgFunction
EirFunction	eirFunction
GbLink	gbLink
GgsnFunction	ggsnFunction
GmscFunction	gmscFunction
HlrFunction	hlrFunction
MscServerFunction	mscServerFunction
GmscServerFunction	gmscServerFunction
SgsnFunction	sgsnFunction
SmsGmscFunction	smsGmscFunction
SmsIwmscFunction	smsIwmscFunction
VlrFunction	vlrFunction
SmlcFunction	smlcFunction
GmlcFunction	gmlcFunction
ScfFunction	scfFunction
SrfFunction	srfFunction
CbcFunction	cbcFunction
CgfFunction	cgfFunction
CsMgwFunction	csMgwFunction
ImsMgwFunction	imsMgwFunction
GmscFunction	gmscFunction
IwfFunction	iwfFunction
MnpSrfFunction	mnpSrfFunction
NpdbFunction	npdbFunction
SgwFunction	rSgwFunction
SsfFunction	ssfFunction
BsFunction	bsFunction
ScscfFunction	scscfFunction
PcscfFunction	pcscfFunction
IcscfFunction	icscfFunction
SlfFunction	slfFunction
BgcfFunction	bgcfFunction
MrfcFunction	mrfcFunction
AsFunction	asFunction
MqcfFunction	mqcfFunction
MrfpFunction	mrfpFunction

4.2.2 Mapping of Information Object Class Attributes

4.2.2.1 Attribute Mapping of the IOC *MscServerFunction*

Attribute mapping of the IOC *MscServerFunction*

IS Attribute	CMIP SS Attributes	Support Qualifier	Read Qualifier	Write Qualifier
mscServerFunctionId	mscServerFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
mccList	mccList	M	M	M
mncList	mncList	M	M	M
lacList	lacList	M	M	M
sacList	sacList	M	M	M
gcaList	gcaList	M	M	M
mscId	mscId	M	M	M
mscServerFunction-GsmCell	mscServerFunction-GSMcell	M	M	--
mscServerFunction-ExternalGsmCell	mscServerFunction-ExternalGSMcell	M	M	--
mscServerFunction-CsMgwFunction	mscServerFunction-CsMgwFunction	M	M	--

4.2.2.2 Attribute Mapping of the IOC *HlrFunction*

Attribute mapping of the IOC *HlrFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
hlrFunctionId	hlrFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.3 Attribute Mapping of the IOC *VlrFunction*

Attribute mapping of the IOC *VlrFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
vlrFunctionId	vlrFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.4 Attribute Mapping of the IOC *AucFunction*

Attribute mapping of the IOC *AucFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
aucFunctionId	aucFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.5 Attribute Mapping of the IOC *EirFunction*

Attribute mapping of the IOC *EirFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
eirFunctionId	eirFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.6 Attribute Mapping of the IOC *SmslwmscFunction***Attribute mapping of the IOC *SmslwmscFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
smslwmscFunctionId	smslwmscFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.7 Attribute Mapping of the IOC *SmsGmscFunction***Attribute mapping of the IOC *SmsGmscFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
smsGmscFunctionId	smsGmscFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.8 Attribute Mapping of the IOC *SgsnFunction***Attribute mapping of the IOC *SgsnFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
sgsnFunctionId	sgsnFunctionId	M	M	--
UserLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
mccList	mccList	M	M	M
mncList	mncList	M	M	M
lacList	lacList	M	M	M
racList	racList	M	M	M
sacList	sacList	M	M	M
sgsnId	sgsnId	M	M	M
sgsnFunction-GSMCell	sgsnFunction-GSMCell	M	M	--
sgsnFunction-ExternalGSMCell	sgsnFunction-ExternalGSMCell	M	M	--

4.2.2.9 Attribute Mapping of the IOC *GgsnFunction***Attribute mapping of the IOC *GgsnFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
ggsnFunctionId	ggsnFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.10 Attribute Mapping of the IOC *BgFunction***Attribute mapping of the IOC *BgFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
bgFunctionId	bgFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.11 Attribute Mapping of the IOC *GmscFunction***Attribute mapping of the IOC *GmscFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
gmscFunctionId	gmscFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.12 Attribute Mapping of the IOC *SmlcFunction***Attribute mapping of the IOC *SmlcFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
smlcFunctionId	smlcFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.13 Attribute Mapping of the IOC *GmlcFunction***Attribute mapping of the IOC *GmlcFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
gmlcFunctionId	gmlcFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.14 Attribute Mapping of the IOC *ScfFunction***Attribute mapping of the IOC *ScfFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
scfFunctionId	scfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.15 Attribute Mapping of the IOC *SrfFunction***Attribute mapping of the IOC *SrfFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
srfFunctionId	srfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.16 Attribute Mapping of the IOC *CbcFunction***Attribute mapping of the IOC *CbcFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
cbcFunctionId	cbcFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.17 Attribute Mapping of the IOC *CgfFunction***Attribute mapping of the IOC *CgfFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
cgfFunctionId	cgfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.18 Attribute Mapping of the IOC *ImsMgwFunction***Attribute mapping of the IOC *ImsMgwFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
imsMgwFunctionId	imsMgwFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.19 Attribute Mapping of the IOC *GmscServerFunction***Attribute mapping of the IOC *GmscServerFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
gmscServerFunctionId	gmscServerFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.20 Attribute Mapping of the IOC *IwfFunction***Attribute mapping of the IOC *IwfFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
iwfFunctionId	iwfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.21 Attribute Mapping of the IOC *MnpSrfFunction***Attribute mapping of the IOC *MnpSrfFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
mnpSrfFunctionId	mnpSrfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.22 Attribute Mapping of the IOC *NpdbFunction***Attribute mapping of the IOC *NpdbFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
npdbFunctionId	npdbFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.23 Attribute Mapping of the IOC *SgwFunction*Attribute mapping of the IOC *SgwFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
sgwFunctionId	sgwFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.24 Attribute Mapping of the IOC *SsfFunction*Attribute mapping of the IOC *SsfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
ssfFunctionId	ssfFunctionId	M	M	--
userLabel	UserLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.25 Attribute Mapping of the IOC *BsFunction*Attribute mapping of the IOC *BsFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
bsFunctionId	bsFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.26 Attribute Mapping of the IOC *IucsLink*Attribute mapping of the IOC *IucsLink*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
iucsLinkId	iucsLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedRnc	connectedRnc	M	M	--
connectedBss	connectedBss	M	M	--

4.2.2.27 Attribute Mapping of the IOC *IupsLink*Attribute mapping of the IOC *IupsLink*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
iupsLinkId	iupsLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedRnc	connectedRnc	O	M	--
connectedBss	connectedBss	O	M	--

4.2.2.28 Attribute Mapping of the IOC *IubcLink*Attribute mapping of the IOC *IubcLink*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
iubcLinkId	iubcLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedRnc	connectedRnc	M	M	--

4.2.2.29 Attribute Mapping of the IOC *ALink***Attribute mapping of the IOC *ALink***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
aLinkId	aLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedBss	connectedBss	M	M	--

4.2.2.30 Attribute Mapping of the IOC *GbLink***Attribute mapping of the IOC *GbLink***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
gbLinkId	gbLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedBss	connectedBss	M	M	--

4.2.2.31 Attribute Mapping of the IOC *CsMgwFunction***Attribute mapping of the IOC *CsMgwFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
csMgwFunctionId	CsmgwFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
csMgwFunction-MscServerFunction	csMgwFunction-mscServerFunction	M	M	--
csMgwFunction-IucsLink	csMgwFunction-iucsLink	M	M	--
csMgwFunction-ALink	csMgwFunction-ALink	M	M	--

4.2.2.32 Attribute Mapping of the IOC *ScscfFunction***Attribute mapping of the IOC *ScscfFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
scscfFunctionId	ScscfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.33 Attribute Mapping of the IOC *PcscfFunction***Attribute mapping of the IOC *PcscfFunction***

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
pcscfFunctionId	pcscfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.34 Attribute Mapping of the IOC *IcscfFunction*Attribute mapping of the IOC *IcscfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
icscfFunctionId	icscfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.35 Attribute Mapping of the IOC *SlfFunction*Attribute mapping of the IOC *SlfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
slfFunctionId	slfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.36 Attribute Mapping of the IOC *BgcfFunction*Attribute mapping of the IOC *BgcfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
bgcfFunctionId	bgcfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.37 Attribute Mapping of the IOC *MrfcFunction*Attribute mapping of the IOC *MrfcFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
mrfcFunctionId	mrfcFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.38 Attribute Mapping of the IOC *AsFunction*Attribute mapping of the IOC *AsFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
asFunctionId	asFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.39 Attribute Mapping of the IOC *MgcfFunction*Attribute mapping of the IOC *MgcfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
mgcfFunctionId	mgcfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.40 Attribute Mapping of the IOC *MrfpFunction*Attribute mapping of the IOC *MrfpFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
mrfpFunctionId	mrfpFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.3 Mapping of Name Containments

Mapping of name containments

IS Name Containment	CMIP SS Name Binding
smlcFunction - managedElement	smlcFunction-managedElement
gmlcFunction - managedElement	gmlcFunction-managedElement
scfFunction - managedElement	scfFunction-managedElement
srffFunction - managedElement	srffFunction-managedElement
cbcFunction - managedElement	cbcFunction-managedElement
cbcFunction - managedElement	cbcFunction-managedElement
cgfFunction - managedElement	cgfFunction-managedElement
imsMgwFunction - managedElement	imsMgwFunction-managedElement
gmscFunction - managedElement	gmscFunction-managedElement
iwfFunction - managedElement	iwfFunction-managedElement
mnpSrfFunction - managedElement	mnpSrfFunction-managedElement
npdbFunction - managedElement	npdbFunction-managedElement
rSgwFunction - managedElement	rSgwFunction-managedElement
ssfFunction - managedElement	ssfFunction-managedElement
bsFunction - managedElement	bsFunction-managedElement
bsFunction - managedElement	bsFunction-managedElement
bsFunction - managedElement	bsFunction-managedElement
aucFunction - managedElement	aucFunction-managedElement
bgFunction - managedElement	bgFunction-managedElement
eirFunction - managedElement	eirFunction-managedElement
ggsnFunction - managedElement	ggsnFunction-managedElement
hlrFunction - managedElement	hlrFunction-managedElement
mscServerFunction - managedElement	mscServerFunction-managedElement
vlrFunction - managedElement	vlrFunction-managedElement
sgsnFunction - managedElement	sgsnFunction-managedElement
smsGmscFunction - managedElement	smsGmscFunction-managedElement
smsIwmscFunction - managedElement	smsIwmscFunction-managedElement
gbLink - managedElement	gbLink-managedElement
aLink - managedElement	aLink-managedElement
iucsLink - managedElement	iucsLink-managedElement
iupsLink - managedElement	iupsLink-managedElement
iubcLink - managedElement	iubcLink-managedElement
gmscServerFunction - managedElement	gmscServerFunction-managedElement
csMgwFunction - managedElement	csMgwFunction-managedElement
scscfFunction - managedElement	scscfFunction-managedElement
pcscfFunction - managedElement	pcscfFunction-managedElement
icscfFunction - managedElement	icscfFunction-managedElement
slfFunction - managedElement	slfFunction-managedElement
bgcfFunction - managedElement	bgcfFunction-managedElement
mrfcFunction - managedElement	mrfcFunction-managedElement
asFunction - managedElement	asFunction-managedElement
mgcfFunction - managedElement	mgcfFunction-managedElement
mrfpFunction - managedElement	mrfpFunction-managedElement

-- 5 GDMO Definitions

-- 5.1 Information Object Classes (IOCs)

-- 5.1.1 smlcFunction

```
smlcFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  smlcFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
  PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
    ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
    is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 1};
```

-- 5.1.2 gmlcFunction

```
gmlcFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  gmlcFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
  PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
    ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
    is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 2};
```

-- 5.1.3 scfFunction

```
scfFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  scfFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
  PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
    ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
    is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 3};
```

-- 5.1.4 srfFunction

```
srfFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
```

```

srfFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
  "the objectCreation and the objectDeletion notifications defined in
  ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
  "the attributeValueChange notification defined in ITU-T Rec. X.721
  is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 4};

```

-- 5.1.5 cbcFunction

```

cbcFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  cbcFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
  "the objectCreation and the objectDeletion notifications defined in
  ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
  "the attributeValueChange notification defined in ITU-T Rec. X.721
  is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 5};

```

-- 5.1.6 cgfFunction

```

cgfFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  cgfFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
  "the objectCreation and the objectDeletion notifications defined in
  ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
  "the attributeValueChange notification defined in ITU-T Rec. X.721
  is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 6};

```

-- 5.1.7 imsMgwFunction

```

imsMgwFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  imsMgwFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
  "the objectCreation and the objectDeletion notifications defined in
  ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
  "the attributeValueChange notification defined in ITU-T Rec. X.721
  is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 70503};

```

-- 5.1.8 gmscFunction

```

gmscFunction MANAGED OBJECT CLASS

```

```

DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
gmscFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 8};

```

-- 5.1.9 iwFunction

```

iwFunction MANAGED OBJECT CLASS
DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
iwFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 9};

```

-- 5.1.10 mnpSrfFunction

```

mnpSrfFunction MANAGED OBJECT CLASS
DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
mnpSrfFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 10};

```

-- 5.1.11 npdbFunction

```

npdbFunction MANAGED OBJECT CLASS
DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
npdbFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 11};

```

-- 5.1.12 rSgwFunction

```

rSgwFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  rSgwFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 12};

```

-- 5.1.13 ssfFunction

```

ssfFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  ssfFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 13};

```

-- 5.1.14 bsFunction

```

bsFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  bsFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 14};

```

-- 5.1.15 aucFunction

```

aucFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  aucFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721

```


is supported by an instance of this class."
REGISTERED AS {ts32-634ObjectClass 15};

-- 5.1.16 bgFunction

bgFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 bgFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class."
REGISTERED AS {ts32-634ObjectClass 16};

-- 5.1.17 eirFunction

eirFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 eirFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class."
REGISTERED AS {ts32-634ObjectClass 17};

-- 5.1.18 ggsnFunction

ggsnFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 ggsnFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class."
REGISTERED AS {ts32-634ObjectClass 18};

-- 5.1.19 hlrFunction

hlrFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 hlrFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",

```

"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
    is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 19};

```

-- 5.1.20 mscServerFunction

```

mscServerFunction MANAGED OBJECT CLASS
  DERIVED FROM
    "3GPP TS 32.624": managedFunction;
  CHARACTERIZED BY
    mscServerFunctionBasicPackage,
    mscServerFunctionAssociationPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
  CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
      PRESENT IF
        "the objectCreation and the objectDeletion notifications defined in
        ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
      PRESENT IF
        "the attributeValueChange notification defined in ITU-T Rec. X.721
        is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 20};

```

-- 5.1.21 sgsnFunction

```

sgsnFunction MANAGED OBJECT CLASS
  DERIVED FROM
    "3GPP TS 32.624": managedFunction;
  CHARACTERIZED BY
    sgsnFunctionBasicPackage,
    sgsnFunctionAssociationPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
  CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
      PRESENT IF
        "the objectCreation and the objectDeletion notifications defined in
        ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
      PRESENT IF
        "the attributeValueChange notification defined in ITU-T Rec. X.721
        is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 21};

```

-- 5.1.22 smsGmscFunction

```

smsGmscFunction MANAGED OBJECT CLASS
  DERIVED FROM
    "3GPP TS 32.624": managedFunction;
  CHARACTERIZED BY
    smsGmscFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
  CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
      PRESENT IF
        "the objectCreation and the objectDeletion notifications defined in
        ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
      PRESENT IF
        "the attributeValueChange notification defined in ITU-T Rec. X.721
        is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 22};

```

-- 5.1.23 smsIwmscFunction

```

smsIwmscFunction MANAGED OBJECT CLASS
  DERIVED FROM
    "3GPP TS 32.624": managedFunction;
  CHARACTERIZED BY
    smsIwmscFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;

```

CONDITIONAL PACKAGES

"Rec. M.3100: 1995":createDeleteNotificationsPackage

PRESENT IF

"the objectCreation and the objectDeletion notifications defined in ITU-T Rec. X.721 are supported by an instance of this class.",

"Rec. M.3100: 1995":attributeValueChangeNotificationPackage

PRESENT IF

"the attributeValueChange notification defined in ITU-T Rec. X.721 is supported by an instance of this class.";

REGISTERED AS {ts32-634ObjectClass 23};

-- 5.1.24 vlrFunction

vlrFunction **MANAGED OBJECT CLASS**

DERIVED FROM

"3GPP TS 32.624": managedFunction;

CHARACTERIZED BY

vlrFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;

CONDITIONAL PACKAGES

"Rec. M.3100: 1995":createDeleteNotificationsPackage

PRESENT IF

"the objectCreation and the objectDeletion notifications defined in ITU-T Rec. X.721 are supported by an instance of this class.",

"Rec. M.3100: 1995":attributeValueChangeNotificationPackage

PRESENT IF

"the attributeValueChange notification defined in ITU-T Rec. X.721 is supported by an instance of this class.";

REGISTERED AS {ts32-634ObjectClass 24};

-- 5.1.25 gbLink

gbLink **MANAGED OBJECT CLASS**

DERIVED FROM

"3GPP TS 32.624": managedFunction;

CHARACTERIZED BY

gbLinkBasicPackage,
gbLinkAssociationPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;

CONDITIONAL PACKAGES

"Rec. M.3100: 1995":createDeleteNotificationsPackage

PRESENT IF

"the objectCreation and the objectDeletion notifications defined in ITU-T Rec. X.721 are supported by an instance of this class.",

"Rec. M.3100: 1995":attributeValueChangeNotificationPackage

PRESENT IF

"the attributeValueChange notification defined in ITU-T Rec. X.721 is supported by an instance of this class.";

REGISTERED AS {ts32-634ObjectClass 25};

-- 5.1.26 aLink

aLink **MANAGED OBJECT CLASS**

DERIVED FROM

"3GPP TS 32.624": managedFunction;

CHARACTERIZED BY

aLinkBasicPackage,
aLinkAssociationPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;

CONDITIONAL PACKAGES

"Rec. M.3100: 1995":createDeleteNotificationsPackage

PRESENT IF

"the objectCreation and the objectDeletion notifications defined in ITU-T Rec. X.721 are supported by an instance of this class.",

"Rec. M.3100: 1995":attributeValueChangeNotificationPackage

PRESENT IF

"the attributeValueChange notification defined in ITU-T Rec. X.721 is supported by an instance of this class.";

REGISTERED AS {ts32-634ObjectClass 26};

-- 5.1.27 iucsLink

iucsLink **MANAGED OBJECT CLASS**

```

DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
iucsLinkBasicPackage,
iucsLinkAssociationPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 27};

```

-- 5.1.28 iupsLink

```

iupsLink MANAGED OBJECT CLASS
DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
iupsLinkBasicPackage,
iupsLinkAssociationPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 28};

```

-- 5.1.29 iubcLink

```

iubcLink MANAGED OBJECT CLASS
DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
iubcLinkBasicPackage,
iubcLinkAssociationPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 29};

```

-- 5.1.30 csMgwFunction

```

csMgwFunction MANAGED OBJECT CLASS
DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
csMgwFunctionBasicPackage,
csMgwFunctionAssociationPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721

```

is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 30};

-- 5.1.31 gmscServerFunction

gmscServerFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 gmscServerFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 31};

-- 5.1.32 scscfFunction

scscfFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 scscfFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 32};

-- 5.1.33 pcscfFunction

pcscfFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 pcscfFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 33};

-- 5.1.34 icscfFunction

icscfFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 icscfFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721

is supported by an instance of this class."
REGISTERED AS {ts32-634ObjectClass 34};

-- 5.1.35 slfFunction

slfFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 slfFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class."
REGISTERED AS {ts32-634ObjectClass 35};

-- 5.1.36 bgcfFunction

bgcfFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 bgcfFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class."
REGISTERED AS {ts32-634ObjectClass 36};

-- 5.1.37 mrfcFunction

mrfcFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 mrfcFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class."
REGISTERED AS {ts32-634ObjectClass 37};

-- 5.1.38 asFunction

asFunction **MANAGED OBJECT CLASS**
DERIVED FROM
 "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
 asFunctionBasicPackage,
 "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
 "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
 "the objectCreation and the objectDeletion notifications defined in
 ITU-T Rec. X.721 are supported by an instance of this class.",
 "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
 "the attributeValueChange notification defined in ITU-T Rec. X.721
 is supported by an instance of this class.";

REGISTERED AS {ts32-634ObjectClass 38};

-- 5.1.39 mgcfFunction

```
mgcfFunction MANAGED OBJECT CLASS
  DERIVED FROM
    "3GPP TS 32.624": managedFunction;
  CHARACTERIZED BY
    mgcfFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
  CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
  PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
    ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
    is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 39};
```

-- 5.1.40 mrfpFunction

```
mrfpFunction MANAGED OBJECT CLASS
  DERIVED FROM
    "3GPP TS 32.624": managedFunction;
  CHARACTERIZED BY
    mrfpFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
  CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
  PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
    ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
    is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 40};
```

-- 5.2 Packages

-- 5.2.1 smlcFunctionBasicPackage

```
smlcFunctionBasicPackage PACKAGE
  BEHAVIOUR
    smlcFunctionBasicPackageBehaviour;
  ATTRIBUTES
    smlcFunctionId GET;
REGISTERED AS {ts32-634Package 1};
```

```
smlcFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'SmlcFunction' Information Object represents the SMLC functionality. For more information
  about the SMLC, see 3GPP TS 23.002";
```

-- 5.2.2 gmlcFunctionBasicPackage

```
gmlcFunctionBasicPackage PACKAGE
  BEHAVIOUR
    gmlcFunctionBasicPackageBehaviour;
  ATTRIBUTES
    gmlcFunctionId GET;
REGISTERED AS {ts32-634Package 2};
```

```
gmlcFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'GmlcFunction' Information Object represents the GMLC functionality. For more information
  about the GMLC, see 3GPP TS 23.002";
```

-- 5.2.3 scfFunctionBasicPackage

```
scfFunctionBasicPackage PACKAGE
  BEHAVIOUR
    scfFunctionBasicPackageBehaviour;
  ATTRIBUTES
    scfFunctionId GET;
REGISTERED AS {ts32-634Package 3};

scfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'ScfFunction' Information Object represents the SCF functionality. For more information
  about the SCF, see 3GPP TS 23.002";
```

-- 5.2.4 srfFunctionBasicPackage

```
srfFunctionBasicPackage PACKAGE
  BEHAVIOUR
    srfFunctionBasicPackageBehaviour;
  ATTRIBUTES
    srfFunctionId GET;
REGISTERED AS {ts32-634Package 4};

srfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'SrfFunction' Information Object represents the SRF functionality. For more information
  about the SRF, see 3GPP TS 23.002";
```

-- 5.2.5 cbcFunctionBasicPackage

```
cbcFunctionBasicPackage PACKAGE
  BEHAVIOUR
    cbcFunctionBasicPackageBehaviour;
  ATTRIBUTES
    cbcFunctionId GET;
REGISTERED AS {ts32-634Package 5};

cbcFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'CbcFunction' Information Object represents the SBC functionality. For more
  information about the SBC, see 3GPP TS 23.002";
```

-- 5.2.6 cgfFunctionBasicPackage

```
cgfFunctionBasicPackage PACKAGE
  BEHAVIOUR
    cgfFunctionBasicPackageBehaviour;
  ATTRIBUTES
    cgfFunctionId GET;
REGISTERED AS {ts32-634Package 6};

cgfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'CgfFunction' Information Object represents the CGF functionality. For more information
  about the CGF, see 3GPP TS 23.002";
```

-- 5.2.7 imsMgwFunctionBasicPackage

```
imsMgwFunctionBasicPackage PACKAGE
  BEHAVIOUR
    imsMgwFunctionBasicPackageBehaviour;
  ATTRIBUTES
    imsMgwFunctionId GET;
REGISTERED AS {ts32-634Package 70503};

imsMgwFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'imsMgwFunction' Information Object represents the IMS-MGW functionality. For more
  information about the IMS-MGW, see 3GPP TS 23.002";
```


-- 5.2.8 gmscFunctionBasicPackage

```
gmscFunctionBasicPackage PACKAGE
  BEHAVIOUR
    gmscFunctionBasicPackageBehaviour;
  ATTRIBUTES
    gmscFunctionId      GET;
REGISTERED AS {ts32-634Package 8};

gmscFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'GmscFunction' Information Object represents the GMSC functionality. For more information
  about the GMSC, see 3GPP TS 23.002";
```

-- 5.2.9 iwfunctionBasicPackage

```
iwfunctionBasicPackage PACKAGE
  BEHAVIOUR
    iwfunctionBasicPackageBehaviour;
  ATTRIBUTES
    iwfunctionId      GET;
REGISTERED AS {ts32-634Package 9};

iwfunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'Iwfunction' Information Object represents the IWF functionality. For more information
  about the IWF, see 3GPP TS 23.002";
```

-- 5.2.10 mnpSrfFunctionBasicPackage

```
mnpSrfFunctionBasicPackage PACKAGE
  BEHAVIOUR
    mnpSrfFunctionBasicPackageBehaviour;
  ATTRIBUTES
    mnpSrfFunctionId  GET;
REGISTERED AS {ts32-634Package 10};

mnpSrfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'MnpSrfFunction' Information Object represents the MNPSRF functionality. For more
  information about the MNPSRF, see 3GPP TS 23.002";
```

-- 5.2.11 npdbFunctionBasicPackage

```
npdbFunctionBasicPackage PACKAGE
  BEHAVIOUR
    npdbFunctionBasicPackageBehaviour;
  ATTRIBUTES
    npdbFunctionId  GET;
REGISTERED AS {ts32-634Package 11};

npdbFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'NpdbFunction' Information Object represents the NPDB functionality. For more information
  about the NPDB, see 3GPP TS 23.002";
```

-- 5.2.12 rSgwFunctionBasicPackage

```
rSgwFunctionBasicPackage PACKAGE
  BEHAVIOUR
    rSgwFunctionBasicPackageBehaviour;
  ATTRIBUTES
    rSgwFunctionId  GET;
REGISTERED AS {ts32-634Package 12};

rSgwFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'RSgwFunction' Information Object represents the R-SGW functionality. For more information
  about the R-SGW, see 3GPP TS 23.002";
```

-- 5.2.13 ssfFunctionBasicPackage

ssfFunctionBasicPackage **PACKAGE**

BEHAVIOUR

ssfFunctionBasicPackageBehaviour;

ATTRIBUTES

ssfFunctionId GET;

REGISTERED AS {ts32-634Package 13};

ssfFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'SsfFunction' Information Object represents the SSF functionality. For more information about the SSF, see 3GPP TS 23.002";

-- 5.2.14 bsFunctionBasicPackage

bsFunctionBasicPackage **PACKAGE**

BEHAVIOUR

bsFunctionBasicPackageBehaviour;

ATTRIBUTES

bsFunctionId GET;

REGISTERED AS {ts32-634Package 14};

bsFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'BsFunction' Information Object represents the BS functionality. For more information about the BS, see 3GPP TS 23.002";

-- 5.2.15 aucFunctionBasicPackage

aucFunctionBasicPackage **PACKAGE**

BEHAVIOUR

aucFunctionBasicPackageBehaviour;

ATTRIBUTES

aucFunctionId GET;

REGISTERED AS {ts32-634Package 15};

aucFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'aucFunction' Information Object represents the AUC functionality. For more information about the AUC, see 3GPP TS 23.002";

-- 5.2.16 bgFunctionBasicPackage

bgFunctionBasicPackage **PACKAGE**

BEHAVIOUR

bgFunctionBasicPackageBehaviour;

ATTRIBUTES

bgFunctionId GET;

REGISTERED AS {ts32-634Package 16};

bgFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'bgFunction' Information Object represents the BG functionality. For more information about the BG, see 3GPP TS 23.002";

-- 5.2.17 eirFunctionBasicPackage

eirFunctionBasicPackage **PACKAGE**

BEHAVIOUR

eirFunctionBasicPackageBehaviour;

ATTRIBUTES

eirFunctionId GET;

REGISTERED AS {ts32-634Package 17};

eirFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'EirFunction' Information Object represents the EIR functionality. For more information about the EIR, see 3GPP TS 23.002";

-- 5.2.18 ggsnFunctionBasicPackage

```
ggsnFunctionBasicPackage PACKAGE
  BEHAVIOUR
    ggsnFunctionBasicPackageBehaviour;
  ATTRIBUTES
    ggsnFunctionId GET;
REGISTERED AS {ts32-634Package 18};

ggsnFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'GGSNFunction' Information Object represents the GGSN functionality. For more information
  about the GGSN, see 3GPP TS 23.002";
```

-- 5.2.19 hlrFunctionBasicPackage

```
hlrFunctionBasicPackage PACKAGE
  BEHAVIOUR
    hlrFunctionBasicPackageBehaviour;
  ATTRIBUTES
    hlrFunctionId GET;
REGISTERED AS {ts32-634Package 19};

hlrFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'HLRFunction' Information Object represents the HLR functionality. For more information
  about the HLR, see 3GPP TS 23.002";
```

-- 5.2.20 mscServerFunctionBasicPackage

```
mscServerFunctionBasicPackage PACKAGE
  BEHAVIOUR
    mscServerFunctionBasicPackageBehaviour;
  ATTRIBUTES
    mscServerFunctionId GET,
    mccList GET-REPLACE,
    mncList GET-REPLACE,
    lacList GET-REPLACE,
    sacList GET-REPLACE,
    gcaList GET-REPLACE,
    mscId GET-REPLACE;
REGISTERED AS {ts32-634Package 20};

mscServerFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'MSCServerFunction' Information Object represents the MSCServer functionality.
  For more information about the MSCServer, see 3GPP TS 23.002";
```

-- 5.2.21 mscServerFunctionAssociationPackage

```
mscServerFunctionAssociationPackage PACKAGE
  BEHAVIOUR
    mscServerFunctionAssociationPackageBehaviour;
  ATTRIBUTES
    mscServerFunction-GSMcell GET,
    mscServerFunction-ExternalGSMcell GET,
    mscServerFunction-CsMgwFunction GET;
REGISTERED AS {ts32-634Package 21};

mscServerFunctionAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'MscServerFunction' information object in
  relation with associations to GsmCell, ExternalGsmCell and CsMgwFunction information objects";
```

-- 5.2.22 sgsnFunctionBasicPackage

```
sgsnFunctionBasicPackage PACKAGE
  BEHAVIOUR
    sgsnFunctionBasicPackageBehaviour;
  ATTRIBUTES
    sgsnFunctionId GET,
    mccList GET-REPLACE,
```

```

mncList          GET-REPLACE,
lacList          GET-REPLACE,
racList          GET-REPLACE,
sgsnId           GET-REPLACE,
mscId            GET-REPLACE;

```

REGISTERED AS {ts32-634Package 22};

sgsnFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'sgsnFunction' Information Object represents the SGSN functionality. For more information about the SGSN, see 3GPP TS 23.002";

-- 5.2.23 sgsnFunctionAssociationPackage

sgsnFunctionAssociationPackage **PACKAGE**

BEHAVIOUR

sgsnFunctionAssociationPackageBehaviour;

ATTRIBUTES

```

sgsnFunction-GSMcell          GET,
sgsnFunction-ExternalGSMcell GET;

```

REGISTERED AS {ts32-634Package 23};

sgsnFunctionAssociationPackageBehaviour **BEHAVIOUR**

DEFINED AS

"This Package contains the attributes of an 'SGSNFunction' information object in relation with associations to GsmCell and ExternalGsmCell information objects.";

-- 5.2.24 smsGmscFunctionBasicPackage

smsGmscFunctionBasicPackage **PACKAGE**

BEHAVIOUR

smsGmscFunctionBasicPackageBehaviour;

ATTRIBUTES

```

smsGmscFunctionId          GET;

```

REGISTERED AS {ts32-634Package 24};

smsGmscFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'smsGmscFunction' Information Object represents the SMS-GMSC functionality. For more information about the SMS-GMSC, see 3GPP TS 23.002";

-- 5.2.25 smsIwmscFunctionBasicPackage

smsIwmscFunctionBasicPackage **PACKAGE**

BEHAVIOUR

smsIwmscFunctionBasicPackageBehaviour;

ATTRIBUTES

```

smsIwmscFunctionId          GET;

```

REGISTERED AS {ts32-634Package 25};

smsIwmscFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'smsIwmscFunction' Information Object represents the SmsIwMSC functionality. For more information about the SmsIwMsc, see 3GPP TS 23.002";

-- 5.2.26 vlrFunctionBasicPackage

vlrFunctionBasicPackage **PACKAGE**

BEHAVIOUR

vlrFunctionBasicPackageBehaviour;

ATTRIBUTES

```

vlrFunctionId          GET;

```

REGISTERED AS {ts32-634Package 26};

vlrFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'vlrFunction' Information Object represents the VLR functionality. For more information about the VLR, see 3GPP TS 23.002";

-- 5.2.27 gbLinkBasicPackage

```
gbLinkBasicPackage PACKAGE
  BEHAVIOUR
    gbLinkBasicPackageBehaviour;
  ATTRIBUTES
    gbLinkId GET;
REGISTERED AS {ts32-634Package 27};
```

```
gbLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'gbLink' Information Object represents the Gb link functionality. For more information
  about the Gb link, see 3GPP TS 23.002";
```

-- 5.2.28 gbLinkAssociationPackage

```
gbLinkAssociationPackage PACKAGE
  BEHAVIOUR
    gbLinkAssociationPackageBehaviour;
  ATTRIBUTES
    connectedBss GET;
REGISTERED AS {ts32-634Package 28};
```

```
gbLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'gbLink' information object in relation with
  associations to BssFunction or ExternalBssFunction objects";
```

-- 5.2.29 aLinkBasicPackage

```
aLinkBasicPackage PACKAGE
  BEHAVIOUR
    aLinkBasicPackageBehaviour;
  ATTRIBUTES
    aLinkId GET;
REGISTERED AS {ts32-634Package 29};
```

```
aLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'aLink' Information Object represents the A link functionality. For more information
  about the A link, see 3GPP TS 23.002";
```

-- 5.2.30 aLinkAssociationPackage

```
aLinkAssociationPackage PACKAGE
  BEHAVIOUR
    aLinkAssociationPackageBehaviour;
  ATTRIBUTES
    connectedBss GET;
REGISTERED AS {ts32-634Package 30};
```

```
aLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'aLink' information object in relation with
  associations to BssFunction or ExternalBssFunction objects";
```

-- 5.2.31 iucsLinkBasicPackage

```
iucsLinkBasicPackage PACKAGE
  BEHAVIOUR
    iucsLinkBasicPackageBehaviour;
  ATTRIBUTES
    iucsLinkId GET;
REGISTERED AS {ts32-634Package 31};
```

```
iucsLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'iucsLink' Information Object represents the Iu-cs link functionality. For more
  information about the Iu-cs link, see 3GPP TS 23.002";
```

-- 5.2.32 iucsLinkAssociationPackage

```
iucsLinkAssociationPackage PACKAGE
  BEHAVIOUR
    iucsLinkAssociationPackageBehaviour;
  ATTRIBUTES
    connectedRnc      GET,
    connectedBss      GET;
REGISTERED AS {ts32-634Package 32};

iucsLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'iucsLink' information object in relation with
  associations to Bss/RncFunction or ExternalBss/RncFunction objects";
```

-- 5.2.33 iupsLinkBasicPackage

```
iupsLinkBasicPackage PACKAGE
  BEHAVIOUR
    iupsLinkBasicPackageBehaviour;
  ATTRIBUTES
    iupsLinkId      GET;
REGISTERED AS {ts32-634Package 33};

iupsLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'iupsLink' Information Object represents the Iu-ps link functionality. For more
  information about the Iu-ps link, see 3GPP TS 23.002";
```

-- 5.2.34 iupsLinkAssociationPackage

```
iupsLinkAssociationPackage PACKAGE
  BEHAVIOUR
    iupsLinkAssociationPackageBehaviour;
  ATTRIBUTES
    connectedRnc      GET,
    connectedBss      GET;
REGISTERED AS {ts32-634Package 34};

iupsLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'iupsLink' information object in relation with
  associations to Bss/RncFunction or ExternalBss/RncFunction objects";
```

-- 5.2.35 iubcLinkBasicPackage

```
iubcLinkBasicPackage PACKAGE
  BEHAVIOUR
    iubcLinkBasicPackageBehaviour;
  ATTRIBUTES
    iubcLinkId      GET;
REGISTERED AS {ts32-634Package 35};

iubcLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'iubcLink' Information Object represents the Iu-bc link functionality. For more
  information about the Iu-bc link, see 3GPP TS 23.002";
```

-- 5.2.36 iubcLinkAssociationPackage

```
iubcLinkAssociationPackage PACKAGE
  BEHAVIOUR
    iubcLinkAssociationPackageBehaviour;
  ATTRIBUTES
    connectedRnc      GET;
REGISTERED AS {ts32-634Package 36};

iubcLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'iubcLink' information object in relation with
  associations to RncFunction or ExternalRncFunction objects";
```

-- 5.2.37 csMgwFunctionBasicPackage

```
csMgwFunctionBasicPackage PACKAGE
  BEHAVIOUR
    csMgwFunctionBasicPackageBehaviour;
  ATTRIBUTES
    csMgwFunctionId      GET;
REGISTERED AS {ts32-634Package 37};

csMgwFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'csMgwFunction' Information Object represents the CS-MGW functionality. For more
  information about the CS-MGW, see 3GPP TS 23.002";
```

-- 5.2.38 csMgwFunctionAssociationPackage

```
csMgwFunctionAssociationPackage PACKAGE
  BEHAVIOUR
    csMgwFunctionAssociationPackageBehaviour;
  ATTRIBUTES
    csMgwFunction-MscServerFunction  GET,
    csMgwFunction-IucsLink           GET,
    csMgwFunction-Alink              GET;
REGISTERED AS {ts32-634Package 38};

csMgwFunctionAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'csMgwFunction' information object in relation
  with associations to mscServerFunction, iucsLink or aLink objects";
```

-- 5.2.39 gmscServerFunctionBasicPackage

```
gmscServerFunctionBasicPackage PACKAGE
  BEHAVIOUR
    gmscServerFunctionBasicPackageBehaviour;
  ATTRIBUTES
    gmscServerFunctionId  GET;
REGISTERED AS {ts32-634Package 39};

gmscServerFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'gmscServerFunction' Information Object represents the GMSCServer functionality. For more
  information about the GMSCServer, see 3GPP TS 23.002";
```

-- 5.2.40 scscfFunctionBasicPackage

```
scscfFunctionBasicPackage PACKAGE
  BEHAVIOUR
    scscfFunctionBasicPackageBehaviour;
  ATTRIBUTES
    scscfFunctionId  GET;
REGISTERED AS {ts32-634Package 40};

scscfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'scscfFunction' Information Object represents the S-CSCF functionality. For more
  information about the S-CSCF, see 3GPP TS 23.002";
```

-- 5.2.41 pcscfFunctionBasicPackage

```
pcscfFunctionBasicPackage PACKAGE
  BEHAVIOUR
    pcscfFunctionBasicPackageBehaviour;
  ATTRIBUTES
    pcscfFunctionId  GET;
REGISTERED AS {ts32-634Package 41};

pcscfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'pcscfFunction' Information Object represents the P-CSCF functionality. For more
  information about the P-CSCF, see 3GPP TS 23.002";
```

-- 5.2.42 icscfFunctionBasicPackage

icscfFunctionBasicPackage **PACKAGE**

BEHAVIOUR

icscfFunctionBasicPackageBehaviour;

ATTRIBUTES

icscfFunctionId GET;

REGISTERED AS {ts32-634Package 42};

icscfFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'icscfFunction' Information Object represents the I-CSCF functionality. For more information about the I-CSCF, see 3GPP TS 23.002";

-- 5.2.43 slfFunctionBasicPackage

slfFunctionBasicPackage **PACKAGE**

BEHAVIOUR

slfFunctionBasicPackageBehaviour;

ATTRIBUTES

slfFunctionId GET;

REGISTERED AS {ts32-634Package 43};

slfFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'slfFunction' Information Object represents the SLF functionality. For more information about the SLF, see 3GPP TS 23.002";

-- 5.2.44 bgcfFunctionBasicPackage

bgcfFunctionBasicPackage **PACKAGE**

BEHAVIOUR

bgcfFunctionBasicPackageBehaviour;

ATTRIBUTES

bgcfFunctionId GET;

REGISTERED AS {ts32-634Package 44};

bgcfFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'bgcfFunction' Information Object represents the BGCF functionality. For more information about the BGCF, see 3GPP TS 23.002";

-- 5.2.45 mrfcFunctionBasicPackage

mrfcFunctionBasicPackage **PACKAGE**

BEHAVIOUR

mrfcFunctionBasicPackageBehaviour;

ATTRIBUTES

mrfcFunctionId GET;

REGISTERED AS {ts32-634Package 45};

mrfcFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'mrfcFunction' Information Object represents the MRFC functionality. For more information about the MRFC, see 3GPP TS 23.002";

-- 5.2.46 asFunctionBasicPackage

asFunctionBasicPackage **PACKAGE**

BEHAVIOUR

asFunctionBasicPackageBehaviour;

ATTRIBUTES

asFunctionId GET;

REGISTERED AS {ts32-634Package 46};

asFunctionBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'asFunction' Information Object represents the AS functionality. For more information about the AS, see 3GPP TS 23.002";

-- 5.2.47 mgcfFunctionBasicPackage

```
mgcfFunctionBasicPackage PACKAGE
  BEHAVIOUR
    mgcfFunctionBasicPackageBehaviour;
  ATTRIBUTES
    mgcfFunctionId      GET;
REGISTERED AS {ts32-634Package 47};

mgcfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'mgcfFunction' Information Object represents the MGCF functionality. For more
  information about the MGCF, see 3GPP TS 23.002";
```

-- 5.2.48 mrfpFunctionBasicPackage

```
mrfpFunctionBasicPackage PACKAGE
  BEHAVIOUR
    mrfpFunctionBasicPackageBehaviour;
  ATTRIBUTES
    mrfpFunctionId      GET;
REGISTERED AS {ts32-634Package 48};

mrfpFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'mrfpFunction' Information Object represents the MRFP functionality. For more
  information about the MRFP, see 3GPP TS 23.002";
```

-- 5.3 Attributes

-- 5.3.1 smlcFunctionId

```
smlcFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    smlcFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 1};

smlcFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a smlcFunction instance.";
```

-- 5.3.2 gmlcFunctionId

```
gmlcFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    gmlcFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 2};

gmlcFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a gmlcFunction instance.";
```

-- 5.3.3 scfFunctionId

```
scfFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    scfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 3};
```

```
scfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a scfFunction instance.";
```

-- 5.3.4 srfFunctionId

```
srfFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    srfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 4};
```

```
srfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a srfFunction instance.";
```

-- 5.3.5 cbcFunctionId

```
cbcFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    cbcFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 5};
```

```
cbcFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a cbcFunction instance.";
```

-- 5.3.6 cgfFunctionId

```
cgfFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    cgfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 6};
```

```
cgfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a cgfFunction instance.";
```

-- 5.3.7 imsMgwFunctionId

```
imsMgwFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    imsMgwFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 70503};
```

```
imsMgwFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies an imsMgwFunction instance.";
```

-- 5.3.8 gmscFunctionId

```
gmscFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
```

```
    EQUALITY;
    BEHAVIOUR
    gsmcFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 8};

gsmcFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a gsmcFunction instance.";
```

-- 5.3.9 iwFunctionId

```
iwFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
    EQUALITY;
    BEHAVIOUR
    iwFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 9};

iwFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a iwFunction instance.";
```

-- 5.3.10 mnpSrfFunctionId

```
mnpSrfFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
    EQUALITY;
    BEHAVIOUR
    mnpSrfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 10};

mnpSrfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a mnpSrfFunction instance.";
```

-- 5.3.11 npdbFunctionId

```
npdbFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
    EQUALITY;
    BEHAVIOUR
    npdbFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 11};

npdbFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a npdbFunction instance.";
```

-- 5.3.12 rSgwFunctionId

```
rSgwFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
    EQUALITY;
    BEHAVIOUR
    rSgwFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 12};

rSgwFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a rSgwFunction instance.";
```

-- 5.3.13 ssfFunctionId

```
ssfFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    ssfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 13};

ssfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a ssfFunction instance.";
```

-- 5.3.14 bsFunctionId

```
bsFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    bsFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 14};

bsFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a bsFunction instance.";
```

-- 5.3.15 aucFunctionId

```
aucFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    aucFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 15};

aucFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a aucFunction instance.";
```

-- 5.3.16 bgFunctionId

```
bgFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    bgFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 16};

bgFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a bgFunction instance.";
```

-- 5.3.17 eirFunctionId

```
eirFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    eirFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 17};
```

```
eirFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a eirFunction instance.";
```

-- 5.3.18 ggsnFunctionId

```
ggsnFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    ggsnFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 18};

ggsnFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a ggsnFunction instance.";
```

-- 5.3.19 hlrFunctionId

```
hlrFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    hlrFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 19};

hlrFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a hlrFunction instance.";
```

-- 5.3.20 mscServerFunctionId

```
mscServerFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    mscServerFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 20};

mscServerFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a mscServerFunction instance.";
```

-- 5.3.21 vlrFunctionId

```
vlrFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    vlrFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 21};

vlrFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a vlrFunction instance.";
```

-- 5.3.22 sgsnFunctionId

```
sgsnFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
```

BEHAVIOUR

```
sgsnFunctionIdBehaviour;  
REGISTERED AS {ts32-634Attribute 22};
```

```
sgsnFunctionIdBehaviour BEHAVIOUR  
DEFINED AS
```

```
"This attribute identifies a sgsnFunction instance.";
```

-- 5.3.23 smsGmscFunctionId

```
smsGmscFunctionId ATTRIBUTE  
WITH ATTRIBUTE SYNTAX  
TS32-634TypeModule.GeneralObjectId;  
MATCHES FOR  
EQUALITY;  
BEHAVIOUR
```

```
smsGmscFunctionIdBehaviour;  
REGISTERED AS {ts32-634Attribute 23};
```

```
smsGmscFunctionIdBehaviour BEHAVIOUR  
DEFINED AS
```

```
"This attribute identifies a smsGmscFunction instance.";
```

-- 5.3.24 smsIwmscFunctionId

```
smsIwmscFunctionId ATTRIBUTE  
WITH ATTRIBUTE SYNTAX  
TS32-634TypeModule.GeneralObjectId;  
MATCHES FOR  
EQUALITY;  
BEHAVIOUR
```

```
smsIwmscFunctionIdBehaviour;  
REGISTERED AS {ts32-634Attribute 24};
```

```
smsIwmscFunctionIdBehaviour BEHAVIOUR  
DEFINED AS
```

```
"This attribute identifies a smsIwmscFunction instance.";
```

-- 5.3.25 gbLinkId

```
gbLinkId ATTRIBUTE  
WITH ATTRIBUTE SYNTAX  
TS32-634TypeModule.GeneralObjectId;  
MATCHES FOR  
EQUALITY;  
BEHAVIOUR
```

```
gbLinkIdBehaviour;  
REGISTERED AS {ts32-634Attribute 25};
```

```
gbLinkIdBehaviour BEHAVIOUR  
DEFINED AS
```

```
"This attribute identifies a gbLink instance.";
```

-- 5.3.26 aLinkId

```
aLinkId ATTRIBUTE  
WITH ATTRIBUTE SYNTAX  
TS32-634TypeModule.GeneralObjectId;  
MATCHES FOR  
EQUALITY;  
BEHAVIOUR
```

```
aLinkIdBehaviour;  
REGISTERED AS {ts32-634Attribute 26};
```

```
aLinkIdBehaviour BEHAVIOUR  
DEFINED AS
```

```
"This attribute identifies a aLink instance.";
```

-- 5.3.27 iucsLinkId

```
iucsLinkId ATTRIBUTE
```

```
WITH ATTRIBUTE SYNTAX
  TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  iucsLinkIdBehaviour;
REGISTERED AS {ts32-634Attribute 27};

iucsLinkIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a iucsLink instance.";
```

-- 5.3.28 iupsLinkId

```
iupsLinkId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
  TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  iupsLinkIdBehaviour;
REGISTERED AS {ts32-634Attribute 28};

iupsLinkIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a iupsLink instance.";
```

-- 5.3.29 iubcLinkId

```
iubcLinkId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
  TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  iubcLinkIdBehaviour;
REGISTERED AS {ts32-634Attribute 29};

iubcLinkIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a iubcLink instance.";
```

-- 5.3.30 csMgwFunctionId

```
csMgwFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
  TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  csMgwFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 30};

csMgwFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a csMgwFunction instance.";
```

-- 5.3.31 gmscServerFunctionId

```
gmscServerFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
  TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  gmscServerFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 31};

gmscServerFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a gmscServerFunction instance.";
```

-- 5.3.32 mccList

```
mccList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.MccList;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mccListBehaviour;
REGISTERED AS {ts32-634Attribute 32};

mccListBehaviour BEHAVIOUR
DEFINED AS
  "List of Mobile Country Codes, MCC. The MCC is part of the PLMN Id (Ref. 3 GPP TS 23.003).";
```

-- 5.3.33 mncList

```
mncList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.MncList;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mncListBehaviour;
REGISTERED AS {ts32-634Attribute 33};

mncListBehaviour BEHAVIOUR
DEFINED AS
  "List of Mobile Network Code, MNC. The MNC is part of the PLMN Id (Ref. 3 GPP TS 23.003).";
```

-- 5.3.34 lacList

```
lacList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.LacList;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    lacListBehaviour;
REGISTERED AS {ts32-634Attribute 34};

lacListBehaviour BEHAVIOUR
DEFINED AS
  "List of Location Area Codes covered by SGSN (Ref. 3 GPP TS 23.003).";
```

-- 5.3.35 sacList

```
sacList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.SacList;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    sacListBehaviour;
REGISTERED AS {ts32-634Attribute 35};

sacListBehaviour BEHAVIOUR
DEFINED AS
  "List of Service Area Codes covered by SGSN (Ref. 3 GPP TS 23.003).";
```

-- 5.3.36 uraList

-- Void.

-- 5.3.37 gcaList

```
gcaList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.CgaList;
  MATCHES FOR
```



```

    EQUALITY;
    BEHAVIOUR
    gcaListBehaviour;
    REGISTERED AS {ts32-634Attribute 37};

gcaListBehaviour BEHAVIOUR
DEFINED AS
    "List of Group Call Area (Ref. 3 GPP TS 23.003).";

```

-- 5.3.38 mscId

```

mscId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
    EQUALITY;
    BEHAVIOUR
    mscIdBehaviour;
    REGISTERED AS {ts32-634Attribute 38};

```

```

mscIdBehaviour BEHAVIOUR
DEFINED AS
    "Unique MSC ID (Ref. 3 GPP TS 23.002).";

```

-- 5.3.39 mscServerFunction-GSMcell

```

mscServerFunction-GSMcell ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
    MATCHES FOR
    EQUALITY;
    BEHAVIOUR
    mscServerFunction-GSMcellBehaviour;
    REGISTERED AS {ts32-634Attribute 39};

```

```

mscServerFunction-GSMcellBehaviour BEHAVIOUR
DEFINED AS
    "This value contains the DN of the related GSMcell instance. This is a reference attribute
    modelling the role (of the association AssociatedWith) that this MscServerFunction
    is associated with to 0-* GSMcell.";

```

-- 5.3.40 mscServerFunction-ExternalGSMcell

```

mscServerFunction-ExternalGSMcell ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
    MATCHES FOR
    EQUALITY;
    BEHAVIOUR
    mscServerFunction-ExternalGSMcellBehaviour;
    REGISTERED AS {ts32-634Attribute 40};

```

```

mscServerFunction-ExternalGSMcellBehaviour BEHAVIOUR
DEFINED AS
    "This value contains the DN of the related ExternalGSMcell instance. This is a reference
    attribute modelling the role (of the association AssociatedWith) that this MscServerFunction
    is associated with to 0-* ExternalGSMcell.";

```

-- 5.3.41 mscServerFunction-CsMgwFunction

```

mscServerFunction-CsMgwFunction ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
    MATCHES FOR
    EQUALITY;
    BEHAVIOUR
    mscServerFunction-CsMgwFunctionBehaviour;
    REGISTERED AS {ts32-634Attribute 41};

```

```

mscServerFunction-CsMgwFunctionBehaviour BEHAVIOUR
DEFINED AS
    "This value contains the DN of the related CsMgwFunction instance. This is a reference
    attribute modelling the role (of the association AssociatedWith) that this MscServerFunction

```

is associated with to 0-* CsMgwFunction.";

-- 5.3.42 racList

```
racList ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.RacList;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    racListBehaviour;
REGISTERED AS {ts32-634Attribute 42};

racListBehaviour BEHAVIOUR
DEFINED AS
    "List of Routing Area Codes covered by SGSN (Ref. 3 GPP TS 23.003).";
```

-- 5.3.43 sgsnId

```
sgsnId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    sgsnIdBehaviour;
REGISTERED AS {ts32-634Attribute 43};

sgsnIdBehaviour BEHAVIOUR
DEFINED AS
    "Unique SGSN ID (Ref. 3 GPP TS 23.002).";
```

-- 5.3.44 sgsnFunction-GSMcell

```
sgsnFunction-GSMcell ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    sgsnFunction-GSMcellBehaviour;
REGISTERED AS {ts32-634Attribute 44};

sgsnFunction-GSMcellBehaviour BEHAVIOUR
DEFINED AS
    "This value contains the DN of the related GSMcell instance. This is a reference attribute
    modelling the role (of the association AssociatedWith) that this SgsnFunction is associated
    with to 0-* GSMcell.";
```

-- 5.3.45 sgsnFunction-ExternalGSMcell

```
sgsnFunction-ExternalGSMcell ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    sgsnFunction-ExternalGSMcellBehaviour;
REGISTERED AS {ts32-634Attribute 45};

sgsnFunction-ExternalGSMcellBehaviour BEHAVIOUR
DEFINED AS
    "This value contains the DN of the related ExternalGSMcell instance. This is a reference
    attribute modelling the role (of the association AssociatedWith) that this SgsnFunction
    is associated with to 0-* ExternalGSMcell.";
```

-- 5.3.46 connectedBss

```
connectedBss ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
```

```

MATCHES FOR
  EQUALITY;
BEHAVIOUR
  connectedBssBehaviour;
REGISTERED AS {ts32-634Attribute 46};

```

```

connectedBssBehaviour BEHAVIOUR
DEFINED AS

```

```

"This value contains the DN of the related BssFunction or ExternalBssFunction instance. This is
a reference attribute modelling the role (of the association AssociatedWith) that link is
connected to 0-1 BssFunction or 0-1 ExternalBssFunction.";

```

-- 5.3.47 connectedRnc

```

connectedRnc ATTRIBUTE
WITH ATTRIBUTE SYNTAX
  TS32-634TypeModule.GeneralObjectPointer;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  connectedRncBehaviour;
REGISTERED AS {ts32-634Attribute 47};

```

```

connectedRncBehaviour BEHAVIOUR
DEFINED AS

```

```

"This value contains the DN of the related RncFunction or ExternalRncFunction instance. This is
a reference attribute modelling the role (of the association AssociatedWith) that link is
connected to 0-1 RncFunction or 0-1 ExternalRncFunction.";

```

-- 5.3.48 csMgwFunction-MscServerFunction

```

csMgwFunction-MscServerFunction ATTRIBUTE
WITH ATTRIBUTE SYNTAX
  TS32-634TypeModule.GeneralObjectPointer;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  csMgwFunction-MscServerFunctionBehaviour;
REGISTERED AS {ts32-634Attribute 48};

```

```

csMgwFunction-MscServerFunctionBehaviour BEHAVIOUR
DEFINED AS

```

```

"This value contains the DN of the related mscServerFunction instance. This is a reference
attribute modelling the role (of the association AssociatedWith) that this csMgwFunction is
associated with to 0-* mscServerFunction.";

```

-- 5.3.49 csMgwFunction-IucsLink

```

csMgwFunction-IucsLink ATTRIBUTE
WITH ATTRIBUTE SYNTAX
  TS32-634TypeModule.GeneralObjectPointer;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  csMgwFunction-IucsLinkBehaviour;
REGISTERED AS {ts32-634Attribute 49};

```

```

csMgwFunction-IucsLinkBehaviour BEHAVIOUR
DEFINED AS

```

```

"This value contains the DN of the related IucsLink instance. This is a reference attribute
modelling the role (of the association AssociatedWith) that this csMgwFunction is
connected to 0-* IucsLink.";

```

-- 5.3.50 csMgwFunction-Alink

```

csMgwFunction-Alink ATTRIBUTE
WITH ATTRIBUTE SYNTAX
  TS32-634TypeModule.GeneralObjectPointer;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  csMgwFunction-AlinkBehaviour;
REGISTERED AS {ts32-634Attribute 50};

```

csMgwFunction-ALinkBehaviour **BEHAVIOUR**
DEFINED AS

"This value contains the DN of the related ALink instance. This is a reference attribute modelling the role (of the association AssociatedWith) that this csMgwFunction is connected to 0-* ALink.";

-- 5.3.51 scscfFunctionId

scscfFunctionId **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
scscfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 51};

scscfFunctionIdBehaviour **BEHAVIOUR**
DEFINED AS
"This attribute identifies a scscfFunction instance.";

-- 5.3.52 pcscfFunctionId

pcscfFunctionId **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
pcscfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 52};

pcscfFunctionIdBehaviour **BEHAVIOUR**
DEFINED AS
"This attribute identifies a pcscfFunction instance.";

-- 5.3.53 icscfFunctionId

icscfFunctionId **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
icscfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 53};

icscfFunctionIdBehaviour **BEHAVIOUR**
DEFINED AS
"This attribute identifies a icscfFunction instance.";

-- 5.3.54 slfFunctionId

slfFunctionId **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
slfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 54};

slfFunctionIdBehaviour **BEHAVIOUR**
DEFINED AS
"This attribute identifies a slfFunction instance.";

-- 5.3.55 bgcfFunctionId

bgcfFunctionId **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX

```
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    bgcfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 55};

bgcfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a bgcfFunction instance.";
```

-- 5.3.56 mrfcFunctionId

```
mrfcFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    mrfcFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 56};

mrfcFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a mrfcFunction instance.";
```

-- 5.3.57 asFunctionId

```
asFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    asFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 57};

asFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a asFunction instance.";
```

-- 5.3.58 mgcfFunctionId

```
mgcfFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    mgcfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 58};

mgcfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a mgcfFunction instance.";
```

-- 5.3.59 mrfpFunctionId

```
mrfpFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    mrfpFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 59};

mrfpFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a mrfpFunction instance.";
```

-- 5.4 Name Binding

-- 5.4.1 smlcFunction - managedElement

```
smlcFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    smlcFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    smlcFunctionId;
  BEHAVIOUR
    smlcFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 1};
```

```
smlcFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
```

"The name binding represents a relationship in which a managedElement contains and controls a smlcFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.2 gmlcFunction - managedElement

```
gmlcFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    gmlcFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    gmlcFunctionId;
  BEHAVIOUR
    gmlcFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 2};
```

```
gmlcFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
```

"The name binding represents a relationship in which a managedElement contains and controls a gmlcFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.3 scfFunction - managedElement

```
scfFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    scfFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    scfFunctionId;
  BEHAVIOUR
    scfFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 3};
```

```
scfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
```

"The name binding represents a relationship in which a managedElement contains and controls a scfFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.4 srfFunction - managedElement

```
srfFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    srfFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    srfFunctionId;
  BEHAVIOUR
    srfFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 4};
```

```
srfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  srfFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

-- 5.4.5 cbcFunction - managedElement

```
cbcFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    cbcFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    cbcFunctionId;
  BEHAVIOUR
    cbcFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 5};
```

```
cbcFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  cbcFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

-- 5.4.6 cgfFunction - managedElement

```
cgfFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    cgfFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    cgfFunctionId;
  BEHAVIOUR
    cgfFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 6};
```

```
cgfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  cgfFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

-- 5.4.7 imsMgwFunction - managedElement

```
imsMgwFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
```

```

    imsMgwFunction;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    imsMgwFunctionId;
BEHAVIOUR
    imsMgwFunction-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 70503};

```

```

imsMgwFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls an mimsMgwFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.8 gmscFunction - managedElement

```

gmscFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
    gmscFunction;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    gmscFunctionId;
BEHAVIOUR
    gmscFunction-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 8};

```

```

gmscFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a gmscFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.9 iwfFunction - managedElement

```

iwfFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
    iwfFunction;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    iwfFunctionId;
BEHAVIOUR
    iwfFunction-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 9};

```

```

iwfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a iwfFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.10 mnpSrfFunction - managedElement

```

mnpSrfFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
    mnpSrfFunction;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    mnpSrfFunctionId;

```



```

BEHAVIOUR
  mnpSrfFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 10};

```

```
mnpSrfFunction-managedElementBehaviour BEHAVIOUR
```

```

DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  mnpSrfFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.11 npdbFunction - managedElement

```

npdbFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    npdbFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    npdbFunctionId;
  BEHAVIOUR
    npdbFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
  REGISTERED AS {ts32-634NameBinding 11};

```

```
npdbFunction-managedElementBehaviour BEHAVIOUR
```

```

DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  npdbFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.12 rSgwFunction - managedElement

```

rSgwFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    rSgwFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    rSgwFunctionId;
  BEHAVIOUR
    rSgwFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
  REGISTERED AS {ts32-634NameBinding 12};

```

```
rSgwFunction-managedElementBehaviour BEHAVIOUR
```

```

DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  rSgwFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.13 ssfFunction - managedElement

```

ssfFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    ssfFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    ssfFunctionId;
  BEHAVIOUR
    ssfFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE

```

```

ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 13};

```

```

ssfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a ssfFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.14 bsFunction - managedElement

```

bsFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  bsFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  bsFunctionId;
BEHAVIOUR
  bsFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 14};

```

```

bsFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a bsFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.15 aucFunction - managedElement

```

aucFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  aucFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  aucFunctionId;
BEHAVIOUR
  aucFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 15};

```

```

aucFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a aucFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.16 bgFunction - managedElement

```

bgFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  bgFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  bgFunctionId;
BEHAVIOUR
  bgFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 16};

```

```

bgFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a bgFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.17 eirFunction - managedElement

```

eirFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    eirFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    eirFunctionId;
  BEHAVIOUR
    eirFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 17};

```

```

eirFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  eirFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.18 ggsnFunction - managedElement

```

ggsnFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    ggsnFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    ggsnFunctionId;
  BEHAVIOUR
    ggsnFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 18};

```

```

ggsnFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  ggsnFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.19 hlrFunction - managedElement

```

hlrFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    hlrFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    hlrFunctionId;
  BEHAVIOUR
    hlrFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 19};

```

```

hlrFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  hlrFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.20 mscServerFunction - managedElement

```

mscServerFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    mscFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    mscServerFunctionId;
  BEHAVIOUR
    mscServerFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 20};

```

```

mscServerFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  mscServerFunction. When automatic instance naming is used, the choice of name bindings is left
  as a local matter.";

```

-- 5.4.21 vlrFunction - managedElement

```

vlrFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    vlrFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    vlrFunctionId;
  BEHAVIOUR
    vlrFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 21};

```

```

vlrFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  vlrFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.22 sgsnFunction - managedElement

```

sgsnFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    sgsnFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    sgsnFunctionId;
  BEHAVIOUR
    sgsnFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 22};

```

```

sgsnFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  sgsnFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.23 smsGmscFunction - managedElement

```

smsGmscFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS

```

```

    smsGmscFunction;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    smsGmscFunctionId;
BEHAVIOUR
    smsGmscFunction-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 23};

```

```

smsGmscFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a smsGmscFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.24 smsIwmscFunction - managedElement

```

smsIwmscFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
    smsIwmscFunction;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    smsIwmscFunctionId;
BEHAVIOUR
    smsIwmscFunction-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 24};

```

```

smsIwmscFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a smsIwmscFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.25 gbLink - managedElement

```

gbLink-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
    gbLink;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    gbLinkId;
BEHAVIOUR
    gbLink-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 25};

```

```

gbLink-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a gbLink. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.26 aLink - managedElement

```

aLink-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
    aLink;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    aLinkId;

```

```

BEHAVIOUR
  aLink-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 26};

aLink-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  aLink. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.27 iucsLink - managedElement

```

iucsLink-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  iucsLink;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  iucsLinkId;
BEHAVIOUR
  iucsLink-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 27};

iucsLink-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  iucsLink. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.28 iupsLink - managedElement

```

iupsLink-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  iupsLink;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  iupsLinkId;
BEHAVIOUR
  iupsLink-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 28};

iupsLink-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  iupsLink. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";

```

-- 5.4.29 iubcLink - managedElement

```

iubcLink-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  iubcLink;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  iubcLinkId;
BEHAVIOUR
  iubcLink-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE

```

```
ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 29};
```

```
iubcLink-managedElementBehaviour BEHAVIOUR
DEFINED AS
```

```
"The name binding represents a relationship in which a managedElement contains and controls a
iubcLink. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

-- 5.4.30 gmscServerFunction - managedElement

```
gmscServerFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  gmscServerFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  gmscServerFunctionId;
BEHAVIOUR
  gmscServerFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 30};
```

```
gmscServerFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
```

```
"The name binding represents a relationship in which a managedElement contains and controls a
gmscServerFunction. When automatic instance naming is used, the choice of name bindings is left
as a local matter.";
```

-- 5.4.31 csMgwFunction - managedElement

```
csMgwFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  csMgwFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  csMgwFunctionId;
BEHAVIOUR
  csMgwFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 31};
```

```
csMgwFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
```

```
"The name binding represents a relationship in which a managedElement contains and controls a
csMgwFunction. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

-- 5.4.32 scscfFunction - managedElement

```
scscfFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  scscfFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  scscfFunctionId;
BEHAVIOUR
  scscfFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 32};
```

```
scscfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
```

"The name binding represents a relationship in which a managedElement contains and controls a scscfFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.33 pcscfFunction - managedElement

```
pcscfFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  pcscfFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  pcscfFunctionId;
BEHAVIOUR
  pcscfFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 33};
```

```
pcscfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  pcscfFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

-- 5.4.34 icscfFunction - managedElement

```
icscfFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  icscfFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  icscfFunctionId;
BEHAVIOUR
  icscfFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 34};
```

```
icscfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  icscfFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

-- 5.4.35 slfFunction - managedElement

```
slfFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  slfFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  slfFunctionId;
BEHAVIOUR
  slfFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 35};
```

```
slfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  slfFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```


-- 5.4.36 bgcfFunction - managedElement

```

bgcfFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    bgcfFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    bgcfFunctionId;
  BEHAVIOUR
    bgcfFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 36};

```

```

bgcfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a bgcfFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.37 mrfcFunction - managedElement

```

mrfcFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    mrfcFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    mrfcFunctionId;
  BEHAVIOUR
    mrfcFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 37};

```

```

mrfcFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a mrfcFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.38 asFunction - managedElement

```

asFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    asFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    asFunctionId;
  BEHAVIOUR
    asFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 38};

```

```

asFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a asFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

-- 5.4.39 mgcfFunction - managedElement

```

mgcfFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS

```

```

    mgcfFunction;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    mgcfFunctionId;
BEHAVIOUR
    mgcfFunction-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 39};

```

```

mgcfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

```

    "The name binding represents a relationship in which a managedElement contains and controls a
    mgcfFunction. When automatic instance naming is used, the choice of name bindings is left as
    a local matter.";

```

-- 5.4.40 mrfpFunction - managedElement

```

mrfpFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
    mrfpFunction;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
    mrfpFunctionId;
BEHAVIOUR
    mrfpFunction-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 40};

```

```

mrfpFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

```

    "The name binding represents a relationship in which a managedElement contains and controls a
    mrfpFunction. When automatic instance naming is used, the choice of name bindings is left as
    a local matter.";

```

-- 6 ASN.1 Definitions

```

TS32-634TypeModule {ccitt (0) identified-organization (4) etsi (0) mobileDomain (0) umts-Operation-
Maintenance (3) ts32-634 (634) informationModel (0) asn1Module (2) version1 (1)}

```

```

DEFINITIONS IMPLICIT TAGS ::=

```

```

BEGIN

```

```

--EXPORTS everything

```

```

IMPORTS

```

```

GeneralObjectId, GeneralObjectPointer
    FROM TS32-624TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0)
    umts-Operation-Maintenance(3) ts32-624(624) informationModel(0) asn1Module(2) version1(1)}

```

```

MobileCountryCode, MobileNetworkCode, LocationAreaCode
    FROM GSM1220TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0)
    gsm-Operation-Maintenance(3) gsm-12-20(20) informationModel(0) asn1Module(2)
    asn1TypeModule(0)};

```

```

-- 3GPP TS 32.634 related Object Identifiers

```

```

baseNodeUMTS          OBJECT IDENTIFIER ::= {itu-t(0) identified-organization(4) etsi(0)
    mobileDomain(0) umts-Operation-Maintenance(3)}

```

```

ts32-634              OBJECT IDENTIFIER ::= {baseNodeUMTS ts32-634(634)}

```

```

ts32-634InfoModel    OBJECT IDENTIFIER ::= {ts32-634 informationModel(0)}

```

```
ts32-634ObjectClass    OBJECT IDENTIFIER ::= {ts32-634InfoModel managedObjectClass(3)}
ts32-634Package        OBJECT IDENTIFIER ::= {ts32-634InfoModel package(4)}
ts32-634Parameter     OBJECT IDENTIFIER ::= {ts32-634InfoModel parameter(5)}
ts32-634NameBinding   OBJECT IDENTIFIER ::= {ts32-634InfoModel nameBinding(6)}
ts32-634Attribute     OBJECT IDENTIFIER ::= {ts32-634InfoModel attribute(7)}
ts32-634Action        OBJECT IDENTIFIER ::= {ts32-634InfoModel action(9)}
ts32-634Notification  OBJECT IDENTIFIER ::= {ts32-634InfoModel notification(10)}
```

```
-- Start of 3GPP SA5 own definitions
```

```
MccList ::= SET OF MobileCountryCode
```

```
MncList ::= SET OF MobileNetworkCode
```

```
LacList ::= SET OF LocationAreaCode
```

```
Rac ::= INTEGER
```

```
RacList ::= SET OF Rac
```

```
Sac ::= INTEGER
```

```
SacList ::= SET OF Sac
```

```
Cga ::= INTEGER
```

```
CgaList ::= SET OF Cga
```

```
END -- of TS32-634TypeModule
```

Annex A (informative): List of assigned Object Identifiers

This annex provides a list with all Object Identifiers (OIDs) that have been assigned in TS 32.634. These OIDs shall not be assigned to new objects.

Basic Object Name	Name and OID of the current TS Version	Name and OIDs of previous TS Versions
Managed Object Classes		
smlcFunction	Name: smlcFunction OID : ts32-634ObjectClass 1	--
gmlcFunction	Name: gmlcFunction OID : ts32-634ObjectClass 2	--
scfFunction	Name: scfFunction OID : ts32-634ObjectClass 3	--
srfFunction	Name: srfFunction OID : ts32-634ObjectClass 4	--
cbcFunction	Name: cbcFunction OID : ts32-634ObjectClass 5	--
cgfFunction	Name: cgfFunction OID : ts32-634ObjectClass 6	--
mgwFunction	--	Name: mgwFunction OID : ts32-634ObjectClass 7
imsMgwFunction	Name: imsMgwFunction OID : ts32-634ObjectClass 70503	--
gmscFunction	Name: gmscFunction OID : ts32-634ObjectClass 8	--
iwfFunction	Name: iwfFunction OID : ts32-634ObjectClass 9	--
mnpSrfFunction	Name: mnpSrfFunction OID : ts32-634ObjectClass 10	--
npdbFunction	Name: npdbFunction OID : ts32-634ObjectClass 11	--
rSgwFunction	Name: rSgwFunction OID : ts32-634ObjectClass 12	--
ssfFunction	Name: ssfFunction OID : ts32-634ObjectClass 13	--
bsFunction	Name: bsFunction OID : ts32-634ObjectClass 14	--
aucFunction	Name: aucFunction OID : ts32-634ObjectClass 15	--
bgFunction	Name: bgFunction OID : ts32-634ObjectClass 16	--
eirFunction	Name: eirFunction OID : ts32-634ObjectClass 17	--
ggsnFunction	Name: ggsnFunction OID : ts32-634ObjectClass 18	--
hlrFunction	Name: hlrFunction OID : ts32-634ObjectClass 19	--
mscFunction	Name: mscFunction OID : ts32-634ObjectClass 20	--
sgsnFunction	Name: sgsnFunction OID : ts32-634ObjectClass 21	--
smsGmscFunction	Name: smsGmscFunction OID : ts32-634ObjectClass 22	--
smslwmscFunction	Name: smslwmscFunction OID : ts32-634ObjectClass 23	--
vlrFunction	Name: vlrFunction OID : ts32-634ObjectClass 24	--
gbLink	Name: gbLink OID : ts32-634ObjectClass 25	--
aLink	Name: aLink OID : ts32-634ObjectClass 26	--
iucsLink	Name: iucsLink OID : ts32-634ObjectClass 27	--

iupsLink	Name: iupsLink OID : ts32-634ObjectClass 28	--
iubcLink	Name: iubcLink OID : ts32-634ObjectClass 29	--
csMgwFunction	Name: csMgwFunction OID : ts32-634ObjectClass 30	--
gmscServerFunction	Name: gmscServerFunction OID : ts32-634ObjectClass 31	--
scscfFunction	Name: ScscfFunction OID : ts32-634ObjectClass 32	--
pcscfFunction	Name: PcscfFunction OID : ts32-634ObjectClass 33	--
icscfFunction	Name: IcscfFunction OID : ts32-634ObjectClass 34	--
sllFunction	Name: SllFunction OID : ts32-634ObjectClass 35	--
bgcfFunction	Name: BgcfFunction OID : ts32-634ObjectClass 36	--
mrfcFunction	Name: MrfcFunction OID : ts32-634ObjectClass 37	--
asFunction	Name: AsFunction OID : ts32-634ObjectClass 38	--
mgcfFunction	Name: MgcfFunction OID : ts32-634ObjectClass 39	--
mrfpFunction	Name: MrfpFunction OID : ts32-634ObjectClass 40	--
Packages		
smlcFunctionBasicPackage	Name: smlcFunctionBasicPackage OID : ts32-634Package 1	--
gmlcFunctionBasicPackage	Name: gmlcFunctionBasicPackage OID : ts32-634Package 2	--
scfFunctionBasicPackage	Name: scfFunctionBasicPackage OID : ts32-634Package 3	--
srfFunctionBasicPackage	Name: srfFunctionBasicPackage OID : ts32-634Package 4	--
cbcFunctionBasicPackage	Name: cbcFunctionBasicPackage OID : ts32-634Package 5	--
cgfFunctionBasicPackage	Name: cgfFunctionBasicPackage OID : ts32-634Package 6	--
mgwFunctionBasicPackage	--	Name: mgwFunctionBasicPackage OID : ts32-634Package 7
imsMgwFunctionBasicPackage	Name: imsMgwFunctionBasicPackage OID : ts32-634Package 70503	--
gmscFunctionBasicPackage	Name: gmscFunctionBasicPackage OID : ts32-634Package 8	--
iwfFunctionBasicPackage	Name: iwfFunctionBasicPackage OID : ts32-634Package 9	--
mnpSrfFunctionBasicPackage	Name: mnpSrfFunctionBasicPackage OID : ts32-634Package 10	--
npdbFunctionBasicPackage	Name: npdbFunctionBasicPackage OID : ts32-634Package 11	--
rSgwFunctionBasicPackage	Name: rSgwFunctionBasicPackage OID : ts32-634Package 12	--
ssfFunctionBasicPackage	Name: ssfFunctionBasicPackage OID : ts32-634Package 13	--
bsFunctionBasicPackage	Name: bsFunctionBasicPackage OID : ts32-634Package 14	--
aucFunctionBasicPackage	Name: aucFunctionBasicPackage OID : ts32-634Package 15	--
bgFunctionBasicPackage	Name: bgFunctionBasicPackage OID : ts32-634Package 16	--
eirFunctionBasicPackage	Name: eirFunctionBasicPackage OID : ts32-634Package 17	--
ggsnFunctionBasicPackage	Name: ggsnFunctionBasicPackage OID : ts32-634Package 18	--
hlrFunctionBasicPackage	Name: hlrFunctionBasicPackage OID : ts32-634Package 19	--
mscServerFunctionBasicPackage	Name: mscServerFunctionBasicPackage OID : ts32-634Package 20	--

mscServerFunctionAssociationPackage	Name: mscServerFunctionAssociationPackage OID : ts32-634Package 21	--
sgsnFunctionBasicPackage	Name: sgsnFunctionBasicPackage OID : ts32-634Package 22	--
sgsnFunctionAssociationPackage	Name: sgsnFunctionAssociationPackage OID : ts32-634Package 23	--
smsGmscFunctionBasicPackage	Name: smsGmscFunctionBasicPackage OID : ts32-634Package 24	--
smslwmScFunctionBasicPackage	Name: smslwmScFunctionBasicPackage OID : ts32-634Package 25	--
vlrFunctionBasicPackage	Name: vlrFunctionBasicPackage OID : ts32-634Package 26	--
gbLinkBasicPackage	Name: gbLinkBasicPackage OID : ts32-634Package 27	--
gbLinkAssociationPackage	Name: gbLinkAssociationPackage OID : ts32-634Package 28	--
aLinkBasicPackage	Name: aLinkBasicPackage OID : ts32-634Package 29	--
aLinkAssociationPackage	Name: aLinkAssociationPackage OID : ts32-634Package 30	--
iucsLinkBasicPackage	Name: iucsLinkBasicPackage OID : ts32-634Package 31	--
iucsLinkAssociationPackage	Name: iucsLinkAssociationPackage OID : ts32-634Package 32	--
iupsLinkBasicPackage	Name: iupsLinkBasicPackage OID : ts32-634Package 33	--
iupsLinkAssociationPackage	Name: iupsLinkAssociationPackage OID : ts32-634Package 34	--
iubcLinkBasicPackage	Name: iubcLinkBasicPackage OID : ts32-634Package 35	--
iubcLinkAssociationPackage	Name: iubcLinkAssociationPackage OID : ts32-634Package 36	--
csMgwFunctionBasicPackage	Name: csMgwFunctionBasicPackage OID : ts32-634Package 37	--
csMgwFunctionAssociationPackage	Name: csMgwFunctionAssociationPackage OID : ts32-634Package 38	--
gmscServerFunctionBasicPackage	Name: gmscServerFunctionBasicPackage OID : ts32-634Package 39	--
scscfFunctionBasicPackage	Name: scscfFunctionBasicPackage OID : ts32-634Package 40	--
pcscfFunctionBasicPackage	Name: pcscfFunctionBasicPackage OID : ts32-634Package 41	--
icscfFunctionBasicPackage	Name: icscfFunctionBasicPackage OID : ts32-634Package 42	--
slffFunctionBasicPackage	Name: slffFunctionBasicPackage OID : ts32-634Package 43	--
bgcfFunctionBasicPackage	Name: bgcfFunctionBasicPackage OID : ts32-634Package 44	--
mrfcFunctionBasicPackage	Name: mrfcFunctionBasicPackage OID : ts32-634Package 45	--
asFunctionBasicPackage	Name: asFunctionBasicPackage OID : ts32-634Package 46	--
mgcfFunctionBasicPackage	Name: mgcfFunctionBasicPackage OID : ts32-634Package 47	--
mrfpFunctionBasicPackage	Name: mrfpFunctionBasicPackage OID : ts32-634Package 48	--

Actions

Notifications

Attributes

smlcFunctionId	Name: smlcFunctionId OID : ts32-634Attribute 1	--
gmlcFunctionId	Name: gmlcFunctionId OID : ts32-634Attribute 2	--
scfFunctionId	Name: scfFunctionId OID : -634Attribute 3	--

srfFunctionId	Name: srfFunctionId OID : ts32-634Attribute 4	--
cbcFunctionId	Name: cbcFunctionId OID : ts32-634Attribute 5	--
cgfFunctionId	Name: cgfFunctionId OID : ts32-634Attribute 6	--
mgwFunctionId	--	Name: mgwFunctionId OID : ts32-634Attribute 7
imsMgwFunctionId	Name: imsMgwFunctionId OID : ts32-634Attribute 70503	--
gmscFunctionId	Name: gmscFunctionId OID : ts32-634Attribute 8	--
iwfFunctionId	Name: iwfFunctionId OID : ts32-634Attribute 9	--
mnpSrfFunctionId	Name: mnpSrfFunctionId OID : ts32-634Attribute 10	--
npdbFunctionId	Name: npdbFunctionId OID : ts32-634Attribute 11	--
rSgwFunctionId	Name: rSgwFunctionId OID : ts32-634Attribute 12	--
ssfFunctionId	Name: ssfFunctionId OID : ts32-634Attribute 13	--
bsFunctionId	Name: bsFunctionId OID : ts32-634Attribute 14	--
aucFunctionId	Name: aucFunctionId OID : ts32-634Attribute 15	--
bgFunctionId	Name: bgFunctionId OID : ts32-634Attribute 16	--
eirFunctionId	Name: eirFunctionId OID : ts32-634Attribute 17	--
ggsnFunctionId	Name: ggsnFunctionId OID : ts32-634Attribute 18	--
hlrFunctionId	Name: hlrFunctionId OID : ts32-634Attribute 19	--
mscServerFunctionId	Name: mscServerFunctionId OID : ts32-634Attribute 20	--
vlrFunctionId	Name: vlrFunctionId OID : ts32-634Attribute 21	--
sgsnFunctionId	Name: sgsnFunctionId OID : ts32-634Attribute 22	--
smsGmscFunctionId	Name: smsGmscFunctionId OID : ts32-634Attribute 23	--
smsIwmscFunctionId	Name: smsIwmscFunctionId OID : ts32-634Attribute 24	--
gbLinkId	Name: gbLinkId OID : ts32-634Attribute 25	--
aLinkId	Name: aLinkId OID : ts32-634Attribute 26	--
iucsLinkId	Name: iucsLinkId OID : ts32-634Attribute 27	--
iupsLinkId	Name: iupsLinkId OID : ts32-634Attribute 28	--
iubcLinkId	Name: iubcLinkId OID : ts32-634Attribute 29	--
csMgwFunctionId	Name: csMgwFunctionId OID : ts32-634Attribute 30	--
gmscServerFunctionId	Name: gmscServerFunctionId OID : ts32-634Attribute 31	--
mccList	Name: mccList OID : ts32-634Attribute 32	--
mncList	Name: mncList OID : ts32-634Attribute 33	--
lacList	Name: lacList OID : ts32-634Attribute 34	--
sacList	Name: sacList OID : ts32-634Attribute 35	--
uraList	--	Name: uraList OID : ts32-634Attribute 36

gcaList	Name: gcaList OID : ts32-634Attribute 37	--
mscld	Name: mscld OID : ts32-634Attribute 38	--
mscServerFunction-GSMcell	Name: mscServerFunction-GSMcell OID : ts32-634Attribute 39	--
mscServerFunction-ExternalGSMcell	Name: mscServerFunction-ExternalGSMcell OID : ts32-634Attribute 40	--
mscServerFunction-CsMgwFunction	Name: mscServerFunction-CsMgwFunction OID : ts32-634Attribute 41	--
racList	Name: racList OID : ts32-634Attribute 42	--
sgsnld	Name: sgsnld OID : -634Attribute 43	--
sgsnFunction-GSMcell	Name: sgsnFunction-GSMcell OID : ts32-634Attribute 44	--
sgsnFunction-ExternalGSMcell	Name: sgsnFunction-ExternalGSMcell OID : ts32-634Attribute 45	--
connectedBss	Name: connectedBss OID : ts32-634Attribute 46	--
connectedRnc	Name: connectedRnc OID : ts32-634Attribute 47	--
csMgwFunction-MscServerFunction	Name: csMgwFunction-MscServerFunction OID : ts32-634Attribute 48	--
csMgwFunction-lucsLink	Name: csMgwFunction-lucsLink OID : ts32-634Attribute 49	--
csMgwFunction-Alink	Name: csMgwFunction-Alink OID : ts32-634Attribute 50	--
scscfFunctionId	Name: scscfFunctionId OID : ts32-634Attribute 51	--
pcscfFunctionId	Name: pcscfFunctionId OID : ts32-634Attribute 52	--
icscfFunctionId	Name: icscfFunctionId OID : ts32-634Attribute 53	--
slfFunctionId	Name: slfFunctionId OID : ts32-634Attribute 54	--
bgcfFunctionId	Name: bgcfFunctionId OID : ts32-634Attribute 55	--
mrfcFunctionId	Name: mrfcFunctionId OID : ts32-634Attribute 56	--
asFunctionId	Name: asFunctionId OID : ts32-634Attribute 57	--
mgcfFunctionId	Name: mgcfFunctionId OID : ts32-634Attribute 58	--
mrfpFunctionId	Name: mrfpFunctionId OID : ts32-634Attribute 59	--

Parameters

Name Bindings

smlcFunction-managedElement	Name: smlcFunction-managedElement OID : ts32-634NameBinding 1	--
gmlcFunction-managedElement	Name: gmlcFunction-managedElement OID : ts32-634NameBinding 2	--
scfFunction-managedElement	Name: scfFunction-managedElement OID : ts32-634NameBinding 3	--
srfFunction-managedElement	Name: srfFunction-managedElement OID : ts32-634NameBinding 4	--
cbcFunction-managedElement	Name: cbcFunction-managedElement OID : ts32-634NameBinding 5	--
cgfFunction-managedElement	Name: cgfFunction-managedElement OID : ts32-634NameBinding 6	--
mgwFunction-managedElement	--	Name: mgwFunction-managedElement OID : ts32-634NameBinding 7
imsMgwFunction-managedElement	Name: imsMgwFunction-managedElement OID : ts32-634NameBinding 70503	--
gmscFunction-managedElement	Name: gmscFunction-managedElement OID : ts32-634NameBinding 8	--
iwfFunction-managedElement	Name: iwfFunction-managedElement OID : ts32-634NameBinding 9	--

mntSrfFunction-managedElement	Name: mntSrfFunction-managedElement OID : ts32-634NameBinding 10	--
npdbFunction-managedElement	Name: npdbFunction-managedElement OID : ts32-634NameBinding 11	--
rSgwFunction-managedElement	Name: rSgwFunction-managedElement OID : ts32-634NameBinding 12	--
ssfFunction-managedElement	Name: ssfFunction-managedElement OID : ts32-634NameBinding 13	--
bsFunction-managedElement	Name: bsFunction-managedElement OID : ts32-634NameBinding 14	--
aucFunction-managedElement	Name: aucFunction-managedElement OID : ts32-634NameBinding 15	--
bgFunction-managedElement	Name: bgFunction-managedElement OID : ts32-634NameBinding 16	--
eirFunction-managedElement	Name: eirFunction-managedElement OID : ts32-634NameBinding 17	--
ggsnFunction-managedElement	Name: ggsnFunction-managedElement OID : ts32-634NameBinding 18	--
hlrFunction-managedElement	Name: hlrFunction-managedElement OID : ts32-634NameBinding 19	--
mscServerFunction-managedElement	Name: mscServerFunction-managedElement OID : ts32-634NameBinding 20	--
vlrFunction-managedElement	Name: vlrFunction-managedElement OID : ts32-634NameBinding 21	--
sgsnFunction-managedElement	Name: sgsnFunction-managedElement OID : ts32-634NameBinding 22	--
smsGmscFunction-managedElement	Name: smsGmscFunction-managedElement OID : ts32-634NameBinding 23	--
smslwmscFunction-managedElement	Name: smslwmscFunction-managedElement OID : ts32-634NameBinding 24	--
gbLink-managedElement	Name: gbLink-managedElement OID : ts32-634NameBinding 25	--
aLink-managedElement	Name: aLink-managedElement OID : ts32-634NameBinding 26	--
iucsLink-managedElement	Name: iucsLink-managedElement OID : ts32-634NameBinding 27	--
iupsLink-managedElement	Name: iupsLink-managedElement OID : ts32-634NameBinding 28	--
iubcLink-managedElement	Name: iubcLink-managedElement OID : ts32-634NameBinding 29	--
gmscServerFunction-managedElement	Name: gmscServerFunction-managedElement OID : ts32-634NameBinding 30	--
csMgwFunction-managedElement	Name: csMgwFunction-managedElement OID : ts32-634NameBinding 31	--
scscfFunction-managedElement	Name: scscfFunction-managedElement OID : ts32-634NameBinding 32	--
pcscfFunction-managedElement	Name: pcscfFunction-managedElement OID : ts32-634NameBinding 33	--
icscfFunction-managedElement	Name: icscfFunction-managedElement OID : ts32-634NameBinding 34	--
slfFunction-managedElement	Name: slfFunction-managedElement OID : ts32-634NameBinding 35	--
bgcfFunction-managedElement	Name: bgcfFunction-managedElement OID : ts32-634NameBinding 36	--
mrfcFunction-managedElement	Name: mrfcFunction-managedElement OID : ts32-634NameBinding 37	--
scscfFunction-managedElement	Name: scscfFunction-managedElement OID : ts32-634NameBinding 38	--
scscfFunction-managedElement	Name: scscfFunction-managedElement OID : ts32-634NameBinding 39	--
mrfpFunction-managedElement	Name: mrfpFunction-managedElement OID : ts32-634NameBinding 40	--

Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Jun 2001	S_12	SP-010283	--	--	Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0
Sep 2001	S_13	SP-010478	001	--	Correction due to TS renumbering	4.0.0	4.1.0
Sep 2002	--	--	--	--	Cosmetics/Styles	4.1.0	4.1.1
Dec 2002	S_18	SP-020749	002	--	Alignment of the CMIP SS with the Rel-5 version of the IS in 32.632	4.1.1	5.0.0
Dec 2003	S_22	SP-030642	003	--	Add notifications to functional objects - Align with 32.632 (IS)	5.0.0	5.1.0
Mar 2004	S_23	SP-040130	004	--	Removal of the attribute uraList from the MOC MscServerFunction – Alignment with the IS 32.632	5.1.0	5.2.0
Sep 2004	S_25	SP-040582	005	--	Correction of modelling of Media GateWay (MGW)	5.2.0	5.3.0
Sep 2004	S_25	SP-040591	006	--	Removal of the 3GPP Release# cross references in the GDMO section	5.2.0	5.3.0
Sep 2004	S_25	SP-040541	--	--	Automatic upgrade to Rel- 6 (no CR) as per request in SP-040541 SA5_presentation_SA_25.ppt (slide 17)	5.3.0	6.0.0
Mar 2005	S_27	SP-050047	009	--	Align with 32.632, regarding the IS template and UML repertoire	6.0.0	6.1.0
Mar 2005	S_27	SP-050047	010	--	Add the IMS objects - Align with 32.632 Configuration Management (CM); Core Network Resources IRP NRM	6.0.0	6.1.0

History

Document history		
V6.0.0	September 2004	Publication
V6.1.0	March 2005	Publication