

ETSI TS 132 644 V5.6.0 (2004-09)

Technical Specification

**Universal Mobile Telecommunications System (UMTS);
Telecommunication management;
Configuration Management (CM);
UTRAN network resources Integration Reference Point (IRP):
Common Management Information Protocol (CMIP)
Solution Set (SS)
(3GPP TS 32.644 version 5.6.0 Release 5)**



Reference

RTS/TSGS-0532644v560

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
3 Definitions, symbols and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Basic aspects	8
4.1 Architectural aspects	8
4.2 Mapping	8
4.2.1 Mapping of Information Object Classes	8
4.2.2 Mapping of Information Object Class Attributes.....	8
4.2.2.1 Attribute Mapping of the IOC <i>RncFunction</i>	8
4.2.2.2 Attribute Mapping of the IOC <i>NodeBFunction</i>	8
4.2.2.3 Attribute Mapping of the IOC <i>UtranCell</i>	9
4.2.2.4 Attribute Mapping of the IOC <i>IubLink</i>	9
4.2.2.5 Attribute Mapping of the IOC <i>UtranRelation</i>	9
4.2.2.6 Attribute Mapping of the IOC <i>ExternalUtranCell</i>	10
4.2.3 Mapping of Name Containments	10
5 GDMO Definitions.....	11
5.1 Managed Object Classes	11
5.1.1 <i>rncFunction</i>	11
5.1.2 <i>utranCell</i>	11
5.1.3 <i>utranRelation</i>	11
5.1.4 <i>externalUtranCell</i>	12
5.1.5 <i>iubLink</i>	12
5.1.6 <i>nodeBFunction</i>	12
5.2 Packages	12
5.2.1 <i>rncFunctionHandoverPackage</i>	12
5.2.2 <i>utranCellHandoverPackage</i>	13
5.2.3 <i>utranRelationBasicPackage</i>	13
5.2.4 <i>utranRelationAssociationPackage</i>	13
5.2.5 <i>externalUtranCellPackage</i>	13
5.2.6 <i>rncFunctionBasicPackage</i>	14
5.2.7 <i>utranCellBasicPackage</i>	14
5.2.8 <i>utranCellAssociationPackage</i>	14
5.2.9 <i>iubLinkBasicPackage</i>	14
5.2.10 <i>iubLinkAssociation</i>	15
5.2.11 <i>nodeBFunctionBasicPackage</i>	15
5.2.12 <i>nodeBFunctionAssociationPackage</i>	15
5.3 Attributes	15
5.3.1 <i>mcc</i>	15
5.3.2 <i>mnc</i>	15
5.3.3 <i>rncId</i>	16
5.3.4 <i>cId</i>	16
5.3.5 <i>localCellId</i>	16
5.3.6 <i>uarfcnUl</i>	16
5.3.7 <i>uarfcnDl</i>	16
5.3.8 <i>primaryScramblingCode</i>	17
5.3.9 <i>primaryCpichPower</i>	17

5.3.10	maximumTransmissionPower.....	17
5.3.11	primarySchPower	17
5.3.12	secondarySchPower	18
5.3.13	bchPower	18
5.3.14	lac.....	18
5.3.15	rac	18
5.3.16	sac	18
5.3.17	ura	19
5.3.18	utranRelationId	19
5.3.19	relationType	19
5.3.20	adjacentCell	19
5.3.21	externalUtranCellId	19
5.3.22	rncFunctionId.....	19
5.3.23	utranCellId	20
5.3.24	utranCell2iubLink.....	20
5.3.25	iubLinkId	20
5.3.26	iubLink2nodeBFunction	20
5.3.27	iubLink2utranCell.....	20
5.3.28	nodeBFunctionId	21
5.3.29	nodeB2iubLink	21
5.3.30	uraList	21
5.4	Name Binding	21
5.4.1	rncFunction - managedElement	21
5.4.2	nodeBFunction - managedElement.....	22
5.4.3	utranCell - rncFunction	22
5.4.4	utranRelation - utranCell	22
5.4.5	externalUtranCell - subNetwork	23
5.4.6	vsDataContainer - rncFunction	23
5.4.7	vsDataContainer - nodeBFunction.....	23
5.4.8	vsDataContainer - utranCell	23
5.4.9	vsDataContainer - utranRelation.....	23
5.4.10	iubLink - rncFunction	23
5.4.11	gsmRelation - utranCell	23
6	ASN.1 Definitions	25
Annex A (informative):	List of assigned Object Identifiers.....	26
Annex B (informative):	Change history	29
History		30

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; Configuration Management (CM), as identified below:

- 32.641: "UTRAN network resources Integration Reference Point (IRP): Requirements".
- 32.642: "UTRAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- 32.643: "UTRAN network resources Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
- 32.644: "UTRAN network resources Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".**
- 32.645: "UTRAN network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition".

The interface Itf-N, defined in 3GPP TS 32.102 [2], is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2].

1 Scope

The present document specifies the Common Management Information Protocol (CMIP) Solution Set (SS) for the UTRAN Network Resource Integration Reference Point (IRP): Network Resource Model defined in 3GPP TS 32.642 [4]. In detail:

- Clause 4 contains an introduction to some concepts that are the base for some specific aspects of the CMIP interfaces.
- Clause 5 contains the GDMO definitions for the Alarm Management over the CMIP interfaces
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

This Solution Set specification is related to 3GPP TS 32.642 V5.5.x.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.304: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".
- [4] 3GPP TS 32.642: "Telecommunication management; Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [5] ITU-T Recommendation X.710 (1991): "Common Management Information Service Definition for CCITT Applications".
- [6] ITU-T Recommendation X.721 (02/92): "Information Technology - Open Systems Interconnection – Structure of Management Information: Definition of Management Information".
- [7] ITU-T Recommendation X.730 (01/92): "Information Technology - Open Systems Interconnection – Systems Management: Object Management Function".
- [8] ITU-T Recommendation X.733 (02/92): "Information Technology - Open Systems Interconnection - Alarm Reporting Function".
- [9] ITU-T Recommendation M.3100 (07/95): "Maintenance Telecommunications Management Network – Generic Network Information Model".
- [10] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.600 [10] and 3GPP TS 32.642 [4] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CMIP	Common Management Information Protocol
DN	Distinguished Name
GDMO	Guidelines for the Definition of Managed Objects
IDL	Interface Definition Language
IEC	International Electro-technical Commission
ISO	International Standards Organization
MIB	Management Information Base
MIM	Management Information Model
MIT	Management Information Tree (or Naming Tree)
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NR	Network Resource
NRM	Network Resource Model
TMN	Telecommunications Management Network
UTRAN	Universal Terrestrial Radio Access Network

4 Basic aspects

4.1 Architectural aspects

A technology independent UTRAN network resource model is defined in 3GPP TS 32.642 [4] for 3G networks. This document provides an implementation of this UTRAN network resource model by using CMIP technology.

4.2 Mapping

The semantic of the UTRAN Network Resource Model is defined in 3GPP TS 32.642 [4]. The specification of the information object classes defined there is independent of any implementation technology and protocol. This clause maps these technology and protocol independent definitions onto the equivalencies of the CMIP Solution Set of the UTRAN Network Resource IRP.

4.2.1 Mapping of Information Object Classes

Table 1 maps the information object classes defined in the UTRAN Network Resource Model onto the equivalent MOCs of the CMIP Solution Set.

Table 1: Mapping of IOCs

IS IOC	CMIP SS MOC
RncFunction	rncFunctionR55
NodeBFunction	nodeBFunction
UtranCell	utranCellR55
IubLink	iubLink
UtranRelation	utranRelation
ExternalUtranCell	externalUtranCellR0506

4.2.2 Mapping of Information Object Class Attributes

This clause depicts the mapping of the attributes defined in 3GPP TS 32.642 [4] on the corresponding attributes of the CMIP Solution Set.

4.2.2.1 Attribute Mapping of the IOC *RncFunction*

Table 2: Attribute mapping of the IOC *RncFunction*

IS Attribute	CMIP SS Attribute	Qualifier
rncFunctionId	rncFunctionId	M
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M
mcc	mcc	M
mnc	mnc	M
rnclId	rnclIdR55	M

4.2.2.2 Attribute Mapping of the IOC *NodeBFunction*

Table 3: Attribute mapping of the IOC *NodeBFunction*

IS Attribute	CMIP SS Attribute	Qualifier
nodeBFunctionId	nodeBFunctionId	M
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M
nodeBFunction-IubLink	NodeBFunction2IubLink	M

4.2.2.3 Attribute Mapping of the IOC *UtranCell*Table 4: Attribute mapping of the IOC *UtranCell*

IS Attribute	CMIP SS Attribute	Qualifier
utranCellId	utranCellId	M
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M
cId	cIdR55	M
localCellId	localCellIdR55	M
uarfcnDI	uarfcnDI	M
uarfcnUI	uarfcnUI	M
primaryScramblingCode	primaryScramblingCode	M
primaryCpichPower	primaryCpichPower	M
maximumTransmissionPower	maximumTransmissionPower	M
primarySchPower	primarySchPower	M
secondarySchPower	secondarySchPower	M
bchPower	bchPower	M
lac	lac	M
rac	rac	M
sac	sac	M
uraList	uraList	M
utranCell-IubLink	utranCell2IubLink	M
operationalState	operationalState	O

4.2.2.4 Attribute Mapping of the IOC *IubLink*Table 5: Attribute mapping of the IOC *IubLink*

IS Attribute	CMIP SS Attribute	Qualifier
iubLinkId	iubLinkId	M
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M
iubLink-UtranCell	iubLink2utranCell	M
iubLink-NodeBFunction	iubLink2nodeBFunction	M

4.2.2.5 Attribute Mapping of the IOC *UtranRelation*Table 6: Attribute mapping of the IOC *UtranRelation*

IS Attribute	CMIP SS Attribute	Qualifier
utranRelationId	utranRelationId	M
adjacentCell	adjacentCell	M
uarfcnUI	uarfcnUI	O
uarfcnDI	uarfcnDI	O
primaryScramblingCode	primaryScramblingCode	O
primaryCpichPower	primaryCpichPower	O
lac	lac	O

4.2.2.6 Attribute Mapping of the IOC *ExternalUtranCell***Table 7: Attribute mapping of the IOC *ExternalUtranCell***

IS Attribute	CMIP SS Attribute	Qualifier
externalUtranCellId	externalUtranCellId	M
userLabel	userLabel	M
cId	cIdR55	M
mcc	mcc	M
mnc	mnc	M
rnclId	rnclIdR55	M
uarfcnUI	uarfcnUI	M
uarfcnDI	uarfcnDI	M
primaryScramblingCode	primaryScramblingCode	M
primaryCpichPower	primaryCpichPower	M
lac	lac	M
rac	rac	M

4.2.3 Mapping of Name Containments

Table 8: Mapping of name containments

IS Name Containment	CMIP SS Name Binding
rncFunction - managedElement	rncFunctionR55-managedElement
nodeBFunction - managedElement	nodeBFunction-managedElement
utranCell - rncFunction	utranCellR55-rncFunctionR55
utranRelation - utranCell	utranRelation-utranCellR55
externalUtranCell - subNetwork	externalUtranCellR0506-subNetwork
iubLink - rncFunction	iubLink-rncFunctionR55
gsmRelation - utranCell	gsmRelation-utranCellR55

5 GDMO Definitions

5.1 Managed Object Classes

5.1.1 rncFunction

```
rncFunctionR55 MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  rncFunctionBasicPackage,
  rncFunctionHandoverPackageR55,
  "3GPP TS 32.111-4 Release 5": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995": createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995": attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.";
REGISTERED AS {ts32-644ObjectClass 8};
```

5.1.2 utranCell

```
utranCellR55 MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  utranCellBasicPackage,
  utranCellHandoverPackageR55,
  utranCellAssociationPackage,
  "3GPP TS 32.111-4 Release 5": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995": createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995": attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.",
  "3GPP TS 32.674 Release 5": operationalStateAttributePackage
    PRESENT IF
      "instances of this MOC support the operationalState attribute.";
REGISTERED AS {ts32-644ObjectClass 9};
```

5.1.3 utranRelation

```
utranRelation MANAGED OBJECT CLASS
DERIVED FROM
  "Rec. X.721 | ISO/IEC 10165-2 : 1992": top;
CHARACTERIZED BY
  utranRelationBasicPackage,
  utranRelationAssociationPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995": createDeleteNotificationsPackage
    PRESENT IF
      "The objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995": attributeValueChangeNotificationPackage
    PRESENT IF
      "The attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.";
REGISTERED AS {ts32-644ObjectClass 3};
```

5.1.4 externalUtranCell

```
externalUtranCellR0506 MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  externalUtranCellPackageR0506;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.";
REGISTERED AS {ts32-644ObjectClass 40506};
```

5.1.5 iubLink

```
iubLink MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  iubLinkBasicPackage,
  iubLinkAssociationPackage,
  "3GPP TS 32.111-4 Release 5": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.";
REGISTERED AS {ts32-644ObjectClass 5};
```

5.1.6 nodeBFunction

```
nodeBFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  nodeBFunctionBasicPackage,
  nodeBFunctionAssociationPackage,
  "3GPP TS 32.111-4 Release 5": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.";
REGISTERED AS {ts32-644ObjectClass 6};
```

5.2 Packages

5.2.1 rncFunctionHandoverPackage

```
rncFunctionHandoverPackageR55 PACKAGE
BEHAVIOUR
  rncFunctionHandoverPackageR55Behaviour;
ATTRIBUTES
  mcc          GET-REPLACE,
  mnc          GET-REPLACE,
  rncIdR55     GET-REPLACE;
REGISTERED AS {ts32-644Package 14};
```

rncFunctionHandoverPackageR55Behaviour **BEHAVIOUR**

DEFINED AS

"This package contains all new attributes defined for UTRAN handover management.
These attributes are introduced in R4.";

5.2.2 utranCellHandoverPackage

utranCellHandoverPackageR55 **PACKAGE**

BEHAVIOUR

utranCellHandoverPackageR55Behaviour;

ATTRIBUTES

cIdR55	GET-REPLACE,
localCellIdR55	GET-REPLACE,
uarfcnUl	GET-REPLACE,
uarfcnDl	GET-REPLACE,
primaryScramblingCode	GET-REPLACE,
primaryCpichPower	GET-REPLACE,
maximumTransmissionPower	GET-REPLACE,
primarySchPower	GET-REPLACE,
secondarySchPower	GET-REPLACE,
bchPower	GET-REPLACE,
lac	GET-REPLACE,
rac	GET-REPLACE,
sac	GET-REPLACE,
uraList	GET-REPLACE;

REGISTERED AS {ts32-644Package 15};

utranCellHandoverPackageR55Behaviour **BEHAVIOUR**

DEFINED AS

"This package contains all new attributes defined for UTRAN handover management.
These attributes are introduced in R4.";

5.2.3 utranRelationBasicPackage

utranRelationBasicPackage **PACKAGE**

BEHAVIOUR

utranRelationBasicPackageBehaviour;

ATTRIBUTES

utranRelationId	GET,
uarfcnUl	GET,
uarfcnDl	GET,
primaryScramblingCode	GET,
primaryCpichPower	GET,
lac	GET;

REGISTERED AS {ts32-644Package 3};

utranRelationBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The 'UtranRelation' managed object contains radio network related parameters for the relation to the 'UtranCell' or 'ExternalUtranCell' managed object. Note: In handover relation terms, the cell containing the UTRAN Relation object is the source cell for the handover. The cell referred to in the UTRAN relation object is the target cell for the handover. This defines a one-way handover relation where the direction is from source cell to target cell.";

5.2.4 utranRelationAssociationPackage

utranRelationAssociationPackage **PACKAGE**

BEHAVIOUR

utranRelationAssociationPackageBehaviour;

ATTRIBUTES

adjacentCell	GET-REPLACE;
--------------	--------------

REGISTERED AS {ts32-644Package 4};

utranRelationAssociationPackageBehaviour **BEHAVIOUR**

DEFINED AS

"This package contains all attributes implementing associations related to an utranRelation";

5.2.5 externalUtranCellPackage

externalUtranCellPackageR0506 **PACKAGE**

BEHAVIOUR

externalUtranCellPackageBehaviour;

ATTRIBUTES

```

externalUtranCellId      GET,
cIdR55                   GET-REPLACE,
mcc                      GET-REPLACE,
mnc                      GET-REPLACE,
rncIdR55                 GET-REPLACE,
uarfcnUl                 GET-REPLACE,
uarfcnDl                 GET-REPLACE,
primaryScramblingCode    GET-REPLACE,
primaryCpichPower        GET-REPLACE,
lac                      GET-REPLACE,
rac                      GET-REPLACE;

```

```
REGISTERED AS {ts32-644Package 50506};
```

```
externalUtranCellPackageBehaviour BEHAVIOUR
```

DEFINED AS

```
"This Managed Object Class represents a radio cell controlled by another IRPagent. It a
necessary attribute for inter-system handover. This MOC is a subreplication of a MOC
in another NEM.";
```

5.2.6 rncFunctionBasicPackage

```
rncFunctionBasicPackage PACKAGE
```

BEHAVIOUR

```
rncFunctionBasicPackageBehaviour;
```

ATTRIBUTES

```
rncFunctionId      GET;
```

```
REGISTERED AS {ts32-644Package 6};
```

```
rncFunctionBasicPackageBehaviour BEHAVIOUR
```

DEFINED AS

```
"The MOC rncFunction represents UMTS RNC function.";
```

5.2.7 utranCellBasicPackage

```
utranCellBasicPackage PACKAGE
```

BEHAVIOUR

```
utranCellBasicPackageBehaviour;
```

ATTRIBUTES

```
utranCellId      GET;
```

```
REGISTERED AS {ts32-644Package 7};
```

```
utranCellBasicPackageBehaviour BEHAVIOUR
```

DEFINED AS

```
"This managed object class represents the radio cell controlled by a RNC.";
```

5.2.8 utranCellAssociationPackage

```
utranCellAssociationPackage PACKAGE
```

BEHAVIOUR

```
utranCellAssociationPackageBehaviour;
```

ATTRIBUTES

```
utranCell2iubLink      GET;
```

```
REGISTERED AS {ts32-644Package 8};
```

```
utranCellAssociationPackageBehaviour BEHAVIOUR
```

DEFINED AS

```
"This package contains the pointer attributes that implement associations related to utranCell.";
```

5.2.9 iubLinkBasicPackage

```
iubLinkBasicPackage PACKAGE
```

BEHAVIOUR

```
iubLinkBasicPackageBehaviour;
```

ATTRIBUTES

```
iubLinkId      GET;
```

```
REGISTERED AS {ts32-644Package 9};
```

```
iubLinkBasicPackageBehaviour BEHAVIOUR
```

DEFINED AS

```
"This managed object class models the Iub Link between a Node-B and a RNC.";
```

5.2.10 iubLinkAssociation

```
iubLinkAssociationPackage PACKAGE
  BEHAVIOUR
    iubLinkAssociationPackageBehaviour;
  ATTRIBUTES
    iubLink2nodeBFunction      GET,
    iubLink2utranCell          GET;
REGISTERED AS {ts32-644Package 10};

iubLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "The attribute 'iubLink2NodeBFunction' points to the nodeBFunction instance which this
  iubLink instance connects to. The attribute 'iubLink2utranCell' points to a list of
  utranCell instances which attach to the nodeBFunction this iubLink connects to.";
```

5.2.11 nodeBFunctionBasicPackage

```
nodeBFunctionBasicPackage PACKAGE
  BEHAVIOUR
    nodeBFunctionBasicPackageBehaviour;
  ATTRIBUTES
    nodeBFunctionId            GET;
REGISTERED AS {ts32-644Package 11};

nodeBFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "This managed object class represents the NodeB functionality.";
```

5.2.12 nodeBFunctionAssociationPackage

```
nodeBFunctionAssociationPackage PACKAGE
  BEHAVIOUR
    nodeBFunctionAssociationPackageBehaviour;
  ATTRIBUTES
    nodeB2iubLink              GET;
REGISTERED AS {ts32-644Package 12};

nodeBFunctionAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "The attribute 'nodeB2iubLink' points to the iubLink instance
  which connects to this nodeBFunction instance directly.";
```

5.3 Attributes

5.3.1 mcc

```
mcc ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-644TypeModule.MobileCountryCode;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mccBehaviour;
REGISTERED AS {ts32-644Attribute 1};

mccBehaviour BEHAVIOUR
DEFINED AS
  "Mobile Country Code, MCC. It is a part of the PLMN Id (Ref. 3 GPP TS 23.003).";
```

5.3.2 mnc

```
mnc ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-644TypeModule.MobileNetworkCode;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mncBehaviour;
REGISTERED AS {ts32-644Attribute 2};
```


mncBehaviour **BEHAVIOUR**

DEFINED AS

"Mobile Network Code, MNC. It is a part of the PLMN Id (Ref. 3 GPP TS 23.003).";

5.3.3 rncId

rncIdR55 **ATTRIBUTE**

WITH ATTRIBUTE SYNTAX

TS32-644TypeModule.RncId;

MATCHES FOR

EQUALITY;

BEHAVIOUR

rncIdR55Behaviour;

REGISTERED AS {ts32-644Attribute 31};

rncIdR55Behaviour **BEHAVIOUR**

DEFINED AS

"Unique RNC ID (Ref. 3 GPP TS 23.003).";

5.3.4 cId

cIdR55 **ATTRIBUTE**

WITH ATTRIBUTE SYNTAX

TS32-644TypeModule.CId;

MATCHES FOR

EQUALITY;

BEHAVIOUR

cIdR55Behaviour;

REGISTERED AS {ts32-644Attribute 32};

cIdR55Behaviour **BEHAVIOUR**

DEFINED AS

"cId is the identifier of a cell in one RNC (Ref. 3 GPP TS 25.401).";

5.3.5 localCellId

localCellIdR55 **ATTRIBUTE**

WITH ATTRIBUTE SYNTAX

TS32-644TypeModule.LocalCellId;

MATCHES FOR

EQUALITY;

BEHAVIOUR

localCellIdR55Behaviour;

REGISTERED AS {ts32-644Attribute 33};

localCellIdR55Behaviour **BEHAVIOUR**

DEFINED AS

"Local Cell id is used to uniquely identify the set of resources defined in a Node B to support a cell (as defined by a Cid Ref. 3 GPP TS 25.401). It must be unique in Node B at a minimum, but may be unique in UTRAN. It can be used to tie the cell in the RNC to a specific set of resources in the Node B.";

5.3.6 uarfcnUl

uarfcnUl **ATTRIBUTE**

WITH ATTRIBUTE SYNTAX

TS32-644TypeModule.UarfcnUl;

MATCHES FOR

EQUALITY;

BEHAVIOUR

uarfcnUlBehaviour;

REGISTERED AS {ts32-644Attribute 6};

uarfcnUlBehaviour **BEHAVIOUR**

DEFINED AS

"The UL UTRA absolute Radio Frequency Channel number, UARFCN (Ref. 3 GPP TS 25.433).";

5.3.7 uarfcnDl

uarfcnDl **ATTRIBUTE**

```

WITH ATTRIBUTE SYNTAX
  TS32-644TypeModule.UarfcnDl;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  uarfcnDlBehaviour;
REGISTERED AS {ts32-644Attribute 7};

uarfcnDlBehaviour BEHAVIOUR
DEFINED AS
  "The DL UTRA absolute Radio Frequency Channel number, UARFCN (Ref. 3 GPP TS 25.433).";

```

5.3.8 primaryScramblingCode

```

primaryScramblingCode ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-644TypeModule.PrimaryScramblingCode;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  primaryScramblingCodeBehaviour;
REGISTERED AS {ts32-644Attribute 8};

primaryScramblingCodeBehaviour BEHAVIOUR
DEFINED AS
  "The primary DL scrambling code used by the cell (Ref. 3 GPP TS 25.433).";

```

5.3.9 primaryCpichPower

```

primaryCpichPower ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-644TypeModule.PrimaryCpichPower;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  primaryCpichPowerBehaviour;
REGISTERED AS {ts32-644Attribute 9};

primaryCpichPowerBehaviour BEHAVIOUR
DEFINED AS
  "The power of the primary CPICH channel in the cell (Ref. 3 GPP TS 25.433).";

```

5.3.10 maximumTransmissionPower

```

maximumTransmissionPower ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-644TypeModule.MaximumTransmissionPower;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  maximumTransmissionPowerBehaviour;
REGISTERED AS {ts32-644Attribute 10};

maximumTransmissionPowerBehaviour BEHAVIOUR
DEFINED AS
  "The maximum transmission power of a cell, DL Power (Ref. 3 GPP TS 25.433).";

```

5.3.11 primarySchPower

```

primarySchPower ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-644TypeModule.PrimarySchPower;
MATCHES FOR
  EQUALITY;
BEHAVIOUR
  primarySchPowerBehaviour;
REGISTERED AS {ts32-644Attribute 11};

primarySchPowerBehaviour BEHAVIOUR
DEFINED AS
  "The power of the primary synchronisation channel in the cell, DL Power (Ref. 3 GPP TS 25.433).";

```

5.3.12 secondarySchPower

secondarySchPower **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
 TS32-644TypeModule.SecondarySchPower;
MATCHES FOR
 EQUALITY;
BEHAVIOUR
 secondarySchPowerBehaviour;
REGISTERED AS {ts32-644Attribute 12};

secondarySchPowerBehaviour **BEHAVIOUR**
DEFINED AS
 "The power of the secondary synchronisation channel in the cell,
 DL Power (Ref. 3 GPP TS 25.433).";

5.3.13 bchPower

bchPower **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
 TS32-644TypeModule.BchPower;
MATCHES FOR
 EQUALITY;
BEHAVIOUR
 bchPowerBehaviour;
REGISTERED AS {ts32-644Attribute 13};

bchPowerBehaviour **BEHAVIOUR**
DEFINED AS
 "The power of the broadcast channel in the cell (Ref. 3 GPP TS 25.433).";

5.3.14 lac

lac **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
 TS32-644TypeModule.LocationAreaCode;
MATCHES FOR
 EQUALITY;
BEHAVIOUR
 lacBehaviour;
REGISTERED AS {ts32-644Attribute 14};

lacBehaviour **BEHAVIOUR**
DEFINED AS
 "Location Area Code, LAC (Ref. 3 GPP TS 23.003)";

5.3.15 rac

rac **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
 TS32-644TypeModule.Rac;
MATCHES FOR
 EQUALITY;
BEHAVIOUR
 racBehaviour;
REGISTERED AS {ts32-644Attribute 15};

racBehaviour **BEHAVIOUR**
DEFINED AS
 "Routing Area Code, RAC (Ref. 3 GPP TS 23.003)";

5.3.16 sac

sac **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
 TS32-644TypeModule.Sac;
MATCHES FOR
 EQUALITY;
BEHAVIOUR
 sacBehaviour;
REGISTERED AS {ts32-644Attribute 16};

sacBehaviour **BEHAVIOUR**
DEFINED AS
"Service Area Code, RAC (Ref. 3 GPP TS 23.003)";

5.3.17 ura

Void.

5.3.18 utranRelationId

utranRelationId **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
TS32-644TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
utranRelationIdBehaviour;
REGISTERED AS {ts32-644Attribute 18};

utranRelationIdBehaviour **BEHAVIOUR**
DEFINED AS
"This attribute identifies an utranRelation object.";

5.3.19 relationType

Void.

5.3.20 adjacentCell

adjacentCell **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
TS32-644TypeModule.GeneralObjectPointer;
MATCHES FOR
EQUALITY;
BEHAVIOUR
adjacentCellBehaviour;
REGISTERED AS {ts32-644Attribute 20};

adjacentCellBehaviour **BEHAVIOUR**
DEFINED AS
"Pointer to UTRAN cell or external UTRAN cell. Distinguished name of the corresponding object.";

5.3.21 externalUtranCellId

externalUtranCellId **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
TS32-644TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
adjacentCellBehaviour;
REGISTERED AS {ts32-644Attribute 21};

externalUtranCellIdBehaviour **BEHAVIOUR**
DEFINED AS
"This attribute identifies an externalUtranCell object.";

5.3.22 rncFunctionId

rncFunctionId **ATTRIBUTE**
WITH ATTRIBUTE SYNTAX
TS32-644TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
rncFunctionIdBehaviour;
REGISTERED AS {ts32-644Attribute 22};

rncFunctionIdBehaviour **BEHAVIOUR**

DEFINED AS

"This attribute names an instance of the 'rncFunction' object class.";

5.3.23 utranCellId

utranCellId ATTRIBUTE**WITH ATTRIBUTE SYNTAX**

TS32-644TypeModule.GeneralObjectId;

MATCHES FOR

EQUALITY;

BEHAVIOUR

utranCellIdBehaviour;

REGISTERED AS {ts32-644Attribute 23};

utranCellIdBehaviour BEHAVIOUR**DEFINED AS**

"This attribute names an instance of the 'utranCell' object class.";

5.3.24 utranCell2iubLink

utranCell2iubLink ATTRIBUTE**WITH ATTRIBUTE SYNTAX**

TS32-644TypeModule.GeneralObjectPointer;

MATCHES FOR

EQUALITY;

BEHAVIOUR

utranCell2iubLinkBehaviour;

REGISTERED AS {ts32-644Attribute 24};

utranCell2iubLinkBehaviour BEHAVIOUR**DEFINED AS**

"This attribute points to the iubLink instance connecting to this utranCell.";

5.3.25 iubLinkId

iubLinkId ATTRIBUTE**WITH ATTRIBUTE SYNTAX**

TS32-644TypeModule.GeneralObjectId;

MATCHES FOR

EQUALITY;

BEHAVIOUR

iubLinkIdBehaviour;

REGISTERED AS {ts32-644Attribute 25};

iubLinkIdBehaviour BEHAVIOUR**DEFINED AS**

"This attribute names an instance of the 'iubLink' object class.";

5.3.26 iubLink2nodeBFunction

iubLink2nodeBFunction ATTRIBUTE**WITH ATTRIBUTE SYNTAX**

TS32-644TypeModule.GeneralObjectPointer;

MATCHES FOR

EQUALITY;

BEHAVIOUR

iubLink2nodeBFunctionBehaviour;

REGISTERED AS {ts32-644Attribute 26};

iubLink2nodeBFunctionBehaviour BEHAVIOUR**DEFINED AS**

"This attribute points to the nodeBFunction instance which this iubLink instance connects directly to.";

5.3.27 iubLink2utranCell

iubLink2utranCell ATTRIBUTE**WITH ATTRIBUTE SYNTAX**

TS32-644TypeModule.GeneralObjectPointerList;

MATCHES FOR

EQUALITY;

```

BEHAVIOUR
    iubLink2utranCellBehaviour;
REGISTERED AS {ts32-644Attribute 27};

iubLink2utranCellBehaviour BEHAVIOUR
DEFINED AS
    "This attribute points from an iubLink instance to a list of utranCell instance";

```

5.3.28 nodeBFunctionId

```

nodeBFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-644TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    nodeBFunctionIdBehaviour;
REGISTERED AS {ts32-644Attribute 28};

nodeBFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute names an instance of the 'nodeBFunction' object class.";

```

5.3.29 nodeB2iubLink

```

nodeB2iubLink ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-644TypeModule.GeneralObjectPointer;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    nodeB2iubLinkBehaviour;
REGISTERED AS {ts32-644Attribute 29};

nodeB2iubLinkBehaviour BEHAVIOUR
DEFINED AS
    "This attribute points to the IubLink instance which connects to the
    related nodeBFunction instance directly.";

```

5.3.30 uraList

```

uraList ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-644TypeModule.UraList;
MATCHES FOR
    EQUALITY;
BEHAVIOUR
    uraListBehaviour;
REGISTERED AS {ts32-644Attribute 30};

uraListBehaviour BEHAVIOUR
DEFINED AS
    "List of UTRAN Registration Area, URA (Ref. 3 GPP TS 25.331)";

```

5.4 Name Binding

5.4.1 rncFunction - managedElement

```

rncFunctionR55-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
    rncFunctionR55;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624 Release 5": managedElement;
WITH ATTRIBUTE
    rncFunctionId;
BEHAVIOUR
    rncFunctionR55-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;

```

REGISTERED AS {ts32-644NameBinding 15};

rncFunctionR55-managedElementBehaviour **BEHAVIOUR**
DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls a rncFunctionR55. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.4.2 nodeBFunction - managedElement

nodeBFunction-managedElement **NAME BINDING**
SUBORDINATE OBJECT CLASS

nodeBFunction;

NAMED BY SUPERIOR OBJECT CLASS

"3GPP TS 32.624 Release 5": managedElement;

WITH ATTRIBUTE

nodeBFunctionId;

BEHAVIOUR

nodeBFunction-managedElementBehaviour;

CREATE

WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE

ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-644NameBinding 2};

nodeBFunction-managedElementBehaviour **BEHAVIOUR**
DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls a nodeBFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.4.3 utranCell - rncFunction

utranCellR55-rncFunctionR55 **NAME BINDING**

SUBORDINATE OBJECT CLASS

utranCellR55;

NAMED BY SUPERIOR OBJECT CLASS

rncFunctionR55;

WITH ATTRIBUTE

utranCellId;

BEHAVIOUR

utranCellR55-rncFunctionR55Behaviour;

CREATE

WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE

ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-644NameBinding 17};

utranCellR55-rncFunctionR55Behaviour **BEHAVIOUR**
DEFINED AS

"The name binding represents a relationship in which a rncFunctionR55 contains and controls an utranCellR55. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.4.4 utranRelation - utranCell

utranRelation-utranCellR55 **NAME BINDING**

SUBORDINATE OBJECT CLASS

utranRelation;

NAMED BY SUPERIOR OBJECT CLASS

utranCellR55;

WITH ATTRIBUTE

utranRelationId;

BEHAVIOUR

utranRelation-utranCellR55Behaviour;

CREATE

WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE

ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-644NameBinding 18};

utranRelation-utranCellR55Behaviour **BEHAVIOUR**
DEFINED AS

"The name binding represents a relationship in which an utranCellR55 contains

and controls an utranRelation. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.4.5 externalUtranCell - subNetwork

```
externalUtranCellR0506-subNetwork NAME BINDING
  SUBORDINATE OBJECT CLASS
    externalUtranCellR0506;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624 Release 5": subNetwork;
  WITH ATTRIBUTE
    externalUtranCellId;
  BEHAVIOUR
    externalUtranCellR0506-subNetworkBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-644NameBinding 50506};
```

```
externalUtranCellR0506-subNetworkBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a subNetwork contains
  and controls an externalUtranCellR0506. When automatic instance naming is used, the choice
  of name bindings is left as a local matter.";
```

5.4.6 vsDataContainer - rncFunction

Void.

5.4.7 vsDataContainer - nodeBFunction

Void.

5.4.8 vsDataContainer - utranCell

Void.

5.4.9 vsDataContainer - utranRelation

Void.

5.4.10 iubLink - rncFunction

```
iubLink-rncFunctionR55 NAME BINDING
  SUBORDINATE OBJECT CLASS
    iubLink;
  NAMED BY SUPERIOR OBJECT CLASS
    rncFunctionR55;
  WITH ATTRIBUTE
    iubLinkId;
  BEHAVIOUR
    iubLink-rncFunctionR55Behaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-644NameBinding 16};
```

```
iubLink-rncFunctionR55Behaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a rncFunctionR55 contains
  and controls a iubLink. When automatic instance naming is used, the choice
  of name bindings left as a local matter.";
```

5.4.11 gsmRelation - utranCell

```
gsmRelation-utranCellR55 NAME BINDING
```



```
SUBORDINATE OBJECT CLASS
  "3GPP TS 32.654 Release 5": gsmRelation;
NAMED BY SUPERIOR OBJECT CLASS
  utranCellR55;
WITH ATTRIBUTE
  "3GPP TS 32.654 Release 5": gsmRelationId;
BEHAVIOUR
  gsmRelation-utranCellR55Behaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-644NameBinding 19};

gsmRelation-utranCellR55Behaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which an utranCellR55 contains
  and controls a gsmRelation. When automatic instance naming is used, the choice
  of name bindings left as a local matter.";
```

6 ASN.1 Definitions

```
TS32-644TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0) umts-Operation-
Maintenance(3) ts32-644(644) informationModel(0) asn1Module(2) version1(1)}
```

```
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
```

```
--EXPORTS everything
```

```
IMPORTS
```

```
GeneralObjectId, GeneralObjectPointer, GeneralObjectPointerList
FROM TS32-624TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0)
umts-Operation-Maintenance(3) ts32-624(624) informationModel(0) asn1Module(2) version1(1)}
```

```
MobileCountryCode, MobileNetworkCode, LocationAreaCode
FROM GSM1220TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0)
gsm-Operation-Maintenance(3) gsm-12-20(20) informationModel(0) asn1Module(2)
asn1TypeModule(0)};
```

```
-- 3GPP TS 32.644 related Object Identifiers
```

```
baseNodeUMTS OBJECT IDENTIFIER ::= {itu-t(0) identified-organization(4) etsi(0)
mobileDomain(0) umts-Operation-Maintenance(3)}
```

```
ts32-644 OBJECT IDENTIFIER ::= {baseNodeUMTS ts32-644(644)}
ts32-644InfoModel OBJECT IDENTIFIER ::= {ts32-644 informationModel(0)}
```

```
ts32-644ObjectClass OBJECT IDENTIFIER ::= {ts32-644InfoModel managedObjectClass(3)}
ts32-644Package OBJECT IDENTIFIER ::= {ts32-644InfoModel package(4)}
ts32-644Parameter OBJECT IDENTIFIER ::= {ts32-644InfoModel parameter(5)}
ts32-644NameBinding OBJECT IDENTIFIER ::= {ts32-644InfoModel nameBinding(6)}
ts32-644Attribute OBJECT IDENTIFIER ::= {ts32-644InfoModel attribute(7)}
ts32-644Action OBJECT IDENTIFIER ::= {ts32-644InfoModel action(9)}
ts32-644Notification OBJECT IDENTIFIER ::= {ts32-644InfoModel notification(10)}
```

```
-- Start of 3GPP SA5 own definitions
```

```
BchPower ::= INTEGER
```

```
CId ::= INTEGER
```

```
Lac ::= INTEGER
```

```
LocalCellId ::= INTEGER
```

```
MaximumTransmissionPower ::= INTEGER
```

```
PrimaryCpichPower ::= INTEGER
```

```
PrimarySchPower ::= INTEGER
```

```
PrimaryScramblingCode ::= INTEGER
```

```
Rac ::= INTEGER
```

```
RncId ::= INTEGER
```

```
Sac ::= INTEGER
```

```
SecondarySchPower ::= INTEGER
```

```
UarfcnDL ::= INTEGER
```

```
UarfcnUL ::= INTEGER
```

```
UraList ::= SET OF INTEGER
```

```
END -- of TS32-644TypeModule
```

Annex A (informative): List of assigned Object Identifiers

This annex provides a list with all Object Identifiers (OIDs) that have been assigned in TS 32.644 up to the latest version of Release 5. These OIDs shall not be assigned to new objects.

Basic Object Name	Name and OID of the current TS Version	Name and OIDs of previous TS Versions
Managed Object Classes		
rncFunction	Name: rncFunctionR55 OID : ts32-644ObjectClass 8	Name: rncFunction OID : ts32-644ObjectClass 1
utranCell	Name: utranCellR55 OID : ts32-644ObjectClass 9	Name: utranCellR54 OID : ts32-644ObjectClass 7 Name: utranCell OID : ts32-644ObjectClass 2
utranRelation	Name: utranRelation OID : ts32-644ObjectClass 3	--
externalUtranCell	Name: externalUtranCellR0506 OID : ts32-644ObjectClass 40506	Name: externalUtranCell OID : ts32-644ObjectClass 4
iubLink	Name: iubLink OID : ts32-644ObjectClass 5	--
nodeBFunction	Name: nodeBFunction OID : ts32-644ObjectClass 6	--
Packages		
rncFunctionHandoverPackage	Name: rncFunctionHandoverPackageR55 OID : ts32-644Package 14	Name: rncFunctionHandoverPackage OID : ts32-644Package 1
utranCellHandoverPackage	Name: utranCellHandoverPackageR55 OID : ts32-644Package 15	Name: utranCellHandoverPackageR54 OID : ts32-644Package 13 Name: utranCellHandoverPackage OID : ts32-644Package 2
utranRelationBasicPackage	Name: utranRelationBasicPackage OID : ts32-644Package 3	--
utranRelationAssociationPackage	Name: utranRelationAssociationPackage OID : ts32-644Package 4	--
externalUtranCellPackage	Name: externalUtranCellPackageR0506 OID : ts32-644Package 50506	Name: externalUtranCellPackage OID : ts32-644Package 5
rncFunctionBasicPackage	Name: rncFunctionBasicPackage OID : ts32-644Package 6	--
utranCellBasicPackage	Name: utranCellBasicPackage OID : ts32-644Package 7	--
utranCellAssociationPackage	Name: utranCellAssociationPackage OID : ts32-644Package 8	--
iubLinkBasicPackage	Name: iubLinkBasicPackage OID : ts32-644Package 9	--
iubLinkAssociationPackage	Name: iubLinkAssociationPackage OID : ts32-644Package 10	--
nodeBFunctionBasicPackage	Name: nodeBFunctionBasicPackage OID : ts32-644Package 11	--
nodeBFunctionAssociationPackage	Name: nodeBFunctionAssociationPackage OID : ts32-644Package 12	--
Actions		
Notifications		
Attributes		
mcc	Name: mcc OID : ts32-644Attribute 1	--
mnc	Name: mnc OID : ts32-644Attribute 2	--
rnclId	Name: rnclIdR55 OID : ts32-644Attribute 31	Name: rnclId OID : ts32-644Attribute 3

cld	Name: cldR55 OID : ts32-644Attribute 32	Name: cld OID : ts32-644Attribute 4
localCellId	Name: localCellIdR55 OID : ts32-644Attribute 33	Name: localCellId OID : ts32-644Attribute 5
uarfcnUI	Name: uarfcnUI OID : ts32-644Attribute 6	--
uarfcnDI	Name: uarfcnDI OID : ts32-644Attribute 7	--
primaryScramblingCode	Name: primaryScramblingCode OID : ts32-644Attribute 8	--
primaryCpichPower	Name: primaryCpichPower OID : ts32-644Attribute 9	--
maximumTransmissionPower	Name: maximumTransmissionPower OID : ts32-644Attribute 10	--
primarySchPower	Name: primarySchPower OID : ts32-644Attribute 11	--
secondarySchPower	Name: secondarySchPower OID : ts32-644Attribute 12	--
bchPower	Name: bchPower OID : ts32-644Attribute 13	--
lac	Name: lac OID : ts32-644Attribute 14	--
rac	Name: rac OID : ts32-644Attribute 15	--
sac	Name: sac OID : ts32-644Attribute 16	--
ura	--	Name: ura OID : ts32-644Attribute 17
utranRelationId	Name: utranRelationId OID : ts32-644Attribute 18	--
relationType	--	Name: relationType OID : ts32-644Attribute 19
adjacentCell	Name: adjacentCell OID : ts32-644Attribute 20	--
externalUtranCellId	Name: externalUtranCellId OID : ts32-644Attribute 21	--
rncFunctionId	Name: rncFunctionId OID : ts32-644Attribute 22	--
utranCellId	Name: utranCellId OID : ts32-644Attribute 23	--
utranCell2iubLink	Name: utranCell2iubLink OID : ts32-644Attribute 24	--
iubLinkId	Name: iubLinkId OID : ts32-644Attribute 25	--
iubLink2nodeBFunction	Name: iubLink2nodeBFunction OID : ts32-644Attribute 26	--
iubLink2utranCell	Name: iubLink2utranCell OID : ts32-644Attribute 27	--
nodeBFunctionId	Name: nodeBFunctionId OID : ts32-644Attribute 28	--
nodeB2iubLink	Name: nodeB2iubLink OID : ts32-644Attribute 29	--
uraList	Name: uraList OID : ts32-644Attribute 30	--

Parameters

Name Bindings

rncFunction-managedElement	Name: rncFunctionR55-managedElement OID : ts32-644NameBinding 15	Name: rncFunction-managedElement OID : ts32-644NameBinding 1
nodeBFunction-managedElement	Name: nodeBFunction-managedElement OID : ts32-644NameBinding 2	--
utranCell-rncFunction	Name: utranCellR55-rncFunctionR55 OID : ts32-644NameBinding 17	Name: utranCellR54-rncFunction OID : ts32-644NameBinding 12 Name: utranCell-rncFunction OID : ts32-644NameBinding 3

utranRelation-utranCell	Name: utranRelation-utranCellR55 OID : ts32-644NameBinding 18	Name: utranRelation-utranCellR54 OID : ts32-644NameBinding 13 Name: utranRelation-utranCell OID : ts32-644NameBinding 4
externalUtranCell - subNetwork	Name: externalUtranCellR0506- subNetwork OID : ts32-644NameBinding 50506	Name: externalUtranCell-subNetwork OID : ts32-644NameBinding 5
vsDataContainer-rncFunction	--	Name: vsDataContainer-rncFunction OID : ts32-644NameBinding 6
vsDataContainer-nodeBFunction	--	Name: vsDataContainer- nodeBFunction OID : ts32-644NameBinding 7
vsDataContainer-utranCell	--	Name: vsDataContainer-utranCell OID : ts32-644NameBinding 8
vsDataContainer-utranRelation	--	Name: vsDataContainer-utranRelation OID : ts32-644NameBinding 9
iubLink-rncFunction	Name: iubLink-rncFunctionR55 OID : ts32-644NameBinding 16	Name: iubLink-rncFunction OID : ts32-644NameBinding 10
gsmRelation-utranCell	Name: gsmRelation-utranCellR55 OID : ts32-644NameBinding 19	Name: gsmRelation-utranCellR54 OID : ts32-644NameBinding 14 Name: gsmRelation-utranCell OID : ts32-644NameBinding 11

Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Jun 2001	S_12	SP-010283	--	--	Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0
Sep 2001	S_13	SP-010478	001	--	Correction due to TS renumbering	4.0.0	4.1.0
Sep 2002	--	--	--	--	Cosmetics/Styles	4.1.0	4.1.1
Dec 2002	S_18	SP-020749	007	--	Alignment of the CMIP SS with the Rel-5 version of the IS in 32.642	4.1.1	5.0.0
Jun 2003	S_20	SP-030283	003	--	Removal of relationType	5.0.0	5.1.0
Sep 2003	S_21	SP-030420	004	--	Correction of wrong attribute name	5.1.0	5.2.0
Dec 2003	S_22	SP-030646	009	--	Correction of the number of possible URAs from 1 to 8	5.2.0	5.3.0
Dec 2003	S_22	SP-030642	010	--	Add notifications to functional objects - Align with 32.642 (IS)	5.2.0	5.3.0
Mar 2004	S_23	SP-040132	011	--	Correction of OIDs of the MOCs, packages and attributes affected by the change from ura to uraList	5.3.0	5.4.0
Jun 2004	S_24	SP-040255	012	--	Correction of type of the attributes cld, localCellId and rncld	5.4.0	5.5.0
Jun 2004	S_24	SP-040254	013	--	The specification does not support all UMTS frequency bands	5.4.0	5.5.0
Sep 2004	S_25	SP-040591	014	--	Correction of the types of the attributes cld, localCellId and rncld	5.5.0	5.6.0

History

Document history		
V5.0.0	December 2002	Publication
V5.1.0	June 2003	Publication
V5.2.0	September 2003	Publication
V5.3.0	December 2003	Publication
V5.4.0	March 2004	Publication
V5.5.0	June 2004	Publication
V5.6.0	September 2004	Publication