

ETSI TS 136 307 V10.16.0 (2015-10)



**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
Requirements on User Equipments (UEs)
supporting a release-independent frequency band
(3GPP TS 36.307 version 10.16.0 Release 10)**



Reference

RTS/TSGR-0436307vag0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	18
1 Scope	19
2 References	19
3 Definitions and Abbreviations.....	20
3.1 Definitions	20
3.2 Abbreviations	20
3A General	20
4 Void.....	20
5 Void.....	20
6 Void.....	20
7 Void.....	21
8 Void.....	21
9 Void.....	21
10 Void.....	21
11 Void.....	21
12 Void.....	21
13 Void.....	21
14 Void.....	21
15 Band 26 Independent of Release	21
15.1 Band 26 UE	21
15.1.1 RF Requirements	21
15.1.2 RRM Requirements	22
15.1.3 Void	22
16 Band 27 Independent of Release	22
16.1 Band 27 UE	22
16.1.1 RF Requirements	22
16.1.2 RRM Requirements	22
16.1.3 Void	22
17 Band 28 Independent of Release	22
17.1 Band 28 UE	22
17.1.1 RF Requirements	22
17.1.2 RRM Requirements	23
17.1.3 Void	23
18 Band 44 Independent of Release	23
18.1 Band 44 UE	23
18.1.1 RF Requirements	23
18.1.2 RRM Requirements	23
18.1.3 Void	23
19 CA configuration CA_41C Independent of Release	23
19.1 Band 41 UE	23

19.1.1	RF Requirements	23
19.1.2	RRM Requirements	24
19.1.3	Demodulation performance and CSI reporting Requirements	24
20	CA configuration CA_1A-19A Independent of Release	24
20.1	CA_1A-19A UE	24
20.1.1	RF Requirements	24
20.1.2	RRM Requirements	24
20.1.3	Demodulation performance and CSI reporting Requirements	24
21	CA configuration CA_7C Independent of Release	24
21.1	CA_7C UE	25
21.1.1	RF Requirements	25
21.1.2	RRM Requirements	25
21.1.3	Demodulation performance and CSI reporting Requirements	25
22	CA configuration CA_38C Independent of Release	25
22.1	Band 38 UE	25
22.1.1	RF Requirements	25
22.1.2	RRM Requirements	25
22.1.3	Demodulation performance and CSI reporting Requirements	25
23	CA configuration CA_1A-18A Independent of Release	26
23.1	CA_1A-18A UE	26
23.1.1	RF Requirements	26
23.1.2	RRM Requirements	26
23.1.3	Demodulation performance and CSI reporting Requirements	26
24	CA configuration CA_1A-21A Independent of Release	26
24.1	CA_1A-21A UE	26
24.1.1	RF Requirements	26
24.1.2	RRM Requirements	27
24.1.3	Demodulation performance and CSI reporting Requirements	27
25	CA configuration CA_3A-5A Independent of Release	27
25.1	CA_3A-5A UE	27
25.1.1	RF Requirements	27
25.1.2	RRM Requirements	27
25.1.3	Demodulation performance and CSI reporting Requirements	27
26	CA configuration CA_3A-7A Independent of Release	27
26.1	CA_3A-7A UE	27
26.1.1	RF Requirements	28
26.1.2	RRM Requirements	28
26.1.3	Demodulation performance and CSI reporting Requirements	28
27	CA configuration CA_3A-20A Independent of Release	28
27.1	CA_3A-20A UE	28
27.1.1	RF Requirements	28
27.1.2	RRM Requirements	28
27.1.3	Demodulation performance and CSI reporting Requirements	28
28	CA configuration CA_7A-20A Independent of Release	29
28.1	CA_7A-20A UE	29
28.1.1	RF Requirements	29
28.1.2	RRM Requirements	29
28.1.3	Demodulation performance and CSI reporting Requirements	29
29	CA configuration CA_8A-20A Independent of Release	29
29.1	CA_8A-20A UE	29
29.1.1	RF Requirements	29
29.1.2	RRM Requirements	30
29.1.3	Demodulation performance and CSI reporting Requirements	30
30	CA configuration CA_2A-17A Independent of Release	30
30.1	CA_2A-17A UE	30

30.1.1	RF Requirements	30
30.1.2	RRM Requirements	30
30.1.3	Demodulation performance and CSI reporting Requirements	30
31	CA configuration CA_2A-29A Independent of Release	30
31.1	CA_2A-29A UE	30
31.1.1	RF Requirements	31
31.1.2	RRM Requirements	31
31.1.3	Demodulation performance and CSI reporting Requirements	31
32	CA configuration CA_4A-29A Independent of Release	31
32.1	CA_4A-29A UE	31
32.1.1	RF Requirements	31
32.1.2	RRM Requirements	31
32.1.3	Demodulation performance and CSI reporting Requirements	31
33	CA configuration CA_3A-8A Independent of Release	32
33.1	CA_3A-8A UE	32
33.1.1	RF Requirements	32
33.1.2	RRM Requirements	32
33.1.3	Demodulation performance and CSI reporting Requirements	32
34	CA configuration CA_4A-5A Independent of Release	32
34.1	CA_4A-5A UE	32
34.1.1	RF Requirements	32
34.1.2	RRM Requirements	32
34.1.3	Demodulation performance and CSI reporting Requirements	33
35	CA configuration CA_4A-12A Independent of Release	33
35.1	CA_4A-12A UE	33
35.1.1	RF Requirements	33
35.1.2	RRM Requirements	33
35.1.3	Demodulation performance and CSI reporting Requirements	33
36	CA configuration CA_4A-13A Independent of Release	33
36.1	CA_4A-13A UE	33
36.1.1	RF Requirements	33
36.1.2	RRM Requirements	34
36.1.3	Demodulation performance and CSI reporting Requirements	34
37	CA configuration CA_4A-17A Independent of Release	34
37.1	CA_4A-17A UE	34
37.1.1	RF Requirements	34
37.1.2	RRM Requirements	34
37.1.3	Demodulation performance and CSI reporting Requirements	34
38	CA configuration CA_5A-12A Independent of Release	34
38.1	CA_5A-12A UE	35
38.1.1	RF Requirements	35
38.1.2	RRM Requirements	35
38.1.3	Demodulation performance and CSI reporting Requirements	35
39	CA configuration CA_5A-17A Independent of Release	35
39.1	CA_5A-17A UE	35
39.1.1	RF Requirements	35
39.1.2	RRM Requirements	35
39.1.3	Demodulation performance and CSI reporting Requirements	35
40	CA configuration CA_4A-7A Independent of Release	36
40.1	CA_4A-7A UE	36
40.1.1	RF Requirements	36
40.1.2	RRM Requirements	36
40.1.3	Demodulation performance and CSI reporting Requirements	36
41	CA configuration CA_11A-18A Independent of Release	36
41.1	CA_11A-18A UE	36

41.1.1	RF Requirements	36
41.1.2	RRM Requirements	36
41.1.3	Demodulation performance and CSI reporting Requirements	37
42	Band 30 Independent of Release	37
42.1	Band 30 UE	37
42.1.1	RF Requirements	37
42.1.2	RRM Requirements	37
42.1.3	Void	37
43	Band 31 Independent of Release	37
43.1	Band 31 UE	37
43.1.1	RF Requirements	37
43.1.2	RRM Requirements	37
43.1.3	Demodulation performance and CSI reporting Requirements	38
44	CA configuration CA_1A-8A Independent of Release	38
44.1	CA_1A-8A UE	38
44.1.1	RF Requirements	38
44.1.2	RRM Requirements	38
44.1.3	Demodulation performance and CSI reporting Requirements	38
45	CA configuration CA_2A-13A Independent of Release	39
45.1	CA_2A-13A UE	39
45.1.1	RF Requirements	39
45.1.2	RRM Requirements	39
45.1.3	Demodulation performance and CSI reporting Requirements	39
46	CA configuration CA_3A-19A Independent of Release	39
46.1	CA_3A-19A UE	39
46.1.1	RF Requirements	39
46.1.2	RRM Requirements	40
46.1.3	Demodulation performance and CSI reporting Requirements	40
47	CA configuration CA_3A-26A Independent of Release	40
47.1	CA_3A-26A UE	40
47.1.1	RF Requirements	40
47.1.2	RRM Requirements	40
47.1.3	Demodulation performance and CSI reporting Requirements	40
48	CA configuration CA_3A-28A Independent of Release	40
48.1	CA_3A-28A UE	40
48.1.1	RF Requirements	41
48.1.2	RRM Requirements	41
48.1.3	Demodulation performance and CSI reporting Requirements	41
49	CA configuration CA_19A-21A Independent of Release	41
49.1	CA_19A-21A UE	41
49.1.1	RF Requirements	41
49.1.2	RRM Requirements	41
49.1.3	Demodulation performance and CSI reporting Requirements	41
50	CA configuration CA_23A-29A Independent of Release	42
50.1	CA_23A-29A UE	42
50.1.1	RF Requirements	42
50.1.2	RRM Requirements	42
50.1.3	Demodulation performance and CSI reporting Requirements	42
51	Void	42
52	CA configuration CA_3C Independent of Release	42
52.1	CA_3C UE	42
52.1.1	RF Requirements	42
52.1.2	RRM Requirements	43
52.1.3	Demodulation performance and CSI reporting Requirements	43

53	CA configuration CA_1A-26A Independent of Release	43
53.1	CA_1A-26A UE	43
53.1.1	RF Requirements	43
53.1.2	RRM Requirements	43
53.1.3	Demodulation performance and CSI reporting Requirements	43
54	CA configuration CA_2A-4A Independent of Release	43
54.1	CA_2A-4A UE	43
54.1.1	RF Requirements	44
54.1.2	RRM Requirements	44
54.1.3	Demodulation performance and CSI reporting Requirements	44
55	CA configuration CA_2A-5A Independent of Release	44
55.1	CA_2A-5A UE	44
55.1.1	RF Requirements	44
55.1.2	RRM Requirements	44
55.1.3	Demodulation performance and CSI reporting Requirements	44
56	CA configuration CA_23B Independent of Release	44
56.1	CA_23B UE	45
56.1.1	RF Requirements	45
56.1.2	RRM Requirements	45
56.1.3	Demodulation performance and CSI reporting Requirements	45
57	A configuration CA_27B Independent of Release	45
57.1	CA_27B UE	45
57.1.1	RF Requirements	45
57.1.2	RRM Requirements	45
57.1.3	Demodulation performance and CSI reporting Requirements	45
58	CA configuration CA_2A-12A Independent of Release	46
58.1	CA_2A-12A UE	46
58.1.1	RF Requirements	46
58.1.2	RRM Requirements	46
58.1.3	Demodulation performance and CSI reporting Requirements	46
59	CA configuration CA_5A-7A Independent of Release	46
59.1	CA_5A-7A UE	46
59.1.1	RF Requirements	46
59.1.2	RRM Requirements	47
59.1.3	Demodulation performance and CSI reporting Requirements	47
60	CA configuration CA_5A-25A Independent of Release	47
60.1	CA_5A-25A UE	47
60.1.1	RF Requirements	47
60.1.2	RRM Requirements	47
60.1.3	Demodulation performance and CSI reporting Requirements	47
61	CA configuration CA_7A-28A Independent of Release	47
61.1	CA_7A-28A UE	48
61.1.1	RF Requirements	48
61.1.2	RRM Requirements	48
61.1.3	Demodulation performance and CSI reporting Requirements	48
62	CA configuration CA_12A-25A Independent of Release	48
62.1	CA_12A-25A UE	48
62.1.1	RF Requirements	48
62.1.2	RRM Requirements	48
62.1.3	Demodulation performance and CSI reporting Requirements	48
63	Void.....	49
64	Void.....	49
65	Void.....	49

66	CA configuration CA_3A-27A Independent of Release	49
66.1	CA_3A-27A UE	49
66.1.1	RF Requirements	49
66.1.2	RRM Requirements	49
66.1.3	Demodulation performance and CSI reporting Requirements	49
67	CA configuration CA_39C Independent of Release	49
67.1	CA_39C UE	49
67.1.1	RF Requirements	50
67.1.2	RRM Requirements	50
67.1.3	Demodulation performance and CSI reporting Requirements	50
68	CA configuration CA_39A-41A Independent of Release	50
68.1	CA_39A-41A UE	50
68.1.1	RF Requirements	50
68.1.2	RRM Requirements	50
68.1.3	Demodulation performance and CSI reporting Requirements	50
69	Band 14 Class 1 HPUE Independent of Release	50
69.1	Band 14 HPUE	51
69.1.1	RF Requirements	51
70	CA configuration CA_1A-5A Independent of Release	51
70.1	CA_1A-5A UE	51
70.1.1	RF Requirements	51
70.1.2	RRM Requirements	51
70.1.3	Demodulation performance and CSI reporting Requirements	51
71	CA configuration CA_1A-11A Independent of Release	51
71.1	CA_1A-11A UE	51
71.1.1	RF Requirements	52
71.1.2	RRM Requirements	52
71.1.3	Demodulation performance and CSI reporting Requirements	52
72	CA configuration CA_1A-20A Independent of Release	52
72.1	CA_1A-20A UE	52
72.1.1	RF Requirements	52
72.1.2	RRM Requirements	52
72.1.3	Demodulation performance and CSI reporting Requirements	52
73	CA configuration CA_4A-27A Independent of Release	52
73.1	CA_4A-27A UE	53
73.1.1	RF Requirements	53
73.1.2	RRM Requirements	53
73.1.3	Demodulation performance and CSI reporting Requirements	53
74	CA configuration CA_20A-32A Independent of Release	53
74.1	CA_20A-32A UE	53
74.1.1	RF Requirements	53
74.1.2	RRM Requirements	53
74.1.3	Demodulation performance and CSI reporting Requirements	53
75	CA configuration CA_41D Independent of Release	54
75.1	CA_41D UE	54
75.1.1	RF Requirements	54
75.1.2	RRM Requirements	54
75.1.3	Demodulation performance and CSI reporting Requirements	54
76	CA configuration CA_42C Independent of Release	54
76.1	CA_42C UE	54
76.1.1	RF Requirements	54
76.1.2	RRM Requirements	54
76.1.3	Demodulation performance and CSI reporting Requirements	54
77	Void	55

78	Void.....	55
79	CA configuration CA_40C Independent of Release	55
79.1	CA_40C UE	55
79.1.1	RF Requirements	55
79.1.2	RRM Requirements	55
79.1.3	Demodulation performance and CSI reporting Requirements	55
80	CA configuration CA_8A-11A Independent of Release	55
80.1	CA_8A-11A UE.....	55
80.1.1	RF Requirements	55
80.1.2	RRM Requirements	56
80.1.3	Demodulation performance and CSI reporting Requirements	56
81	CA configuration CA_41A-42A Independent of Release.....	56
81.1	CA_41A-42A UE.....	56
81.1.1	RF Requirements	56
81.1.2	RRM Requirements	56
81.1.3	Demodulation performance and CSI reporting Requirements	56
82	CA configuration CA_18A-28A Independent of Release.....	56
82.1	CA_18A-28A UE.....	56
82.1.1	RF Requirements	57
82.1.2	RRM Requirements	57
82.1.3	Demodulation performance and CSI reporting Requirements	57
83	CA configuration CA_1A-5A-7A Independent of Release.....	57
83.1	CA_1A-5A-7A UE.....	57
83.1.1	RF Requirements	57
83.1.2	RRM Requirements	57
83.1.3	Demodulation performance and CSI reporting Requirements	57
84	CA configuration CA_1A-3A-5A Independent of Release.....	57
84.1	CA_1A-3A-5A UE.....	58
84.1.1	RF Requirements	58
84.1.2	RRM Requirements	58
84.1.3	Demodulation performance and CSI reporting Requirements	58
85	CA configuration CA_1A-3A-8A Independent of Release.....	58
85.1	CA_1A-3A-8A UE.....	58
85.1.1	RF Requirements	58
85.1.2	RRM Requirements	58
85.1.3	Demodulation performance and CSI reporting Requirements	58
86	CA configuration CA_1A-3A-19A Independent of Release.....	59
86.1	CA_1A-3A-19A UE.....	59
86.1.1	RF Requirements	59
86.1.2	RRM Requirements	59
86.1.3	Demodulation performance and CSI reporting Requirements	59
87	CA configuration CA_1A-3A-20A Independent of Release.....	59
87.1	CA_1A-3A-20A UE.....	59
87.1.1	RF Requirements	59
87.1.2	RRM Requirements	59
87.1.3	Demodulation performance and CSI reporting Requirements	60
88	CA configuration CA_1A-3A Independent of Release.....	60
88.1	CA_1A-3A UE.....	60
88.1.1	RF Requirements	60
88.1.2	RRM Requirements	60
88.1.3	Demodulation performance and CSI reporting Requirements	60
89	CA configuration CA_1A-7A-20A Independent of Release.....	60
89.1	CA_1A-7A-20A UE.....	60
89.1.1	RF Requirements	60
89.1.2	RRM Requirements	61

89.1.3	Demodulation performance and CSI reporting Requirements	61
90	CA configuration CA_1A-7A Independent of Release	61
90.1	CA_1A-7A UE	61
90.1.1	RF Requirements	61
90.1.2	RRM Requirements	61
90.1.3	Demodulation performance and CSI reporting Requirements	61
91	CA configuration CA_1A-19A-21A Independent of Release	61
91.1	CA_1A-19A-21A UE	61
91.1.1	RF Requirements	61
91.1.2	RRM Requirements	62
91.1.3	Demodulation performance and CSI reporting Requirements	62
92	Void	62
93	CA configuration CA_2A-4A-5A Independent of Release	62
93.1	CA_2A-4A-5A UE	62
93.1.1	RF Requirements	62
93.1.2	RRM Requirements	62
93.1.3	Demodulation performance and CSI reporting Requirements	62
94	CA configuration CA_2A-4A-13A Independent of Release	62
94.1	CA_2A-4A-13A UE	63
94.1.1	RF Requirements	63
94.1.2	RRM Requirements	63
94.1.3	Demodulation performance and CSI reporting Requirements	63
95	CA configuration CA_2A-4A-12A Independent of Release	63
95.1	CA_2A-4A-12A UE	63
95.1.1	RF Requirements	63
95.1.2	RRM Requirements	63
95.1.3	Demodulation performance and CSI reporting Requirements	63
96	CA configuration CA_2A-12B Independent of Release	64
96.1	CA_2A-12B UE	64
96.1.1	RF Requirements	64
96.1.2	RRM Requirements	64
96.1.3	Demodulation performance and CSI reporting Requirements	64
97	CA configuration CA_3A-7C Independent of Release	64
97.1	CA_3A-7C UE	64
97.1.1	RF Requirements	64
97.1.2	RRM Requirements	64
97.1.3	Demodulation performance and CSI reporting Requirements	64
98	CA configuration CA_3A-7A-20A Independent of Release	65
98.1	CA_3A-7A-20A UE	65
98.1.1	RF Requirements	65
98.1.2	RRM Requirements	65
98.1.3	Demodulation performance and CSI reporting Requirements	65
99	Void	65
100	CA configuration CA_4A-12B Independent of Release	65
100.1	CA_4A-12B UE	65
100.1.1	RF Requirements	65
100.1.2	RRM Requirements	65
100.1.3	Demodulation performance and CSI reporting Requirements	66
101	CA configuration CA_12B Independent of Release	66
101.1	CA_12B UE	66
101.1.1	RF Requirements	66
101.1.2	RRM Requirements	66
101.1.3	Demodulation performance and CSI reporting Requirements	66
102	Void	66

102.1	Void.....	66
102.1.1	Void	66
102.1.2	Void	66
102.1.3	Void	66
103	Void.....	67
103.1	Void.....	67
103.1.1	Void	67
103.1.2	Void	67
103.1.3	Void	67
104	CA configuration CA_3C-7A Independent of Release	67
104.1	CA_3C-7A UE	67
104.1.1	RF Requirements	67
104.1.2	RRM Requirements	67
104.1.3	Demodulation performance and CSI reporting Requirements	67
105	CA configuration CA_2A-5A-12A Independent of Release.....	67
105.1	CA_2A-5A-12A UE.....	67
105.1.1	RF Requirements	68
105.1.2	RRM Requirements	68
105.1.3	Demodulation performance and CSI reporting Requirements	68
106	CA configuration CA_4A-5A-12A Independent of Release.....	68
106.1	CA_4A-5A-12A UE.....	68
106.1.1	RF Requirements	68
106.1.2	RRM Requirements	68
106.1.3	Demodulation performance and CSI reporting Requirements	68
107	CA configuration CA_2A-5A-30A Independent of Release.....	68
107.1	CA_2A-5A-30A UE.....	69
107.1.1	RF Requirements	69
107.1.2	RRM Requirements	69
107.1.3	Demodulation performance and CSI reporting Requirements	69
108	CA configuration CA_2A-12A-30A Independent of Release.....	69
108.1	CA_2A-12A-30A UE.....	69
108.1.1	RF Requirements	69
108.1.2	RRM Requirements	69
108.1.3	Demodulation performance and CSI reporting Requirements	69
109	CA configuration CA_2A-29A-30A Independent of Release.....	70
109.1	CA_2A-29A-30A UE.....	70
109.1.1	RF Requirements	70
109.1.2	RRM Requirements	70
109.1.3	Demodulation performance and CSI reporting Requirements	70
110	CA configuration CA_4A-5A-30A Independent of Release.....	70
110.1	CA_4A-5A-30A UE.....	70
110.1.1	RF Requirements	70
110.1.2	RRM Requirements	70
110.1.3	Demodulation performance and CSI reporting Requirements	71
111	CA configuration CA_4A-12A-30A Independent of Release.....	71
111.1	CA_4A-12A-30A UE.....	71
111.1.1	RF Requirements	71
111.1.2	RRM Requirements	71
111.1.3	Demodulation performance and CSI reporting Requirements	71
112	CA configuration CA_4A-29A-30A Independent of Release.....	71
112.1	CA_4A-29A-30A UE.....	71
112.1.1	RF Requirements	71
112.1.2	RRM Requirements	72
112.1.3	Demodulation performance and CSI reporting Requirements	72
113	CA configuration CA_2A-30A Independent of Release.....	72

113.1	CA_2A-30A UE.....	72
113.1.1	RF Requirements	72
113.1.2	RRM Requirements	72
113.1.3	Demodulation performance and CSI reporting Requirements	72
114	CA configuration CA_4A-30A Independent of Release.....	72
114.1	CA_4A-30A UE.....	72
114.1.1	RF Requirements	72
114.1.2	RRM Requirements	73
114.1.3	Demodulation performance and CSI reporting Requirements	73
115	CA configuration CA_5A-30A Independent of Release.....	73
115.1	CA_5A-30A UE.....	73
115.1.1	RF Requirements	73
115.1.2	RRM Requirements	73
115.1.3	Demodulation performance and CSI reporting Requirements	73
116	CA configuration CA_12A-30A Independent of Release.....	73
116.1	CA_12A-30A UE.....	73
116.1.1	RF Requirements	74
116.1.2	RRM Requirements	74
116.1.3	Demodulation performance and CSI reporting Requirements	74
117	CA configuration CA_29A-30A Independent of Release.....	74
117.1	CA_29A-30A UE.....	74
117.1.1	RF Requirements	74
117.1.2	RRM Requirements	74
117.1.3	Demodulation performance and CSI reporting Requirements	74
118	CA configuration CA_40D Independent of Release.....	74
118.1	CA_40D UE.....	75
118.1.1	RF Requirements	75
118.1.2	RRM Requirements	75
118.1.3	Demodulation performance and CSI reporting Requirements	75
119	Void.....	75
120	Void.....	75
121	Void.....	75
122	CA configuration CA_1A-28A Independent of Release.....	75
122.1	CA_1A-28A UE.....	75
122.1.1	RF Requirements	75
122.1.2	RRM Requirements	76
122.1.3	Demodulation performance and CSI reporting Requirements	76
124	CA configuration CA_1A-3A-26A Independent of Release.....	76
124.1	CA_1A-3A-26A UE.....	76
124.1.1	RF Requirements	76
124.1.2	RRM Requirements	77
124.1.3	Demodulation performance and CSI reporting Requirements	77
125	CA configuration CA_2C Independent of Release.....	77
125.1	CA_2C UE.....	77
125.1.1	RF Requirements	77
125.1.2	RRM Requirements	77
125.1.3	Demodulation performance and CSI reporting Requirements	77
126	CA configuration CA_2C-29A Independent of Release.....	77
126.1	CA_2C-29A UE.....	77
126.1.1	RF Requirements	77
126.1.2	RRM Requirements	77
126.1.3	Demodulation performance and CSI reporting Requirements	78
127	CA configuration CA_2A-4A-29A Independent of Release.....	78
127.1	CA_2A-4A-29A UE.....	78

127.1.1	RF Requirements	78
127.1.2	RRM Requirements	78
127.1.3	Demodulation performance and CSI reporting Requirements	78
128	CA configuration CA_7A-8A Independent of Release	78
128.1	CA_7A-8A UE	78
128.1.1	RF Requirements	78
128.1.2	RRM Requirements	78
128.1.3	Demodulation performance and CSI reporting Requirements	78
129	CA configuration CA_7A-8A-20A Independent of Release	79
129.1	CA_7A-8A-20A UE	79
129.1.1	RF Requirements	79
129.1.2	RRM Requirements	79
129.1.3	Demodulation performance and CSI reporting Requirements	79
130	CA configuration CA_39C-41A Independent of Release	79
130.1	CA_39C-41A UE	79
130.1.1	RF Requirements	79
130.1.2	RRM Requirements	79
130.1.3	Demodulation performance and CSI reporting Requirements	79
131	CA configuration CA_39A-41C Independent of Release	80
131.1	CA_39A-41C UE	80
131.1.1	RF Requirements	80
131.1.2	RRM Requirements	80
131.1.3	Demodulation performance and CSI reporting Requirements	80
132	CA configuration CA_7A-12A Independent of Release	80
132.1	CA_7A-12A UE	80
132.1.1	RF Requirements	80
132.1.2	RRM Requirements	80
132.1.3	Demodulation performance and CSI reporting Requirements	80
133	CA configuration CA_4A-7A-12A Independent of Release	81
133.1	CA_4A-7A-12A UE	81
133.1.1	RF Requirements	81
133.1.2	RRM Requirements	81
133.1.3	Demodulation performance and CSI reporting Requirements	81
134	CA configuration CA_2A-5A-13A Independent of Release	81
134.1	CA_2A-5A-13A UE	81
134.1.1	RF Requirements	81
134.1.2	RRM Requirements	81
134.1.3	Demodulation performance and CSI reporting Requirements	81
135	CA configuration CA_4A-5A-13A Independent of Release	82
135.1	CA_4A-5A-13A UE	82
135.1.1	RF Requirements	82
135.1.2	RRM Requirements	82
135.1.3	Demodulation performance and CSI reporting Requirements	82
136	CA configuration CA_1A-18A-28A Independent of Release	82
136.1	CA_1A-18A-28A UE	82
136.1.1	RF Requirements	82
136.1.2	RRM Requirements	82
136.1.3	Demodulation performance and CSI reporting Requirements	82
137	Void	82
138	Void	83
139	Void	83
140	CA configuration CA_1A-3A-28A Independent of Release	83
140.1	CA_1A-3A-28A UE	83
140.1.1	RF Requirements	83

140.1.2	RRM Requirements	83
140.1.3	Demodulation performance and CSI reporting Requirements	83
141	CA configuration CA_1A-7A-28A Independent of Release	83
141.1	CA_1A-7A-28A UE	83
141.1.1	RF Requirements	83
141.1.2	RRM Requirements	84
141.1.3	Demodulation performance and CSI reporting Requirements	84
142	CA configuration CA_2A_5A_29A Independent of Release	84
142.1	CA_2A-5A-29A UE	84
142.1.1	RF Requirements	84
142.1.2	RRM Requirements	84
142.1.3	Demodulation performance and CSI reporting Requirements	84
143	CA configuration CA_3C_5A Independent of Release	84
143.1	CA_3C-5A UE	84
143.1.1	RF Requirements	84
143.1.2	RRM Requirements	85
143.1.3	Demodulation performance and CSI reporting Requirements	85
144	CA configuration CA_3A_7B Independent of Release	85
144.1	CA_3A-7B UE	85
144.1.1	RF Requirements	85
144.1.2	RRM Requirements	85
144.1.3	Demodulation performance and CSI reporting Requirements	85
145	CA configuration CA_3A_7A_8A Independent of Release	85
145.1	CA_3A-7A-8A UE	85
145.1.1	RF Requirements	85
145.1.2	RRM Requirements	86
145.1.3	Demodulation performance and CSI reporting Requirements	86
146	CA configuration CA_3A_7A_28A Independent of Release	86
146.1	CA_3A-7A-28A UE	86
146.1.1	RF Requirements	86
146.1.2	RRM Requirements	86
146.1.3	Demodulation performance and CSI reporting Requirements	86
147	CA configuration CA_5A-29A Independent of Release	86
147.1	CA_5A-29A UE	86
147.1.1	RF Requirements	86
147.1.2	RRM Requirements	87
147.1.3	Demodulation performance and CSI reporting Requirements	87
148	CA configuration CA_7B Independent of Release	87
148.1	CA_7B UE	87
148.1.1	RF Requirements	87
148.1.2	RRM Requirements	87
148.1.3	Demodulation performance and CSI reporting Requirements	87
149	CA configuration CA_7B_28A Independent of Release	87
149.1	CA_7B-28A UE	87
149.1.1	RF Requirements	87
149.1.2	RRM Requirements	87
149.1.3	Demodulation performance and CSI reporting Requirements	88
150	CA configuration CA_7C_28A Independent of Release	88
150.1	CA_7C-28A UE	88
150.1.1	RF Requirements	88
150.1.2	RRM Requirements	88
150.1.3	Demodulation performance and CSI reporting Requirements	88
151	Void	88
151.1	Void	88
151.1.1	Void	88

151.1.2	Void	88
151.1.3	Void	88
152	CA configuration CA_38A-40A Independent of Release	88
152.1	CA_38A-40A UE	89
152.1.1	RF Requirements	89
152.1.2	RRM Requirements	89
152.1.3	Demodulation performance and CSI reporting Requirements	89
153	CA configuration CA_38A-40C Independent of Release	89
153.1	CA_38A-40C UE	89
153.1.1	RF Requirements	89
153.1.2	RRM Requirements	89
153.1.3	Demodulation performance and CSI reporting Requirements	89
154	Void	90
154.1	Void	90
154.1.1	Void	90
154.1.2	Void	90
154.1.3	Void	90
155	CA configuration CA_41A_42C Independent of Release	90
155.1	CA_41A-42C UE	90
155.1.1	RF Requirements	90
155.1.2	RRM Requirements	90
155.1.3	Demodulation performance and CSI reporting Requirements	90
156	CA configuration CA_2A-28A Independent of Release	90
156.1	CA_2A-28A UE	90
156.1.1	RF Requirements	91
156.1.2	RRM Requirements	91
156.1.3	Demodulation performance and CSI reporting Requirements	91
157	CA configuration CA_3A-31A Independent of Release	91
157.1	CA_3A-31A UE	91
157.1.1	RF Requirements	91
157.1.2	RRM Requirements	91
157.1.3	Demodulation performance and CSI reporting Requirements	91
158	CA configuration CA_4A-28A Independent of Release	91
158.1	CA_4A-28A UE	91
158.1.1	RF Requirements	92
158.1.2	RRM Requirements	92
158.1.3	Demodulation performance and CSI reporting Requirements	92
159	CA configuration CA_7A-22A Independent of Release	92
159.1	CA_7A-22A UE	92
159.1.1	RF Requirements	92
159.1.2	RRM Requirements	92
159.1.3	Demodulation performance and CSI reporting Requirements	92
160	CA configuration CA_20A-31A Independent of Release	92
160.1	CA_20A-31A UE	92
160.1.1	RF Requirements	93
160.1.2	RRM Requirements	93
160.1.3	Demodulation performance and CSI reporting Requirements	93
161	CA configuration CA_25A-26A Independent of Release	93
161.1	CA_25A-26A UE	93
161.1.1	RF Requirements	93
161.1.2	RRM Requirements	93
161.1.3	Demodulation performance and CSI reporting Requirements	93
162	CA configuration CA_42D Independent of Release	93
162.1	CA_42D UE	93
162.1.1	RF Requirements	94

162.1.2	RRM Requirements	94
162.1.3	Demodulation performance and CSI reporting Requirements	94
163	Void.....	94
164	Void.....	94
165	CA configuration CA_2C-5A Independent of Release	94
165.1	CA_2C-5A UE	94
165.1.1	RF Requirements	94
165.1.2	RRM Requirements	94
165.1.3	Demodulation performance and CSI reporting Requirements	94
166	Void.....	94
167	CA configuration CA_2C-12A Independent of Release	95
167.1	CA_2C-12A UE	95
167.1.1	RF Requirements	95
167.1.2	RRM Requirements	95
167.1.3	Demodulation performance and CSI reporting Requirements	95
168	CA configuration CA_2C-30A Independent of Release	95
168.1	CA_2C-30A UE	95
168.1.1	RF Requirements	95
168.1.2	RRM Requirements	95
168.1.3	Demodulation performance and CSI reporting Requirements	95
169	Void.....	95
170	Void.....	96
171	Void.....	96
172	Void.....	96
173	Void.....	96
174	CA configuration CA_2A-4A-30A Independent of Release.....	96
174.1	CA_2A-4A-30A UE.....	96
174.1.1	RF Requirements	96
174.1.2	RRM Requirements	96
174.1.3	Demodulation performance and CSI reporting Requirements	96
175 – 204	Void	96
205	CA configuration CA_19A-28A Independent of Release	97
205.1	CA_19A-28A UE.....	97
205.1.1	RF Requirements	97
205.1.2	RRM Requirements	97
205.1.3	Demodulation performance and CSI reporting Requirements	97
206	CA configuration CA_1A-19A-28A Independent of Release.....	97
206.1	CA_1A-19A-28A UE.....	97
206.1.1	RF Requirements	97
206.1.2	RRM Requirements	97
206.1.3	Demodulation performance and CSI reporting Requirements	97
207	CA configuration CA_1A-8A-11A Independent of Release.....	98
207.1	CA_1A-8A-11A UE.....	98
207.1.1	RF Requirements	98
207.1.2	RRM Requirements	98
207.1.3	Demodulation performance and CSI reporting Requirements	98
208	CA configuration CA_1A-3C Independent of Release	98
208.1	CA_1A-3C UE	98
208.1.1	RF Requirements	98
208.1.2	RRM Requirements	98
208.1.3	Demodulation performance and CSI reporting Requirements	98

209 – 213	Void	99
Annex A (informative):	Frequency arrangement for overlapping operating bands	100
Annex B (normative):	Common Requirements	101
B.1	Purpose of annex	101
B.2	Common RRM requirements	101
B.2.1	Common RRM requirements for a band independent of release	101
B.2.2	Common RRM requirements for an intra-band contiguous CA configuration	102
B.2.3	Common RRM requirements for an inter-band CA configuration	102
B.3	Common UE performance requirements	103
B.3.1	Void	103
B.3.2	Void	103
B.3.3	Void	103
B.4	Common UE RF requirements	103
B.4.1	Common UE RF requirements for a band independent of release	103
B.4.2	Common UE RF requirements for an intra-band contiguous CA configuration	103
B.4.3	Common UE RF requirements for an inter-band CA configuration	104
Annex C (informative):	Change history	106
History		109

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies requirements on UEs supporting a frequency band and inter-band/intra-band CA configurations that are independent of release.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 36.101 (Release 11): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".
- [3] 3GPP TS 36.133 (Release 11): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Radio Resource Management".
- [4] 3GPP TS 36.101 (Release 12): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".
- [5] 3GPP TS 36.133 (Release 12): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Radio Resource Management".
- [6] 3GPP TS 36.307 (Release 11): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements on User Equipments (UEs) Supporting a release-independent frequency band".
- [7] 3GPP TS 36.307 (Release 12): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements on User Equipments (UEs) Supporting a release-independent frequency band".
- [8] 3GPP TS 36.133 (Release 10): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Radio Resource Management".
- [9] 3GPP TS 36.101 (Release 10): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".
- [10] 3GPP TS 36.306 (Release 10): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio access capabilities".
- [11] 3GPP TS 36.101 (Release 13): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".
- [12] 3GPP TS 36.133 (Release 13): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Radio Resource Management".
- [13] 3GPP TS 36.307 (Release 13): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements on User Equipments (UEs) Supporting a release-independent frequency band".

3 Definitions and Abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in [1] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CA	Carrier Aggregation
FDD	Frequency Division Duplex
RRC	Radio Resource Control
RRM	Radio Resource Management
TDD	Time Division Duplex
UE	User Equipment

3A General

TSG-RAN has agreed that the standardisation of new frequency bands may be independent of a release, and that the standardisations of new inter-band/intra-band CA configurations also may be independent of a release for Rel-10 upwards. However, in order to implement a UE that conforms to a particular release but supports a band of operation or carrier aggregation of particular inter-band/intra-band CA configurations that is specified in a later release, it is necessary to specify some extra requirements.

For example, Band 19 is contained in the Release 9 specifications. In order to implement a UE conforming to Release 8 but supporting Band 19, it is necessary for the UE to additionally conform to some parts of the Release 9 specifications, such as the radio frequency and radio resource management requirements for the Band 19.

For another example on carrier aggregations, CA configuration CA_1A-19A is contained in the Release 11 specifications. In order to implement a UE conforming to Release 10 but supporting the CA configuration CA_1A-19A, it is necessary for the UE to additionally conform to some parts of the Release 11 specifications, such as the radio frequency and radio resource management requirements for the CA configuration CA_1A-19A.

All frequency bands are fully specified in this release of the specifications. The present document does not contain any requirements for UEs supporting frequency bands independent of release.

NOTE: See NOTE in clause 4.4 in [9].

4 Void

5 Void

6 Void

Void

8 Void

9 Void

10 Void

11 Void

12 Void

13 Void

14 Void

15 Band 26 Independent of Release

Band 26 is specified in Release 11 but is defined as a release-independent frequency band. This approach aligns the Band 26 with other frequency bands when considering features that have to be supported in different releases.

15.1 Band 26 UE

UEs that conform to Release 10 and support Band 26 shall support the following requirements in Release 11.

15.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 26 specified in [2] which are listed in Table B.4.1-1 of [6].

Table 15.1.1-1: Void

15.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 26 specified in [3] which are listed in Table B.2.1-1 of [6].

Table 15.1.2-1: Void

15.1.3 Void

16 Band 27 Independent of Release

Band 27 is specified in Release 11, but is defined as a release-independent frequency band. This approach aligns the Band 27 with other frequency bands when considering features that have to be supported in different releases.

16.1 Band 27 UE

UEs that conform to Release 10 and support Band 27 shall support the following requirements in Release 11.

16.1.1 RF Requirements

The UE shall comply with the Release 11 RF requirements for Band 27 specified [2] which are listed in Table B.4.1-1 of [6].

Table 16.1.1-1: RF Void

16.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 27 specified in [3] which are listed in Table B.2.1-1 of [6].

Table 16.1.2-1: Void

16.1.3 Void

17 Band 28 Independent of Release

Band 28 is specified in Release 11 but is defined as a release-independent frequency band. This approach aligns the Band 28 with other frequency bands when considering features that have to be supported in different releases.

17.1 Band 28 UE

UEs that conform to Release 10 and support Band 28 shall support the following requirements in Release 11.

17.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 28 specified [2] which are listed in Table B.4.1-1 of [6].

Table 17.1.1-1: Void

17.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 28 specified in [3] which are listed in Table B.2.1-1 of [6].

Table 17.1.2-1: Void

17.1.3 Void

18 Band 44 Independent of Release

Band 44 is specified in Release 11 but is defined as a release-independent frequency band. This approach aligns the Band 44 with other frequency bands when considering features that have to be supported in different releases.

18.1 Band 44 UE

UEs that conform to Release 10 and support Band 44 shall support the following requirements in Release 11.

18.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 44 specified [2] which are listed in Table B.4.1-1 of [6].

Table 18.1.1-1: Void

18.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 44 specified in [3] which are listed in Table B.2.1-1 of [6].

Table 18.1.2-1: Void

18.1.3 Void

19 CA configuration CA_41C Independent of Release

CA_41C is specified in Release 11 and Release 13 but is defined as a release-independent E-UTRA CA configuration.

19.1 Band 41 UE

UEs that conform to Release 10 and support CA_41C shall support the following requirements in Release 11 for both one uplink and simultaneous transmission on two uplinks.

19.1.1 RF Requirements

The UE shall comply with the following RF requirements for CA_41C specified in [11] which are listed in Table B.4.2-1 of [13].

Table 19.1.1-1: Void

19.1.2 RRM Requirements

The UE shall comply with the RRM Requirements for CA_41C specified in [12] which are listed in Table B.2.2-1 of [13].

Table 19.1.1-2: Void

19.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_41C among the CA demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

20 CA configuration CA_1A-19A Independent of Release

CA configuration CA_1A-19A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

20.1 CA_1A-19A UE

UEs that conform to Release 10 and support CA_1A-19A shall support the following requirements in Release 11.

20.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-19A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 20.1.1-1: Void

20.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-19A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 20.1.2-1: Void

20.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-19A among the CA demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

21 CA configuration CA_7C Independent of Release

CA configuration CA_7C is specified in Release 11, Release 12 and Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

21.1 CA_7C UE

UEs that conform to Release 10 and support CA_7C shall support the following requirements in Release 13.

21.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7C specified in [11] which are listed in Table B.4.2-1 of [13].

Table 21.1.1-1: Void

21.1.2 RRM Requirements

The UE shall comply with the RRM Requirements for CA_7C specified in [12] which are listed in Table B.2.2-1 of [13].

Table 21.1.1-2: Void

21.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7C among the CA demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

22 CA configuration CA_38C Independent of Release

CA_38C is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

22.1 Band 38 UE

UEs that conform to Release 10 and support CA_38C shall support the following requirements in Release 11 for both one uplink and simultaneous transmission on two uplinks.

22.1.1 RF Requirements

The UE shall comply with the following RF requirements for CA_38C specified in [2] which are listed in Table B.4.2-1 of [6].

Table 22.1.1-1: Void

22.1.2 RRM Requirements

The UE shall comply with the RRM Requirements for CA_38C specified in [3] which are listed in Table B.2.2-1 of [6].

Table 22.1.2-1: Void

22.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_38C among the CA demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

23 CA configuration CA_1A-18A Independent of Release

CA configuration CA_1A-18A is specified in Release 11 and 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

23.1 CA_1A-18A UE

UEs that conform to Release 10 and support CA_1A-18A shall support the following requirements in Release 12.

23.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-18A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 23.1.1-1: Void

23.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-18A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 23.1.2-1: Void

23.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-18A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

24 CA configuration CA_1A-21A Independent of Release

CA configuration CA_1A-21A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

24.1 CA_1A-21A UE

UEs that conform to Release 10 and support CA_1A-21A shall support the following requirements in Release 11.

24.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-21A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 24.1.1-1: Void

24.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-21A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 24.1.2-1: Void

24.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-21A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

25 CA configuration CA_3A-5A Independent of Release

CA configuration CA_3A-5A is specified in Release 11, Release 12 and Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

25.1 CA_3A-5A UE

UEs that conform to Release 10 and support CA_3A-5A shall support the following requirements in Release 13.

25.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-5A specified in [11] which are listed in Table B.4.3-1 of [13].

Table 25.1.1-1: Void

25.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-5A specified in [12] which are listed in Table B.2.4-1 of [13].

Table 25.1.2-1: Void

25.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-5A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

26 CA configuration CA_3A-7A Independent of Release

CA configuration CA_3A-7A is specified in Release 11 and Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

26.1 CA_3A-7A UE

UEs that conform to Release 10 and support CA_3A-7A shall support the following requirements in Release 13.

26.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-7A specified in [11] which are listed in Table B.4.3-1 of [13].

Table 26.1.1-1: Void

26.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-7A specified in [12] which are listed in Table B.2.4-1 of [13].

Table 26.1.2-1: Void

26.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-7A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

27 CA configuration CA_3A-20A Independent of Release

CA configuration CA_3A-20A is specified in Release 11 and Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

27.1 CA_3A-20A UE

UEs that conform to Release 10 and support CA_3A-20A shall support the following requirements in Release 11 and Release 12.

27.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-20A specified in 3GPP TS TS 36.101 [4] which are listed in Table B.4.3-1 of [7].

Table 27.1.1-1: Void

27.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-20A specified in [3] which are listed in Table B.2.4-1 of [7].

Table 27.1.2-1: Void

27.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-20A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

28 CA configuration CA_7A-20A Independent of Release

CA configuration CA_7A-20A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

28.1 CA_7A-20A UE

UEs that conform to Release 10 and support CA_7A-20A shall support the following requirements in Release 11.

28.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7A-20A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 28.1.1-1: Void

28.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_7A-20A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 28.1.2-1: Void

28.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7A-20A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

29 CA configuration CA_8A-20A Independent of Release

CA configuration CA_8A-20A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

29.1 CA_8A-20A UE

UEs that conform to Release 10 and support CA_8A-20A shall support the following requirements in Release 11.

29.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_8A-20A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 29.1.1-1: Void

29.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_8A-20A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 29.1.2-1: Void

29.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_8A-20A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

30 CA configuration CA_2A-17A Independent of Release

CA configuration CA_2A-17A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

30.1 CA_2A-17A UE

UEs that conform to Release 10 and support CA_2A-17A shall support the following requirements in Release 11.

30.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-17A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 30.1.1-1: Void

30.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-17A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 30.1.2-1: Void

30.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-17A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

31 CA configuration CA_2A-29A Independent of Release

CA configuration CA_2A-29A is specified in Release 11 and Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

31.1 CA_2A-29A UE

UEs that conform to Release 10 and support CA_2A-29A shall support the following requirements in Release 12.

31.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-29A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 31.1.1-1: Void

31.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-29A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 31.1.2-1: Void

31.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-29A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

32 CA configuration CA_4A-29A Independent of Release

CA configuration CA_4A-29A is specified in Release 11 and Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

32.1 CA_4A-29A UE

UEs that conform to Release 10 and support CA_4A-29A shall support the following requirements in Release 12.

32.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-29A specified in [4] which are listed in Table B.4.4-1 of [7].

Table 32.1.1-1: Void

32.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-29A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 32.1.2-1: Void

32.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-29A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

33 CA configuration CA_3A-8A Independent of Release

CA configuration CA_3A-8A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

33.1 CA_3A-8A UE

UEs that conform to Release 10 and support CA_3A-8A shall support the following requirements in Release 11.

33.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-8A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 33.1.1-1: Void

33.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-8A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 33.1.2-1: Void

33.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-8A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

34 CA configuration CA_4A-5A Independent of Release

CA configuration CA_4A-5A is specified in Release 11 and Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

34.1 CA_4A-5A UE

UEs that conform to Release 10 and support CA_4A-5A shall support the following requirements in Release 12.

34.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-5A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 34.1.1-1: Void

34.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-5A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 34.1.2-1: Void

34.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-5A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

35 CA configuration CA_4A-12A Independent of Release

CA configuration CA_4A-12A is specified in Release 11, Release 12 and Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

35.1 CA_4A-12A UE

UEs that conform to Release 10 and support CA_4A-12A shall support the following requirements in Release 13.

35.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-12A specified in [11] which are listed in Table B.4.3-1 of [13].

Table 35.1.1-1: Void

35.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-12A specified in [12] which are listed in Table B.2.4-1 of [13].

Table 35.1.2-1: Void

35.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-12A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

36 CA configuration CA_4A-13A Independent of Release

CA configuration CA_4A-13A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

36.1 CA_4A-13A UE

UEs that conform to Release 10 and support CA_4A-13A shall support the following requirements in Release 11.

36.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-13A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 36.1.1-1: Void

36.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-13A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 36.1.2-1: Void

36.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-13A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

37 CA configuration CA_4A-17A Independent of Release

CA configuration CA_4A-17A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

37.1 CA_4A-17A UE

UEs that conform to Release 10 and support CA_4A-17A shall support the following requirements in Release 11.

37.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-17A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 37.1.1-1: Void

37.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-17A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 37.1.2-1: Void

37.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-17A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

38 CA configuration CA_5A-12A Independent of Release

CA configuration CA_5A-12A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

38.1 CA_5A-12A UE

UEs that conform to Release 10 and support CA_5A-12A shall support the following requirements in Release 11.

38.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_5A-12A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 38.1.1-1: Void

38.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_5A-12A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 38.1.2-1: Void

38.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_5A-12A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

39 CA configuration CA_5A-17A Independent of Release

CA configuration CA_5A-17A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

39.1 CA_5A-17A UE

UEs that conform to Release 10 and support CA_5A-17A shall support the following requirements in Release 11.

39.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_5A-17A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 39.1.1-1: Void

39.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_5A-17A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 39.1.2-1: Void

39.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_5A-17A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table Table B.3.2-1 of [6].

40 CA configuration CA_4A-7A Independent of Release

CA_4A-7A is specified in Release 11 but is defined as a release-independent E-UTRA CA configuration.

40.1 CA_4A-7A UE

UEs that conform to Release 10 and support CA_4A-7A shall support the following requirements in Release 11 for one uplink.

40.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-7A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 40.1.1-1: Void

40.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-7A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 40.1.2-1: Void

40.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-7A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

41 CA configuration CA_11A-18A Independent of Release

CA configuration CA_11A-18A is specified in Release 11 but is defined as a release-independent CA configuration for Rel-10 upwards.

41.1 CA_11A-18A UE

UEs that conform to Release 10 and support CA_11A-18A shall support the following requirements in Release 11.

41.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_11A-18A specified in [2] which are listed in Table B.4.3-1 of [6].

Table 41.1.1-1: Void

41.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_11A-18A specified in [3] which are listed in Table B.2.4-1 of [6].

Table 41.1.2-1: Void

41.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_11A-18A among the demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

42 Band 30 Independent of Release

Band 30 is specified in Release 12 but is defined as a release-independent frequency band. This approach aligns the Band 30 with other frequency bands when considering features that have to be supported in different releases.

42.1 Band 30 UE

UEs that conform to Release 10 and support Band 30 shall support the following requirements in Release 12.

42.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 30 specified in [4] which are listed in Table B.4.1-1 of [7].

Table 42.1.1-1: Void

42.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 30 specified in [5] which are listed in Table B.2.1-1 of [7].

Table 42.1.2-1: Void

42.1.3 Void

43 Band 31 Independent of Release

Band 31 is specified in Release 12 but is defined as a release-independent frequency band. This approach aligns the Band 31 with other frequency bands when considering features that have to be supported in different releases.

43.1 Band 31 UE

UEs that conform to Release 10 and support Band 31 shall support the following requirements in Release 12.

43.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 31 specified [4] which are listed in Table B.4.1-1 of [7].

Table 43.1.1-1: Void

43.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 31, for 5 MHz only, specified in [5] which are listed in Table B.2.1-1 of [7].

Table 43.1.2-1: Void

43.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the subset of demodulation performance and CSI reporting requirements specified in [4] which are listed in Table 43.1.3-2.

Table 43.1.3-1: Void**Table 43.1.3-2: Demodulation performance and CSI reporting requirements for Band 31 UE**

Section / Clause	Description	Test case
8.2.1.1.1	Single-antenna port performance	6, 7, 8
8.2.1.2.1	Transmit diversity performance	1
8.2.1.3.1	Open-loop spatial multiplexing performance	2
8.2.1.4.1	Closed-loop spatial multiplexing performance	1A
8.2.1.4.2	Closed-loop spatial multiplexing performance	2A
8.5.1.2.1	PHICH transmit diversity performance	1A
9.2.1.1	CQI reporting definition under AWGN conditions	Table 9.2.1.1-2
9.3.2.1.1	CQI reporting under fading conditions	Table 9.3.2.1.1-3

44 CA configuration CA_1A-8A Independent of Release

CA configuration CA_1A-8A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

44.1 CA_1A-8A UE

UEs that conform to Release 10 and support CA_1A-8A shall support the following requirements in Release 12.

44.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-8A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 44.1.1-1: Void

44.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-8A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 44.1.2-1: Void

44.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-8A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

45 CA configuration CA_2A-13A Independent of Release

CA configuration CA_2A-13A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

45.1 CA_2A-13A UE

UEs that conform to Release 10 and support CA_2A-13A shall support the following requirements in Release 12.

45.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-13A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 45.1.1-1: Void

45.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-13A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 45.1.2-1: Void

45.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-13A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

46 CA configuration CA_3A-19A Independent of Release

CA configuration CA_3A-19A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

46.1 CA_3A-19A UE

UEs that conform to Release 10 and support CA_3A-19A shall support the following requirements in Release 12.

46.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-19A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 46.1.1-1: Void

46.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-19A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 46.1.2-1: Void

46.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-19A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

47 CA configuration CA_3A-26A Independent of Release

CA configuration CA_3A-26A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

47.1 CA_3A-26A UE

UEs that conform to Release 10 and support CA_3A-26A shall support the following requirements in Release 12.

47.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-26A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 47.1.1-1: Void

47.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-26A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 47.1.2-1: Void

47.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-26A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

48 CA configuration CA_3A-28A Independent of Release

CA configuration CA_3A-28A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

48.1 CA_3A-28A UE

UEs that conform to Release 10 and support CA_3A-28A shall support the following requirements in Release 12.

48.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-28A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 48.1.1-1: Void

48.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-28A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 48.1.2-1: Void

48.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-28A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

49 CA configuration CA_19A-21A Independent of Release

CA configuration CA_19A-21A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

49.1 CA_19A-21A UE

UEs that conform to Release 10 and support CA_19A-21A shall support the following requirements in Release 12.

49.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_19A-21A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 49.1.1-1: Void

49.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_19A-21A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 49.1.2-1: Void

49.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_19A-21A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

50 CA configuration CA_23A-29A Independent of Release

CA configuration CA_23A-29A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

50.1 CA_23A-29A UE

UEs that conform to Release 10 and support CA_23A-29A shall support the following requirements in Release 12.

50.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_23A-29A specified in [4] which are listed in Table B.4.4-1 of [7].

Table 50.1.1-1: Void

50.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_23A-29A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 50.1.2-1: Void

50.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_23A-29A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

51 Void

52 CA configuration CA_3C Independent of Release

CA configuration CA_3C is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

52.1 CA_3C UE

UEs that conform to Release 10 and support CA_3C shall support the following requirements in Release 12.

52.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3C specified in [4] which are listed in Table B.4.2-1 of [7].

Table 52.1.1-1: Void

52.1.2 RRM Requirements

The UE shall comply with the RRM Requirements for CA_3C specified in [5] which are listed in Table B.2.2-1 of [7].

Table 52.1.2-2: Void

52.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3C among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

53 CA configuration CA_1A-26A Independent of Release

CA configuration CA_1A-26A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

53.1 CA_1A-26A UE

UEs that conform to Release 10 and support CA_1A-26A shall support the following requirements in Release 12.

53.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-26A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 53.1.1-1: Void

53.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-26A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 53.1.2-1: Void

53.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-26A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

54 CA configuration CA_2A-4A Independent of Release

CA configuration CA_2A-4A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

54.1 CA_2A-4A UE

UEs that conform to Release 10 and support CA_2A-4A shall support the following requirements in Release 12.

54.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-4A specified in [2] which are listed in Table B.4.3-1 of [7].

Table 54.1.1-1: Void

54.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-4A specified in [3] which are listed in Table B.2.4-1 of [7].

Table 54.1.2-1: Void

54.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-4A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

55 CA configuration CA_2A-5A Independent of Release

CA configuration CA_2A-5A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

55.1 CA_2A-5A UE

UEs that conform to Release 10 and support CA_2A-5A shall support the following requirements in Release 12.

55.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-5A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 55.1.1-1: Void

55.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-5A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 55.1.2-1: Void

55.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-5A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

56 CA configuration CA_23B Independent of Release

CA configuration CA_23B is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

56.1 CA_23B UE

UEs that conform to Release 10 and support CA_23B shall support the following requirements in Release 12.

56.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_23B specified in [4] which are listed in Table B.4.2-1 of [7].

Table 56.1.1-1: Void

56.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_23B specified in [5] which are listed in Table B.2.2-1 of [7].

Table 56.1.2-1: Void

56.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_23B among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

57 A configuration CA_27B Independent of Release

CA configuration CA_27B is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

57.1 CA_27B UE

UEs that conform to Release 10 and support CA_27B shall support the following requirements in Release 12.

57.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_27B specified in [4] which are listed in Table B.4.2-1 of [7].

Table 57.1.1-1: Void

57.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_27B specified in [5] which are listed in Table B.2.2-1 of [7].

Table 57.1.1-2: Void

57.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_27B among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

58 CA configuration CA_2A-12A Independent of Release

CA configuration CA_2A-12A is specified in Release 12 and Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

58.1 CA_2A-12A UE

UEs that conform to Release 10 and support CA_2A-12A shall support the following requirements in Release 13.

58.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-12A specified in [11] which are listed in Table B.4.3-1 of [13].

Table 58.1.1-1: Void

58.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-12A specified in [12] which are listed in Table B.2.4-1 of [13].

Table 58.1.2-1: Void

58.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-12A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

59 CA configuration CA_5A-7A Independent of Release

CA configuration CA_5A-7A is specified in Release 12 and Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

59.1 CA_5A-7A UE

UEs that conform to Release 10 and support CA_5A-7A shall support the following requirements in Release 13.

59.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_5A-7A specified in [11] which are listed in Table B.4.3-1 of [13].

Table 59.1.1-1: Void

59.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_5A-7A specified in [12] which are listed in Table B.2.4-1 of [13].

Table 59.1.2-1: Void

59.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_5A-7A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

60 CA configuration CA_5A-25A Independent of Release

CA configuration CA_5A-25A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

60.1 CA_5A-25A UE

UEs that conform to Release 10 and support CA_5A-25A shall support the following requirements in Release 12.

60.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_5A-25A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 60.1.1-1: Void

60.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_5A-25A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 60.1.2-1: Void

60.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_5A-25A among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

61 CA configuration CA_7A-28A Independent of Release

CA configuration CA_7A-28A is specified in Release 12 and Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

61.1 CA_7A-28A UE

UEs that conform to Release 10 and support CA_7A-28A shall support the following requirements in Release 13.

61.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7A-28A specified in [11] which are listed in Table B.4.3-1 of [13].

Table 61.1.1-1: Void

61.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_7A-28A specified in [12] which are listed in Table B.2.4-1 of [13].

61.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7A-28A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

62 CA configuration CA_12A-25A Independent of Release

CA configuration CA_12A-25A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

62.1 CA_12A-25A UE

UEs that conform to Release 10 and support CA_12A-25A shall support the following requirements in Release 12.

62.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_12A-25A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 62.1.1-1: Void

62.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_12A-25A specified in [5] which are listed in Table B.2.4-1 of [7].

Table 62.1.2-1: Void

62.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable CA_12A-25A among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

63 Void

64 Void

65 Void

66 CA configuration CA_3A-27A Independent of Release

CA configuration CA_3A-27A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

66.1 CA_3A-27A UE

UEs that conform to Release 10 and support CA_3A-27A shall support the following requirements in Release 12.

66.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-27A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 66.1.1-1: Void

66.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-27A specified in [5] which are listed in Table B.2.4-1 of [7].

66.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-27A among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

67 CA configuration CA_39C Independent of Release

CA configuration CA_39C is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

67.1 CA_39C UE

UEs that conform to Release 10 and support CA_39C shall support the following requirements in Release 12.

67.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_39C specified in [4] which are listed in Table B.4.2-1 of [7].

Table 67.1.1-1: Void

67.1.2 RRM Requirements

The UE shall comply with the RRM Requirements for CA_39C specified in [5] which are listed in Table B.2.2-1 of [7].

67.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_39C among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

68 CA configuration CA_39A-41A Independent of Release

CA configuration CA_39A-41A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

68.1 CA_39A-41A UE

UEs that conform to Release 10 and support CA_39A-41A shall support the following requirements in Release 12.

68.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_39A-41A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 68.1.1-1: Void

68.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_39A-41A specified in [5] which are listed in Table B.2.4-1 of [7].

68.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_39A-41A among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

69 Band 14 Class 1 HPUE Independent of Release

Band 14 class 1 high power UE is specified in Release 11 but is defined as a release -independent feature and frequency band.

69.1 Band 14 HPUE

UEs that conform to Release 10 and support Band 14 class 1 high power UE shall support the following requirements in Release 11 in addition to all other requirements for Band 14 class 3 UE specified in [9].

69.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 14 class 1 HPUE specified in [2] which are listed in Table B.4.1-1 of [7].

Table 69.1.1-1: Void

70 CA configuration CA_1A-5A Independent of Release

CA configuration CA_1A-5A with bandwidth combination set1 is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

70.1 CA_1A-5A UE

UEs that conform to Release 10 and support CA_1A-5A shall support the following requirements in Release 12.

70.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-5A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 70.1.1-1: Void

70.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-5A specified in [5] which are listed in Table B.2.4-1 of [7].

70.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-5A among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

71 CA configuration CA_1A-11A Independent of Release

CA configuration CA_1A-11A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

71.1 CA_1A-11A UE

UEs that conform to Release 10 and support CA_1A-11A shall support the following requirements in Release 12.

71.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-11A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 71.1.1-1: Void

71.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-11A specified in [5] which are listed in Table B.2.4-1 of [7].

71.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-11A among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

72 CA configuration CA_1A-20A Independent of Release

CA configuration CA_1A-20A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

72.1 CA_1A-20A UE

UEs that conform to Release 10 and support CA_1A-20A shall support the following requirements in Release 12.

72.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-20A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 72.1.1-1: Void

72.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-20A specified in [5] which are listed in Table B.2.4-1 of [7].

72.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-20A among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

73 CA configuration CA_4A-27A Independent of Release

CA configuration CA_4A-27A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

73.1 CA_4A-27A UE

UEs that conform to Release 10 and support CA_4A-27A shall support the following requirements in Release 12.

73.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-27A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 73.1.1-1: Void

73.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-27A specified in [5] which are listed in Table B.2.4-1 of [7].

73.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-27A among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

74 CA configuration CA_20A-32A Independent of Release

CA configuration CA_20A-32A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

74.1 CA_20A-32A UE

UEs that conform to Release 10 and support CA_20A-32A shall support the following requirements in Release 12.

74.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_20A-32A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 74.1.1-1: Void

74.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_20A-32A specified in [5] which are listed in Table B.2.4-1 of [7].

74.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_20A-32A among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

75 CA configuration CA_41D Independent of Release

CA configuration CA_41D is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

75.1 CA_41D UE

UEs that conform to Release 10 and support CA_41D shall support the following requirements in Release 12.

75.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_41D specified in [4] which are listed in Table B.4.2-1 of [7].

Table 75.1.1-1: Void

75.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_41D specified in [5] which are listed in Table B.2.2-1 of [7].

75.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_41D among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

76 CA configuration CA_42C Independent of Release

CA configuration CA_42C is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

76.1 CA_42C UE

UEs that conform to Release 10 and support CA_42C shall support the following requirements in Release 12.

76.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_42C specified in [4] which are listed in Table B.4.2-1 of [7].

Table 76.1.1-1: Void

76.1.2 RRM Requirements

The UE shall comply with the RRM Requirements for CA_42C specified in [5] which are listed in Table B.2.2-1 of [7].

76.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_42C among demodulation performance and CSI reporting requirements specified in [2] and listed in Table B.3.2-1 of [6].

77 Void

78 Void

79 CA configuration CA_40C Independent of Release

CA_40C is specified in Release 10, Release 11 and Release 12. It is defined as a release-independent CA configuration for Rel-10 upwards.

79.1 CA_40C UE

UEs that conform to Release 10 and support CA_40C shall support the following requirements in Release 12 for both one uplink and simultaneous transmission on two uplinks.

79.1.1 RF Requirements

The UE shall comply with the following RF requirements for CA_40C specified in [4] which are listed in Table B.4.2-1 of [7].

Table 79.1.1-1: Void

79.1.2 RRM Requirements

The UE shall comply with the RRM Requirements for CA_40C specified in [5] which are listed in Table B.2.2-1 of [7].

79.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_40C among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

80 CA configuration CA_8A-11A Independent of Release

CA configuration CA_8A-11A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

80.1 CA_8A-11A UE

UEs that conform to Release 10 and support CA_8A-11A shall support the following requirements in Release 12.

80.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_8A-11A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 80.1.1-1: Void

80.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_8A-11A specified in [5] which are listed in Table B.2.4-1 of [7].

80.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_8A-11A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

81 CA configuration CA_41A-42A Independent of Release

CA configuration CA_41A-42A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

81.1 CA_41A-42A UE

UEs that conform to Release 10 and support CA_41A-42A shall support the following requirements in Release 12.

81.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_41A-42A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 81.1.1-1: Void

81.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_41A-42A specified in [5] which are listed in Table B.2.4-1 of [7].

81.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_41A-42A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

82 CA configuration CA_18A-28A Independent of Release

CA configuration CA_18A-28A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

82.1 CA_18A-28A UE

UEs that conform to Release 10 and support CA_18A-28A shall support the following requirements in Release 12.

82.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_18A-28A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 82.1.1-1: Void

82.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_18A-28A specified in [5] which are listed in Table B.2.4-1 of [7].

82.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_18A-28A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

83 CA configuration CA_1A-5A-7A Independent of Release

CA configuration CA_1A-5A-7A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

83.1 CA_1A-5A-7A UE

UEs that conform to Release 10 and support CA_1A-5A-7A shall support the following requirements in Release 12.

83.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-5A-7A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 83.1.1-1: Void

83.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-5A-7A specified in [5].

83.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-5A-7A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

84 CA configuration CA_1A-3A-5A Independent of Release

CA configuration CA_1A-3A-5A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

84.1 CA_1A-3A-5A UE

UEs that conform to Release 10 and support CA_1A-3A-5A shall support the following requirements in Release 12.

84.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-3A-5A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 84.1.1-1: Void

84.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-3A-5A specified in [5].

84.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-3A-5A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

85 CA configuration CA_1A-3A-8A Independent of Release

CA configuration CA_1A-3A-8A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

85.1 CA_1A-3A-8A UE

UEs that conform to Release 10 and support CA_1A-3A-8A shall support the following requirements in Release 12.

85.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-3A-8A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 85.1.1-1: Void

85.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-3A-8A specified in [5].

85.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-3A-8A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

86 CA configuration CA_1A-3A-19A Independent of Release

CA configuration CA_1A-3A-19A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

86.1 CA_1A-3A-19A UE

UEs that conform to Release 10 and support CA_1A-3A-19A shall support the following requirements in Release 12.

86.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-3A-19A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 86.1.1-1: Void

86.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-3A-19A specified in [5] which are listed in Table B.2.4-1 of [7].

86.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-3A-19A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

87 CA configuration CA_1A-3A-20A Independent of Release

CA configuration CA_1A-3A-20A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

87.1 CA_1A-3A-20A UE

UEs that conform to Release 10 and support CA_1A-3A-20A shall support the following requirements in Release 12.

87.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-3A-20A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 87.1.1-1: Void

87.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-3A-20A specified in [5] which are listed in Table B.2.4-1 of [7].

87.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-3A-20A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

88 CA configuration CA_1A-3A Independent of Release

CA configuration CA_1A-3A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

88.1 CA_1A-3A UE

UEs that conform to Release 10 and support CA_1A-3A shall support the following requirements in Release 12.

88.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-3A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 88.1.1-1: Void

88.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-3A specified in [5] which are listed in Table B.2.4-1 of [7].

88.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-3A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

89 CA configuration CA_1A-7A-20A Independent of Release

CA configuration CA_1A-7A-20A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

89.1 CA_1A-7A-20A UE

UEs that conform to Release 10 and support CA_1A-7A-20A shall support the following requirements in Release 12.

89.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-7A-20A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 89.1.1-1: Void

89.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-7A-20A specified in [5] which are listed in Table B.2.4-1 of [7].

89.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-7A-20A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

90 CA configuration CA_1A-7A Independent of Release

CA configuration CA_1A-7A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

90.1 CA_1A-7A UE

UEs that conform to Release 10 and support CA_1A-7A shall support the following requirements in Release 12.

90.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-7A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 90.1.1-1: Void

90.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-7A specified in [5] which are listed in Table B.2.4-1 of [7].

90.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-7A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

91 CA configuration CA_1A-19A-21A Independent of Release

CA configuration CA_1A-19A-21A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

91.1 CA_1A-19A-21A UE

UEs that conform to Release 10 and support CA_1A-19A-21A shall support the following requirements in Release 12.

91.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-19A-21A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 91.1.1-1: Void

91.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-19A-21A specified in [5].

91.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-19A-21A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

92 Void

93 CA configuration CA_2A-4A-5A Independent of Release

CA configuration CA_2A-4A-5A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

93.1 CA_2A-4A-5A UE

UEs that conform to Release 10 and support CA_2A-4A-5A shall support the following requirements in Release 12.

93.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-4A-5A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 93.1.1-1: Void

93.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-4A-5A specified in [5].

93.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-4A-5A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

94 CA configuration CA_2A-4A-13A Independent of Release

CA configuration CA_2A-4A-13A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

94.1 CA_2A-4A-13A UE

UEs that conform to Release 10 and support CA_2A-4A-13A shall support the following requirements in Release 12.

94.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-4A-13A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 94.1.1-1: Void

94.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-4A-13A specified in [5].

94.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-4A-13A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

95 CA configuration CA_2A-4A-12A Independent of Release

CA configuration CA_2A-4A-12A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

95.1 CA_2A-4A-12A UE

UEs that conform to Release 10 and support CA_2A-4A-12A shall support the following requirements in Release 12.

95.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-4A-12A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 95.1.1-1: Void

95.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-4A-12A specified in [5].

95.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-4A-12A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

96 CA configuration CA_2A-12B Independent of Release

CA configuration CA_2A-12B is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

96.1 CA_2A-12B UE

UEs that conform to Release 10 and support CA_2A-12B shall support the following requirements in Release 12.

96.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-12B specified in [4] which are listed in Table B.4.3-1 of [7].

Table 96.1.1-1: Void

96.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-12B specified in [5].

96.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-12B among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

97 CA configuration CA_3A-7C Independent of Release

CA configuration CA_3A-7C is specified in Release 12 and Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

97.1 CA_3A-7C UE

UEs that conform to Release 10 and support CA_3A-7C shall support the following requirements in Release 13.

97.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-7C specified in [11] which are listed in Table B.4.3-1 of [13].

Table 97.1.1-1: Void

97.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-7C specified in [12].

97.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-7C among the CA demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

98 CA configuration CA_3A-7A-20A Independent of Release

CA configuration CA_3A-7A-20A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

98.1 CA_3A-7A-20A UE

UEs that conform to Release 10 and support CA_3A-7A-20A shall support the following requirements in Release 12.

98.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-7A-20A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 98.1.1-1: Void

98.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-7A-20A specified in [5].

98.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-7A-20A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

99 Void

100 CA configuration CA_4A-12B Independent of Release

CA configuration CA_4A-12B is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

100.1 CA_4A-12B UE

UEs that conform to Release 10 and support CA_4A-12B shall support the following requirements in Release 12.

100.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-12B specified in [4] which are listed in Table B.4.3-1 of [7].

Table 100.1.1-1: Void

100.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-12B specified in [5].

100.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-12B among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

101 CA configuration CA_12B Independent of Release

CA configuration CA_12B is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

101.1 CA_12B UE

UEs that conform to Release 10 and support CA_12B shall support the following requirements in Release 12.

101.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_12B specified in [4] which are listed in Table B.4.2-1 of [7].

Table 101.1.1-1: Void

101.1.2 RRM Requirements

The UE shall comply with the RRM Requirements for CA_12B specified in [5] which are listed in Table B.2.2-1 of [7].

101.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_12B among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

102 Void

102.1 Void

102.1.1 Void

Table 102.1.1-1: Void

102.1.2 Void

102.1.3 Void

103 Void

103.1 Void

103.1.1 Void

Table 103.1.1-1: Void

103.1.2 Void

103.1.3 Void

104 CA configuration CA_3C-7A Independent of Release

CA configuration CA_3C-7A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

104.1 CA_3C-7A UE

UEs that conform to Release 10 and support CA_3C-7A shall support the following requirements in Release 12.

104.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3C-7A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 104.1.1-1: Void

104.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3C-7A specified in [5].

104.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3C-7A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

105 CA configuration CA_2A-5A-12A Independent of Release

CA configuration CA_2A-5A-12A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

105.1 CA_2A-5A-12A UE

UEs that conform to Release 10 and support CA_4A-4A-12A shall support the following requirements in Release 12.

105.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-5A-12A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 105.1.1-1: Void

105.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-5A-12A specified in [5].

105.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-5A-12A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

106 CA configuration CA_4A-5A-12A Independent of Release

CA configuration CA_4A-5A-12A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

106.1 CA_4A-5A-12A UE

UEs that conform to Release 10 and support CA_2A-4A-12A shall support the following requirements in Release 12.

106.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-5A-12A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 106.1.1-1: Void

106.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-5A-12A specified in [5].

106.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-5A-12A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

107 CA configuration CA_2A-5A-30A Independent of Release

CA configuration CA_2A-5A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

107.1 CA_2A-5A-30A UE

UEs that conform to Release 10 and support CA_2A-5A-30A shall support the following requirements in Release 12.

107.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-5A-30A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 107.1.1-1: Void

107.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-5A-30A specified in [3].

107.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-5A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

108 CA configuration CA_2A-12A-30A Independent of Release

CA configuration CA_2A-12A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

108.1 CA_2A-12A-30A UE

UEs that conform to Release 10 and support CA_2A-12A-30A shall support the following requirements in Release 12.

108.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-12A-30A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 108.1.1-1: Voir

108.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-12A-30A specified in [5].

108.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-12A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

109 CA configuration CA_2A-29A-30A Independent of Release

CA configuration CA_2A-29A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

109.1 CA_2A-29A-30A UE

UEs that conform to Release 10 and support CA_2A-29A-30A shall support the following requirements in Release 12.

109.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-29A-30A specified in [4] which are listed in Table B.4.4-1 of [7].

Table 109.1.1-1: Void

109.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-29A-30A specified in [5].

109.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-29A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

110 CA configuration CA_4A-5A-30A Independent of Release

CA configuration CA_4A-5A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

110.1 CA_4A-5A-30A UE

UEs that conform to Release 10 and support CA_4A-5A-30A shall support the following requirements in Release 12.

110.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-5A-30A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 110.1.1-1: Void

110.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-5A-30A specified in [5].

110.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-5A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

111 CA configuration CA_4A-12A-30A Independent of Release

CA configuration CA_4A-12A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

111.1 CA_4A-12A-30A UE

UEs that conform to Release 10 and support CA_4A-12A-30A shall support the following requirements in Release 12.

111.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-12A-30A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 111.1.1-1: Void

111.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-12A-30A specified in [5].

111.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-12A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

112 CA configuration CA_4A-29A-30A Independent of Release

CA configuration CA_4A-29A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

112.1 CA_4A-29A-30A UE

UEs that conform to Release 10 and support CA_4A-29A-30A shall support the following requirements in Release 12.

112.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-29A-30A specified in [4] which are listed in Table B.4.4-1 of [7].

Table 112.1.1-1: Void

112.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-92A-30A specified in [5].

112.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-92A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

113 CA configuration CA_2A-30A Independent of Release

CA configuration CA_2A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10.

113.1 CA_2A-30A UE

UEs that conform to Release 10 and support CA_2A-30A shall support the following requirements in Release 12.

113.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-30A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 113.1.1-1: Void

113.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-30A specified in [5] which are listed in Table B.2.4-1 of [7].

113.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

114 CA configuration CA_4A-30A Independent of Release

CA configuration CA_4A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

114.1 CA_4A-30A UE

UEs that conform to Release 10 and support CA_4A-30A shall support the following requirements in Release 12.

114.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-30A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 114.1.1-1: Void

114.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-30A specified in [5] which are listed in Table B.2.4-1 of [7].

114.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

115 CA configuration CA_5A-30A Independent of Release

CA configuration CA_5A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards

115.1 CA_5A-30A UE

UEs that conform to Release 10 and support CA_5A-30A shall support the following requirements in Release 12.

115.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_5A-30A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 115.1.1-1: Void

115.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_5A-30A specified in [5] which are listed in Table B.2.4-1 of [7].

115.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_5A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

116 CA configuration CA_12A-30A Independent of Release

CA configuration CA_12A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

116.1 CA_12A-30A UE

UEs that conform to Release 10 and support CA_12A-30A shall support the following requirements in Release 12.

116.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_12A-30A specified in [4] which are listed in Table B.4.3-1 of [7].

Table 116.1.1-1: Void

116.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_12A-30A specified in [5] which are listed in Table B.2.4-1 of [7].

116.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-4A-13A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

117 CA configuration CA_29A-30A Independent of Release

CA configuration CA_29A-30A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

117.1 CA_29A-30A UE

UEs that conform to Release 10 and support CA_29A-30A shall support the following requirements in Release 12.

117.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_29A-30A specified in [4] which are listed in Table B.4.4-1 of [7].

Table 117.1.1-1: Void

117.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_29A-30A specified in [5] which are listed in Table B.2.4-1 of [7].

117.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_29A-30A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

118 CA configuration CA_40D Independent of Release

CA configuration CA_40D is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

118.1 CA_40D UE

UEs that conform to Release 10 and support CA_40D shall support the following requirements in Release 12.

118.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_40D specified in [4] which are listed in Table B.4.2-1 of [7].

118.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_40D specified in [5] which are listed in Table B.2.2-1 of [7].

118.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_40D among demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

119 Void

120 Void

121 Void

122 CA configuration CA_1A-28A Independent of Release

CA configuration CA_1A-28A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

122.1 CA_1A-28A UE

UEs that conform to Release 10 and support CA_1A-28A shall support the following requirements in Release 12.

122.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-28A specified in [4] which are listed in Table B.4.3-1 of [7].

122.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-28A specified in [5] which are listed in Table B.2.4-1 of [7].

122.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-28A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

123 CA configuration CA_5A-13A Independent of Release

CA configuration CA_5A-13A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

123.1 CA_5A-13A UE

UEs that conform to Release 10 and support CA_5A-13A shall support the following requirements in Release 12.

123.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_5A-13A specified in [4] which are listed in Table B.4.3-1 of [7].

123.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_5A-13A specified in [5] which are listed in Table B.2.4-1 of [7].

123.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_5A-13A among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

124 CA configuration CA_1A-3A-26A Independent of Release

CA configuration CA_1A-3A-26A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

124.1 CA_1A-3A-26A UE

UEs that conform to Release 10 and support CA_1A-3A-26A shall support the following requirements in Release 12.

124.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-3A-26A specified in [4] which are listed in Table B.4.3-1 of [7].

124.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-3A-26A specified in [5].

124.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-3A-26A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

125 CA configuration CA_2C Independent of Release

CA configuration CA_2C is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

125.1 CA_2C UE

UEs that conform to Release 10 and support CA_2C shall support the following requirements in Release 12.

125.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2C specified in [4] which are listed in Table B.4.2-1 of [7].

125.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2C specified in [5] which are listed in Table B.2.2-1 of [7].

125.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2C among the demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

126 CA configuration CA_2C-29A Independent of Release

CA configuration CA_2C-29A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

126.1 CA_2C-29A UE

UEs that conform to Release 10 and support CA_2C-29A shall support the following requirements in Release 12.

126.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2C-29A specified in [4] which are listed in Table B.4.4-1 of [7].

126.1.2 RRM Requirements

The UE shall comply with the RRM requirements for 2C-29A specified in [5].

126.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2C-29A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

127 CA configuration CA_2A-4A-29A Independent of Release

CA configuration CA_2A-4A-29A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

127.1 CA_2A-4A-29A UE

UEs that conform to Release 10 and support CA_2A-4A-29A shall support the following requirements in Release 12.

127.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-4A-29A specified in [4] which are listed in Table B.4.4-1 of [7].

127.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-4A-29A specified in [5].

127.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-4A-29A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

128 CA configuration CA_7A-8A Independent of Release

CA configuration CA_7A-8A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

128.1 CA_7A-8A UE

UEs that conform to Release 10 and support CA_7A-8A shall support the following requirements in Release 12.

128.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7A-8A specified in [4] which are listed in Table B.4.3-1 of [7].

128.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_7A-8A specified in [5] which are listed in Table B.2.4-1 of [7].

128.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7A-8A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

129 CA configuration CA_7A-8A-20A Independent of Release

CA configuration CA_7A-8A-20A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

129.1 CA_7A-8A-20A UE

UEs that conform to Release 10 and support CA_7A-8A-20A shall support the following requirements in Release 12.

129.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7A-8A-20A specified in [4] which are listed in Table B.4.3-1 of [7].

129.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_7A-8A-20A specified in [5].

129.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7A-8A-20A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

130 CA configuration CA_39C-41A Independent of Release

CA configuration CA_39C-41A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

130.1 CA_39C-41A UE

UEs that conform to Release 10 and support CA_39C-41A shall support the following requirements in Release 12.

130.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_39C-41A specified in [4] which are listed in Table B.4.3-1 of [7].

130.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_39C-41A specified in [5].

130.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_39C-41A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

131 CA configuration CA_39A-41C Independent of Release

CA configuration CA_39A-41C is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

131.1 CA_39A-41C UE

UEs that conform to Release 10 and support 39A-41C shall support the following requirements in Release 12.

131.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_39A-41C specified in [4] which are listed in Table B.4.3-1 of [7].

131.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_39A-41C specified in [5].

131.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_39A-41C among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

132 CA configuration CA_7A-12A Independent of Release

CA configuration CA_7A-12A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards.

132.1 CA_7A-12A UE

UEs that conform to Release 10 and support CA_7A-12A shall support the following requirements in Release 12.

132.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7A-12A specified in [4] which are listed in Table B.4.3-1 of [7].

132.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_7A-12A specified in [5] which are listed in Table B.2.4-1 of [7].

132.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7A-12A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1 of [7].

133 CA configuration CA_4A-7A-12A Independent of Release

CA configuration CA_4A-7A-12A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

133.1 CA_4A-7A-12A UE

UEs that conform to Release 10 and support CA_4A-7A-12A shall support the following requirements in Release 12.

133.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-7A-12A specified in [4] which are listed in Table B.4.3-1 of [7].

133.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-7A-12A specified in [5].

133.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-7A-12A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

134 CA configuration CA_2A-5A-13A Independent of Release

CA configuration CA_2A-5A-13A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

134.1 CA_2A-5A-13A UE

UEs that conform to Release 10 and support CA_2A-5A-13A shall support the following requirements in Release 12.

134.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-5A-13A specified in [4] which are listed in Table B.4.3-1 of [7].

134.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-5A-13A specified in [5].

134.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-5A-13A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

135 CA configuration CA_4A-5A-13A Independent of Release

CA configuration CA_4A-5A-13A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

135.1 CA_4A-5A-13A UE

UEs that conform to Release 10 and support CA_4A-5A-13A shall support the following requirements in Release 12.

135.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-5A-13A specified in [4] which are listed in Table B.4.3-1 of [7].

135.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-5A-13A specified in [5].

135.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-5A-13A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

136 CA configuration CA_1A-18A-28A Independent of Release

CA configuration CA_1A-18A-28A is specified in Release 12 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

136.1 CA_1A-18A-28A UE

UEs that conform to Release 10 and support CA_1A-18A-28A shall support the following requirements in Release 12.

136.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-18A-28A specified in [4] which are listed in Table B.4.3-1 of [7].

136.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-18A-28A specified in [5].

136.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-18A-28A among the CA demodulation performance and CSI reporting requirements specified in [4] and listed in Table B.3.2-1of [7].

137 Void

138 Void

139 Void

140 CA configuration CA_1A-3A-28A Independent of Release

CA configuration CA_1A-3A-28A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

140.1 CA_1A-3A-28A UE

UEs that conform to Release 10 and support CA_1A-3A-28A shall support the following requirements in Release 13.

140.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-3A-28A specified in [11] which are listed in Table B.4.3-1 of [13].

140.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-3A-28A specified in [12] which are listed in Table B.2.4-1 of [13].

140.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-3A-28A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

141 CA configuration CA_1A-7A-28A Independent of Release

CA configuration CA_1A-7A-28A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

141.1 CA_1A-7A-28A UE

UEs that conform to Release 10 and support CA_1A-7A-28A shall support the following requirements in Release 13.

141.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-7A-28A specified in [11] which are listed in Table B.4.3-1 of [13].

141.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-7A-28A specified in [12] which are listed in Table B.2.4-1 of [13].

141.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-7A-28A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

142 CA configuration CA_2A_5A_29A Independent of Release

CA configuration CA_2A-5A-29A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

142.1 CA_2A-5A-29A UE

UEs that conform to Release 10 and support CA_2A-5A-29A shall support the following requirements in Release 13.

142.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-5A-29A specified in [11] which are listed in Table B.4.4-1 of [13].

142.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-5A-29A specified in [12] which are listed in Table B.2.4-1 of [13].

142.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-5A-29A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

143 CA configuration CA_3C_5A Independent of Release

CA configuration CA_3C-5A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

143.1 CA_3C-5A UE

UEs that conform to Release 10 and support CA_3C-5A shall support the following requirements in Release 13.

143.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3C-5A specified in [11] which are listed in Table B.4.3-1 of [13].

143.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3C-5A specified in [12] which are listed in Table B.2.4-1 of [13].

143.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3C-5A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

144 CA configuration CA_3A_7B Independent of Release

CA configuration CA_3A-7B is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

144.1 CA_3A-7B UE

UEs that conform to Release 10 and support CA_3A-7B shall support the following requirements in Release 13.

144.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-7B specified in [11] which are listed in Table B.4.3-1 of [13].

144.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-7 B specified in [12] which are listed in Table B.2.4-1 of [13].

144.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-7B among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

145 CA configuration CA_3A_7A_8A Independent of Release

CA configuration CA_3A-7A-8A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

145.1 CA_3A-7A-8A UE

UEs that conform to Release 10 and support CA_3A-7A-8A shall support the following requirements in Release 13.

145.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-7A-8A specified in [11] which are listed in Table B.4.3-1 of [13].

145.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-7A-8A specified in [12] which are listed in Table B.2.4-1 of [13].

145.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-7A-8A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

146 CA configuration CA_3A_7A_28A Independent of Release

CA configuration CA_3A-7A-28A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

146.1 CA_3A-7A-28A UE

UEs that conform to Release 10 and support CA_3A-7A-28A shall support the following requirements in Release 13.

146.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-7A-28A specified in [11] which are listed in Table B.4.3-1 of [13].

146.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-7A-28A specified in [12] which are listed in Table B.2.4-1 of [13].

146.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-7A-28A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

147 CA configuration CA_5A-29A Independent of Release

CA configuration CA_5A-29A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

147.1 CA_5A-29A UE

UEs that conform to Release 10 and support CA_5A-29A shall support the following requirements in Release 13.

147.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_5A-29A specified in [11] which are listed in Table B.4.4-1 of [13].

147.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_5A-29A specified in [12] which are listed in Table B.2.4-1 of [13].

147.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_5A-29A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

148 CA configuration CA_7B Independent of Release

CA configuration CA_7B is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

148.1 CA_7B UE

UEs that conform to Release 10 and support CA_7B shall support the following requirements in Release 13.

148.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7B specified in [11] which are listed in Table B.4.2-1 of [13].

148.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_7B specified in [12] which are listed in Table B.2.4-1 of [13].

148.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7B among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

149 CA configuration CA_7B_28A Independent of Release

CA configuration CA_7B-28A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

149.1 CA_7B-28A UE

UEs that conform to Release 10 and support CA_7B-28A shall support the following requirements in Release 13.

149.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7B-28A specified in [11] which are listed in Table B.4.3-1 of [13].

149.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_7B-28A specified in [12] which are listed in Table B.2.4-1 of [13].

149.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7B-28A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

150 CA configuration CA_7C_28A Independent of Release

CA configuration CA_7C-28A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

150.1 CA_7C-28A UE

UEs that conform to Release 10 and support CA_7C-28A shall support the following requirements in Release 13.

150.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7C-28A specified in [11] which are listed in Table B.4.3-1 of [13].

150.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_7C-28A specified in [12] which are listed in Table B.2.4-1 of [13].

150.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7C-28A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

151 Void

151.1 Void

151.1.1 Void

151.1.2 Void

151.1.3 Void

152 CA configuration CA_38A-40A Independent of Release

CA configuration CA_38A-40A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

152.1 CA_38A-40A UE

UEs that conform to Release 10 and support CA_38A-40A shall support the following requirements in Release 13.

152.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_38A-40A specified in [11] which are listed in Table B.4.3-1 of [13].

152.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_38A-40A specified in [12] which are listed in Table B.2.4-1 of [13].

152.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_38A-40A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

153 CA configuration CA_38A-40C Independent of Release

CA configuration CA_38A-40C is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

153.1 CA_38A-40C UE

UEs that conform to Release 10 and support CA_38A-40C shall support the following requirements in Release 13.

153.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_38A-40C specified in [11] which are listed in Table B.4.3-1 of [13].

153.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_38A-40C specified in [12] which are listed in Table B.2.4-1 of [13].

153.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_38A-40C among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

154 Void

154.1 Void

154.1.1 Void

154.1.2 Void

154.1.3 Void

155 CA configuration CA_41A_42C Independent of Release

CA configuration CA_41A-42C is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

155.1 CA_41A-42C UE

UEs that conform to Release 10 and support CA_41A-42C shall support the following requirements in Release 13.

155.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_41A-42C specified in [11] which are listed in Table B.4.3-1 of [13].

155.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_41A-42C specified in [12] which are listed in Table B.2.4-1 of [13].

155.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_41A-42C among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

156 CA configuration CA_2A-28A Independent of Release

CA configuration CA_2A-28A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

156.1 CA_2A-28A UE

UEs that conform to Release 10 and support CA_2A-28A shall support the following requirements in Release 13.

156.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-28A specified in [11] which are listed in Table B.4.3-1 of [13].

156.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-28A specified in [12] which are listed in Table B.2.4-1 of [13].

156.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-28A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

157 CA configuration CA_3A-31A Independent of Release

CA configuration CA_3A-31A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

157.1 CA_3A-31A UE

UEs that conform to Release 10 and support CA_3A-31A shall support the following requirements in Release 13.

157.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_3A-31A specified in [11] which are listed in Table B.4.3-1 of [13].

157.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_3A-31A specified in [12] which are listed in Table B.2.4-1 of [13].

157.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_3A-31A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

158 CA configuration CA_4A-28A Independent of Release

CA configuration CA_4A-28A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

158.1 CA_4A-28A UE

UEs that conform to Release 10 and support CA_4A-28A shall support the following requirements in Release 13.

158.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_4A-28A specified in [11] which are listed in Table B.4.3-1 of [13].

158.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_4A-28A specified in [12] which are listed in Table B.2.4-1 of [13].

158.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_4A-28A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

159 CA configuration CA_7A-22A Independent of Release

CA configuration CA_7A-22A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

159.1 CA_7A-22A UE

UEs that conform to Release 10 and support CA_7A-22A shall support the following requirements in Release 13.

159.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_7A-22A specified in [11] which are listed in Table B.4.3-1 of [13].

159.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_7A-22A specified in [12] which are listed in Table B.2.4-1 of [13].

159.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_7A-22A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

160 CA configuration CA_20A-31A Independent of Release

CA configuration CA_20A-31A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

160.1 CA_20A-31A UE

UEs that conform to Release 10 and support CA_20A-31A shall support the following requirements in Release 13.

160.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_20A-31A specified in [11] which are listed in Table B.4.3-1 of [13].

160.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_20A-31A specified in [12] which are listed in Table B.2.4-1 of [13].

160.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_20A-31A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

161 CA configuration CA_25A-26A Independent of Release

CA configuration CA_25A-12A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

161.1 CA_25A-26A UE

UEs that conform to Release 10 and support CA_25A-26A shall support the following requirements in Release 13.

161.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_25A-26A specified in [11] which are listed in Table B.4.3-1 of [13] with the following exception. For uplink transmissions in Band 26, the UE shall comply with the additional spurious emissions requirements in sub-clause 6.6.3.3.5 (“NS_12”) and sub-clause 6.6.3.36 (“NS_13”) as specified in [2].

161.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_25A-26A specified in [12] which are listed in Table B.2.4-1 of [13].

161.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_25A-26A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

162 CA configuration CA_42D Independent of Release

CA configuration CA_42D is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

162.1 CA_42D UE

UEs that conform to Release 10 and support CA_42D shall support the following requirements in Release 13.

162.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_42D specified in [11] which are listed in Table B.4.2-1 of [13].

162.1.2 RRM Requirements

The UE shall comply with the following RRM Requirements for CA_42D specified in [12] which are listed in Table B.2.2-1 of [13].

162.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the demodulation performance and CSI reporting requirements for CA_42D specified in [11], which are listed in section B.3.2-1 of [13].

163 Void

164 Void

165 CA configuration CA_2C-5A Independent of Release

CA configuration CA_2C-5A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

165.1 CA_2C-5A UE

UEs that conform to Release 10 and support CA_2C-5A shall support the following requirements in Release 13.

165.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2C-5A specified in [11] which are listed in Table B.4.3-1 of [13].

165.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2C-5A specified in [12].

165.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2C-5A among the CA demodulation performance and CSI reporting requirements demodulation performance and CSI reporting specified in [11].

166 Void

167 CA configuration CA_2C-12A Independent of Release

CA configuration CA_2C-12A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

167.1 CA_2C-12A UE

UEs that conform to Release 10 and support CA_2C-12A shall support the following requirements in Release 13.

167.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2C-12A specified in [11] which are listed in Table B.4.3-1 of [13].

167.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2C-12A specified in [12].

167.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2C-12A among the CA demodulation performance and CSI reporting requirements demodulation performance and CSI reporting specified in [11].

168 CA configuration CA_2C-30A Independent of Release

CA configuration CA_2C-30A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

168.1 CA_2C-30A UE

UEs that conform to Release 10 and support CA_2C-30A shall support the following requirements in Release 13.

168.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2C-30A specified in [11] which are listed in Table B.4.3-1 of [13].

168.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2C-30A specified in [12].

168.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2C-30A among the CA demodulation performance and CSI reporting requirements demodulation performance and CSI reporting specified in [11].

169 Void

170 Void

171 Void

172 Void

173 Void

174 CA configuration CA_2A-4A-30A Independent of Release

CA configuration CA_2A-4A-30A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

174.1 CA_2A-4A-30A UE

UEs that conform to Release 10 and support CA_2A-4A-30A shall support the following requirements in Release 13.

174.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_2A-4A-30A specified in [11] which are listed in Table B.4.3-1 of [13].

174.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_2A-4A-30A specified in [12].

174.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_2A-4A-30A among the CA demodulation performance and CSI reporting requirements demodulation performance and CSI reporting specified in [11].

175 – 204 Void

205 CA configuration CA_19A-28A Independent of Release

CA configuration CA_19A-28A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards.

205.1 CA_19A-28A UE

UEs that conform to Release 10 and support CA_19A-28A shall support the following requirements in Release 13.

205.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_19A-28A specified in [11] which are listed in Table B.4.3-1 of [13].

205.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_19A-28A specified in [12] which are listed in Table B.2.4-1 of [13].

205.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_19A-28A among the demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

206 CA configuration CA_1A-19A-28A Independent of Release

CA configuration CA_1A-19A-28A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

206.1 CA_1A-19A-28A UE

UEs that conform to Release 10 and support CA_1A-19A-28A shall support the following requirements in Release 13.

206.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-19A-28A specified in [11] which are listed in Table B.4.3-1 of [13].

206.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-19A-28A specified in [12] which are listed in Table B.2.4-1 of [13].

206.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-19A-28A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

207 CA configuration CA_1A-8A-11A Independent of Release

CA configuration CA_1A-8A-11A is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

207.1 CA_1A-8A-11A UE

UEs that conform to Release 10 and support CA_1A-8A-11A shall support the following requirements in Release 13.

207.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-8A-11A specified in [11] which are listed in Table B.4.3-1 of [13].

207.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-8A-11A specified in [12] which are listed in Table B.2.4-1 of [13].

207.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-8A-11A among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

208 CA configuration CA_1A-3C Independent of Release

CA configuration CA_1A-3C is specified in Release 13 but is defined as a release-independent CA configuration for Rel-10 upwards for UE Categories specified in [10].

208.1 CA_1A-3C UE

UEs that conform to Release 10 and support CA_1A-3C shall support the following requirements in Release 13.

208.1.1 RF Requirements

The UE shall comply with the RF requirements for CA_1A-3C specified in [11] which are listed in Table B.4.3-1 of [13].

208.1.2 RRM Requirements

The UE shall comply with the RRM requirements for CA_1A-3C specified in [12] which are listed in Table B.2.4-1 of [13].

208.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the tests applicable for CA_1A-3C among demodulation performance and CSI reporting requirements specified in [11] and listed in Table B.3.2-1 of [13].

209 – 213 Void

Annex A (informative): Frequency arrangement for overlapping operating bands

The following information is provided in order to assist a UE derive the DL EARFCN and UL EARFCN in a multi-band environment, in which multiple overlapping operating bands may be indicated in the fields *freqBandIndicator* and *multiBandInfoList* of SIB1.

The overlapping bands, independent of release, which may be indicated in a cell are shown in Table A-1 for applicable E-UTRA bands. The DL EARFCN and UL EARFCN are derived according to [2].

Table A-1: Overlapping bands (multi-band environments) for each E-UTRA band

E-UTRA Operating Band	Overlapping E-UTRA operating bands	Duplex Mode
2	25	FDD
3	9	FDD
4	10	FDD
5	18, 19, 26	FDD
9	3	FDD
10	4	FDD
12	17	FDD
17	12	FDD
18	5, 26, 27	FDD
19	5, 26	FDD
25	2	FDD
26	5, 18, 19, 27	FDD
27	18, 26	FDD
33	39	TDD
38	41	TDD
39	33	TDD
41	38	TDD

Annex B (normative): Common Requirements

B.1 Purpose of annex

The purpose of Annex B is to group the requirements that are common for several bands or CA configurations in this specification and use the common tables as references.

B.2 Common RRM requirements

B.2.1 Common RRM requirements for a band independent of release

The requirements and test cases listed in Table B.2.1-1 are specified in [8].

Table B.2.1-1: Common RRM requirements for a band independent of release

Section / Clause	Description
4 ^{Note 1}	E-UTRAN RRC_IDLE state mobility
5	E-UTRAN RRC_CONNECTED state mobility
6 ^{Note 2}	RRC Connection Mobility Control
7 ^{Note 3}	Timing and signalling characteristics
8 ^{Note 4}	UE Measurements Procedures in RRC_CONNECTED State
9 ^{Note 5}	Measurements performance requirements for UE
A.4 ^{Note 1}	E-UTRAN RRC_IDLE state
A.5	E-UTRAN RRC CONNECTED Mode Mobility
A.6 ^{Note 2}	RRC Connection Control
A.7 ^{Note 3}	Timing and Signalling Characteristics
A.8 ^{Note 4}	UE Measurements Procedures
A.9 ^{Note 5}	Measurement Performance Requirements
<p>NOTE 1: All requirements and the corresponding test cases shall apply, except: - for supporting the corresponding band in Rel-9 and below: clause 4.3 (Minimization of Drive Tests).</p> <p>NOTE 2: All requirements and the corresponding test cases shall apply, except: - for supporting the corresponding band in Rel-8: clauses 6.3 (RRC Connection Release with Redirection), 6.4 (CSG Proximity Indication for E-UTRAN and UTRAN).</p> <p>NOTE 3: All requirements and corresponding test cases shall apply, except those defined in sections 7.4 and 7.5.</p> <p>NOTE 4: All requirements and corresponding test cases shall apply, except: - for supporting the corresponding band in Rel-8: clauses 8.1.2.5 (E-UTRAN OTDOA Intra-Frequency RSTD Measurements), 8.1.2.6 (E-UTRAN Inter-Frequency OTDOA Measurements), 8.1.2.7 (E-UTRAN E-CID Measurements).</p> <p>NOTE 5: All requirements and corresponding test cases shall apply, except: - for supporting the corresponding band in Rel-8: clauses 9.1.9 (UE Rx-Tx time difference), 9.1.10 (Reference Signal Time Difference).</p> <p>NOTE 6: All requirements and test cases in this table shall apply, except those defined for: carrier aggregation; measurements under time-domain measurement resource restriction, in addition to the exceptions listed above.</p>	

B.2.2 Common RRM requirements for an intra-band contiguous CA configuration

The requirements and test cases listed in Table B.2.2-1 are specified in [8].

Table B.2.2-1: Common RRM requirements for a single-band CA configuration independent of release

Section / Clause	Description
7.1	UE transmit timing
7.7	SCell Activation and Deactivation Delay for E-UTRA Carrier Aggregation
7.8	Interruptions with Carrier Aggregation
8.2	Capabilities for Support of Event Triggering and Reporting Criteria
8.3	Measurements for E-UTRA carrier aggregation
8.4	OTDOA RSTD Measurements for E-UTRAN carrier aggregation
9.1.11	Carrier aggregation measurement accuracy
9.1.12	Reference Signal Time Difference (RSTD) Measurement Accuracy Requirements for Carrier Aggregation
A.8	UE Measurements Procedures
A.9	Measurement Performance Requirements
NOTE:	Only requirements and test cases in this table defined for intra-band contiguous carrier aggregation shall apply.

B.2.3 Common RRM requirements for an inter-band CA configuration

The requirements and test cases listed in Table B.2.3-1 are specified in [8].

Table B.2.3-1: Common RRM requirements for a band-combination CA configuration

Section / Clause	Description
7.1	UE transmit timing
7.7	SCell Activation and Deactivation Delay for E-UTRA Carrier Aggregation
7.8	Interruptions with Carrier Aggregation
8.2	Capabilities for Support of Event Triggering and Reporting Criteria
8.3	Measurements for E-UTRA carrier aggregation
8.4	OTDOA RSTD Measurements for E-UTRAN carrier aggregation
9.1.11	Carrier aggregation measurement accuracy
9.1.12	Reference Signal Time Difference (RSTD) Measurement Accuracy Requirements for Carrier Aggregation
A.8	UE Measurements Procedures
A.9	Measurement Performance Requirements
NOTE:	Only requirements and test cases in this table defined for inter-band carrier aggregation shall apply.

B.3 Common UE performance requirements

B.3.1 Void

Table B.3.1-1: Void

B.3.2 Void

Table B.3.2-1: Void

B.3.3 Void

Table B.3.3-1: Void

B.4 Common UE RF requirements

B.4.1 Common UE RF requirements for a band independent of release

The requirements and test cases listed in Table B.4.1-1 are specified in [9].

Table B.4.1-1: Common UE RF requirements for a band independent of release

Section / Clause	Description
5.5	Operating bands
5.6	Channel bandwidth
5.7	Channel arrangement
6.2	Transmit power
6.3	Output power dynamics
6.5	Transmit signal quality
6.6	Output RF spectrum emissions
6.7	Transmit intermodulation
7.3	Reference sensitivity power level
7.4	Maximum input level
7.5	Adjacent Channel Selectivity (ACS)
7.6	Blocking characteristics
7.7	Spurious response
7.8	Intermodulation characteristics
7.9	RX spurious emissions

B.4.2 Common UE RF requirements for an intra-band contiguous CA configuration

The requirements and test cases listed in Table B.4.2-1 are specified in [9].

Table B.4.2-1: Common UE RF requirements for an intra-band contiguous CA configuration independent of release

Section / Clause	Description
5.5A	Operating bands for CA
5.6A	Channel bandwidths per operating band for CA
5.7.1A	Channel spacing for CA
5.7.2A	Channel raster for CA
5.7.4A	TX–RX frequency separation for CA
6.2.2A	UE maximum output power for CA
6.2.3A	UE maximum output power for modulation/channel bandwidth for CA
6.2.4A	UE maximum output power with additional requirements for CA
6.2.5A	Configured transmitted power for CA
6.3.2A	UE Minimum output power for CA
6.3.3A	UE Transmit OFF power for CA
6.3.4A	ON/OFF time mask for CA
6.3.5A	Power control for CA
6.5.1A	Frequency error for CA
6.5.2A	Transmit modulation quality for CA
6.6.1A	Occupied bandwidth for CA
6.6.2.1A	Spectrum emission mask for CA
6.6.2.2A	Additional Spectrum Emission mask for CA
6.6.2.3.2A	UTRA ACLR for CA
6.6.2.3.3A	E-UTRA ACLR for CA
6.6.3.1A	Minimum requirements for CA
6.6.3.2A	Spurious emission band UE co-existence for CA
6.6.3.3A	Additional spurious emissions for CA
6.7.1A	Minimum requirement for CA
7.3.1A	Reference sensitivity for CA
7.4.1A	Maximum input level for CA
7.5.1A	Adjacent Channel Selectivity (ACS) for CA
7.6.1.1A	In-band blocking for CA
7.6.2.1A	Out-of-band blocking for CA
7.6.3.1A	Narrow band blocking for CA
7.7.1A	Spurious response for CA
7.8.1A	Wideband intermodulation for CA
7.10.1A	Receiver response for CA

B.4.3 Common UE RF requirements for an inter-band CA configuration

The requirements and test cases listed in Table B.4.3-1 are specified in [9].

Table B.4.3-1: Common UE RF requirements for an inter-band CA configuration independent of release

Section / Clause	Description
5.5A	Operating bands for CA
5.6A.1	Channel bandwidths per operating band for CA
5.7.2A	Channel raster for CA
6.2.2A	UE maximum output power for CA
6.2.3A	UE maximum output power for modulation/channel bandwidth for CA
6.2.5	Configured transmitted power
7.3.1A	Reference sensitivity for CA
7.4.1A	Maximum input level for CA
7.5.1A	Adjacent Channel Selectivity (ACS) for CA
7.6.1.1A	In-band blocking for CA
7.6.2.1A	Out-of-band blocking for CA
7.6.3.1A	Narrow band blocking for CA
7.7.1A	Spurious response for CA
7.8.1A	Wideband intermodulation for CA

Annex C (informative): Change history

Table C.1: Change History

Date	TSG#	TSG Doc.	CR	Subject	Old	New
11-2009	RP#46	RP-091141		TS36.307 V0.1.0 approved by RAN (Originally in R4-095022)	-	0.1.0
02-2010	R4#54	R4-100419		For release 9 version, replace sections 4 to 6 as 'Void' and add a new void section as section 7.	0.1.0	0.2.0
03-2010	RP#47	RP-100162		TS36.307 v1.0.0 for approval	0.2.0	1.0.0
03-2010	RP#47	RP-100162		Approved by RAN	1.0.0	9.0.0
09-2010	RP-49	RP-100927	2	CR LTE_TDD_2600_US spectrum band definition additions to TS 36.307 V900	9.0.0	9.1.0
				Correction of section numbering	9.1.0	9.1.1
12-2010	RP-50	RP-101356	008	Band 42 and 43 parameters for UMTS/LTE 3500 (TDD) for TS 36.307	9.1.1	9.2.0
12-2010	RP-50	RP-101361	005	Introduction of L-band in TS 36.307	9.1.1	9.2.0
12-2010	RP-50	RP-101344	016	CR creating the rel-10 of the 36.307 specification	9.2.0	9.3.0
12-2010	RP-50	RP-101356	012	Band 42 and 43 parameters for UMTS/LTE 3500 (TDD) for TS 36.307	9.2.0	9.3.0
12-2010	RP-50			Raised to Rel-10 with no technical change	9.3.0	10.0.0
01-2011				Correction to history table	10.0.0	10.0.1
06-2011	RP-52	RP-110804	015	Add Expanded 1900 MHz Band (Band 25) in 36.307	10.0.1	10.1.0
06-2011	RP-52	RP-110812	022	Add 2GHz S-Band (Band 23) in 36.307 (Rel 10)	10.0.1	10.1.0
09-2011	RP-53	RP-111255	025	Add Band 22 for LTE/UMTS 3500 (FDD) to TS 36.307	10.1.0	10.2.0
03-2012	RP-55	RP-120305	028	Introduction of Band 26/XXVI to TS 36.307	10.2.0	10.3.0
2012-06	RP-56	RP-120778	036r1	Correction of references	10.3.0	10.4.0
2012-06	RP-56	RP-120789	042	Introduction of CA_1A-19A to TS 36.307	10.3.0	10.4.0
2012-06	RP-56	RP-120785	044r1	Backdating CA_41C to Rel-10	10.3.0	10.4.0
2012-06	RP-56	RP-120793	048	Introduction of APAC700(FDD) into TS 36.307 Rel.10	10.3.0	10.4.0
2012-06	RP-56	RP-120793	052	Introduction of APAC700(TDD) into TS 36.307 Rel.10	10.3.0	10.4.0
2012-06	RP-56	RP-120791	056	Introduction of e850_LB (Band 27) to TS 36.307	10.3.0	10.4.0
2012-09	RP-57	RP-121335	058	Introduction of CA_1A-21A to TS 36.307	10.4.0	10.5.0
2012-09	RP-57	RP-121337	060r1	TS 36.307 CR for CA_38	10.4.0	10.5.0
2012-09	RP-57	RP-121327	061	Introduction of CA_B7_B20 in 36.307	10.4.0	10.5.0
2012-09	RP-57	RP-121334	062r1	Add requirements for inter-band CA of B_1-18 in TS36.307	10.4.0	10.5.0
2012-09	RP-57	RP-121329	063	Introduction of CA band combination Band3 + Band5 to TS 36.307	10.4.0	10.5.0
2012-09	RP-57	RP-121338	064r1	36.307 CR for LTE_CA_B7	10.4.0	10.5.0
2012-09	RP-57	RP-121331	065	Introduction of CA_3A-20A to TS 36.307	10.4.0	10.5.0
2012-09	RP-57	RP-121333	066	Introduction of CA_8_20 RF requirements into TS36.307	10.4.0	10.5.0
2012-09	RP-57	RP-121295	069r1	Relation between EARFCN for overlapping bands with multiple FBI indication	10.4.0	10.5.0
2012-09	RP-57	RP-121324	071	Introduction of CA_B3_B7 in 36.307	10.4.0	10.5.0
2012-12	RP-58	RP-121884	080	Introduction of CA_3A-8A to TS 36.307	10.5.0	10.6.0
2012-12	RP-58	RP-121890	085	Introduction of CA_4A-5A into 36.307	10.5.0	10.6.0
2012-12	RP-58	RP-121889	087	Introduction of CA band combination Band4 + Band13 to TS 36.307 (Rel-10)	10.5.0	10.6.0
2012-12	RP-58	RP-121894	089	Introduction of CA_B5_B12 in 36.307	10.5.0	10.6.0
2012-12	RP-58	RP-121896	090	Introduction of Band 5 + Band 17 inter-band CA configuration into 36.307	10.5.0	10.6.0
2012-12	RP-58	RP-121887	094	Introduction of CA_4-12 into TS 36.307 (Rel-10)	10.5.0	10.6.0
2012-12	RP-58	RP-121882	096	[Rel-10] Introduction of inter-band CA_11-18 into TS36.307	10.5.0	10.6.0
2012-12	RP-58	RP-121861	098	Release-independent implementation of carrier aggregation configuration CA_4-7	10.5.0	10.6.0
2012-12	RP-58	RP-121901	100	Introduction of Band 29	10.5.0	10.6.0
2012-12	RP-58	RP-121719	0103	Introduction of CA band combination Band2 + Band17 to TS 36.307 (Rel-10)	10.5.0	10.6.0
2012-12	RP-58	RP-121721	0105	Introduction of CA band combination Band4 + Band17 to	10.5.0	10.6.0

				TS 36.307 (Rel-10)		
2013-06	RP-60	RP-130771	106r1	Introduction of CA 1+8 into TS36.307(Rel-10)	10.6.0	10.7.0
2013-06	RP-60	RP-130782	109r1	Introduction of LTE Advanced inter-band Carrier Aggregation of Band 3 and Band 28 to TS 36.307 Rel-10	10.6.0	10.7.0
2013-06	RP-60	RP-130785	112	Introduction of LTE Advanced inter-band Carrier Aggregation of Band 23 and Band 29 to TS 36.307 (Rel-10)	10.6.0	10.7.0
2013-06	RP-60	RP-130779	115	Introduction of LTE Advanced inter-band Carrier Aggregation of Band 3 and Band 26 to TS 36.307 (Rel-10)	10.6.0	10.7.0
2013-06	RP-60	RP-130777	118	Introduction of CA_3A-19A to TS 36.307	10.6.0	10.7.0
2013-06	RP-60	RP-130783	121	Introduction of CA_19A-21A to TS 36.307	10.6.0	10.7.0
2013-06	RP-60	RP-130775	129	Introduction of CA_2A-13A to TS 36.307	10.6.0	10.7.0
2013-06	RP-60	RP-130791	134r1	Introduction of Band 30	10.6.0	10.7.0
2013-06	RP-60	RP-130790	141	Introduction of LTE 450 into TS 36.307 R10	10.6.0	10.7.0
2013-06	RP-60	RP-130765	145	Corrections to release independent specifications	10.6.0	10.7.0
09-2013	RP-61	RP-131300	151	36.307 CR for LTE_CA_C_B3 (Rel-10)	10.7.0	10.8.0
09-2013	RP-61	RP-131303	154r1	Band 31 release independence for UE demodulation performance	10.7.0	10.8.0
09-2013	RP-61	RP-131285	156	[Rel-10] Modify requirements for CA_1A-18A in TS36.307	10.7.0	10.8.0
09-2013	RP-61	RP-131296	157	[Rel-10] Add requirements for CA_1A-26A into TS36.307	10.7.0	10.8.0
09-2013	RP-61	RP-131297	161	Introduction of CA_2A-4A into 36.307 REL-10	10.7.0	10.8.0
09-2013	RP-61	RP-131298	165	Introduction of inter-band CA Band 2+5	10.7.0	10.8.0
12-2013	RP-62	RP-131946	176	Introduction of CA band combination Band2 + Band12 to TS 36.307	10.8.0	10.9.0
12-2013	RP-62	RP-131954	179	Introduction of CA band combination Band12 + Band25 to TS 36.307	10.8.0	10.9.0
12-2013	RP-62	RP-131927	188r1	Correction to release independent specification	10.8.0	10.9.0
12-2013	RP-62	RP-131957	190	Introduction of CA_23B to TS 36.307	10.8.0	10.9.0
12-2013	RP-62	RP-131950	198	Introduction of CA band combination Band5 + Band25 to TS 36.307	10.8.0	10.9.0
12-2013	RP-62	RP-131948	202r1	Introduction of CA band combination B5 + B7 to TS 36.307	10.8.0	10.9.0
12-2013	RP-62	RP-131952	205	Introduction of CA band combination B7 + B28 to TS 36.307	10.8.0	10.9.0
12-2013	RP-62	RP-131925	214r1	UE performance requirements in release independent specification for CA	10.8.0	10.9.0
12-2013	RP-62	RP-131924	222	Introducing 'General' clause with note referring to note in clause 4.4 in TS36.101, editorial corrections and modifications to Forward and Scope clauses	10.8.0	10.9.0
12-2013	RP-62	RP-131959	224	Introduction of LTE_CA_C_B27 to 36.307 (Rel-10)	10.8.0	10.9.0
03-2014	RP-63	RP-140386	225r1	Introduction of CA band combination Band 3 and Band 27 to TS 36.307	10.9.0	10.10.0
03-2014	RP-63	RP-140368	230r1	CR on UE performance requirements in release independent specification	10.9.0	10.10.0
03-2014	RP-63	RP-140368	243r1	Correction to release independent specification	10.9.0	10.10.0
03-2014	RP-63	RP-140371	233	Release independence of Band 14 HPUE	10.9.0	10.10.0
03-2014	RP-63	RP-140187	246	Addition of bandwidth combination set for CA_2A-29A and CA_4A-29A	10.9.0	10.10.0
03-2014	RP-63	RP-140387	195r1	Introduction of CA_39A-41A to TS 36.307	10.9.0	10.10.0
03-2014	RP-63	RP-140388	208r2	Introduction of CA_39C to TS 36.307	10.9.0	10.10.0
06-2014	RP-64	RP-140911	298	Correction of Common RRM requirements for CA in release independent specification (Rel-10)	10.10.0	10.11.0
06-2014	RP-64	RP-140911	257	Introduction of CA band combination Band 1 and Band 5 to TS 36.307	10.10.0	10.11.0
06-2014	RP-64	RP-140911	270	CR on UE performance requirements in release independent specification	10.10.0	10.11.0
06-2014	RP-64	RP-140926	278	Introduction of Band 20+32 CA	10.10.0	10.11.0
06-2014	RP-64	RP-140931	263	Introduction of CA 1+11 to 36.307 (Rel-10)	10.10.0	10.11.0
06-2014	RP-64	RP-140932	344	Additional bandwidth combination set for LTE Advanced inter-band Carrier Aggregation of Band 3 and Band 20, independent of LTE Release	10.10.0	10.11.0
06-2014	RP-64	RP-140933	273	Introduction of CA band combination Band 4 and Band 27 to TS 36.307	10.10.0	10.11.0
06-2014	RP-64	RP-140935	276	Addition of bandwidth combination sets for CA_3A-5A, CA_4A-5A, and CA_4A-12A into 36.307	10.10.0	10.11.0
06-2014	RP-64	RP-140942	338	Introduction of CA band combination Band 1 and Band 20 to TS	10.10.0	10.11.0

				36.307		
06-2014	RP-64	RP-140942	251	Introduction of CA band combination Band 1 and Band 20 to TS 36.307	10.10.0	10.11.0
06-2014	RP-64	RP-140943	345	Introduction of CA band combination CA_41D into TS 36.307 (Rel-10)	10.10.0	10.11.0
06-2014	RP-64	RP-140946	343	Introduction of CA_42C to TS 36.307	10.10.0	10.11.0
06-2014	RP-64	RP-140952	0304	Introduction of a new CA_7C bandwidth combination set into 36.307 (Rel-10)	10.10.0	10.11.0
09-2014	RP-65	RP-141112	0390r1	[Rel-10] Introduction of inter-band CA_18-28 into TS36.307	10.11.0	10.12.0
09-2014	RP-65	RP-141198	0364r1	Introduction of CA_B1_B3_B19 into TS 36.307 (Rel-10)	10.11.0	10.12.0
09-2014	RP-65	RP-141203	0361r1	Introduction of CA_B1_B3 into TS 36.307 (Rel-10)	10.11.0	10.12.0
09-2014	RP-65	RP-141329	0427r1	Introduction of CA_1A-7A into 36.307 (REI-10)	10.11.0	10.12.0
09-2014	RP-65	RP-141338	0374r2	Introduction of CA_B1_B5_B7 into TS 36.307 (Rel-10)	10.11.0	10.12.0
09-2014	RP-65	RP-141465	0430	Introduction of 3 DL CA for Band 1+7+20	10.11.0	10.12.0
09-2014	RP-65	RP-141527	413	CR for 36.307 on CA UE performance requirement in Rel-10	10.11.0	10.12.0
09-2014	RP-65	RP-141541	411	CR on UE performance requirement for Band 31 for 36.307 Rel-10	10.11.0	10.12.0
09-2014	RP-65	RP-141551	358	Introduction of CA 8+11 to 36.307 (Rel-10)	10.11.0	10.12.0
09-2014	RP-65	RP-141552	377	Introduction of CA_41A-42A to TS 36.307	10.11.0	10.12.0
09-2014	RP-65	RP-141554	416r1	Introduction of requirements for 3DL inter-band carrier aggregation (FDD) and 2DL fallback	10.11.0	10.12.0
09-2014	RP-65	RP-141554	419r1	Introduction of requirements for 3DL inter-band carrier aggregation including Band 30 and 2DL fallback	10.11.0	10.12.0
09-2014	RP-65	RP-141555	382r1	Introduction of 3 Band Carrier Aggregation of Band 1,Band 3 and Band 5 to TS 36.307(Rel.10)	10.11.0	10.12.0
09-2014	RP-65	RP-141556	355r1	Introduction of 3 Band Carrier Aggregation (3DL/1UL) of Band 1, Band 3 and Band 8 to TS 36.307	10.11.0	10.12.0
09-2014	RP-65	RP-141558	400	Introduction of CA band combination Band 1, Band 3 and Band 20 to TS 36.307	10.11.0	10.12.0
09-2014	RP-65	RP-141560	350	Introduction of new CA_40C bandwidth combination set into 36.307	10.11.0	10.12.0
12-2014	RP-66	RP-142142	438	UE RF requirements in the release independent spec	10.12.0	10.13.0
12-2014	RP-66	RP-142166	441	Inclusion of 40D in 36.307	10.12.0	10.13.0
12-2014	RP-66	RP-142182	446	[Rel-10] Introduction of inter-band CA_1-28 into TS36.307	10.12.0	10.13.0
12-2014	RP-66	RP-142189	453	CR for TR 36.307: LTE_CA_B5_B13	10.12.0	10.13.0
12-2014	RP-66	RP-142190	456r2	Introduction of additional band combinations for 3DL inter-band CA	10.12.0	10.13.0
03-2015	RP-67	RP-150392	466	CR for 36.307 on CA UE performance requirement in Rel-10	10.13.0	10.14.0
07-2015	RP-68	RP-151024	473r3	Introduction of CA_42D to TS 36.307(Rel-10)	10.14.0	10.15.0
07-2015	RP-68	RP-150958	480	Removal of CA_2A-2A-13A, CA_4A-4A-13A from rel-10 36.307	10.14.0	10.15.0
07-2015	RP-68	RP-150968	496r2	Release independence CR for 2DL inter-band CA Rel-10	10.14.0	10.15.0
07-2015	RP-68	RP-150972	500r1	Release independence CR for 3DL inter-band CA Rel-10	10.14.0	10.15.0
09-2015	RP-69	RP-151501	0517	Introduction of the finished 4DL inter-band CAs fall back mode to TS 36.307 This CR was not implemented as the cover page said it is for 36.101	10.15.0	10.16.0
09-2015	RP-69	RP-151498	531r1	Rel-13 2DL combinations	10.15.0	10.16.0
09-2015	RP-69	RP-151499	535	Rel-13 3DL combinations	10.15.0	10.16.0
09-2015	RP-69	RP-151487	0542	Correction of TS 36.307 for release independent	10.15.0	10.16.0

History

Document history		
V10.0.1	January 2011	Publication
V10.1.0	June 2011	Publication
V10.2.0	November 2011	Publication
V10.3.0	April 2012	Publication
V10.4.0	July 2012	Publication
V10.5.0	November 2012	Publication
V10.6.0	February 2013	Publication
V10.7.0	July 2013	Publication
V10.8.0	October 2013	Publication
V10.9.0	January 2014	Publication
V10.10.0	April 2014	Publication
V10.11.0	July 2014	Publication
V10.12.0	October 2014	Publication
V10.13.0	February 2015	Publication
V10.14.0	April 2015	Publication
V10.15.0	July 2015	Publication
V10.16.0	October 2015	Publication