

ETSI TS 136 307 V9.11.0 (2014-03)



Technical Specification

**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
Requirements on User Equipments (UEs)
supporting a release-independent frequency band
(3GPP TS 36.307 version 9.11.0 Release 9)**



Reference

RTS/TSGR-0436307v9b0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Foreword..... | 6 |
| 1 Scope | 7 |
| 2 References | 7 |
| 3 Definitions and Abbreviations..... | 7 |
| 3.1 Definitions | 7 |
| 3.2 Abbreviations | 8 |
| 3A General | 8 |
| 4 Void..... | 9 |
| 5 Void..... | 9 |
| 6 Void..... | 9 |
| 7 Void..... | 9 |
| 8 Band 41 Independent of Release | 9 |
| 8.1 Band 41 UE | 9 |
| 8.1.1 RF Requirements | 9 |
| 8.1.2 RRM Requirements | 10 |
| 8.1.3 Void | 10 |
| 9 Band 42 Independent of Release | 10 |
| 9.1 Band 42 UE | 10 |
| 9.1.1 RF Requirements | 10 |
| 9.1.2 RRM Requirements | 10 |
| 9.1.3 Void | 10 |
| 10 Band 43 Independent of Release | 10 |
| 10.1 Band 43 UE | 11 |
| 10.1.1 RF Requirements | 11 |
| 10.1.2 RRM Requirements | 11 |
| 10.1.3 Void | 11 |
| 11 Band 24 Independent of Release | 11 |
| 11.1 Band 24 UE | 11 |
| 11.1.1 RF Requirements | 11 |
| 11.1.2 RRM Requirements | 12 |
| 11.1.3 Void | 12 |
| 12 Band 23 Independent of Release | 12 |
| 12.1 Band 23 UE | 12 |
| 12.1.1 RF Requirements | 12 |
| 12.1.2 RRM Requirements | 13 |
| 12.1.3 Void | 13 |
| 13 Band 25 Independent of Release | 13 |
| 13.1 Band 25 UE | 13 |
| 13.1.1 RF Requirements | 13 |
| 13.1.2 RRM Requirements | 14 |
| 13.1.3 Void | 14 |
| 14 Band 22 Independent of Release | 14 |
| 14.1 Band 22 UE | 14 |
| 14.1.1 RF Requirements | 14 |

14.1.2 RRM Requirements15

14.1.3 Void15

15 Band 26 Independent of Release15

15.1 Band 26 UE15

15.1.1 RF Requirements15

15.1.2 RRM Requirements16

15.1.3 Void16

16 Band 27 Independent of Release16

16.1 Band 27 UE16

16.1.1 RF Requirements16

16.1.2 RRM Requirements17

16.1.3 Void17

17 Band 28 Independent of Release17

17.1 Band 28 UE17

17.1.1 RF Requirements17

17.1.2 RRM Requirements18

17.1.3 Void18

18 Band 44 Independent of Release18

18.1 Band 44 UE18

18.1.1 RF Requirements18

18.1.2 RRM Requirements19

18.1.3 Void19

19 Void.....19

20 Void.....19

21 Void.....19

22 Void.....19

23 Void.....19

24 Void.....20

25 Void.....20

26 Void.....20

27 Void.....20

28 Void.....20

29 Void.....20

30 Void.....20

31 Void.....20

32 Void.....20

33 Void.....20

34 Void.....20

35 Void.....21

36 Void.....21

37 Void.....21

38 Void.....21

39 Void.....21

40 Void.....21

41 Void.....21

| | | |
|---|--|-----------|
| 42 | Band 30 Independent of Release | 21 |
| 42.1 | Band 30 UE | 21 |
| 42.1.1 | RF Requirements | 21 |
| 42.1.2 | RRM Requirements | 22 |
| 42.1.3 | Void | 22 |
| 43 | Band 31 Independent of Release | 22 |
| 43.1 | Band 31 UE | 22 |
| 43.1.1 | RF Requirements | 22 |
| 43.1.2 | RRM Requirements | 23 |
| 43.1.3 | Demodulation performance and CSI reporting Requirements | 23 |
| Annex A (informative): Frequency arrangement for overlapping operating bands | | 24 |
| Annex B (normative): Common Requirements..... | | 25 |
| B.1 | Purpose of annex | 25 |
| B.2 | Common RRM requirements | 25 |
| B.2.1 | Common RRM requirements for a band independent of release..... | 25 |
| B.3 | Common UE performance requirements..... | 26 |
| B.3.1 | Common UE performance requirements and tests for a band independent of release | 26 |
| Annex C (informative): Change history | | 27 |
| History | | 28 |

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies requirements on UEs supporting a frequency band that is independent of release.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 36.101 (Release 10): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".
- [3] 3GPP TS 36.133 (Release 10): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Radio Resource Management".
- [4] 3GPP TS 36.101 (Release 11): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".
- [5] 3GPP TS 36.133 (Release 11): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Radio Resource Management".
- [6] 3GPP TS 36.101 (Release 12): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".
- [7] 3GPP TS 36.133 (Release 12): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Radio Resource Management".
- [8] 3GPP TS 36.307 (Release 10): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements on User Equipments (UEs) Supporting a release-independent frequency band".
- [9] 3GPP TS 36.307 (Release 11): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements on User Equipments (UEs) Supporting a release-independent frequency band".
- [10] 3GPP TS 36.307 (Release 12): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements on User Equipments (UEs) Supporting a release-independent frequency band".
- [11] 3GPP TS 36.133 (Release 9): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Radio Resource Management".
- [12] 3GPP TS 36.101 (Release 9): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".

3 Definitions and Abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in [1] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|-----|---------------------------|
| FDD | Frequency Division Duplex |
| TDD | Time Division Duplex |
| RRC | Radio Resource Control |
| RRM | Radio Resource Management |
| UE | User Equipment |

3A General

TSG-RAN has agreed that the standardisation of new frequency bands may be independent of a release. However, in order to implement a UE that conforms to a particular release but supports a band of operation that is specified in a later release, it is necessary to specify some extra requirements.

For example, Band 19 is contained in the Release 9 specifications. In order to implement a UE conforming to Release 8 but supporting Band 19, it is necessary for the UE to additionally conform to some parts of the Release 9 specifications, such as the radio frequency and radio resource management requirements for the Band 19.

All frequency bands are fully specified in this release of the specifications. The present document does not contain any requirements for UEs supporting frequency bands independent of release.

NOTE: See NOTE in clause 4.4 in [12].

4 Void

5 Void

6 Void

7 Void

8 Band 41 Independent of Release

Band 41 is specified in Release 10 but is defined as a release-independent frequency band. This approach aligns the Band 41 with other frequency bands when considering features that have to be supported in different releases.

8.1 Band 41 UE

UEs that conform to Release 9 and support band 41 shall support the following requirements in Release 10.

8.1.1 RF Requirements

The UE shall comply with the RF requirements for band 41 specified in [2]. These requirements are:

Table 8.1.1-1: RF Requirements for Band 41 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

8.1.2 RRM Requirements

The UE shall comply with the RRM requirements for band 41 specified in [3] which are listed in Table B.2.1-1 of [8].

Table 8.1.2-1: Void

8.1.3 Void

9 Band 42 Independent of Release

Band 42 is specified in Release 10 but is defined as a release-independent frequency band. This approach aligns the Band 42 with other frequency bands when considering features that have to be supported in different releases.

9.1 Band 42 UE

UEs that conform to Release 9 and support band 42 shall support the following requirements in Release 10.

9.1.1 RF Requirements

The UE shall comply with the RF requirements for band 42 specified in [2]. These requirements are:

Table 9.1.1-1: RF Requirements for Band 42 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

9.1.2 RRM Requirements

The UE shall comply with the RRM requirements for band 42 specified in [3] which are listed in Table B.2.1-1 of [8].

Table 9.1.2-1: Void

9.1.3 Void

10 Band 43 Independent of Release

Band 43 is specified in Release 10 but is defined as a release-independent frequency band. This approach aligns the Band 43 with other frequency bands when considering features that have to be supported in different releases.

10.1 Band 43 UE

UEs that conform to Release 9 and support band 43 shall support the following requirements in Release 10.

10.1.1 RF Requirements

The UE shall comply with the RF requirements for band 43 specified in [2]. These requirements are:

Table 10.1.1-1: RF Requirements for Band 43 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

10.1.2 RRM Requirements

The UE shall comply with the RRM requirements for band 43 specified in [3] which are listed in Table B.2.1-1 of [8].

Table 10.1.2-1: Void

10.1.3 Void

11 Band 24 Independent of Release

Band 24 is specified in Release 10 but is defined as a release-independent frequency band. This approach aligns the Band 24 with other frequency bands when considering features that have to be supported in different releases.

11.1 Band 24 UE

UEs that conform to Release 9 and support Band 24 shall support the following requirements in Release 10.

11.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 24 specified in [2]. These requirements are:

Table 11.1.1-1: RF Requirements for Band 24 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

11.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 24 specified in [3] which are listed in Table B.2.1-1 of [8].

Table 11.1.2-1: Void

11.1.3 Void

12 Band 23 Independent of Release

Band 23 is specified in Release 10 but is defined as a release-independent frequency band. This approach aligns the Band 23 with other frequency bands when considering features that have to be supported in different releases.

12.1 Band 23 UE

UEs that conform to Release 9 and support band 23 shall support the following requirements in Release 10.

12.1.1 RF Requirements

The UE shall comply with the RF requirements for band 23 specified in [2]. These requirements are:

Table 12.1.1-1: RF Requirements for Band 23 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

12.1.2 RRM Requirements

The UE shall comply with the RRM requirements for band 23 specified in [3] which are listed in Table B.2.1-1 of [8].

Table 12.1.2-1: Void

12.1.3 Void

13 Band 25 Independent of Release

Band 25 is specified in Release 10 but is defined as a release-independent frequency band. This approach aligns the Band 25 with other frequency bands when considering features that have to be supported in different releases.

13.1 Band 25 UE

UEs that conform to Release 9 and support band 25 shall support the following requirements in Release 10.

13.1.1 RF Requirements

The UE shall comply with the RF requirements for band 25 specified in [2]. These requirements are:

Table 13.1.1-1: RF Requirements for Band 25 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

13.1.2 RRM Requirements

The UE shall comply with the RRM requirements for band 25 specified in [3] which are listed in Table B.2.1-1 of [8].

Table 13.1.2-1: Void

13.1.3 Void

14 Band 22 Independent of Release

Band 22 is specified in Release 10 but is defined as a release-independent frequency band. This approach aligns the Band 22 with other frequency bands when considering features that have to be supported in different releases.

14.1 Band 22 UE

UEs that conform to Release 9 and support band 22 shall support the following requirements in Release 10.

14.1.1 RF Requirements

The UE shall comply with the RF requirements for band 22 specified in [2]. These requirements are:

Table 14.1.1-1: RF Requirements for Band 22 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |
| 7.9 | Spurious emissions |

14.1.2 RRM Requirements

The UE shall comply with the RRM requirements for band 22 specified in [3] which are listed in Table B.2.1-1 of [8].

Table 14.1.2-1: Void

14.1.3 Void

15 Band 26 Independent of Release

Band 26 is specified in Release 11 but is defined as a release-independent frequency band. This approach aligns the Band 26 with other frequency bands when considering features that have to be supported in different releases.

15.1 Band 26 UE

UEs that conform to Release 9 and support Band 26 shall support the following requirements in Release 11.

15.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 26 specified [4]. The requirements are:

Table 15.1.1-1: RF Requirements for Band 26 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

15.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 26 specified in [5] which are listed in Table B.2.1-1 of [9].

Table 15.1.2-1: Void

15.1.3 Void

16 Band 27 Independent of Release

Band 27 is specified in Release 11, but is defined as a release-independent frequency band. This approach aligns the Band 27 with other frequency bands when considering features that have to be supported in different releases.

16.1 Band 27 UE

UEs that conform to Release 9 and support Band 27 shall support the following requirements in Release 11.

16.1.1 RF Requirements

The UE shall comply with the Release 11 RF requirements for Band 27 specified [4]. The requirements are:

Table 16.1.1-1: RF Requirements for Band 27 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

16.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 27 specified in [5] which are listed in Table B.2.1-1 of [9].

Table 16.1.2-1: Void

16.1.3 Void

17 Band 28 Independent of Release

Band 28 is specified in Release 11 but is defined as a release-independent frequency band. This approach aligns the Band 28 with other frequency bands when considering features that have to be supported in different releases.

17.1 Band 28 UE

UEs that conform to Release 9 and support Band 28 shall support the following requirements in Release 11.

17.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 28 specified [4]. The requirements are:

Table 17.1.1-1: RF Requirements for Band 28 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

17.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 28 specified in [5] which are listed in Table B.2.1-1 of [9].

Table 17.1.2-1: Void

17.1.3 Void

18 Band 44 Independent of Release

Band 44 is specified in Release 11 but is defined as a release-independent frequency band. This approach aligns the Band 44 with other frequency bands when considering features that have to be supported in different releases.

18.1 Band 44 UE

UEs that conform to Release 9 and support Band 44 shall support the following requirements in Release 11.

18.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 44 specified [4]. The requirements are:

Table 18.1.1-1: RF Requirements for Band 44 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

18.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 44 specified in [5] which are listed in Table B.2.1-1 of [9].

Table 18.1.2-1: Void

18.1.3 Void

19 Void

20 Void

21 Void

22 Void

23 Void

24 Void

25 Void

26 Void

27 Void

28 Void

29 Void

30 Void

31 Void

32 Void

33 Void

34 Void

35 Void

36 Void

37 Void

38 Void

39 Void

40 Void

41 Void

42 Band 30 Independent of Release

Band 30 is specified in Release 12 but is defined as a release-independent frequency band. This approach aligns the Band 30 with other frequency bands when considering features that have to be supported in different releases.

42.1 Band 30 UE

UEs that conform to Release 9 and support Band 30 shall support the following requirements in Release 12.

42.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 30 specified [6]. The requirements are:

Table 42.1.1-1: RF Requirements for Band 30 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

42.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 30 specified in [7] which are listed in Table B.2.1-1 of [10].

Table 42.1.2-1: Void

42.1.3 Void

43 Band 31 Independent of Release

Band 31 is specified in Release 12 but is defined as a release-independent frequency band. This approach aligns the Band 31 with other frequency bands when considering features that have to be supported in different releases.

43.1 Band 31 UE

UEs that conform to Release 9 and support Band 31 shall support the following requirements in Release 12.

43.1.1 RF Requirements

The UE shall comply with the RF requirements for Band 31 specified [6]. The requirements are:

Table 43.1.1-1: RF Requirements for Band 31 UE

| Section / Clause | Description |
|------------------|------------------------------------|
| 5.5 | Operating bands |
| 5.6 | Channel bandwidth |
| 5.7 | Channel arrangement |
| 6.2 | Transmit power |
| 6.3 | Output power dynamics |
| 6.6 | Output RF spectrum emissions |
| 6.7 | Transmit intermodulation |
| 7.3 | Reference sensitivity power level |
| 7.4 | Maximum input level |
| 7.5 | Adjacent Channel Selectivity (ACS) |
| 7.6 | Blocking characteristics |
| 7.7 | Spurious response |
| 7.8 | Intermodulation characteristics |

43.1.2 RRM Requirements

The UE shall comply with the RRM requirements for Band 31, for 5 MHz only, specified in [7] which are listed in Table B.2.1-1 of [10].

Table 43.1.2-1: Void

43.1.3 Demodulation performance and CSI reporting Requirements

The UE shall comply with the subset of demodulation performance and CSI reporting requirements specified in [6] which are listed in Table 43.1.3-2.

Table 43.1.3-1: Void**Table 43.1.3-2: Demodulation performance and CSI reporting requirements for Band 31 UE**

| Section / Clause | Description | Test case |
|------------------|--|-------------------|
| 8.2.1.1.1 | Single-antenna port performance | 6, 7, 8 |
| 8.2.1.2.1 | Transmit diversity performance | 1 |
| 8.2.1.3.1 | Open-loop spatial multiplexing performance | 1B |
| 8.2.1.4.1 | Closed-loop spatial multiplexing performance | 1A |
| 8.2.1.4.2 | Closed-loop spatial multiplexing performance | 2A |
| 8.5.1.2.1 | PHICH transmit diversity performance | 1A |
| 9.2.1.1 | CQI reporting definition under AWGN conditions | Table 9.2.1.1-2 |
| 9.3.2.1.1 | CQI reporting under fading conditions | Table 9.3.2.1.1-3 |

Annex A (informative): Frequency arrangement for overlapping operating bands

The following information is provided in order to assist a UE derive the DL EARFCN and UL EARFCN in a multi-band environment, in which multiple overlapping operating bands may be indicated in the fields *freqBandIndicator* and *multiBandInfoList* of SIB1.

The overlapping bands, independent of release, which may be indicated in a cell are shown in Table A-1 for applicable E-UTRA bands. The DL EARFCN and UL EARFCN are derived according to [4].

Table A-1: Overlapping bands (multi-band environments) for each E-UTRA band

| E-UTRA Operating Band | Overlapping E-UTRA operating bands | Duplex Mode |
|-----------------------|------------------------------------|-------------|
| 2 | 25 | FDD |
| 3 | 9 | FDD |
| 4 | 10 | FDD |
| 5 | 18, 19, 26 | FDD |
| 9 | 3 | FDD |
| 10 | 4 | FDD |
| 12 | 17 | FDD |
| 17 | 12 | FDD |
| 18 | 5, 26, 27 | FDD |
| 19 | 5, 26 | FDD |
| 25 | 2 | FDD |
| 26 | 5, 18, 19, 27 | FDD |
| 27 | 18, 26 | FDD |
| 33 | 39 | TDD |
| 38 | 41 | TDD |
| 39 | 33 | TDD |
| 41 | 38 | TDD |

Annex B (normative): Common Requirements

B.1 Purpose of annex

The purpose of Annex B is to group the requirements that are common for several bands or CA configurations in this specification and use the common tables as references.

B.2 Common RRM requirements

B.2.1 Common RRM requirements for a band independent of release

The requirements and test cases listed in Table B.2.1-1 are specified in [11].

Table B.2.1-1: Common RRM requirements for a band independent of release

| Section / Clause | Description |
|--|---|
| 4 | E-UTRAN RRC_IDLE state mobility |
| 5 | E-UTRAN RRC_CONNECTED state mobility |
| 6 ^{Note 1} | RRC Connection Mobility Control |
| 7 ^{Note 2} | Timing and signalling characteristics |
| 8 ^{Note 3} | UE Measurements Procedures in RRC_CONNECTED State |
| 9 ^{Note 4} | Measurements performance requirements for UE |
| A.4 | E-UTRAN RRC_IDLE state |
| A.5 | E-UTRAN RRC CONNECTED Mode Mobility |
| A.6 ^{Note 1} | RRC Connection Control |
| A.7 ^{Note 2} | Timing and Signalling Characteristics |
| A.8 ^{Note 3} | UE Measurements Procedures |
| A.9 ^{Note 4} | Measurement Performance Requirements |
| <p>NOTE 1: All requirements and the corresponding test cases shall apply, except:</p> <ul style="list-style-type: none"> - for supporting the corresponding band in Rel-8: clauses 6.3 (RRC Connection Release with Redirection), 6.4 (CSG Proximity Indication for E-UTRAN and UTRAN). <p>NOTE 2: All requirements and corresponding test cases shall apply, except those defined in sections 7.4 and 7.5.</p> <p>NOTE 3: All requirements and corresponding test cases shall apply, except:</p> <ul style="list-style-type: none"> - for supporting the corresponding band in Rel-8: clauses 8.1.2.5 (E-UTRAN OTDOA Intra-Frequency RSTD Measurements), 8.1.2.6 (E-UTRAN Inter-Frequency OTDOA Measurements), 8.1.2.7 (E-UTRAN E-CID Measurements). <p>NOTE 4: All requirements and corresponding test cases shall apply, except:</p> <ul style="list-style-type: none"> - for supporting the corresponding band in Rel-8: clauses 9.1.9 (UE Rx-Tx time difference), 9.1.10 (Reference Signal Time Difference). | |

B.3 Common UE performance requirements

B.3.1 Common UE performance requirements and tests for a band independent of release

The requirements and test cases listed in Table B.3.1-1 are specified in [12].

Table B.3.1-1: Common UE performance requirements and tests for a band independent of release

| Section / Clause | Description |
|------------------|---|
| 8 | Performance requirement |
| 9.2 | CQI reporting under AWGN conditions |
| 9.3 | CQI reporting under fading conditions |
| 9.4 | Reporting of Precoding Matrix Indicator (PMI) |
| 9.5 | Reporting of Rank Indicator (RI) |

Annex C (informative): Change history

Table C.1: Change History

| Date | TSG# | TSG Doc. | CR | Subject | Old | New |
|---------|-------|-----------|-------|---|--------|--------|
| 11-2009 | RP#46 | RP-091141 | | TS36.307 V0.1.0 approved by RAN (Originally in R4-095022) | - | 0.1.0 |
| 02-2010 | R4#54 | R4-100419 | | For release 9 version, replace sections 4 to 6 as "Void" and add a new void section as section 7. | 0.1.0 | 0.2.0 |
| 03-2010 | RP#47 | RP-100162 | | TS36.307 v1.0.0 for approval | 0.2.0 | 1.0.0 |
| 03-2010 | RP#47 | RP-100162 | | Approved by RAN | 1.0.0 | 9.0.0 |
| 09-2010 | RP-49 | RP-100927 | 2 | CR LTE_TDD_2600_US spectrum band definition additions to TS 36.307 V900 | 9.0.0 | 9.1.0 |
| | | | | Correction of section numbering | 9.1.0 | 9.1.1 |
| 12-2010 | RP-50 | RP-101356 | 008 | Band 42 and 43 parameters for UMTS/LTE 3500 (TDD) for TS 36.307 | 9.1.1 | 9.2.0 |
| 12-2010 | RP-50 | RP-101361 | 005 | Introduction of L-band in TS 36.307 | 9.1.1 | 9.2.0 |
| 06-2011 | RP-52 | RP-110804 | 014r3 | Add Expanded 1900 MHz Band (Band 25) in 36.307 | 9.2.0 | 9.3.0 |
| 06-2011 | RP-52 | RP-110812 | 021r1 | Add 2GHz S-Band (Band 23) in 36.307 (Rel 9) | 9.2.0 | 9.3.0 |
| 09-2011 | RP-53 | RP-111255 | 024 | Add Band 22 for LTE/UMTS 3500 (FDD) to TS 36.307 | 9.3.0 | 9.4.0 |
| 03-2012 | RP-55 | RP-120305 | 027 | Introduction of Band 26/XXVI to TS 36.307 | 9.4.0 | 9.5.0 |
| 2012-06 | RP-56 | RP-120769 | 035r1 | Correction of references | 9.5.0 | 9.6.0 |
| 2012-06 | RP-56 | RP-120793 | 047 | Introduction of APAC700(FDD) into TS 36.307 Rel-9 | 9.5.0 | 9.6.0 |
| 2012-06 | RP-56 | RP-120793 | 051 | Introduction of APAC700(TDD) into TS 36.307 Rel-9 | 9.5.0 | 9.6.0 |
| 2012-06 | RP-56 | RP-120791 | 055 | Introduction of e850_LB (Band 27) to TS 36.307 | 9.5.0 | 9.6.0 |
| 2012-09 | RP-57 | RP-121295 | 068r1 | Relation between EARFCN for overlapping bands with multiple FBI indication | 9.6.0 | 9.7.0 |
| 2013-06 | RP-60 | RP-130791 | 133r1 | Introduction of Band 30 | 9.7.0 | 9.8.0 |
| 2013-06 | RP-60 | RP-130790 | 140 | Introduction of LTE 450 into TS 36.307 R9 | 9.7.0 | 9.8.0 |
| 2013-06 | RP-60 | RP-130763 | 144 | Corrections to release independent specifications | 9.7.0 | 9.8.0 |
| 09-2013 | RP-61 | RP-131303 | 172 | Band 31 release independence for UE demodulation performance | 9.8.0 | 9.9.0 |
| 12-2013 | RP-62 | RP-131925 | 187r1 | Correction to release independent specification | 9.9.0 | 9.10.0 |
| 12-2013 | RP-62 | RP-131925 | 213r1 | UE performance requirements in release independent specification for CA | 9.9.0 | 9.10.0 |
| 12-2013 | RP-62 | RP-131924 | 221 | Introducing 'General' clause with note referring to note in clause 4.4 in TS25.101, editorial modifications to Scope clause | 9.9.0 | 9.10.0 |
| 03-2014 | RP-63 | RP-140367 | 229r1 | CR on UE performance requirements in release independent specification | 9.10.0 | 9.11.0 |
| 03-2014 | RP-63 | RP-140367 | 242r1 | Correction to release independent specification | 9.10.0 | 9.11.0 |

History

| Document history | | |
|-------------------------|---------------|-------------|
| V9.0.0 | April 2010 | Publication |
| V9.1.1 | October 2010 | Publication |
| V9.2.0 | January 2011 | Publication |
| V9.3.0 | June 2011 | Publication |
| V9.4.0 | November 2011 | Publication |
| V9.5.0 | April 2012 | Publication |
| V9.6.0 | July 2012 | Publication |
| V9.7.0 | November 2012 | Publication |
| V9.8.0 | July 2013 | Publication |
| V9.9.0 | October 2013 | Publication |
| V9.10.0 | January 2014 | Publication |
| V9.11.0 | March 2014 | Publication |