ETSITS 101 580-1 V2.1.1 (2013-12)



Core Network and Interoperability Testing (INT); Diameter Conformance testing for Rx interface (3GPP Release 10);

Part 1: Protocol Implementation Conformance Statement (PICS)

Reference

RTS/INT-00081-1

Keywords

conformance, diameter, PICS, testing

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: <u>http://portal.etsi.org/chaircor/ETSI_support.asp</u>

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| Intelle | ectual Property Rights | 4 |
|--|--|----|
| Forev | vord | 4 |
| Introd | luction | 4 |
| 1 | Scope | |
| 2 2.1 2.2 | References Normative references Informative references | 5 |
| 3 3.1 3.2 | Definitions and abbreviations. Definitions Abbreviations | 6 |
| 4 | Conformance | 6 |
| Anne | x A (normative): PICS proforma | 7 |
| A.1 A.1.1 A.1.2 A.1.3 | Guidance for completing the ICS proforma Purposes and structure | 7 |
| A.2 A.2.1 A.2.2 A.2.3 A.2.4 A.2.5 | Identification of the Network Equipment Date of the statement Network Equipment Under Test identification Product supplier Client PICS contact person | 9 |
| A.3 | Identification of the protocol | 11 |
| A.4 | Global statement of conformance | 11 |
| A.5 A.5.1 A.5.2 A.5.3 | PICS proforma tables | 11 |
| Histor | | 13 |

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Core Network and Interoperability Testing (INT).

The present document is part 1 of a multi-part deliverable covering the test specifications for the Diameter protocol on the Rx interface, as identified below:

- Part 1: "Protocol Implementation Conformance Statement (PICS)";
- Part 2: "Test Suite Structure (TSS) and Test Purposes (TP)";
- Part 3: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification".

Introduction

To evaluate protocol conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called a Protocol Implementation Conformance Statement (PICS).

1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for the test specifications for the Diameter protocol on the Rx interface as specified in TS 129 214 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [3] and ETS 300 406 [4].

The supplier of a protocol implementation which is claimed to conform to TS 129 214 [1] is required to complete a copy of the PICS proforma provided in annex A of the present document and is required to provide the information necessary to identify both the supplier and the implementation.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at http://docbox.etsi.org/Reference.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

| [1] | ETSI TS 129 214 (V10.5.0): "Universal Mobile Telecommunications System (UMTS); LTE; Policy and charging control over Rx reference point (3GPP TS 29.214 version 10.5.0 Release 10)". |
|-----|--|
| [2] | ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts". |
| [3] | ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements". |
| [4] | ETSI ETS 300 406: "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology". |
| [5] | ETSI TS 129 212 (V10.5.0): "Universal Mobile Telecommunications System (UMTS); LTE; Policy and charging control over Gx/Sd reference point (3GPP TS 29.212 version 10.5.0 |

2.2 Informative references

Release 10)".

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TS 129 214 [1] and the following apply:

PICS proforma: document, in the form of a questionnaire, designed by the protocol specifier or conformance test suite specifier, which, when completed for an OSI implementation or system, becomes the PICS

NOTE: See ISO/IEC 9646-1 [2].

Protocol Implementation Conformance Statement (PICS): statement made by the supplier of an Open Systems Interconnection (OSI) implementation or system, stating which capabilities have been implemented for a given OSI protocol

NOTE: See ISO/IEC 9646-1 [2].

static conformance review: review of the extent to which the static conformance requirements are met by the IUT, accomplished by comparing the PICS with the static conformance requirements expressed in the relevant standard(s)

NOTE: See ISO/IEC 9646-1 [2].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TS 129 214 [1] and the following apply:

PICS Protocol Implementation Conformance Statement

4 Conformance

A PICS proforma which conforms to this PICS proforma specification shall be technically equivalent to annex A, and shall preserve the numbering and ordering of the items in annex A.

A PICS which conforms to this PICS proforma specification shall:

- a) describe an implementation which claims to conform to TS 129 214 [1];
- b) be a conforming ICS proforma which has been completed in accordance with the instructions for completion given in clause A.1;
- c) include the information necessary to uniquely identify both the supplier and the implementation.

Annex A (normative): PICS proforma

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS proforma.

A.1 Guidance for completing the ICS proforma

A.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in relevant specifications may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into clauses for the following categories of information:

- instructions for completing the PICS proforma;
- identification of the implementation;
- identification of the protocol;
- PICS proforma tables (for example: Major capabilities, etc.).

A.1.2 Abbreviations and conventions

This annex does not reflect dynamic conformance requirements but static ones. In particular, a condition for support of a PDU parameter does not reflect requirements about the syntax of the PDU (i.e. the presence of a parameter) but the capability of the implementation to support the parameter.

In the sending direction, the support of a parameter means that the implementation is able to send this parameter (but it does not mean that the implementation always sends it).

In the receiving direction, it means that the implementation supports the whole semantic of the parameter that is described in the main part of the present document.

As a consequence, PDU parameter tables in this annex are not the same as the tables describing the syntax of a PDU in the reference specification.

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [3].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Reference column

The reference column gives reference to the relevant sections in core specifications.

Status column

The various status used in this annex are in accordance with the rules in table A.1.

Table A.1: Key to status codes

| Status code | Status name | Meaning | |
|------------------------|--------------------|--|--|
| m | mandatory | The capability shall be supported. It is a static view of the fact that the conformance requirements related to the capability in the reference specification are mandatory requirements. This does not mean that a given behaviour shall always be observed (this would be a dynamic view), but that it shall be observed when the implementation is placed in conditions where the conformance requirements from the reference specification compel it to do so. For instance, if the support for a parameter in a sent PDU is mandatory, it does not mean that it shall always be present, but that it shall be present according to the description of the behaviour in the reference specification (dynamic conformance requirement). | |
| 0 | optional | The capability may or may not be supported. It is an implementation choice. | |
| n/a | not applicable | It is impossible to use the capability. No answer in the support column is required. | |
| c. <integer></integer> | conditional | The requirement on the capability ("m", "o", "n/a") depends on the support of other optional or conditional items. <integer> is the identifier of the conditional expression.</integer> | |
| o. <integer></integer> | qualified optional | For mutually exclusive or selectable options from a set. <integer> is the identifier of the group of options, and the logic of selection of the options.</integer> | |

Mnemonic column

The Mnemonic column contains mnemonic identifiers for each item.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [3], are used for the support column:

Y or y supported by the implementation

N or n not supported by the implementation

N/A, n/a or - no answer required (allowed only if the status is N/A, directly or after evaluation of a conditional

status)

References to items

For each possible item answer (answer in the support column) within the PICS proforma there exists a unique reference, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table.

EXAMPLE: A.5/4 is the reference to the answer of item 4 in table A.5.

A.1.3 Instructions for completing the PICS proforma

The supplier of the implementation may complete the PICS proforma in each of the spaces provided. More detailed instructions are given at the beginning of the different clauses of the PICS proforma.

A.2 Identification of the Network Equipment

Identification of the Network Equipment should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

| A.2.1 | Date of the statement |
|---|---|
| A.2.2 Name: | Network Equipment Under Test identification |
| Hardware co | onfiguration: |
| Software con | nfiguration: |
| A.2.3 Name: | Product supplier |
| Address: | |
| Telephone n | umber: |
| Facsimile nu | |
| A.2.3 Name: Telephone n Facsimile nu | Product supplier umber: |

| Additional information: | | |
|----------------------------------|--|--|
| | | |
| A.2.4 Client Name: | | |
| Address: | | |
| Telephone number: | | |
| Facsimile number: | | |
| E-mail address: | | |
| Additional information: | | |
| A.2.5 PICS contact person Name: | | |
| Telephone number: | | |
| Facsimile number: | | |
| E-mail address: | | |
| Additional information: | | |
| | | |

A.3 Identification of the protocol

This PICS proforma applies to the following specification:

• TS 129 214 [1].

A.4 Global statement of conformance

The implementation described in this PICS meets all the mandatory requirements of the referenced standard?

[] Yes

NOTE: Answering "No" to this question indicates non-conformance to the protocol specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming. Explanations may be entered in the comments field at the bottom of each table or on attached pages.

In the tabulations which follow, all references are to TS 129 214 [1] unless another numbered reference is explicitly indicated.

A.5 PICS proforma tables

A.5.1 Roles

Table A.2: Roles

| Item | Roles | Reference clause | Status | Support |
|--|-------|------------------|--------|---------|
| 1 | AF | 4.3.1 | 0.1 | |
| 2 | PCRF | 4.3.2 | 0.1 | |
| o.1: At least one of these roles shall be supported. | | | | |

A.5.2 System Capabilities for AF

The tables provided in this clause need only to be completed for AF implementations, where item A.2/1 above is supported.

Table A.3: System Capabilities for AF

| Item | Does the IUT support | Reference clause | Status | Support |
|------|---|----------------------------------|--------|---------|
| 1 | Procedures for the initial provision of service information? | 4.4.1 | m | |
| 2 | The sponsored data connectivity feature? | 4.4.1, TS 129 212 [5], 4.5.20 | 0 | |
| 3 | Procedures for the modification of the session information? | 4.4.2 | 0 | |
| 4 | Gate related procedures? | 4.4.3 | 0 | |
| 5 | Procedures for the termination of AF sessions? | 4.4.4 | m | |
| 6 | Procedures for the subscription to the notification of the status of the AF Signalling transmission path? | 4.4.5 | 0 | |
| 7 | Procedures for the provision of information about AF Signalling IP flows? | 4.4.5a | 0 | |
| 8 | Procedures for the handling of traffic plane events? | 4.6 | m | |

A.5.3 System Capabilities for PCRF

The tables provided in this clause need only to be completed for PCRF implementations, where item A.2/2 above is supported.

Table A.4: System Capabilities for PCRF

| Item | Does the IUT support | Reference clause | Status | Support |
|------|---|----------------------------------|--------|---------|
| 1 | Checking of the service information provided by the AF? | 4.3.2 | 0 | |
| 2 | Usage of the subscription information as basis for the policy and charging control decisions? | 4.3.2 | 0 | |
| 3 | Procedures for the initial provision of service information? | 4.4.1 | m | |
| 4 | The sponsored data connectivity feature? | 4.4.1, TS 129 212 [5], 4.5.20 | 0 | |
| 5 | Procedures for the modification of the session information? | 4.4.2 | m | |
| 6 | Gate related procedures? | 4.4.3 | m | |
| 7 | Procedures for the termination of AF sessions? | 4.4.4 | m | |
| 8 | Procedures for the subscription to the notification of the status of the AF Signalling transmission path? | 4.4.5 | m | |
| 9 | Procedures for the provision of information about AF Signalling IP flows? | 4.4.5a | m | |
| 10 | Procedures for the handling of traffic plane events? | 4.6 | m | |

History

| Document history | | |
|------------------|---------------|-------------|
| V1.1.1 | April 2012 | Publication |
| V2.1.1 | December 2013 | Publication |
| | | |
| | | |
| | | |